

Feedback — Week 1 Quiz

[Help](#)

Thank you. Your submission for this quiz was received.

You submitted this quiz on **Fri 9 Jan 2015 5:10 PM PST**. You got a score of **18.00** out of **20.00**. You can [attempt again](#), if you'd like.

Introduction

This first quiz will check your ability to execute basic operations on objects in R and to understand some basic concepts. For questions 11–20 you will need to load a dataset into R and do some basic manipulations in order to answer the questions on the quiz.

You may want to print a copy of the quiz questions to look at as you work on the assignment. It is recommended that you save your answers as you go in the event that a technical problem should occur with your network connection or computer. Ultimately, you must submit the quiz online to get credit!

Data

The zip file containing the data for questions 11–20 in this Quiz can be downloaded here:

- [Week 1 Quiz Data](#)

For this assignment you will need to unzip this file in your working directory.

Question 1

R was developed by statisticians working at

Your Answer	Score	Explanation
<input type="radio"/> Microsoft		
<input type="radio"/> Bell Labs		
<input type="radio"/> Insightful		
<input checked="" type="radio"/> The University of Auckland	✓ 1.00	The R language was developed by Ross Ihaka and Robert Gentleman who were statisticians at the University of Auckland in New Zealand.

Total	1.00 /
	1.00

Question 2

The definition of free software consists of four freedoms (freedoms 0 through 3). Which of the following is NOT one of the freedoms that are part of the definition?

Your Answer	Score	Explanation
<input checked="" type="radio"/> The freedom to prevent users from using the software for undesirable purposes.	✓ 1.00	This is not part of the free software definition. Freedom 0 requires that the users of free software be free to use the software for any purpose.
<input type="radio"/> The freedom to study how the program works, and adapt it to your needs.		
<input type="radio"/> The freedom to improve the program, and release your improvements to the public, so that the whole community benefits.		
<input type="radio"/> The freedom to redistribute copies so you can help your neighbor.		
Total	1.00 /	
	1.00	

Question 3

In R the following are all atomic data types EXCEPT

Your Answer	Score	Explanation
<input type="radio"/> complex		
<input checked="" type="radio"/> data frame	✓ 1.00	'data frame' is not an atomic data type in R.
<input type="radio"/> numeric		

☐ integer

Total 1.00 / 1.00

Question 4

If I execute the expression `x <- 4L` in R, what is the class of the object `'x'` as determined by the `'class()'` function?

Your Answer

Score

Explanation

☐ complex

☐ logical

☒ numeric

✗

0.00

☐ integer

Total

0.00 / 1.00

Question 5

What is the class of the object defined by the expression `x <- c(4, "a", TRUE)`?

Your Answer

Score

Explanation

☐
integer

☒
character

✓

1.00

The character class is the "lowest common denominator" here and so all elements will be coerced into that class.

☐
numeric

☐ mixed

Total

1.00 /
1.00

Question Explanation

R does automatic coercion of vectors so that all elements of the vector are the same data class.

Question 6

If I have two vectors `x <- c(1,3, 5)` and `y <- c(3, 2, 10)`, what is produced by the expression `rbind(x, y)`?

Your Answer	Score	Explanation
<input type="radio"/> a 3 by 2 matrix		
<input checked="" type="radio"/> a matrix with three columns and two rows	✓ 1.00	The 'rbind' function treats vectors as if they were rows of a matrix. It then takes those vectors and binds them together row-wise to create a matrix.
<input type="radio"/> a vector of length 2		
<input type="radio"/> a 2 by 2 matrix		
Total	1.00 / 1.00	

Question 7

A key property of vectors in R is that

Your Answer	Score	Explanation
<input type="radio"/> a vector cannot have have attributes like dimensions		
<input type="radio"/> the length of a vector must be less than 32,768		
<input checked="" type="radio"/> elements of a vector all must be of the same class	✓ 1.00	
<input type="radio"/> elements of a vector can only be character or numeric		
Total	1.00 / 1.00	

Question 8

Suppose I have a list defined as `x <- list(2, "a", "b", TRUE)`. What does `x[[1]]` give me?

Your Answer	Score	Explanation
<input type="radio"/> a list containing the letter "a".		
<input type="radio"/> a character vector containing the element "2".		
<input checked="" type="radio"/> a numeric vector containing the element 2.	✓ 1.00	
<input type="radio"/> a list containing the number 2.		
Total	1.00 / 1.00	

Question 9

Suppose I have a vector `x <- 1:4` and `y <- 2:3`. What is produced by the expression `x + y`?

Your Answer	Score	Explanation
<input checked="" type="radio"/> an numeric vector with the values 3, 5, 5, 7.	✗ 0.00	
<input type="radio"/> an error.		
<input type="radio"/> a numeric vector with the values 1, 2, 5, 7.		
<input type="radio"/> an integer vector with the values 3, 5, 5, 7.		
Total	0.00 / 1.00	

Question 10

Suppose I have a vector `x <- c(3, 5, 1, 10, 12, 6)` and I want to set all elements of this vector that are less than 6 to be equal to zero. What R code achieves this?

Your Answer	Score	Explanation
<input checked="" type="radio"/> <code>x[x</code>	✓ 1.00	You can create a logical vector with the expression <code>x %in% 1:5</code> and

`%in% 1:5]` then use the `[]` operator to subset the original vector `x`.
`<- 0`

☐ `x[x != 6]`
`<- 0`

☐ `x[x < 6]`
`== 0`

☐ `x[x ==`
`0] <- 6`

Total 1.00 /
 1.00

Question 11

In the dataset provided for this Quiz, what are the column names of the dataset?

Your Answer	Score	Explanation
<input type="radio"/> Month, Day, Temp, Wind		
<input type="radio"/> 1, 2, 3, 4, 5, 6		
<input checked="" type="radio"/> Ozone, Solar.R, Wind, Temp, Month, Day	✓ 1.00	You can get the column names of a data frame with the <code>`names()`</code> function.
<input type="radio"/> Ozone, Solar.R, Wind		
Total	1.00 / 1.00	

Question 12


Extract the first 2 rows of the data frame and print them to the console. What does the output look like?

Your Answer	Score	Explanation
<input type="radio"/> Ozone Solar.R Wind Temp Month Day 1 7 NA 6.9 74		

5 11
2 35 274 10.3 82
7 17

☐ Ozone Solar.R Wind
Temp Month Day
1 18 224 13.8 67
9 17
2 NA 258 9.7 81
7 22

☐ Ozone Solar.R Wind
Temp Month Day
1 9 24 10.9 71
9 14
2 18 131 8.0 76
9 29


☒  1.00 You can extract the first two rows using the [operator and an integer sequence to index the rows.

Ozone Solar.R Wind
Temp Month Day
1 41 190 7.4 67
5 1
2 36 118 8.0 72
5 2

Total 1.00 / 1.00

Question 13

How many observations (i.e. rows) are in this data frame?

Your Answer	Score	Explanation
<input checked="" type="radio"/> 153	 1.00	You can use the `nrow()` function to compute the number of rows in a data frame.
<input type="radio"/> 160		
<input type="radio"/> 45		
<input type="radio"/> 129		

Total1.00 /
1.00

Question 14

Extract the *last* 2 rows of the data frame and print them to the console. What does the output look like?

Your Answer	Score	Explanation
<div><input type="radio"/></div> <div>Ozone Solar.R Wind Te mp Month Day 152 34 307 12.0 66 5 17 153 13 27 10.3 76 9 18</div>		
<div><input type="radio"/></div> <div>Ozone Solar.R Wind Te mp Month Day 152 31 244 10.9 78 8 19 153 29 127 9.7 82 6 7</div>		
<div><input type="radio"/></div> <div>Ozone Solar.R Wind Te mp Month Day 152 11 44 9.7 62 5 20 153 108 223 8.0 85 7 25</div>		
<div><input checked="" type="radio"/></div> <div>Ozone Solar.R Wind Te mp Month Day 152 18 131 8.0 76 9 29 153 20 223 11.5 68 9 30</div>	<div><div>✓</div>1.00</div>	The `tail()` function is an easy way to extract the last few elements of an R object.
Total	1.00 / 1.00	

Question 15

What is the value of Ozone in the 47th row?

Your Answer	Score	Explanation
<input type="radio"/> 18		
<input type="radio"/> 34		
<input type="radio"/> 63		
<input checked="" type="radio"/> 21	✓ 1.00	The single bracket [operator can be used to extract individual rows of a data frame.
Total	1.00 / 1.00	

Question 16

How many missing values are in the Ozone column of this data frame?

Your Answer	Score	Explanation
<input type="radio"/> 78		
<input type="radio"/> 43		
<input checked="" type="radio"/> 37	✓ 1.00	
<input type="radio"/> 9		
Total	1.00 / 1.00	

Question Explanation

The `'is.na'` function can be used to test for missing values.

Question 17

What is the mean of the Ozone column in this dataset? Exclude missing values (coded as NA) from this calculation.

Your Answer	Score	Explanation
<input type="radio"/> 53.2		
<input type="radio"/> 18.0		
<input checked="" type="radio"/> 42.1	✓ 1.00	
<input type="radio"/> 31.5		
Total	1.00 / 1.00	

Question Explanation

The `mean` function can be used to calculate the mean.

Question 18

Extract the subset of rows of the data frame where Ozone values are above 31 and Temp values are above 90. What is the mean of Solar.R in this subset?

Your Answer	Score	Explanation
<input type="radio"/> 334.0		
<input checked="" type="radio"/> 212.8	✓ 1.00	
<input type="radio"/> 185.9		
<input type="radio"/> 205.0		
Total	1.00 / 1.00	

Question Explanation

You need to construct a logical vector in R to match the question's requirements. Then use that logical vector to subset the data frame.

Question 19

What is the mean of "Temp" when "Month" is equal to 6?

Your Answer		Score	Explanation
<input checked="" type="radio"/> 79.1	✓	1.00	
<input type="radio"/> 90.2			
<input type="radio"/> 85.6			
<input type="radio"/> 75.3			
Total		1.00 / 1.00	

Question 20

What was the maximum ozone value in the month of May (i.e. Month = 5)?

Your Answer		Score	Explanation
<input type="radio"/> 100			
<input checked="" type="radio"/> 115	✓	1.00	
<input type="radio"/> 97			
<input type="radio"/> 18			
Total		1.00 / 1.00	