cident, or derailment; driving, trailing, or engine truck axles more than one-half inch under original diameter, except for locomotives having all driving axles of the same diameter, when other than main driving axles, may be worn three-fourths inch below the original diameter.

The date applied, the original diameter of the journal, and the kind of material shall be legibly stamped on one end of each driving axle, trailing truck axle, and engine truck axle applied after January 1, 1916.

34. **Tender truck axles.**—The minimum diameters of axles for various axle loads shall be as follows:

AXLE LOAD	Minimum diameter of journal	Minimum diameter of wheel seat	Minimum diameter of center
	Inches	Inches	Inches
50,000 pounds	5½	7⅜	6 7/16
38,000 pounds	5	6¾	5⅞
31,000 pounds	4½	6¼	5 1/16
22,000 pounds	3¾	5	4⅜
15,000 pounds	3¼	4⅝	3⅞

35. Tender truck axles with any of the following defects shall not be continued in service:

Bent axle; cut journals that can not be made to run cool without turning; seamy journals in steel axles, or transverse seams in journals of iron axles, or unsafe on account of usage, accident, or derailment; collars broken or worn to one-fourth inch or less in thickness; fillet in back shoulder worn out.

36. **Crank pins.**—Crank pins shall be securely applied. Shimming or prick punching crank pins will not be allowed. All crank pins applied after January 1, 1916, shall have the date applied and kind of material used legibly stamped on end of pin.

Crank pin collars and collar bolts shall be maintained in a safe and suitable condition for service.

37. **Driving boxes.**—Driving boxes shall be maintained in a safe and suitable condition for service. Broken and loose bearings shall be renewed. Not more than one shim may be used between box and bearing.

38. **Driving box shoes and wedges.**—Driving box shoes and wedges shall be maintained in a safe and suitable condition for service.

39. **Frames.**—Frames, deck plates, tailpieces, pedestals, and braces shall be maintained in a safe and suitable condition for service, and shall be cleaned and thoroughly inspected each time the locomotive is in shop for heavy repairs.

40. **Lateral motion.**—The total lateral motion or play between the hubs of the wheels and the boxes on any pair of wheels shall not exceed the following limits:

	Inch.
For engine truck wheels (trucks with swing centers)	1
For engine truck wheels (trucks with rigid centers)	1½
For trailing truck wheels	1
For driving wheels (more than one pair)	¾

These limits may be increased on locomotives operating on track where the curvature exceeds 20 degrees when it can be shown that conditions require additional lateral motion.