Continued from page 101 A

When tires are leaned against posts or wheel centers awaiting application or removal to scrap or storage they shall be securely fastened with a $^{3}_{8}$ chain with slip link properly fastened When necessary to lean tires against a wall tires to be blocked at bottom to prevent slipping out. This, however should be avoided wherever possible and tires placed horizontally on the floor

When applying tires to drivers removed from engine either by use of frame or crane clamp as shown on page 101 L, revised May 16 1928 to be used being sure wedge is in place Tire to be raised to position at wheel center and held by the chain block or crane until expanded to permit slipping on wheel center When tire has slipped over wheel center and heater is removed two 3/8 chains with slip link to be applied around rim of wheel center and tire with a double hitch approx imately 20 degrees each side of perpendicular center and drawn tight. Chain through slip link to hang down in all cases. Weight on clamp must not be released until tire has been applied to wheel center as far as clamp will permit and chains applied Chains must not be removed until tire is securely in place and clamped with tire clamps above referred to

When removing tires from drivers removed from engines either by use of a frame or crane after tire is heated two 3/8 chains with slip link, to be applied around rim of wheel center and tire with a double hitch approximately 20 degrees each side of perpendicular center and securely fast ened allowing sufficient slack to permit of removing tire to a point where clamp can be applied. After clamp is applied and weight taken by chain block or crane release chains and remove tire leaning tire against wheel center and securing with a 3/8 chain until ready for further handling

When applying tires to wheel centers when under engine tire to be securely chained to wheel center by two 3/8 chains with slip link applied at approximately 20 degrees each side of perpendiu lar center with a double hitch end of chain to hang down from slip link in all cases. As tire is raised to position slack to be taken out of chains alternately this in order that one chain will be fastened and in place at all times After tire is heated and slips over wheel center slack in chains to be taken up as heretofore stated Chains must not be removed until tire is securely in place

When removing tires from wheel centers while under engines first heat tire until loose then place two 3/8 chains with a double hitch around tire and rim of wheel center at approximately 20 degrees each side of perpendicular center line slacking each chain alternately until tire is removed from wheel center and rests on blocking prepared to receive it Do not remove chains until ready for further handling

QUARTER SLIPS

For obtaining amount of quarter slip on tires gauge as shown on page 101 M is advisable.

Drawing 952 CA 2824 Tires All Classes

8 4 28
CWS