GENERAL DESCRIPTION

NATHAN Type LB Lubricators have been developed to provide positive mechanical lubrication for air compressors and water pumps such as are used on steam locomotives. The driving mechanisms of these compact, efficient lubricators, are directly connected to the cylinders of the air compressors or water pumps which they lubricate. Therefore, lubricator delivery rates vary with compressor or pump speed, assuring oil delivery when—and only when—the apparatus is operating, and in the proper proportion for lubrication requirements.

The oil pumping units in Nathan Type LB Lubricators are built according to the same principle used in the construction of the well-known NATHAN Type DV Lubricators which have proven their merit over many years' service. The reciprocating and oscillating motion of the pumping unit pistons opens and closes intake and outlet ports. This completely eliminates the use of ball checks, valves and packing glands. Individual set screws permit regulation of oil volume delivered from each pump unit outlet.

Because LB Lubricators are designed to be mounted directly on water pumps or air compressors, the need for supplementary heating of the oil chamber is almost always eliminated. In some applications, however, it is not practical to fasten the lubricator to the cylinder wall of the pump or compressor, and for these special cases, a heating chamber is provided in the lubricator body.

A suitable hand crank is provided on all models of LB Lubricators for emergency operation. The hand crank may also be used for filling the oil pipes manually when desired—and as an indicator to show when the lubricator is operating.

All NATHAN Lubricators are supplied with such strainers, oil gauge rods and drain plugs as have been found most suitable for service to which any particular type of Lubricator is to be subjected.

The use of NATHAN LB Lubricators will assure you positive and efficient mechanical lubrication. This means savings in oil consumption . . . and reduced maintenance costs.

COPYRIGHT 1947 NATHAN MFG. CO.

NATHAN
BULLETIN L5

GENERAL SPECIFICATIONS

It has always been the policy of the NATHAN Manufacturing Company to make certain that the material used in every item of NATHAN equipment is the best known for its particular purpose.

For instance—in order to provide positive assurance that the castings used in NATHAN Lubricators are sound, the bodies of the Lubricators are cast of a special grade of iron.

For all highly stressed parts—such as ball pins, shafts, springs, ratchets, etc.—special heat-treated alloys are used.

Moreover, NATHAN Lubricators are provided with generous bearing surfaces for all moving parts.

Equally important, every NATHAN Lubricator is thoroughly tested under actual operating conditions before shipment. Careful engineering, together with close production control, guided by extensive experience assure the user of NATHAN Lubricators the longest possible service life with lowest maintenance cost.

NATHAN engineers will be pleased to consult with your engineers on any problem involving mechanical lubrication. Long experience has enabled them to speak authoritatively on every phase of lubricator operation—and to make practical recommendations for getting the utmost in economy and efficiency from each NATHAN application. This service to you entails no obligation, of course.