```
...signments\131_Assignment_6b\Question_1\Question_1.cpp
 1 // Question_1.cpp : This file contains the 'main' function.Program
     execution begins and ends there.
 2 //
 3 //
 4 // /
 5 //-----
 6 //Name Sai Chaitanya Kilambi
 7 //Course CPSC 131 Data Structures, Fall, 2022
 8 //Assignment No.6b question:1
 9 //Due date 10/12/2022
10 // Purpose:
11 // This program performs postfix arthmatic
12 //-----
13 // list of libraries
14 //
15 //importing the required libraries
16
17 #include <iostream>
18 #include<string>
19 #include "STACKPAC.h"
20 using namespace std;
21
22 bool isNum(string str)
23 {
       for (int i = 0; i < str.length(); i++)</pre>
24
25
           if (isdigit(str[i]) == false)
              return false;
26
27
       return true;
28 }
29 int main(){
30
31
       Stack<int, 100> s1;
32
       s1.clearStack();
       // s is string for taking in input
33
34
       string s;
35
       // s2 is string array to store split words
       string s2[100];
36
       cout<<"Enter a postfix expression:";</pre>
37
       // getline is used to take input string which have spaces
38
39
       getline(cin,s);
40
       // ind is index for s2 to store words
41
       int i,ind=0;
       string word="";
42
       // we access each character in s if we get space then store that word >
43
        in s2
44
       // else add each character to word
45
       for(i=0;i<s.length();i++){</pre>
```

```
...signments\131_Assignment_6b\Question_1\Question_1.cpp
```

```
2
```

```
if(s[i]==' ')
46
47
            {
48
                s2[ind]=word;
                ind++;
49
                // making word empty to use it for another word
50
                word="":
51
52
            }
53
            else
54
                word=word+s[i];
55
        }
        // str have the postfix expression
56
57
        string str="";
       // t is used to ask inputs
58
59
        string t;
       // accessing each word in s2
60
61
       // check whether it is number using isNum or + or - or * or / if true >
         then add them to str
62
       // else ask user to enter int value of that variable
63
       for(i=0;i<ind;i++){</pre>
            if(isNum(s2[i]) || s2[i]=="+" || s2[i]=="*" || s2[i]=="-" || s2[i] →
64
              =="/" )
65
            {
66
                str = str + s2[i] + "";
67
            }
            else{
68
69
                //do while loop because if again user enters string value
                  rather than int
70
                do{
                    cout << "Enter value of "<<s2[i]<<":";</pre>
71
72
                    cin >> t;
73
74
                while(isNum(t)!=true);
75
                // adding newly entered value to str
                str = str + t + " ";
76
77
            }
78
        }
79
       // num stores the number which is in string form
80
        int num=0;
       // accessing each element in the str i.e postfix expression
81
82
        for(i=0;i<str.length();i++){</pre>
            // space or num is not zero then num is pushed to stack and making >
83
               num to 0 for next number
84
            if(str[i]==' ' && num!=0){
85
                s1.pushStack(num);
86
                num=0;
87
88
            // if we encounterd number then we convert that char to number
89
            else if(isdigit(str[i])){
                num = num * 10 + int(str[i]-'0');
90
```

```
\underline{\dots} signments \verb|\|131_Assignment_6b\\\\Question_1\\\\Question_1.cpp
                                                                                      3
 91
92
             // if we encountered +,/,*,- then we pop top 2 elements of stack
               and do respective operation and push them again into stack
             else if(str[i]=='+' || str[i]=='*' || str[i]=='-' || str[i]=='/'){ >
93
94
                 int a,b;
95
                 a=s1.popStack();
96
                 b= s1.popStack();
             switch(str[i]){
97
98
             case '+':s1.pushStack(b+a);break;
             case '-':s1.pushStack(b-a);break;
99
             case '*':s1.pushStack(b*a);break;
100
             case '/':s1.pushStack(b/a);break;
101
102
             }
             }
103
104
         }
         // after doing all operations there will be only 1 element in stack
105
           which is the value of postfix expression
106
         cout<<"\tValue of postfix expression is "<<s1.popStack();</pre>
107
         return 0;
108 }
109
110
111
```