AI versus Numerical Analysis: Two Forms of Computation

Claes Johnson
KTH Royal Institute of Technology, Stockholm
claesjohnson@gmail.com

October 4, 2026

Abstract

A large language model computes with symbols; numerical analysis computes with numbers in digital form. Both are machine computation, both run on the same hardware, and the difference between them is not rigour but what the computed objects denote and how the result is certified. A symbolic computation is certified by derivability: each step follows, and a proof assistant can check that it does. A numerical computation is certified by an error bound that the computation itself produces. The first gives certainty about a statement; the second gives a quantity with a stated accuracy, which can be compared with a measurement.

We take as example the two recent accounts of the incompressible Euler equations. An AI system has produced a proof, formalised in Lean, that smooth compactly supported data can develop infinite velocity gradients in finite time. Adaptive finite element computation produces turbulent solutions past a body whose mean-value outputs — drag, lift, separation — are determined to a computed tolerance and agree with measurement. The first proves *existence without exhibiting an individual case*; the second *computes an individual case* and exhibits nothing general. Each has exactly what the other lacks, neither is the other's refutation, and the pair is instructive about both ways of computing.

We draw two conclusions. Symbolic computation reaches objects that possess exploitable structure — a symmetry, an ansatz, a closed form — and reaches them exactly; it does not reach objects defined by the absence of such structure, of which turbulence is the standing example, and no increase in scale will alter this. And the problem AI now faces, that of trusting a computation no person has followed, is one numerical analysis met fifty years ago and solved, by computing the error alongside the answer. We suggest that a posteriori error control is what symbolic computation presently lacks and what it should take from the older discipline.

1 Two forms of computation

A large language model and a finite element solver are both programs. Both execute on the same processors, both reduce in the end to floating-point arithmetic, and both produce in finite time an output no person could have produced by hand. The distinction between them is not that one is mathematics and the other machinery.

The distinction is in what the computation manipulates and in what it means for the output to be right.

Computation with symbols. A language model operates on tokens — words, formulas, proof steps — and its output is a text. When that text is a proof, correctness means *derivability*: every step follows from previous steps by a rule, and the question of whether it does is decidable by a proof assistant. The verdict is binary. A proof is valid or it is not, and no quantity attaches to it.

Computation with digital numbers. A numerical method operates on numbers held in finite precision over a finite mesh, and its output is a number. Correctness cannot mean derivability, since the computed object is not the exact one and never will be. It means instead a *bound*:

$$|\,\text{output computed} - \text{output exact}\,| \;\leq\; E,$$

where E is itself computed, from the residual of the computed solution weighted by the solution of an adjoint problem. The verdict is quantitative. The answer is right to within a stated amount, and the amount is part of the answer.

Where the difference lies. It is tempting to rank these, and the ranking usually proposed is that derivability is the stronger notion because it is exact. That is true of the notion and misleading about the practice. A derivation is exact about the statement it derives, and a statement can be exactly established and say nothing about the world. A bound is inexact about a quantity, and a quantity can be compared against a measurement made by somebody else. The two kinds of certainty point in different directions: one inward, to consistency; one outward, to agreement.

And the symbolic layer is numerical underneath. The two forms are not disjoint, and it is as well to say where they meet. A language model is not a symbolic engine in the sense of a term rewriter. It is a numerical one. Tokens are vectors, attention is matrix multiplication, the whole forward pass is dense linear algebra in finite precision, and the weights were obtained by gradient descent on a non-convex objective — which is to say by a numerical method for an optimisation problem, run to a tolerance nobody states. Symbolic computation, as practised by these systems, is *implemented as* numerical computation. At the bottom there is floating-point arithmetic and nothing else, and it is the same arithmetic a finite element solver performs.

So the distinction of this section is one of level and not of kind. What is manipulated at the top is symbols; what happens at the bottom is numbers in digital form. Numerical analysis is in that sense logically prior to the symbolic layer rather than an alternative to it.

Two things follow, and the second is the point of Section 5. The arithmetic being the same, its difficulties are the same: conditioning, precision, and a dependence on the order of summation which makes a large model's output irreproducible in the way an unstabilised computation is irreproducible — run it again and the proof may differ. And the numerical layer of these systems carries, at present, no error control whatever. The finite element solver computes a bound on how wrong it is; the transformer computes no such thing, at either level. That is not a limitation of numerical computation. It is a facility of numerical computation which has not been built.

2 The example

The incompressible Euler equations have lately received both treatments, which makes them an unusually clean case.

The symbolic account. An AI system has produced a proof that there exists smooth, compactly supported, divergence-free initial data on $\mathbb{R}^3$ whose smooth Euler solution has finite maximal lifespan: the velocity gradient becomes unbounded and the Beale–Kato–Majda vorticity integral diverges [2]. The proof is fifty-seven pages and is formalised in Lean, so that its correctness is machine-checked. Comparable results were being prepared independently and by hand [3].

What the result delivers is an existence statement. It does not say which data blow up; there is no measure on the set and no claim of genericity. It does not say what the flow looks like. It yields no drag, no lift, no length, no time that could be set beside an experiment. The datum itself is produced as the limit of an iteration and cannot be written down. The result is nonetheless a real advance: a question open for decades is settled, and the settling is exact.

The numerical account. Adaptive finite element computation of the same equations past a body produces turbulent solutions [4, 5, 6]. The velocity stays bounded, the gradients do not, the solution dissipates energy at a rate independent of the viscosity, and the limit of the computed sequence is a weak solution of Euler by the residual control the method carries. Its mean-value outputs are determined: drag to within a few per cent of measurement, the separation line where experiment puts it, the lift curve and the stall.

What this delivers is not a solution. For weak solutions of Euler uniqueness is false, so there is no unique solution to deliver. What is delivered is the quantities that are determined, each with an error bound the computation produces, each open to check by somebody with no interest in the outcome.

The shape of the comparison. Put at its plainest, the difference is between a proof of *existence without an individual case* and the *direct computation of an individual case.*

The symbolic account establishes that a datum with the stated property exists. It does not hand one over. The datum is the limit of an iteration over stages, each adding an oscillation to the one before, and no finite description of it is produced or intended — nothing can be plotted, measured or shown to anybody. What exists is the existence.

The numerical account computes one case: this body, this free stream, this flow, with this drag. It establishes nothing about all data or about any other case. What it produces can be looked at. The wake has a shape, the separation line a position, the drag a value with a bound on its error, and each can be set beside a measurement.

So the two are complementary in the strict sense: each has exactly what the other lacks. Generality without instance, instance without generality. The first is mathematically substantial and physically empty, the second physically substantial and mathematically the weaker. The companion paper [1] argues the fluid mechanics of this and concludes that the singular solutions, whatever their mathematical interest, are not flows. Here we are concerned with what the pair says about the two ways of computing.

3 What each form can reach

The division of labour is not a division between rigour and approximation. It follows from what each form of computation requires of its object.

Symbolic computation requires exploitable structure. A proof proceeds by rewriting, and rewriting needs something to grip. Every construction of a singular solution buys its tractability with a structure: self-similarity, which collapses a partial differential equation to a profile and leaves a fixed point; or axisymmetry, which removes a variable; or an iterative scheme whose stages are similar to one another. This is not a criticism. It is what makes the object reachable at all, and the skill lies in finding the structure that a given problem will support.

Numerical computation requires none. A mesh does not care whether the solution has a symmetry. The computation proceeds identically whether the object is a self-similar profile or a turbulent wake, and the cost is set by the resolution rather than by the structure.

Hence the complementarity, and its sharp edge. Objects *with* structure are reachable both ways, and symbolically with greater precision. Objects *without* structure are reachable only numerically. Turbulence is the standing example of the second kind — it is *defined* by carrying structure at every scale with no organising principle to exploit, so there is no ansatz to be found, and the absence is the phenomenon rather than a gap in anybody's technique.

This bears directly on what AI changes. A language model is a search over symbol sequences, and what it does superlatively is find structures that a human might have found given longer. It therefore amplifies the half of mathematics that was already good at special objects, and amplifies it a great deal. It does not convert the other half. No scale of model makes a turbulent flow analytically constructible, because the obstruction is in the object and not in the searcher.

4 Checking the result, or checking the steps

Neither form of computation can be verified step by step by a person. A finite element computation performs billions of floating-point operations; a fifty-seven page formal development has more inferences than anyone will read. On that both are in the same position, and it is usually where the discussion stops. It should not, because the two escape the position in entirely different ways, and only one of them escapes.

A numerical result can be checked without checking the computation. Given any candidate velocity field, substitute it into the Euler equations and evaluate what is left over:

$$R(u) \;=\; \dot{u} + (u \cdot \nabla)u + \nabla p, \qquad \nabla \cdot u.$$

If the residual is small in the appropriate weighted sense, the field nearly solves the equations; and weighted by the solution of an adjoint problem it bounds the error in any output of interest.

The decisive feature of this test is that it is *independent of how the field was obtained*. It does not inspect the mesh, the solver, the arithmetic or the order of operations. The candidate could have come from a different program, a different method, or a guess, and the test would be the same test. Consequently nobody needs to verify the individual computational steps, and nobody does: an error at the three-millionth operation is not caught by examining that operation, it is caught because the residual comes out large. The equation itself performs the audit, once, on the answer.

A symbolic result cannot. There is no corresponding operation on a proof. A proof does not have a residual, because what it produces is a statement rather than an object, and a statement cannot be substituted into anything. Its correctness simply *is* the correctness of its steps, so there is no alternative to checking them — which is what a proof assistant does, mechanically and reliably, and at a scale no person matches.

This deserves to be put more carefully, because symbolic computation is not in fact without a residual test. It has one, and it is the strongest of all. Given a candidate in *closed form* — a formula for u and p — one inserts it into the equations and simplifies, and the check is exact: either the residual reduces identically to zero or it does not. No tolerance, no mesh, no adjoint. Symbolic manipulation is very good at this, and a computer algebra system performs it unattended. Verifying a solution in symbolic form is thereby both easier and sharper than verifying one in digital form.

What that check requires is a specific symbolic object to insert. Here there is none. The datum of the construction is the limit of an iteration over stages and has no closed form; there is no expression to substitute, nothing to simplify, and no identity to reduce to zero. Nor is the numerical route open, since no finite stage of the iteration exhibits the property — the blowup belongs to the limit. So *both* residual tests fail, the symbolic and the digital, and they fail for the same reason and not for two: there is no individual object, in either form, to put into the equations.

The two observations of this paper are therefore one observation. The construction proves existence without exhibiting an individual case, and an individual case is exactly what any check of the result, symbolic or numerical, would have to be applied to. *Because there is no instance, there is nothing to insert; because there is nothing to insert, only the steps remain.*

What Lean settles and what it leaves. A proof assistant establishes that the steps follow from the stated definitions. It does not establish that the stated definitions say what was intended, and that question cannot be mechanised — somebody has to read the formal statement and agree that it is the theorem. For a development of this length, with its own hierarchy of definitions, that reading is itself substantial work, and it is the part no machine does. So the verification burden is reduced and relocated rather than removed, and what remains of it falls on a human mathematician who must in the end understand something.

The asymmetry is therefore not that one discipline is careful and the other careless. It is that the numerical computation is answerable to an external object — the equation, and beyond it the measurement — which audits the result wholesale, while the symbolic computation is answerable only to its own steps, which must be audited one at a time.

Stated as two kinds of certainty, and without rancour: *a formal proof is internally certain.*

The assistant guarantees that the steps follow. It guarantees nothing about whether the statement proved is about anything, and here the statement is about a datum that cannot be prepared and a flow no instrument will see. The certainty is real and it is certainty of consistency. *A numerical computation is externally checkable.* Its output is a number with a tolerance, and the number can be set beside a measurement somebody else made at a facility with no stake in the outcome. The High Lift Prediction Workshop and the high-order workshops exist for precisely this: predictions are submitted before the measurements are released. That is an accountability a proof does not have and does not need, and a computation does need.

5 What symbolic computation might take from the older discipline

That a result may have to be believed on the strength of a procedure rather than of an understanding is not a new condition. It is the one numerical analysis has worked in since the 1950s, and the discipline's response was not to argue about whether machine results count. It was to make them accountable: to compute, alongside the answer, a bound on how wrong the answer may be, and to refine where the bound says the error lives. That is the content of a posteriori error estimation and adaptivity, and it is why a computed drag coefficient is a scientific statement rather than an opinion produced by a program.

The central practical problem now facing AI in mathematics and elsewhere is this: a system produces an output that is too long to check and too important to trust blindly. That is, exactly, the problem numerical analysis faced when machines first outran hand calculation, and it has a developed answer.

The answer has three parts, and all three transfer in principle.

Compute the error, not merely the answer. A finite element computation returns a solution and a bound on the error in each output of interest. The bound comes from the residual — what the computed solution fails to satisfy — weighted by the solution of an adjoint problem which measures how much that failure matters for the output in question. The structure is general: a residual, a sensitivity, and their product. A language model has a residual in the same sense — the respects in which its output fails to satisfy the conditions it should — and nothing at present weights it.

Let the error direct the effort. Adaptivity refines where the bound says the error is, not uniformly. The analogue for a symbolic system is to concentrate verification where the proof is weakest rather than uniformly over its length, which requires knowing where that is, which requires the weighting above.

Report what is *not* determined. An honest a posteriori estimate sometimes returns a large bound, and that is information: the computation does not determine this output, and no refinement of this kind will make it do so. A system that cannot return that verdict about its own output is not yet accountable, whatever its success rate.

That the machinery is numerical underneath makes this less of an analogy than it may appear. The quantities a posteriori estimation works with — a residual, a sensitivity, their product — are numerical quantities, and a language model is a numerical object. The tools would not have to be carried across a gap; they would have to be applied one level down from where the symbols are.

We put this forward as the constructive half of the comparison. The debate about whether machine proof is mathematics will be settled the way the corresponding debate about machine computation was settled, which is not by argument but by the development of error control. Numerical analysis has fifty years of that, and it was built for precisely the situation symbolic computation is now in.

6 Summary

Symbolic computation and numerical computation are both machine computation and differ in what they manipulate and in how they are certified: derivability against an error bound, consistency against agreement. Symbolic computation reaches objects possessing exploitable structure and reaches them exactly; numerical computation reaches objects without it and reaches them to a stated tolerance. Turbulence is of the second kind by definition, and no amount of symbolic power alters that. The Euler equations have lately been treated both ways, and the results stand in exactly this relation: a proof that blow-up data exists which exhibits no individual case, and the direct computation of an individual case whose observables agree with measurement. Generality without instance, and instance without generality.

The question now being asked of AI — how to trust a result no one has followed — is the question numerical analysis answered by computing the error alongside the answer and refining where it lives. It is the better part of what the older discipline has to offer the newer, and it is not yet taken up.

References

[1] J. Hoffman and C. Johnson, *Incompressible Euler flow: turbulence vs blow-up*, companion paper, 2026.

[2] OpenAI, *Finite time blowup for the Euler equation*, preprint, 2026, 57 pp. `https://cdn.openai.com/pdf/315b36cd-ec98-4023-8342-93345194ece1/euler.pdf`

[3] T. Buckmaster and L. Alpöge, *Statement*, 2026. `https://cims.nyu.edu/~tristanb/statement.pdf`

[4] J. Hoffman and C. Johnson, *Computational Turbulent Incompressible Flow*, Applied Mathematics: Body and Soul, vol. 4, Springer, 2007.

[5] J. Hoffman and C. Johnson, *Resolution of d'Alembert's paradox*, J. Math. Fluid Mech. **12** (2010) 321–334.

[6] J. Hoffman, J. Jansson and C. Johnson, *New theory of flight*, J. Math. Fluid Mech. **18** (2016) 219–241.

[7] K. Eriksson, D. Estep, P. Hansbo and C. Johnson, *Computational Differential Equations*, Cambridge University Press, 1996.

[8] A. Logg, *Automation of computational mathematical modeling*, Ph.D. thesis, Chalmers University of Technology, 2004.

[9] A. Logg, K.-A. Mardal and G. N. Wells (eds.), *Automated Solution of Differential Equations by the Finite Element Method*, Lecture Notes in Computational Science and Engineering 84, Springer, 2012.