

Skipping meals, skipping words, and how the latter can benefit you and the first just makes you hungry

Bayesian Language Modelling with Skipgrams



Bayesian Language Modelling with Skipgrams

Louis Onrust

Centre for Language Studies, Radboud University

Center for Processing Speech and Images, KU Leuven

l.onrust@let.ru.nl

github.com/naiaiden



Language Models

Applications

- Input assists on telephones
- Automatic translation of search results
- Digital court reporting



Language Models

Applications

- Input assists on telephones
- Automatic translation of search results
- Digital court reporting

Flavours

- Frequentist language models
- Bayesian language models
- Neural language models
- ...



The Task at Hand

After all , tomorrow is another [...]



The Task at Hand

After all , tomorrow is another [...]

Word prediction

Word probability

Pattern probability



The Task at Hand

After all , tomorrow is another [...]

Word prediction

- day

Word probability

Pattern probability



The Task at Hand

After all , tomorrow is another [...]


Word prediction

- day

Word probability

- cow
- day
- vegetable
- ...

Pattern probability



The Task at Hand

After all , tomorrow is another [...]

Word prediction


- day

Word probability

- cow
- day
- vegetable
- ...

Pattern probability

- tomorrow is another day
- tomorrow is another important
- tomorrow is another race



Generalising the n -gram

n -grams

- Continuous sequence of n words




Skipgrams

- n -gram with at most $n - 2$ skips of length 1

Flexgrams


- n -gram with any number of skips of any length

Skipgrams in other works

-  A Generalized Language Model as the Combination of Skipped n -grams and Modified Kneser Ney Smoothing, Pickhardt et alia, 2014
-  Skip-gram Language Modeling Using Sparse Non-negative Matrix Probability Estimation, Shazeer et alia, 2014
-  Skipgrams in word2vec



Backoff Patterns with Skipgrams



Backoff patterns

simple Only
n-grams

limited All patterns
until known
pattern

full All patterns
until words



Probability Estimation

Maximum Likelihood Estimate

$$p_{\text{ML}}(w_i | w_{i-N+1}, \dots, w_{i-1}) = \frac{C(w_{i-N+1}, \dots, w_i)}{C(w_{i-N+1}, \dots, w_{i-1})}$$

- Parameter estimation is impossible for $N > 2$
- Naïve priors assuming independent parameters fail as well



Probability Estimation

Maximum Likelihood Estimate

$$p_{\text{ML}}(w_i | w_{i-N+1}, \dots, w_{i-1}) = \frac{C(w_{i-N+1}, \dots, w_i)}{C(w_{i-N+1}, \dots, w_{i-1})}$$

- Parameter estimation is impossible for $N > 2$
- Naïve priors assuming independent parameters fail as well

Smoothing

$$p_{\text{SM}}(w_i | w_{i-N+1}, \dots, w_{i-1}) = \sum_{n=1}^N \lambda(n) Q_n(w_i | w_{i-N+1}, \dots, w_{i-1})$$

- Chen and Goodman found that interpolated and modified Kneser-Ney are best under virtually all circumstances



Bayesian Probability Estimation

Parametrise conditional probabilities

$$p(w_i = w | w_{i-N+1}, \dots, w_{i-1} = u) = G_u(w)$$

$$G_u = [G_u(w)]_{w \in \mathcal{W}}$$

$$\pi(w_{i-N+1}, \dots, w_{i-1}) = w_{i-N+2}, \dots, w_{i-1}$$

- G_u is a probability vector associated with context u



Bayesian Probability Estimation

Parametrise conditional probabilities

$$p(w_i = w | w_{i-N+1}, \dots, w_{i-1} = u) = G_u(w)$$

$$G_u = [G_u(w)]_{w \in \mathcal{W}}$$

$$\pi(w_{i-N+1}, \dots, w_{i-1}) = w_{i-N+2}, \dots, w_{i-1}$$

- G_u is a probability vector associated with context u

Hierarchical Dirichlet language model

- What is $p(G_u | G_{\pi(u)})$?
- Standard Dirichlet distribution over probability vectors: does not outperform ikn and mkn (MacKay and Peto, 1994)



Bayesian Probability Estimation

Parametrise conditional probabilities

$$p(w_i = w | w_{i-N+1}, \dots, w_{i-1} = u) = G_u(w)$$

$$G_u = [G_u(w)]_{w \in \mathcal{W}}$$

$$\pi(w_{i-N+1}, \dots, w_{i-1}) = w_{i-N+2}, \dots, w_{i-1}$$

- G_u is a probability vector associated with context u

Hierarchical Dirichlet language model

- What is $p(G_u | G_{\pi(u)})$?
- Standard Dirichlet distribution over probability vectors: does not outperform ikn and mkn (MacKay and Peto, 1994)

Hierarchical Pitman-Yor process

- Two-parameter extension of the Dirichlet distribution
- PYP produces power-law distributions
- Outperforms ikn and mkn (Teh, 2006)



Experimental Setup

Mixed-domain data

- Google 1 Billion Words
- Wikipedia November 2013

Sampling

1bws 10% of the words

wps 5% of the words

Domain-specific data

- JRC-ACQUIS: European legislation
- European Medicines Agency documents

Thresholding on 1BW

unigrams Threshold on 100: 99561 types

n-grams Thresholds 2, 5, and 10

Method

ccpp C++ library for nonparametric Bayesian modelling with

Pitman-Yor process priors: <https://github.com/redpony/ccpp>

Colibri Core C++ library for working with basic linguistic constructions such as *n*-grams and skipgrams:

<https://github.com/proycon/colibri-core>


cococpp C++ toolkit for Bayesian language modelling:

<https://github.com/naiaden/cococpp>




Comparing the Models

Relative change in perplexity w.r.t. HPYLM (test on Google 1BW)




Skipping Meals

Effects of threshing (test on Google 1BW)




Learning Curves: Effects of Data Reduction

Testing on 1BW




Learning Curves: Effects of Data Reduction

Testing on JRC




Learning Curves: Effects of Data Reduction

Testing on EMEA



Learning Curves: Effects of Data Reduction



Contribution of Skipgrams

HPYLM

	jrc	1bw	emea	wp
jrc	13	1195	961	1011
1bw	1232	171	1749	724
1bws	768	158	946	493
emea	600	1143	4	843
wps	555	455	1005	217

HPYLM + Skipgrams

jrc	1bw	emea	wp
13	1162	938	1008
728	81	1069	542
751	162	921	507
581	1155	4	842
565	470	990	227



Preliminary conclusions

Sampled versus thresholded corpus

- For in-domain evaluation we need about 2 times the amount of thresholded data
- For cross-domain evaluation we need at least 5 times as much data

When to use thresholding

- Within-domain better with thresholding, because more training data (patterns) like test data
- Cross-domain better without thresholding, because more types (100k vs. 1.1M types)

Skipgrams help in all situations

- Within-domain performance converges with ngrams
- Cross-domain performance increases (30-40% reduction in perplexity)

Intrinsic evaluation

- Apply HPYLM+S to ASR, MT, ...



Choosing a Language Model

Quick turnaround

- ✎ Improved backing-off for m-gram language modeling, Kneser & Ney, 1995

Best results

- ✎ Hierarchical Pitman-Yor process language model, Teh, 2006
- ✎ A parallel training algorithm for hierarchical Pitman-Yor process language models, Huang & Renals, 2009
- ✎ Recurrent neural network language model, Mikolov et alia, 2010

Newest

- ✎ Sparse Non-negative Matrix Language Modeling For Skip-grams, Shazeer et alia, 2014
- ✎ Language Modeling with Power Low Rank Ensembles, Parikh et alia, 2014
- ✎ Word representations via Gaussian embedding, Vilnis and MacCallum, under review

