

ValidateThis! Business Object Integration Guide

This document details the steps required to integrate ValidateThis! into your Business Objects. There is a simpler integration method, which is discussed in the file VTQuickStart.txt.

Note that help is just a post away at <http://groups.google.ca/group/validatethis> or via email at bob.silverberg@gmail.com.

The Framework Files

The framework files are in folder in the distribution called ValidateThis. Either copy the contents of the /ValidateThis folder anywhere on your machine and create a CF mapping to it, or copy it underneath the webroot of your application.

Integrating ValidateThis! With Your Model

This method allows you to integrate the framework into your Business Objects, thereby adding behaviour to them. When you want to perform validation related activity, you can ask your Business Object to do it.

Don't Panic:

If you don't feel like reading the following pages, which contain a pretty detailed description of what's required to get the framework working with your model, just take a look at the BODemo app. It's pretty straightforward and should give you all of the information that you need.

If you'd rather have a more detailed walkthrough of what's required, feel free to continue in with The Rest of the Story.

Also, in an attempt to limit the amount that you *must* read in order to get this working, each section below is broken into two parts. *Quick Steps* give you just the information you need, while *The Details* gives you a bit more information. *Quick Steps* assume you are using Transfer and Coldspring.

The Rest of the Story:

Note that the framework can be used without Transfer or Coldspring, but, as that's what I use, I only have a demo configured to work with those frameworks. For that reason I am going to explain how to get it working with that setup. You should be able to look at the demo app and figure out how to integrate it without Transfer quite easily.

Getting Access to the ValidateThis Service Object

Quick Steps

Add the following bean definition to the Coldspring config file for your application:

```
<bean id="ValidateThis" class="ValidateThis.ValidateThis">
  <constructor-arg name="datasourcePath">
    <ref bean="ValidateThisConfig" />
  </constructor-arg>
</bean>
```

The Details

That's all there is to it!

Defining the ValidateThisConfig Bean

Quick Steps

Add the following bean definition to the Coldspring config file for your application:

```
<bean id="ValidateThisConfig"
class="coldspring.beans.factory.config.MapFactoryBean">
  <property name="sourceMap">
    <map>
      <entry key="BOValidatorPath">
        <value>BOValidator</value>
      </entry>
      <entry key="DefaultJSLib">
        <value>jQuery</value>
      </entry>
      <entry key="JSRoot">
        <value>js</value>
      </entry>
      <entry key="defaultFormName">
        <value>frmMain</value>
      </entry>
    </map>
  </property>
</bean>
```

The Details

You can control some of the framework's behaviour and set default values using the ValidateThisConfig bean. More information about these settings can be found at <http://www.silverwareconsulting.com/index.cfm/2009/3/8/ValidateThis-06--A-Whole-Bunch-of-New-Stuff>.

For the most part, you can just leave the first two entries alone. For the JSRoot entry you should provide the path to your JavaScript files, and for the defaultFormName entry you should provide the name/id that you commonly use for your forms.

Adding Some Extra Beans

Quick Steps

Add the following bean definitions to the Coldspring config file for your application:

```
<bean id="CFMLVersion" class="ValidateThis.util.CFMLVersion">
</bean>

<bean id="onMMHelper" class="ValidateThis.util.onMMHelper">
</bean>
```

The Details

As a result of decoupling the framework from Coldspring, you'll need to add the above-mentioned beans into your Coldspring config in order for your AbstractTransferDecorator to work.

Creating the Validation Rules

Quick Steps

Create an xml file for each of your domain objects that require validations. Name the xml file the same as your Transfer class name (e.g., user.user.xml). Follow the schema found in /ValidateThis/validateThis.xsd. A sample file is available in /BODemo/model/user.user.xml.

The Details

The preferred option for defining validation rules is to record them in an xml file. The framework comes with an XML Schema Definition file (/ValidateThis/validateThis.xsd) which describes the format of the XML file, and can be used in conjunction with your favourite XML editor for validation and code hinting. For a detailed explanation of the schema, refer to this blog posting:

<http://www.silverwareconsulting.com/index.cfm/2008/10/17/ValidateThis--Lets-Talk-Metadata>

Create one xml file per domain object for which you wish to define validation rules. In my setup I use the transfer class name of my domain object as the name of the xml file, but you can theoretically call it anything you like.

You can find a sample xml file in the BODemo directory in /model/user.user.xml

Note that a change is being considered which would move from one xml file per domain object to allowing a developer to define multiple domain objects in a single xml file (like transfer.xml).

Allowing the Framework to Find the XML Files

Quick Steps

The behaviour of the framework has been changed to that it will always look for your xml files in the same directory as your domain objects (i.e., Transfer decorators).

The Details

See above ;-)

Integrating the Framework with Your Domain objects

Quick Steps

Make your Transfer decorators resemble /BODemo/model/AbstractTransferDecorator.cfc. Make your Coldspring beans for Transfer resemble the ones in /BODemo/config/Coldspring.xml.cfm. You may need to look at *The Details* for this one.

The Details

Again, assuming a similar setup to the demo, you are using Transfer decorators as your domain objects. In that case integrating the framework is as easy as adding some methods to your abstract decorator (or all of your decorators if you're not using an abstract decorator – but why wouldn't you be?).

Open the file /model/AbstractTransferDecorator.cfc in the demo app and copy the following methods into your decorator:

- setup – note that you only need the setValidator() method – the setTheGateway() method has nothing to do with the framework
- onMissingMethod – note that if you already have an onMissingMethod in your decorator you'll have to integrate the code from this one into yours
- testCondition
- get/setValidateThis
- get/setValidator
- get/setOnMMHelper
- wrapMe – not officially required, but required to take advantage of the ability to record invalid values in the domain object
- get/setWrapper – not officially required, but required to take advantage of the ability to record invalid values in the domain object

Some of these methods rely on Brian Kotek's excellent Bean Injector to inject singletons into the domain object (and to run setup()). That component is included in the download and is defined in the framework's Coldspring config file, so you will already have a copy of it.

You can find more into on Brian's component here:

<http://coldspringutils.riaforge.org/>

There are a number of ways of integrating the Bean Injector, but I find the easiest is to setup a certain configuration in Coldspring for Transfer and the Bean Injector. There is a sample Coldspring config for the demo app, which is located in BODemo/config/Coldspring.xml.cfm. The following bean definitions are the ones that set up Transfer to use the Bean Injector (sorry for the line-wrap):

```
<bean id="transferFactory" class="transfer.TransferFactory">
  <constructor-arg
name="datasourcePath"><value>/model/config/datasource.xml.cfm</value></
constructor-arg>
  <constructor-arg
name="configPath"><value>/model/config/transfer.xml.cfm</value></constr
uctor-arg>
  <constructor-arg
name="definitionPath"><value>/TransferTemp</value></constructor-arg>
</bean>

<bean id="transfer" factory-bean="transferFactory" factory-
method="getTransfer" />

<bean id="TDOBeanInjectorObserver"
class="ValidateThis.util.TDOBeanInjectorObserver" lazy-init="false">
  <constructor-arg name="transfer"><ref bean="transfer"
/></constructor-arg>
  <constructor-arg
name="afterCreateMethod"><value>Setup</value></constructor-arg>
  <property name="beanInjector">
    <ref bean="beanInjector" />
  </property>
</bean>
```

So you'll want to mimic this setup in order to get ValidateThis integrated with your domain objects.

Optional Populate() Method

Quick Steps

This is optional. See *The Details* for more info.

The Details

There is one other method that I currently use in conjunction with my validation scheme and that's populate(). I do all of my datatype validations during populate, but that is not necessary for the framework to function. The only downside to not taking this approach is that you will lose access to the feature that “saves” values entered for properties that subsequently fail a datatype validation.

I understand that many developers already have some form of populate() in their arsenal, so the framework does not force you to change the way you're currently doing that.

If you do want to take advantage of the feature mentioned above, not only will you need to do something similar to what I'm doing in my populate method, you'll also need to “wrap” your domain object when it's first created. Take a look at the get() method in /model/server/AbstractService.cfc to see how it's done in the demo app.

Getting Client Side Validations to Work

Currently there is one implementation of client-side validations available, which uses the jQuery Validation Plugin.

In order to get these validations working in your app, you'll need to make sure that the following libraries are loaded:

jquery-1.3.2.min.js
jquery.field.min.js
jquery.validate.pack.js

Note that these files can be found in the /ValidateThis/client/jquery/JS folder.

There is a method that will be available via your domain object called `generateInitializationScript()` which will generate all of the JavaScript statements required to load and configure those libraries. You can use that method, or, if you are already loading some of the libraries you can choose to do it manually. If you choose to do it manually it is suggested that you look at the source code for the demo to see what statements need to be there.

Boy, That Seems Like a Lot of Work

It's not really. I've done my best to document things well, which is why there is so much to read, but really, if you are trying to integrate this into a site that's already using Transfer and Coldspring, it shouldn't take that long. Defining your validation rules will take some time and effort, but the plumbing required to get the framework working with your model is actually quite minimal.

Need Help?

I am keen to get feedback on the framework, so I'm happy to help anyone attempting to use it. In the interest of keeping things DRY, I request that any questions/comments you have be directed to a Google group that I set up for the project. The group is located at <http://groups.google.ca/group/validatethis>