

GEMP - UFC Quixadá - ICPC Library

Contents

1 Data Structures

1.1	BIT	1
1.2	BIT 2D	1
1.3	BIT In Range	2
1.4	Dynamic Median	2
1.5	Dynamic Wavelet Tree	2
1.6	Implicit Treap	4
1.7	LiChao Tree	5
1.8	Policy Based Tree	6
1.9	Queue Query	6
1.10	Segment Tree	6
1.11	Segment Tree Iterative	7
1.12	Segment Tree Lazy	7
1.13	Set and Clear	8
1.14	Sparse Table	8
1.15	SQRT Decomposition	9
1.16	SQRT Tree	9
1.17	Stack Query	10
1.18	Treap	11
1.19	Union Find	11
1.20	Wavelet Tree	12

2 Graph Algorithms

3 Dynamic Programming

4 Math

5 Geometry

6 String Algorithms

7 Miscellaneous

8 Theorems and Formulas

1 Data Structures

1.1 BIT

```
#include <bits/stdc++.h>
using namespace std;
class Bit{
private:
    typedef long long t_bit;
    int nBit;
    int nLog;
    vector<t_bit> bit;
public:
    Bit(int n){
        nBit = n;
        nLog = 20;
        bit.resize(nBit+1, 0);
    }
    //1-indexed
    t_bit get(int i){
```

```
t_bit s = 0;
for(; i > 0; i -= (i & -i))
    s += bit[i];
return s;
}
//1-indexed [l, r]
t_bit get(int l, int r){
    return get(r) - get(l-1);
}
//1-indexed
void add(int i, t_bit value){
    for(; i <= nBit; i += (i & -i))
        bit[i] += value;
}
t_bit position(t_bit value){
    t_bit sum = 0;
    int pos = 0;
    for(int i=nLog; i>=0; i--){
        if( (pos + (1 << i) <= nBit) and (sum + bit[pos + (1 << i)] <
            value) ){
            sum += bit[pos + (1 << i)];
            pos += (1 << i);
        }
    }
    return pos + 1;
}
};
```

1.2 BIT 2D

```
#include <bits/stdc++.h>
using namespace std;
class Bit2d{
private:
    typedef long long t_bit;
    vector<vector<t_bit>> bit;
    int nBit, mBit;
public:
    Bit2d(int n, int m){
        nBit = n;
        mBit = m;
        bit.resize(nBit+1, vector<t_bit>(mBit+1, 0));
    }
    //1-indexed
    t_bit get(int i, int j){
        t_bit sum = 0;
        for(int a=i; a > 0; a+=(a & -a))
            for(int b=j; b > 0; b+=(b & -b))
                sum += bit[a][b];
        return sum;
    }
    //1-indexed
    t_bit get(int a1, int b1, int a2, int b2){
        return get(a2, b2) - get(a2, b1-1) - get(a1-1, b2) + get(a1-1, b1-1);
    }
    //1-indexed [i, j]
    void add(int i, int j, t_bit value){
        for(int a=i; a <= nBit; a+=(a & -a))
            for(int b=j; b <= mBit; b+=(b & -b))
```

```

        bit[a][b] += value;
    }
};

```

1.3 BIT In Range

```

#include <bits/stdc++.h>
using namespace std;
class BitRange{
private:
    typedef long long t_bit;
    vector<t_bit> bit1, bit2;
    t_bit get(vector<t_bit> &bit, int i) {
        t_bit sum = 0;
        for(; i > 0; i -= (i & -i))
            sum += bit[i];
        return sum;
    }
    void add(vector<t_bit> &bit, int i, t_bit value) {
        for(; i < (int)bit.size(); i += (i & -i))
            bit[i] += value;
    }
public:
    BitRange(int n) {
        bit1.assign(n + 1, 0);
        bit2.assign(n + 1, 0);
    }
    //1-indexed [i, j]
    void add(int i, int j, t_bit v) {
        add(bit1, i, v);
        add(bit1, j+1, -v);
        add(bit2, i, v*(i-1));
        add(bit2, j+1, -v*j);
    }
    //1-indexed
    t_bit get(int i) {
        return get(bit1, i)*i - get(bit2, i);
    }
    //1-indexed [i, j]
    t_bit get(int i, int j) {
        return get(j) - get(i-1);
    }
};

```

1.4 Dynamic Median

```

#include <bits/stdc++.h>
using namespace std;
class DinamicMedian{
    typedef int t_median;
private:
    priority_queue<t_median> mn;
    priority_queue<t_median, vector<t_median>, greater<t_median> > mx;
public:
    double median() {
        if(mn.size() > mx.size())
            return mn.top();
        else

```

```

        return (mn.top() + mx.top())/2.0;
    }
    void push(t_median x) {
        if(mn.size() <= mx.size())
            mn.push(x);
        else
            mx.push(x);
        if((!mx.empty()) and (!mn.empty())) {
            while(mn.top() > mx.top()) {
                t_median a = mx.top(); mx.pop();
                t_median b = mn.top(); mn.pop();
                mx.push(b);
                mn.push(a);
            }
        }
    }
};

```

1.5 Dynamic Wavelet Tree

```

#include <bits/stdc++.h>
using namespace std;
struct SplayTree{
    struct Node{
        int x, y, s;
        Node *p = 0;
        Node *l = 0;
        Node *r = 0;
        Node(int v) {
            x = v;
            y = v;
            s = 1;
        }
        void upd() {
            s = 1;
            y = x;
            if(l) {
                y += l->y;
                s += l->s;
            }
            if(r) {
                y += r->y;
                s += r->s;
            }
        }
        int left_size() {
            return l ? l->s : 0;
        }
    };
    Node *root = 0;
    void rot(Node *c) {
        auto p = c->p;
        auto g = p->p;
        if(g) (g->l == p ? g->l : g->r) = c;
        if(p->l == c) {
            p->l = c->r;
            c->r = p;
            if(p->l) p->l->p = p;
        } else {
            p->r = c->l;

```

```

    c->l = p;
    if(p->r) p->r->p = p;
}
p->p = c;
c->p = g;
p->upd();
c->upd();
}
void splay(Node *c) {
    while(c->p) {
        auto p = c->p;
        auto g = p->p;
        if(g) rot((g->l == p) == (p->l == c) ? p : c);
        rot(c);
    }
    c->upd();
    root = c;
}
Node* join(Node *l, Node *r) {
    if(not l) return r;
    if(not r) return l;
    while(l->r) l = l->r;
    splay(l);
    r->p = l;
    l->r = r;
    l->upd();
    return l;
}
pair<Node*, Node*> split(Node *p, int idx) {
    if(not p)
        return make_pair(nullptr, nullptr);
    if(idx < 0)
        return make_pair(nullptr, p);
    if(idx >= p->s)
        return make_pair(p, nullptr);
    for(int lf = p->left_size(); idx != lf; lf = p->left_size()) {
        if(idx < lf)
            p = p->l;
        else
            p = p->r, idx -= lf+1;
    }
    splay(p);
    Node *l = p;
    Node *r = p->r;
    if(r) {
        l->r = r->p = 0;
        l->upd();
    }
    return make_pair(l, r);
}
Node* get(int idx) {
    auto p = root;
    for(int lf = p->left_size(); idx != lf; lf = p->left_size()) {
        if(idx < lf)
            p = p->l;
        else
            p = p->r, idx -= lf+1;
    }
    splay(p);
    return p;
}

```

```

int insert(int idx, int x) {
    Node *l, *r;
    tie(l, r) = split(root, idx-1);
    int v = l ? l->y : 0;
    root = join(l, join(new Node(x), r));
    return v;
}
void erase(int idx) {
    Node *l, *r;
    tie(l, r) = split(root, idx);
    root = join(l->l, r);
    delete l;
}
int rank(int idx) {
    Node *l, *r;
    tie(l, r) = split(root, idx);
    int x = (l && l->l ? l->l->y : 0);
    root = join(l, r);
    return x;
}
int operator[](int idx) {
    return rank(idx);
}
~SplayTree() {
    if(!root)
        return;
    vector<Node*> nodes {root};
    while(nodes.size()) {
        auto u = nodes.back();
        nodes.pop_back();
        if(u->l) nodes.emplace_back(u->l);
        if(u->r) nodes.emplace_back(u->r);
        delete u;
    }
}
};
class WaveletTree{
private:
    int lo, hi;
    WaveletTree *l = 0;
    WaveletTree *r = 0;
    SplayTree b;
public:
    WaveletTree(int min_value, int max_value) {
        lo = min_value;
        hi = max_value;
        b.insert(0, 0);
    }
    ~WaveletTree() {
        delete l;
        delete r;
    }
    //0-indexed
    void insert(int idx, int x) {
        if(lo >= hi)
            return;
        int mid = (lo + hi - 1) / 2;
        if(x <= mid) {
            l = 1 ? new WaveletTree(lo, mid);
            l->insert(b.insert(idx, 1), x);
        } else {

```

```

    r = r ?: new WaveletTree(mid+1, hi);
    r->insert(idx - b.insert(idx, 0), x);
}
}
//0-indexed
void erase(int idx) {
    if(lo == hi)
        return;
    auto p = b.get(idx);
    int lf = p->l ? p->l->y : 0;
    int x = p->x;
    b.erase(idx);
    if(x == 1)
        l->erase(lf);
    else
        r->erase(idx-lf);
}
//kth smallest element in range [i, j]
//0-indexed
int kth(int i, int j, int k) {
    if(i >= j)
        return 0;
    if(lo == hi)
        return lo;
    int x = b.rank(i);
    int y = b.rank(j);
    if(k <= y-x)
        return l->kth(x, y, k);
    else
        return r->kth(i-x, j-y, k-(y-x));
}
//Amount of numbers in the range [i, j] Less than or equal to k
//0-indexed
int lte(int i, int j, int k) {
    if(i >= j or k < lo) return 0;
    if(hi <= k) return j - i;
    int x = b.rank(i);
    int y = b.rank(j);
    return l->lte(x, y, k) + r->lte(i-x, j-y, k);
}
//Amount of numbers in the range [i, j] equal to k
//0-indexed
int count(int i, int j, int k) {
    if(i >= j or k < lo or k > hi) return 0;
    if(lo == hi) return j - i;
    int mid = (lo + hi - 1)/2;
    int x = b.rank(i);
    int y = b.rank(j);
    if(k <= mid) return l->count(x, y, k);
    return r->count(i-x, j-y, k);
}
//0-indexed
int get(int idx){
    return kth(idx, idx+1, 1);
}
};

```

1.6 Implicit Treap

```
#include <bits/stdc++.h>
```

```

using namespace std;
class ImplicitTreap {
private:
    typedef int t_treap;
    const t_treap neutral = 0;
    inline t_treap join(t_treap a, t_treap b, t_treap c){
        return a + b + c;
    }
    struct Node{
        int y, size;
        t_treap v, op_value;
        bool rev;
        Node *l, *r;
        Node(t_treap _v){
            v = op_value = _v;
            y = rand();
            size = 1;
            l = r = NULL;
            rev = false;
        }
    };
    Node* root;
    int size(Node* t) { return t ? t->size : 0; }
    t_treap op_value(Node* t) { return t ? t->op_value : neutral; }
    Node* refresh(Node* t) {
        if (t == NULL) return t;
        t->size = 1 + size(t->l) + size(t->r);
        t->op_value = join(t->v, op_value(t->l), op_value(t->r));
        if (t->l != NULL) t->l->rev ^= t->rev;
        if (t->r != NULL) t->r->rev ^= t->rev;
        if (t->rev) {
            swap(t->l, t->r);
            t->rev = false;
        }
        return t;
    }
    void split(Node* &t, int k, Node* &a, Node* &b) {
        refresh(t);
        Node * aux;
        if (!t) a = b = NULL;
        else if (size(t->l) < k) {
            split(t->r, k-size(t->l)-1, aux, b);
            t->r = aux;
            a = refresh(t);
        }
        else {
            split(t->l, k, a, aux);
            t->l = aux;
            b = refresh(t);
        }
    }
    Node* merge(Node* a, Node* b) {
        refresh(a); refresh(b);
        if (!a || !b) return a ? a : b;
        if (a->y < b->y) {
            a->r = merge(a->r, b);
            return refresh(a);
        }
        else {
            b->l = merge(a, b->l);
            return refresh(b);
        }
    }
};

```

```

    }
}
Node* at(Node* t, int n) {
    if (!t) return t;
    refresh(t);
    if (n < size(t->l)) return at(t->l, n);
    else if (n == size(t->l)) return t;
    else return at(t->r, n-size(t->l)-1);
}
void del(Node* &t) {
    if (!t) return;
    if (t->l) del(t->l);
    if (t->r) del(t->r);
    delete t;
    t = NULL;
}
public:
    ImplicitTreap() : root(NULL) {
        srand(time(NULL));
    }
    ~ImplicitTreap() { clear(); }
    void clear() { del(root); }
    int size() { return size(root); }
    //0-indexed
    bool insert(int n, int v) {
        Node *a, *b;
        split(root, n, a, b);
        root = merge(merge(a, new Node(v)), b);
        return true;
    }
    //0-indexed
    bool erase(int n) {
        Node *a, *b, *c, *d;
        split(root, n, a, b);
        split(b, 1, c, d);
        root = merge(a, d);
        if (c == NULL) return false;
        delete c;
        return true;
    }
    //0-indexed
    t_treap at(int n) {
        Node* ans = at(root, n);
        return ans ? ans->v : -1;
    }
    //0-indexed [l, r]
    t_treap query(int l, int r) {
        if (l > r) swap(l, r);
        Node *a, *b, *c, *d;
        split(root, l, a, d);
        split(d, r-l+1, b, c);
        t_treap ans = op_value(b);
        root = merge(a, merge(b, c));
        return ans;
    }
    //0-indexed [l, r]
    void reverse(int l, int r) {
        if (l > r) swap(l, r);
        Node *a, *b, *c, *d;
        split(root, l, a, d);
        split(d, r-l+1, b, c);

```

```

        if (b != NULL) b->rev ^= 1;
        root = merge(a, merge(b, c));
    }
};

```

1.7 LiChao Tree

```

#include <bits/stdc++.h>
using namespace std;
const int INF = 0x3f3f3f3f;
class LiChaoTree{
private:
    typedef int t_line;
    struct Line{
        t_line k, b;
        Line() {}
        Line(t_line k, t_line b): k(k), b(b) {}
    };
    int n_tree, min_x, max_x;
    vector<Line> li_tree;
    t_line f(Line l, int x){
        return l.k*x + l.b;
    }
    void add(Line nw, int v, int l, int r) {
        int m = (l + r) / 2;
        bool lef = f(nw, l) > f(li_tree[v], l);
        bool mid = f(nw, m) > f(li_tree[v], m);
        if(mid)
            swap(li_tree[v], nw);
        if(r - l == 1)
            return;
        else if(lef != mid)
            add(nw, 2 * v, l, m);
        else
            add(nw, 2 * v + 1, m, r);
    }
    int get(int x, int v, int l, int r) {
        int m = (l + r) / 2;
        if(r - l == 1)
            return f(li_tree[v], x);
        else if(x < m)
            return max(f(li_tree[v], x), get(x, 2 * v, l, m));
        else
            return max(f(li_tree[v], x), get(x, 2 * v + 1, m, r));
    }
public:
    LiChaoTree(int mn_x, int mx_x){
        min_x = mn_x;
        max_x = mx_x;
        n_tree = max_x-min_x+5;
        li_tree.resize(4*n_tree, Line(0, -INF));
    }
    void add(t_line k, t_line b){
        add(Line(k, b), 1, min_x, max_x);
    }
    t_line get(int x){
        return get(x, 1, min_x, max_x);
    }
};

```

1.8 Policy Based Tree

```
#include <bits/stdc++.h>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
using namespace std;
typedef tree<int, null_type, less<int>, rb_tree_tag,
tree_order_statistics_node_update> OrderedSet;
typedef tree<int, int, less<int>, rb_tree_tag,
tree_order_statistics_node_update> OrderedMap;
//order_of_key(k) : Number of items strictly smaller than k .
//find_by_order(k) : K-th element in a set (counting from zero).
```

1.9 Queue Query

```
#include <bits/stdc++.h>
using namespace std;
class QueueQuery{
private:
    typedef int t_queue;
    stack<pair<t_queue, t_queue> > s1, s2;
    t_queue cmp(t_queue a, t_queue b){
        return min(a, b);
    }
    void move(){
        if (s2.empty()) {
            while (!s1.empty()) {
                t_queue element = s1.top().first;
                s1.pop();
                t_queue result = s2.empty() ? element : cmp(element, s2.top().second);
                s2.push({element, result});
            }
        }
    }
public:
    void push(t_queue x){
        t_queue result = s1.empty() ? x : cmp(x, s1.top().second);
        s1.push({x, result});
    }
    void pop(){
        move();
        s2.pop();
    }
    t_queue front(){
        move();
        return s2.top().first;
    }
    t_queue query(){
        if (s1.empty() || s2.empty())
            return s1.empty() ? s2.top().second : s1.top().second;
        else
            return cmp(s1.top().second, s2.top().second);
    }
    t_queue size(){
        return s1.size() + s2.size();
    }
}
```

};

1.10 Segment Tree

```
#include <bits/stdc++.h>
using namespace std;
class SegTree{
private:
    typedef long long Node;
    Node neutral = 0;
    vector<Node> st;
    vector<int> v;
    int n;
    Node join(Node a, Node b){
        return (a + b);
    }
    void build(int node, int i, int j){
        if(i == j){
            st[node] = v[i];
            return;
        }
        int m = (i+j)/2;
        int l = (node<<1);
        int r = l + 1;
        build(l, i, m);
        build(r, m+1, j);
        st[node] = join(st[l], st[r]);
    }
    Node query(int node, int i, int j, int a, int b){
        if( (i>b) or (j<a) )
            return neutral;
        if( (a<=i) and (j<=b) )
            return st[node];
        int m = (i+j)/2;
        int l = (node<<1);
        int r = l + 1;
        return join( query(l, i, m, a, b), query(r, m+1, j, a, b) );
    }
    void update(int node, int i, int j, int idx, Node value){
        if(i == j){
            st[node] = value;
            return;
        }
        int m = (i+j)/2;
        int l = (node<<1);
        int r = l + 1;
        if(idx <= m)
            update(l, i, m, idx, value);
        else
            update(r, m+1, j, idx, value);
        st[node] = join(st[l], st[r]);
    }
public:
    template <class MyIterator>
    SegTree(MyIterator begin, MyIterator end){
        n = end-begin;
        v = vector<int>(begin, end);
        st.resize(4*n + 5);
        build(1, 0, n-1);
    }
}
```

```
//0-indexed [a, b]
Node query(int a, int b){
    return query(1, 0, n-1, a, b);
}
//0-indexed
void update(int idx, int value){
    update(1, 0, n-1, idx, value);
}
};
```

1.11 Segment Tree Iterative

```
#include <bits/stdc++.h>
using namespace std;
class SegTreeIterative{
private:
    typedef long long Node;
    Node neutral = 0;
    vector<Node> st;
    int n;
    inline Node join(Node a, Node b){
        return a + b;
    }
public:
    template <class MyIterator>
    SegTreeIterative(MyIterator begin, MyIterator end) {
        int sz = end-begin;
        for (n = 1; n < sz; n <= 1);
        st.assign(n < 1, neutral);
        for(int i=0; i<sz; i++, begin++) st[i+n] = (*begin);
        for(int i=n+sz-1; i>1; i--)
            st[i>>1] = join(st[i>>1], st[i]);
    }
    //0-indexed
    void update(int i, Node x) {
        st[i += n] = x;
        for (i >>= 1; i; i >>= 1)
            st[i] = join(st[i<<1], st[1+(i<<1)]);
    }
    //0-indexed [l, r]
    Node query(int l, int r) {
        Node ans = neutral;
        for (l+=n, r+=n+1; l<r; l>>=1, r>>=1) {
            if (l & 1) ans = join(ans, st[l++]);
            if (r & 1) ans = join(ans, st[--r]);
        }
        return ans;
    }
};
```

1.12 Segment Tree Lazy

```
#include <bits/stdc++.h>
using namespace std;
class SegTreeLazy{
private:
    typedef long long Node;
    vector<Node> st;
```

```
vector<long long> lazy;
vector<int> v;
int n;
Node neutral = 0;
inline Node join(Node a, Node b){
    return a+b;
}
inline void upLazy(int &node, int &i, int &j){
    if(lazy[node] != 0){
        st[node] += lazy[node]*(j-i+1);
        //tree[node] += lazy[node];
        if(i != j){
            lazy[(node<<1)] += lazy[node];
            lazy[(node<<1)+1] += lazy[node];
        }
        lazy[node] = 0;
    }
}
void build(int node, int i, int j){
    if(i == j){
        st[node] = v[i];
        return;
    }
    int m = (i+j)/2;
    int l = (node<<1);
    int r = l + 1;
    build(l, i, m);
    build(r, m+1, j);
    st[node] = join(st[l], st[r]);
}
Node query(int node, int i, int j, int a, int b){
    upLazy(node, i, j);
    if( (i>b) or (j<a) )
        return neutral;
    if( (a<=i) and (j<=b) ){
        return st[node];
    }
    int m = (i+j)/2;
    int l = (node<<1);
    int r = l + 1;
    return join( query(l, i, m, a, b), query(r, m+1, j, a, b) );
}
void update(int node, int i, int j, int a, int b, int value){
    upLazy(node, i, j);
    if( (i>j) or (i>b) or (j<a) )
        return;
    if( (a<=i) and (j<=b) ){
        lazy[node] = value;
        upLazy(node, i, j);
    }else{
        int m = (i+j)/2;
        int l = (node<<1);
        int r = l + 1;
        update(l, i, m, a, b, value);
        update(r, m+1, j, a, b, value);
        st[node] = join(st[l], st[r]);
    }
}
public:
    template <class MyIterator>
    SegTreeLazy(MyIterator begin, MyIterator end){
```

```

n = end-begin;
v = vector<int>(begin, end);
st.resize(4*n + 5);
lazy.assign(4*n + 5, 0);
build(1, 0, n-1);
}
//0-indexed [a, b]
Node query(int a, int b){
    return query(1, 0, n-1, a, b);
}
//0-indexed [a, b]
void update(int a, int b, int value){
    update(1, 0, n-1, a, b, value);
}
};

```

1.13 Set and Clear

```

#include <bits/stdc++.h>
using namespace std;
class SetAndClear{
private:
    typedef long long ll;
    typedef pair<ll, ll> pii;
    struct cmp{
        bool operator()(pii a, pii b){
            return a.second < b.second;
        }
    };
    std::set<pii, cmp> st;
    ll ans;
public:
    SetAndClear(ll first, ll last){
        ans = last - first + 1LL;
        clear(first, last);
    }
    //set [a, b]
    void set(ll a, ll b){
        auto p = st.upper_bound(pii(0, a-1LL));
        if( (p == st.end()) or (p->first > b) ){
            return;
        }
        ll x = p->first;
        ll y = p->second;
        ans += (y - x + 1LL);
        p = st.erase(p);
        if(x <= (a - 1LL)){
            ans -= (a - x);
            st.insert(pii(x, a - 1LL));
        }
        if( (b + 1LL) <= y){
            ans -= (y - b);
            st.insert(pii(b + 1LL, y));
        }
        while( (p != st.end()) and (p->first <= b) ){
            x = p->first;
            y = p->second;
            ans += (y - x + 1LL);
            if(y > b){
                ans -= (y - b);
            }
        }
    }
};

```

```

        st.erase(p);
        st.insert(pii(b + 1LL, y));
        break;
    }else{
        p = st.erase(p);
    }
}
}
//clear [a, b]
void clear(ll a, ll b){
    auto p = st.upper_bound(pii(0, a-1LL));
    if( (p == st.end()) or (p->first > b) ){
        ans -= (b - a + 1LL);
        st.insert(pii(a, b));
    }else{
        ll x = p->first;
        ll y = p->second;
        ans += (y - x + 1LL);
        p = st.erase(p);
        a = min(x, a);
        b = max(y, b);
        while( (p != st.end()) and (p->first <= b) ){
            x = p->first;
            y = p->second;
            ans += (y - x + 1LL);
            a = min(x, a);
            b = max(y, b);
            p = st.erase(p);
        }
        ans -= (b - a + 1LL);
        st.insert(pii(a, b));
    }
}
ll count(){
    return ans;
}
};

```

1.14 Sparse Table

```

#include <bits/stdc++.h>
using namespace std;
class SparseTable{
private:
    typedef int t_st;
    vector<vector<t_st> > st;
    vector<int> log2;
    t_st neutral = 0x3f3f3f3f;
    int nLog;
    t_st join(t_st a, t_st b){
        return min(a, b);
    }
public:
    template <class MyIterator>
    SparseTable(MyIterator begin, MyIterator end){
        int n = end-begin;
        nLog = 20;
        log2.resize(n+1);
        log2[1] = 0;
    }
};

```



```

    for (int i = 2; i <= n; i++)
        log2[i] = log2[i/2] + 1;
    st.resize(n, vector<t_st>(nLog, neutral));
    for (int i=0; i<n; i++, begin++){
        st[i][0] = (*begin);
        for (int j=1; j<nLog; j++){
            for (int i=0; (i+(1<<(j-1))) < n; i++){
                st[i][j] = join(st[i][j-1], st[i+(1<<(j-1))][j-1]);
            }
        }
    }
    //0-indexed [a, b]
    t_st query(int a, int b){
        int d = b - a + 1;
        t_st ans = neutral;
        for (int j=nLog-1; j>=0; j--){
            if (d & (1<<j)){
                ans = join(ans, st[a][j]);
                a = a + (1<<j);
            }
        }
        return ans;
    }
    //0-indexed [a, b]
    t_st queryRMQ(int a, int b){
        int j = log2[b - a + 1];
        return join(st[a][j], st[b - (1 << j) + 1][j]);
    }
};

```

1.15 Sqrt Decomposition

```

#include <bits/stdc++.h>
using namespace std;
struct SqrtDecomposition{
    typedef long long t_sqrt;
    int sqrtLen;
    vector<t_sqrt> block;
    vector<t_sqrt> v;
    template <class MyIterator>
    SqrtDecomposition(MyIterator begin, MyIterator end){
        int n = end-begin;
        sqrtLen = (int) sqrt (n + .0) + 1;
        v.resize(n);
        block.resize(sqrtLen + 5);
        for (int i=0; i<n; i++, begin++){
            v[i] = (*begin);
            block[i / sqrtLen] += v[i];
        }
    }
    //0-indexed
    void update(int idx, t_sqrt new_value){
        t_sqrt d = new_value - v[idx];
        v[idx] += d;
        block[idx/sqrtLen] += d;
    }
    //0-indexed [l, r]
    t_sqrt query(int l, int r){
        t_sqrt sum = 0;
        int c_l = l/sqrtLen, c_r = r/sqrtLen;
        if (c_l == c_r){
            for (int i=l; i<=r; i++)

```

```

                sum += v[i];
        } else {
            for (int i=l, end=(c_l+1)*sqrtLen-1; i<=end; i++)
                sum += v[i];
            for (int i=c_l+1; i<=c_r-1; i++)
                sum += block[i];
            for (int i=c_r*sqrtLen; i<=r; i++)
                sum += v[i];
        }
        return sum;
    }
};

```

1.16 Sqrt Tree

```

#include <bits/stdc++.h>
using namespace std;
class SqrtTree{
private:
    typedef long long t_sqrt;
    t_sqrt op(const t_sqrt &a, const t_sqrt &b){
        return a | b;
    }
    inline int log2Up(int n) {
        int res = 0;
        while ((1 << res) < n)
            res++;
        return res;
    }
    int n, lg, indexSz;
    vector<t_sqrt> v;
    vector<int> clz, layers, onLayer;
    vector< vector<t_sqrt> > pref, suf, between;
    inline void buildBlock(int layer, int l, int r) {
        pref[layer][l] = v[l];
        for (int i = l+1; i < r; i++)
            pref[layer][i] = op(pref[layer][i-1], v[i]);
        suf[layer][r-1] = v[r-1];
        for (int i = r-2; i >= l; i--)
            suf[layer][i] = op(v[i], suf[layer][i+1]);
    }
    inline void buildBetween(int layer, int lBound, int rBound, int
        betweenOffs) {
        int bSzLog = (layers[layer]+1) >> 1;
        int bCntLog = layers[layer] >> 1;
        int bSz = 1 << bSzLog;
        int bCnt = (rBound - lBound + bSz - 1) >> bSzLog;
        for (int i = 0; i < bCnt; i++) {
            t_sqrt ans;
            for (int j = i; j < bCnt; j++) {
                t_sqrt add = suf[layer][lBound + (j << bSzLog)];
                ans = (i == j) ? add : op(ans, add);
                between[layer-1][betweenOffs + lBound + (i << bCntLog) + j] =
                    ans;
            }
        }
    }
    inline void buildBetweenZero() {
        int bSzLog = (lg+1) >> 1;
        for (int i = 0; i < indexSz; i++) {

```

```

    v[n+i] = suf[0][i << bSzLog];
}
build(1, n, n + indexSz, (1 << lg) - n);
}
inline void updateBetweenZero(int bid) {
    int bSzLog = (lg+1) >> 1;
    v[n+bid] = suf[0][bid << bSzLog];
    update(1, n, n + indexSz, (1 << lg) - n, n+bid);
}
void build(int layer, int lBound, int rBound, int betweenOffs) {
    if (layer >= (int)layers.size())
        return;
    int bSz = 1 << ((layers[layer]+1) >> 1);
    for (int l = lBound; l < rBound; l += bSz) {
        int r = min(l + bSz, rBound);
        buildBlock(layer, l, r);
        build(layer+1, l, r, betweenOffs);
    }
    if (layer == 0)
        buildBetweenZero();
    else
        buildBetween(layer, lBound, rBound, betweenOffs);
}
void update(int layer, int lBound, int rBound, int betweenOffs, int
x) {
    if (layer >= (int)layers.size())
        return;
    int bSzLog = (layers[layer]+1) >> 1;
    int bSz = 1 << bSzLog;
    int blockIdx = (x - lBound) >> bSzLog;
    int l = lBound + (blockIdx << bSzLog);
    int r = min(l + bSz, rBound);
    buildBlock(layer, l, r);
    if (layer == 0)
        updateBetweenZero(blockIdx);
    else
        buildBetween(layer, lBound, rBound, betweenOffs);
    update(layer+1, l, r, betweenOffs, x);
}
inline t_sqrt query(int l, int r, int betweenOffs, int base) {
    if (l == r)
        return v[l];
    if (l + 1 == r)
        return op(v[l], v[r]);
    int layer = onLayer[clz[(l - base) ^ (r - base)]];
    int bSzLog = (layers[layer]+1) >> 1;
    int bCntLog = layers[layer] >> 1;
    int lBlock = ((l - base) >> layers[layer]) << layers[layer] +
base;
    int lBlock = ((l - lBound) >> bSzLog) + 1;
    int rBlock = ((r - lBound) >> bSzLog) - 1;
    t_sqrt ans = suf[layer][l];
    if (lBlock <= rBlock) {
        t_sqrt add;
        if (layer == 0)
            add = query(n + lBlock, n + rBlock, (1 << lg) - n, n);
        else
            add = between[layer-1][betweenOffs + lBlock <<
bCntLog) + rBlock];
        ans = op(ans, add);
    }
}

```

```

    ans = op(ans, pref[layer][r]);
    return ans;
}
public:
    template <class MyIterator>
    SqrtTree(MyIterator begin, MyIterator end) {
        n = end-begin;
        v.resize(n);
        for (int i=0; i<n; i++, begin++)
            v[i] = (*begin);
        lg = log2Up(n);
        clz.resize(1<<lg);
        onLayer.resize(lg + 1);
        clz[0] = 0;
        for (int i = 1; i < (int)clz.size(); i++)
            clz[i] = clz[i >> 1] + 1;
        int tlg = lg;
        while (tlg > 1) {
            onLayer[tlg] = (int)layers.size();
            layers.push_back(tlg);
            tlg = (tlg+1) >> 1;
        }
        for (int i = lg-1; i >= 0; i--)
            onLayer[i] = max(onLayer[i], onLayer[i+1]);
        int betweenLayers = max(0, (int)layers.size() - 1);
        int bSzLog = (lg+1) >> 1;
        int bSz = 1 << bSzLog;
        indexSz = (n + bSz - 1) >> bSzLog;
        v.resize(n + indexSz);
        pref.assign(layers.size(), vector<t_sqrt>(n + indexSz));
        suf.assign(layers.size(), vector<t_sqrt>(n + indexSz));
        between.assign(betweenLayers, vector<t_sqrt>((1 << lg) + bSz));
        build(0, 0, n, 0);
    }
    //0-indexed
    inline void update(int x, const t_sqrt &item) {
        v[x] = item;
        update(0, 0, n, 0, x);
    }
    //0-indexed [l, r]
    inline t_sqrt query(int l, int r) {
        return query(l, r, 0, 0);
    }
};

```

1.17 Stack Query

```

#include <bits/stdc++.h>
using namespace std;
struct StackQuery{
    typedef int t_stack;
    stack<pair<t_stack, t_stack> > st;
    t_stack cmp(t_stack a, t_stack b){
        return min(a, b);
    }
    void push(t_stack x){
        t_stack new_value = st.empty() ? x : cmp(x, st.top().second);
        st.push({x, new_value});
    }
    void pop() {

```

```

    st.pop();
}
t_stack top(){
    return st.top().first;
}
t_stack query(){
    return st.top().second;
}
t_stack size(){
    return st.size();
}
};

```

1.18 Treap

```

#include <bits/stdc++.h>
using namespace std;
class Treap {
private:
    typedef int t_treap;
    struct Node {
        t_treap x, y, size;
        Node *l, *r;
        Node(t_treap _x) : x(_x), y(rand()), size(1), l(NULL), r(NULL){}
    };
    Node* root;
    int size(Node* t) { return t ? t->size : 0; }
    Node* refresh(Node* t) {
        if (!t) return t;
        t->size = 1 + size(t->l) + size(t->r);
        return t;
    }
    void split(Node* &t, t_treap k, Node* &a, Node* &b) {
        Node* aux;
        if (!t){
            a = b = NULL;
        } else if (t->x < k) {
            split(t->r, k, aux, b);
            t->r = aux;
            a = refresh(t);
        } else {
            split(t->l, k, a, aux);
            t->l = aux;
            b = refresh(t);
        }
    }
    Node* merge(Node* a, Node* b) {
        if (!a || !b) return a ? a : b;
        if (a->y < b->y) {
            a->r = merge(a->r, b);
            return refresh(a);
        }
        else {
            b->l = merge(a, b->l);
            return refresh(b);
        }
    }
    Node* count(Node* t, t_treap k) {
        if (!t) return NULL;
        else if (k < t->x) return count(t->l, k);

```

```

        else if (k == t->x) return t;
        else return count(t->r, k);
    }
    Node* nth(Node* t, int n) {
        if (!t) return NULL;
        if (n <= size(t->l)) return nth(t->l, n);
        else if (n == size(t->l) + 1) return t;
        else return nth(t->r, n-size(t->l)-1);
    }
    void del(Node* &t) {
        if (!t) return;
        if (t->l) del(t->l);
        if (t->r) del(t->r);
        delete t;
        t = NULL;
    }
public:
    Treap() : root(NULL) {}
    ~Treap() { clear(); }
    void clear() { del(root); }
    int size() { return size(root); }
    bool count(t_treap k) { return count(root, k) != NULL; }
    bool insert(t_treap k) {
        if (count(k)) return false;
        Node *a, *b;
        split(root, k, a, b);
        root = merge(merge(a, new Node(k)), b);
        return true;
    }
    bool erase(t_treap k) {
        Node *f = count(root, k);
        if (!f) return false;
        Node *a, *b, *c, *d;
        split(root, k, a, b);
        split(b, k+1, c, d);
        root = merge(a, d);
        delete f;
        return true;
    }
    //1-indexed
    t_treap nth(int n) {
        Node* ans = nth(root, n);
        return ans ? ans->x : -1;
    }
};

```

1.19 Union Find

```

#include <bits/stdc++.h>
using namespace std;
class UnionFind{
private:
    vector<int> p, w, sz;
public:
    UnionFind(int n){
        w.resize(n+1, 1);
        sz.resize(n+1, 1);
        p.resize(n+1);
        for(int i=0; i<=n; i++)
            p[i] = i;
    }

```

```

}
int find(int x){
    if(p[x] == x)
        return x;
    return p[x] = find(p[x]);
}
void join(int x, int y){
    x = find(x);
    y = find(y);
    if(x == y)
        return;
    if(w[x] > w[y])
        swap(x, y);
    p[x] = y;
    sz[y] += sz[x];
    if(w[x] == w[y])
        w[y]++;
}
bool isSame(int x, int y){
    return find(x) == find(y);
}
int size(int x){
    return sz[find(x)];
}
};

```

1.20 Wavelet Tree

```

#include <bits/stdc++.h>
using namespace std;
struct WaveletTree{
private:
    typedef int t_wavelet;
    t_wavelet lo, hi;
    WaveletTree *l, *r;
    vector<int> a, b;
public:
    template <class MyIterator>
    WaveletTree(MyIterator begin, MyIterator end, t_wavelet minX,
        t_wavelet maxX){
        lo = minX, hi = maxX;
        if(lo == hi or begin >= end) return;
        t_wavelet mid = (lo+hi-1)/2;
        auto f = [mid](int x){
            return x <= mid;
        };
        a.reserve(end-begin+1);
        b.reserve(end-begin+1);
        a.push_back(0);
        b.push_back(0);
        for(auto it = begin; it != end; it++){
            a.push_back(a.back() + f(*it));
            b.push_back(b.back() + !f(*it));
        }
        auto pivot = stable_partition(begin, end, f);
        l = new WaveletTree(begin, pivot, lo, mid);
        r = new WaveletTree(pivot, end, mid+1, hi);
    }
};

```

```

}
//kth smallest element in range [i, j]
//1-indexed
int kth(int i, int j, int k){
    if(i > j) return 0;
    if(lo == hi) return lo;
    int inLeft = a[j] - a[i-1];
    int i1 = a[i-1] + 1, j1 = a[j];
    int i2 = b[i-1] + 1, j2 = b[j];
    if(k <= inLeft) return l->kth(i1, j1, k);
    return r->kth(i2, j2, k-inLeft);
}
//Amount of numbers in the range [i, j] Less than or equal to k
//1-indexed
int lte(int i, int j, int k) {
    if(i > j or k < lo) return 0;
    if(hi <= k) return j - i + 1;
    int i1 = a[i-1] + 1, j1 = a[j];
    int i2 = b[i-1] + 1, j2 = b[j];
    return l->lte(i1, j1, k) + r->lte(i2, j2, k);
}
//Amount of numbers in the range [i, j] equal to k
//1-indexed
int count(int i, int j, int k) {
    if(i > j or k < lo or k > hi) return 0;
    if(lo == hi) return j - i + 1;
    int mid = (lo+hi-1)/2;
    int i1 = a[i-1]+1, j1 = a[j];
    int i2 = b[i-1]+1, j2 = b[j];
    if(k <= mid) return l->count(i1, j1, k);
    return r->count(i2, j2, k);
}
~WaveletTree() {
    delete l;
    delete r;
}
};

```

2 Graph Algorithms

3 Dynamic Programming

4 Math

5 Geometry

6 String Algorithms

7 Miscellaneous

8 Theorems and Formulas