

Verifying Robustness of Programs Under Structural Perturbations

Clay Thomas and Jacob Bond

December 1, 2017

Motivation

- An attempt to synthesize the max function using PBE:
 - $(13, 15) \mapsto 15$
 - $(-23, 19) \mapsto 19$
 - $(-75, -13) \mapsto -13$

Motivation

- An attempt to synthesize the max function using PBE:
 - $(13, 15) \mapsto 15$
 - $(-23, 19) \mapsto 19$
 - $(-75, -13) \mapsto -13$
- Synthesized program: `P(a,b):=return b`

Motivation

- An attempt to synthesize the max function using PBE:
 - $(13, 15) \mapsto 15$
 - $(-23, 19) \mapsto 19$
 - $(-75, -13) \mapsto -13$
- Synthesized program: $P(a, b) := \text{return } b$
- Neither synthesized program, nor synthesizer are *robust*

Robustness

- Robustness: behaving predictably on uncertain inputs [?]

Robustness

- Robustness: behaving predictably on uncertain inputs [?]
- $P(13,15) \neq P(15,13)$

Robustness

- Robustness: behaving predictably on uncertain inputs [?]
- $P(13, 15) \neq P(15, 13)$
- - $(15, 13) \mapsto 15$
 - $(-23, 19) \mapsto 19$
 - $(-13, -75) \mapsto -13$

would synthesize very different program

Robustness

- Robustness: behaving predictably on uncertain inputs [?]
- $P(13, 15) \neq P(15, 13)$
- - $(15, 13) \mapsto 15$
 - $(-23, 19) \mapsto 19$
 - $(-13, -75) \mapsto -13$would synthesize very different program
- Synthesize a robust program or develop robust synthesizer

Robustness Properties

- Continuity: small change to input \Rightarrow small change to output

`Sort([1,4,3,6])=[1,3,4,6]`

`Sort([2,3,3,5])=[2,3,3,5]`

Robustness Properties

- Continuity: small change to input \Rightarrow small change to output

`Sort([1,4,3,6])=[1,3,4,6]`

`Sort([2,3,3,5])=[2,3,3,5]`

- Permutation: permuting input permutes the output

`Find([1,4,3,6], 4)=1`

$\sigma = (0 \mapsto 2, 1 \mapsto 3, 2 \mapsto 1, 3 \mapsto 0)$

`Find([6,3,1,4], 4)=3`

Robustness Properties

- Continuity: small change to input \Rightarrow small change to output

$\text{Sort}([1,4,3,6])=[1,3,4,6]$

$\text{Sort}([2,3,3,5])=[2,3,3,5]$

- Permutation: permuting input permutes the output

$\text{Find}([1,4,3,6], 4)=1$

$\sigma = (0 \mapsto 2, 1 \mapsto 3, 2 \mapsto 1, 3 \mapsto 0)$

$\text{Find}([6,3,1,4], 4)=3$

- Permutation: permuting input leaves output invariant

$\text{Sort}([1,4,3,6])=[1,3,4,6]$

$\text{Sort}([6,3,1,4])=[1,3,4,6]$

Verifying Continuity

- Consider
 - 1: **if** $x \geq 0$ **then**
 - 2: $r := y$
 - 3: **else**
 - 4: $r := z$

Verifying Continuity

- Consider
 - 1: **if** $x \geq 0$ **then**
 - 2: $r := y$
 - 3: **else**
 - 4: $r := z$
- If $y \neq z$, discontinuous at $x = 0$

Verifying Continuity

- Consider
 - 1: **if** $x \geq 0$ **then**
 - 2: $r := y$
 - 3: **else**
 - 4: $r := z$
- If $y \neq z$, discontinuous at $x = 0$
- Proof rule:

$$\frac{\begin{array}{ll} c \vdash \text{Cont}(P_1, \text{In}, \text{Out}) & c \vdash \text{Cont}(P_2, \text{In}, \text{Out}) \\ c' \vdash \text{Cont}(b, \text{Var}(b)) & (c \wedge \neg c') \vdash \text{Out}_{P_1} = \text{Out}_{P_2} \end{array}}{c \vdash \text{Cont}(\text{if } b \text{ then } P_1 \text{ else } P_2, \text{In}, \text{Out})}$$

Verifying Continuity

- Consider
 - 1: **if** $x \geq 0$ **then**
 - 2: $r := y$
 - 3: **else**
 - 4: $r := z$
- If $y \neq z$, discontinuous at $x = 0$
- Proof rule:

$$\frac{\begin{array}{ll} c \vdash \text{Cont}(P_1, \text{In}, \text{Out}) & c \vdash \text{Cont}(P_2, \text{In}, \text{Out}) \\ c' \vdash \text{Cont}(b, \text{Var}(b)) & (c \wedge \neg c') \vdash \text{Out}_{P_1} = \text{Out}_{P_2} \end{array}}{c \vdash \text{Cont}(\text{if } b \text{ then } P_1 \text{ else } P_2, \text{In}, \text{Out})}$$

- Only applicable to numerical perturbations

If-Elsif-Elsif-Else Cost

-

$$\begin{array}{ll} c \vdash \text{Cont}(P_1, \text{In}, \text{Out}) & c \vdash \text{Cont}(P_2, \text{In}, \text{Out}) \\ c' \vdash \text{Cont}(b, \text{Var}(b)) & (c \wedge \neg c') \vdash \text{Out}_{P_1} = \text{Out}_{P_2} \end{array}$$

$$c \vdash \text{Cont}(\mathbf{if\ } b \mathbf{\ then\ } P_1 \mathbf{\ else\ } P_2, \text{In}, \text{Out})$$

If-Elsif-Elsif-Else Cost

-

$$\begin{array}{cc} c \vdash \text{Cont}(P_1, \text{In}, \text{Out}) & c \vdash \text{Cont}(P_2, \text{In}, \text{Out}) \\ c' \vdash \text{Cont}(b, \text{Var}(b)) & (c \wedge \neg c') \vdash \text{Out}_{P_1} = \text{Out}_{P_2} \end{array}$$

$$c \vdash \text{Cont}(\mathbf{if\ } b \mathbf{\ then\ } P_1 \mathbf{\ else\ } P_2, \text{In}, \text{Out})$$

- Given if-elsif-elsif-else,

If-Elsif-Elsif-Else Cost

-

$$\begin{array}{ll} c \vdash \text{Cont}(P_1, \text{In}, \text{Out}) & c \vdash \text{Cont}(P_2, \text{In}, \text{Out}) \\ c' \vdash \text{Cont}(b, \text{Var}(b)) & (c \wedge \neg c') \vdash \text{Out}_{P_1} = \text{Out}_{P_2} \end{array}$$

$$c \vdash \text{Cont}(\mathbf{if\ } b \mathbf{\ then\ } P_1 \mathbf{\ else\ } P_2, \text{In}, \text{Out})$$

- Given if-elsif-elsif-else,
 - Reason about each branch (4 branches)

If-Elsif-Elsif-Else Cost



$$\begin{array}{ll} c \vdash \text{Cont}(P_1, \text{In}, \text{Out}) & c \vdash \text{Cont}(P_2, \text{In}, \text{Out}) \\ c' \vdash \text{Cont}(b, \text{Var}(b)) & (c \wedge \neg c') \vdash \text{Out}_{P_1} = \text{Out}_{P_2} \end{array}$$

$$c \vdash \text{Cont}(\mathbf{if\ } b \mathbf{\ then\ } P_1 \mathbf{\ else\ } P_2, \text{In}, \text{Out})$$

- Given if-elsif-elsif-else,
 - Reason about each branch (4 branches)
 - Check equivalence (3 comparisons)

Cartesian Hoare Logic

- Robustness requires 2 executions

Cartesian Hoare Logic

- Robustness requires 2 executions
- Verified using product program

Cartesian Hoare Logic

- Robustness requires 2 executions
- Verified using product program
 - $P_1 \otimes P_2$ is simultaneous execution

Cartesian Hoare Logic

- Robustness requires 2 executions
- Verified using product program
 - $P_1 \otimes P_2$ is simultaneous execution
- Cartesian Hoare Logic reasons about product programs

Cartesian Hoare Logic

- Robustness requires 2 executions
- Verified using product program
 - $P_1 \otimes P_2$ is simultaneous execution
- Cartesian Hoare Logic reasons about product programs
- Cartesian Hoare Triple examples:

Cartesian Hoare Logic

- Robustness requires 2 executions
- Verified using product program
 - $P_1 \otimes P_2$ is simultaneous execution
- Cartesian Hoare Logic reasons about product programs
- Cartesian Hoare Triple examples:
 - Determinism:

$$\|\vec{x}_1 = \vec{x}_2\| f(\vec{x}) \| ret_1 = ret_2 \|$$

Cartesian Hoare Logic

- Robustness requires 2 executions
- Verified using product program
 - $P_1 \otimes P_2$ is simultaneous execution
- Cartesian Hoare Logic reasons about product programs
- Cartesian Hoare Triple examples:
 - Determinism:

$$\|\vec{x}_1 = \vec{x}_2 \| f(\vec{x}) \| ret_1 = ret_2 \|$$

- Symmetry:

$$\|x_1 = y_2 \wedge x_2 = y_1 \| f(x, y) \| ret_1 = ret_2 \|$$

If-Elsif-Elsif-Else Cost

- Given if-elsif-elsif-else, must reason about product of each pair of branches (16 pairs):

$$P_1 \otimes P_1$$

$$\vdots$$

$$P_1 \otimes P_4$$

$$P_2 \otimes P_1$$

$$\vdots$$

$$P_4 \otimes P_4$$

Motivation

- Sanity checks and bug finding
- Functions invariant under order of list
 - max, sum, sort
- Data structures with representing something else
- Invariance under value it represents
 - binary search trees, heaps, hash sets

Lists – Invariance under order



Given an array a

- Let a_{swap} be a with its first and second entry swapped
 - $[a[1], a[0], a[2], a[3], \dots, a[n]]$
- Let a_{rot} be a rotated by 1
 - $[a[1], a[2], a[3], \dots, a[n], a[0]]$

Lemma: If for any a , $P(a) = P(a_{\text{swap}}) = P(a_{\text{rot}})$, then for any permutation a' of a , we have $P(a) = P(a')$.

Proof: Math

Automata – Invariance under order



Automata – Invariance under order

Theorem: Given a deterministic automata M , we can check if M is invariant under the order of its input in time $O(|\Sigma|^2|M|\log(|\Sigma||M|))$.

Proof:

- Construct the machines M_{swap} and M_{rot} by composing M with those machines
 - Requires $O(|\Sigma||M|)$ states
- Check if $L(M_{swap}) = L(M) = L(M_{rot})$
 - E.g. by state minimization in time $O(n|\Sigma|\log n)$

Programs – Invariance under order


- $\text{maxList}([x]) = x$
- $\text{maxList}([x, \dots xs...]) = \text{max}(x, \text{maxList}(xs))$
- Verifying $\text{maxList}(a) = \text{maxList}(a_{\text{swap}})$ has one case:

$$\begin{array}{ccc} \text{maxList}([x, y, \dots xs...]) & \stackrel{?}{=} & \text{maxList}([y, x, \dots xs...]) \\ \parallel & & \parallel \\ \text{max}(x, \text{maxList}([y, \dots xs...])) & & \text{max}(y, \text{maxList}([x, \dots xs...])) \\ \parallel & & \parallel \\ \text{max}(x, \text{max}(y, \text{maxList}(xs))) & & \text{max}(y, \text{max}(x, \text{maxList}(xs))) \\ \parallel & & \parallel \\ \text{max}(x, \text{max}(y, z)) & & \text{max}(y, \text{max}(x, z)) \end{array}$$



Binary Search Trees

- For lists, two simple permutations generated all permutations
- Goal: similar permutations for BSTs


Binary Search Trees



rotate
→



flatten
→




Binary Search Trees

It suffices to show

- Every tree can be transformed into a “normal form” (i.e. list)
- Every operation is reversible


Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




rotate \rightarrow



Binary Search Trees – Proof by example

- Every tree can be transformed into a “normal form” (i.e. list)




More General Procedure

Invariance of a program $P : T \rightarrow Z$ relative to a function $f : T \rightarrow T'$

- E.g. $f : BST \rightarrow List$


Observation: The following are equivalent:

- $f(x) = f(y) \implies P(x) = P(y)$
- There exists a program $\tilde{P} : T' \rightarrow Z$ such that $P = \tilde{P} \circ f$




More General Procedure

- Idea: Synthesize a witness to the invariance
 - A function $\tilde{P} : T' \rightarrow Z$
- P and f provide a *full specification* of \tilde{P}
- Counterexample guided inductive synthesis



More General Procedure



Future Directions

- Develop proof rules for discrete perturbations

Future Directions

- Develop proof rules for discrete perturbations
- Address branching in 2-safety properties

Future Directions

- Develop proof rules for discrete perturbations
- Address branching in 2-safety properties
-