

A Non-Destructive Reverse-Engineering Methodology for Closed Android–ROS Service Robots: Validation on the CYBEL Case Study with Open ROSBRIDGE Integration and an Edge Conversational Stack

Claudia LUSAMOTE KIMFUTA
HESTIM Engineering & Business School
Email: clusamote@gmail.com

Dr. Sridath Tula
HESTIM Engineering & Business School
Supervisor

Abstract—Commercial service robots often ship as closed Android-ROS systems: no public SDK, no message schemas, and mandatory vendor cloud services, which prevents customization of reception flows, guided tours, and conversational assistants. This paper’s primary contribution is a *reproducible, non-destructive reverse-engineering methodology* for such closed platforms, built around four testable hypotheses (H1–H4) about where the true protocol surface lives and how to verify it without vendor cooperation. We validate the methodology end-to-end on a single case study, CYBEL, an open edge platform reconstructed from the CIOT TY1251D-03195 reception robot, a dual-processor system combining a ROS navigation chassis and an Android 7.1 head, without manufacturer documentation or support. The seven-phase pipeline combines network mapping, ROSBRIDGE/rosapi introspection, static APK analysis (JADX) [1], passive MQTT observation, and field validation of H4: a successful ROSBRIDGE transport acknowledgment does not guarantee motor execution. We document reconstructed teleoperation (`/cmd_vel_mux/input/teleop`), autonomous navigation (`/navi_goal` vs. POI chain `/tag_manager/navi`), and an edge conversational layer (local knowledge engine, Android TTS bridge, guided-tour orchestration) offered as an open alternative to the vendor welcome application. Runtime testing falsified the expected advantage of named-POI navigation (H3 rejected: `/tag_manager/navi` non-functional on this firmware), making H3’s rejection a finding in itself and coordinate-based `/navi_goal` the confirmed navigation path. We report a feature-level comparison against the vendor application and quantitative reverse-engineering effort metrics (APKs analyzed, topics/services discovered, elapsed time), in addition to field indicators (<100 ms local API latency, ~90% ROSBRIDGE session reliability). We discuss which parts of the methodology generalize to other closed Android-ROS robots and which remain vendor-specific.

Index Terms—Service robotics, reverse engineering, ROS, ROSBRIDGE, embedded Android, human-robot interaction, edge computing, text-to-speech, vendor lock-in

I. INTRODUCTION

Mobile reception robots integrate mature SLAM and motion planning with touchscreen and speech interfaces, yet remain

software black boxes: no public SDK, no message schemas, and often mandatory vendor cloud services. For research labs and training institutions, this closure blocks custom visit paths, domain-specific knowledge bases, and open conversational agents, and it locks the owner into a single vendor for the lifetime of the hardware.

Problem. Reverse engineering such a robot is hard for three compounding reasons: (i) the chassis and the Android head are two separate operating environments bridged by an undocumented transport, so a single vantage point (e.g. network capture alone) never reveals the full command surface; (ii) commercial firmware actively discourages introspection (locked shell, brute-force lockout), so classic white-box techniques (root, firmware dump) are unavailable or unacceptably destructive; and (iii) a network message being *accepted* by the robot’s software stack is not evidence that it was *executed* by the robot’s body, which invalidates naive black-box protocol fuzzing as a verification method. Existing reverse-engineering practice for network protocols [2] and for Android applications [3] each address one side of this problem but not the chassis/Android/cloud triad found in service robots.

Research question. *Can a third-party, non-destructive methodology reconstruct a closed Android-ROS service robot’s command and interaction surface with no official documentation, and to what extent does the resulting open platform reach feature parity with the vendor application?* We decompose this into four hypotheses, tested empirically throughout the paper:

- **H1 (APK-as-spec):** the vendor’s shared native library is a reliable proxy for the undocumented wire protocol, i.e. static analysis of vendor APKs (JADX) yields the same message schemas as those actually used on the wire.
- **H2 (MQTT-as-command-channel):** the MQTT broker exposed by the chassis can be used, like ROSBRIDGE, to issue motion and navigation commands.
- **H3 (POI reuse):** reusing points of interest created by the




Fig. 1. Overall process: from the closed vendor robot to the open conversational stack. The reverse-engineering methodology (Section IV) is the paper’s central contribution; ROSBRIDGE reconstruction, CYBEL, and the conversational layer are its validation artifacts.

vendor’s own Deployment Tool yields higher navigation reliability than commanding raw coordinates reconstructed independently.

- **H4 (transport $\neq$ execution):** a successful ROSBRIDGE transport acknowledgment (message accepted, no error) does not guarantee that the chassis actually executed the corresponding motion.

Section IV shows that H1 and H4 are *confirmed*; H2 and H3 are *rejected*; each resolution is explained mechanistically, not just reported. The rejection of H3 is itself a finding: `/tag_manager/navi`, present in the APK, is not a functional navigation trigger on this firmware.

Contributions. The central contribution of this paper is C1, a generalizable methodology; C2–C6 are the concrete artifacts produced by applying it to a single robot, offered as empirical validation rather than as independent claims.

- C1.** A reproducible seven-phase non-destructive reverse-engineering *methodology* for closed vendor Android–ROS robots, structured around the four falsifiable hypotheses above and a triangulation principle (network trace $\times$ `rosapi` $\times$ decompiled APK $\times$ field telemetry).
- C2.** Validation of that methodology on the CIOT TY1251D-03195: reconstructed ROSBRIDGE v2 protocol for teleop, POI/coordinate navigation, and telemetry (Section V).
- C3.** CYBEL, an edge-first reference implementation: interchangeable `MockRobot/RealRobot` SDK, dual PC/Termux backend, autonomous kiosk (Section VI).
- C4.** Empirical resolution of TTS channel discovery via a minimal Android broadcast bridge after ROS, HTTP, and MQTT channels were falsified (Section VI).
- C5.** A feature-level comparison between CYBEL and the vendor application, and quantitative reverse-engineering effort metrics, filling the experimental gap of earlier internal reports (Section VII).
- C6.** A discussion of which elements of the methodology are robot-agnostic and which are specific to this vendor, to support reuse on other closed platforms (Section VIII).

Scope. This paper focuses on protocol discovery, methodology validation, and open-stack integration; LLM-based conversational reasoning is architected (Section VI-C) but not yet the object of a dedicated evaluation. The codebase and exploration scripts are maintained as reproducible artifacts [4].

Figure 1 summarizes the overall process described in this paper, from the closed vendor robot to the open conversational stack.

II. RELATED WORK

A. Reverse engineering of Android applications

Static and dynamic analysis of Android applications has been studied extensively for security auditing, notably information-flow tracking of installed apps [3]. That line of work targets *data exfiltration* inside a single app; our setting instead uses APK decompilation (JADX [5]) as a way to recover an *inter-process wire protocol* between an Android head and a separate ROS chassis, which is not the object of prior Android security literature.

B. ROSbridge and robotics middleware interoperability

ROSBIDGE was introduced to let non-ROS clients (web browsers, mobile apps) interact with a ROS graph over a JSON/WebSocket transport [6], [7], and is normally deployed by the system integrator who controls the ROS graph. Our situation is the inverse: ROSBRIDGE is deployed by the vendor and we approach it as an *unknown* client would, without access to the underlying node graph or message definitions, which is closer in spirit to black-box protocol reverse engineering [2] than to conventional ROSBRIDGE integration.

C. Vendor lock-in and platform openness

The tension between proprietary and open platform strategies in commercial hardware/software products has long been studied in the innovation-management literature [8]; service robotics reproduces this tension at the level of a single physical product rather than an industry platform. To our knowledge, no prior work documents a systematic, non-destructive method for a lab to escape such lock-in on a robot it already owns, as opposed to advocating for openness at the vendor level.

D. Edge and cloud robotics

Cloud robotics offloads perception and planning to remote servers [9]; our constraint is the opposite: the robot’s own Wi-Fi network offers no guaranteed Internet path, so every capability, including speech synthesis, must run at the edge. This motivates the edge-first architecture of Section VI and distinguishes our setting from cloud-robotics deployments that assume reliable connectivity.

E. LLM-based conversational and embodied agents

Recent work grounds large language models in robot affordances for task planning [10] and in multimodal embodied observations [11]. These systems assume an already-open action API. Our conversational layer (Section VI-C) is deliberately designed as the *prerequisite* such systems require on a closed robot: a validated, documented set of navigation and speech primitives that an LLM backend can call without itself rediscovering ROSBRIDGE or the TTS channel.




Fig. 2. Network topology. Termux on the tablet uses 192.168.20.22; confusing head DHCP IP with chassis IP causes silent failures (see Section IV-E for why this recurs).

F. Positioning

Related work treats Android security, ROSBRIDGE integration, platform openness, edge robotics, and LLM grounding as separate concerns, each assuming the underlying interface is already known or already open. This paper’s contribution is the missing piece: a methodology to *establish* that interface non-destructively when it is neither known nor open, together with a case study showing the resulting platform can host each of the concerns above (edge deployment, conversational grounding) once the interface is recovered.

III. ROBOT PLATFORM AND NETWORK TOPOLOGY

A. Dual-processor hardware

The CIOT TY1251D-03195 combines:

- **Chassis:** Linux + ROS (Noetic/Melodic), SLAM, move_base, LiDAR/RGBD, ROSBRIDGE, MQTT broker.
- **Head:** Android 7.1 (RK3399, 2GB RAM) - 15.6” touchscreen, cameras, speakers, vendor apps.

CYBEL never obtains shell access on the chassis (SSH locked; brute-force triggers lockout) a deliberate choice explained by principle P4 in Section IV, not a limitation discovered after the fact. Usable channels: WebSocket ROSBRIDGE on port 9090 and MQTT on 1883 (observation only).

B. Triple network segment

Mapping revealed three distinct segments (Fig. 2), which is itself a first reverse-engineering result: nothing in the vendor documentation (there is none) indicates that the head and the chassis sit on different subnets.

- **Robot AP** (TY1251D-03195): chassis at 10.42.0.1:9090.
- **Internal eth0:** head 192.168.20.1 ↔ chassis 192.168.20.22:9090, preferred path from Termux.
- **Lab Wi-Fi:** head 172.16.0.x (DHCP); PC uses ADB for deployment.

Vendor packages identified via ADB: com.ciot.welcomepatrol (welcome UI), com.ciot.sentrymove (Deployment Tool), shared library selfchassislibrary treated as *de facto* protocol specification after JADX audit the empirical basis for hypothesis H1.

IV. REVERSE ENGINEERING METHODOLOGY

This section is the core of the paper: it presents the methodology as a set of falsifiable hypotheses tested through a seven-phase pipeline, and explains *why* each difficulty encountered is structural to closed Android-ROS robots rather than incidental to this particular unit.

A. Guiding principles

- P1.** Observe before publishing (passive MQTT/ROSBRIDGE first) minimizes risk of damaging an undocumented, unowned-source system before its behavior is understood.
- P2.** Verify real effects, not transport acknowledgments rule **H4**: after a teleop publish, /robot_pose must change before the command is considered validated.
- P3.** Triangulate independent sources of evidence: network traces, rosapi introspection, decompiled APK, and field logs. A hypothesis is only accepted when at least two independent sources agree.
- P4.** Remain non-destructive: no firmware flash, no chassis root, no persistent modification of vendor partitions. This is both an ethical commitment (Section VIII) and a practical one: destructive access on a single loaned/owned unit is not reproducible if it bricks the robot.
- P5.** Mock-first development: every SDK feature is built and unit-tested against a MockRobot before being exercised against RealRobot, decoupling software defects from hardware/protocol uncertainty.

B. Hypotheses and their resolution

- **H1 (APK-as-spec) - CONFIRMED.** Every ROSBRIDGE topic and service name later confirmed on the wire (Section V) was first located inside selfchassislibrary via JADX. *Why it holds:* the vendor’s own Android app must itself speak the true protocol to control the chassis, so its compiled code is a lower bound on the real command surface, unlike documentation which may be aspirational or outdated.
- **H2 (MQTT-as-command-channel) - REJECTED.** Passive MQTT observation (wildcard subscription #, multiple sessions, 1 topic logged: test_mul, odometry only) showed only odometry and status telemetry; no motion command reproducibly changed robot state when replayed on MQTT. *Why it fails:* JADX audit of selfchassislibrary shows the MQTT client is wired exclusively to telemetry publishers on the chassis side; the command path is implemented only over the ROSBRIDGE WebSocket, so MQTT is architecturally read-only from this robot’s perspective. This is the diagnostic value of a rejected hypothesis: it saved further engineering effort on a channel that could never work, and it is documented here so future integrators of the *same vendor family* do not repeat the exploration.
- **H3 (POI reuse) - REJECTED.** Runtime testing (5 trials each, Section VII-A) showed S3 via /tag_manager/navi triggered zero confirmed navigations (0/5); two apparent successes at 0.5 s and

TABLE I
REVERSE-ENGINEERING PHASES AND DELIVERABLES

#	Phase	Key deliverable
1	Network scan	Dual-IP map, ports 9090/1883
2	ROS observation	Topic/service inventory
3	MQTT passive	H2 rejected: no movement control via MQTT
4	APK audit (JADX)	H1 confirmed: topic parity vs. Sentrymove
5	Wireshark	WebSocket JSON framing
6	ADB / Termux	TTS bridge, edge backend
7	Field validation	H3 rejected (S3 non-functional); H4 confirmed

0.6s were stale `nav_status=603` reads, not navigation completions. S1 via `/navi_goal` achieved 80% (4/5) with mean arrival time 3.5s. *Why it fails:* the service `/tag_manager/navi`, present in the compiled APK (`SelfChassis.sendMoveByMarkerName`), is not implemented as a navigation trigger on the deployed firmware. This is exactly the failure H4 anticipates: APK-level presence does not guarantee runtime execution.

- **H4 (transport $\neq$ execution) - CONFIRMED, and central to the methodology.** ROSBRIDGE returns a transport-level acknowledgment as soon as a message is syntactically valid and routed to a subscriber; it carries no guarantee that the chassis’s motion controller executed the command. *Why it holds:* ROSBRIDGE sits above ROS’s publish/subscribe layer, which itself is decoupled from the safety and motor-control layer on the chassis (e.g. manual-mode gating, Section V); an ack only certifies the first hop. *Consequence:* every validation step in this paper checks `/robot_pose` or an equivalent status topic, never the ROSBRIDGE response alone.

C. Seven-phase pipeline

Table I summarizes the pipeline; each hypothesis follows *observe* $\rightarrow$ *isolated script* $\rightarrow$ *telemetry check* $\rightarrow$ *SDK integration or documented rejection*.

Rejected hypotheses (documented, not silently discarded): legacy teleop topic `/mobile_base/commands/velocity`; candidate TTS topics (`/play_tts`, `/robot_tts`); HTTP TTS on head ports 80/8080/8888; MQTT movement commands (H2); named-POI service `/tag_manager/navi` as navigation trigger (H3 - APK documented but non-functional at runtime).

D. Reverse-engineering effort

Table II reports the quantitative effort behind the pipeline above, addressing directly how much work the methodology actually required a question the earlier internal report left unanswered.

E. Difficulties and why they occur

The following difficulties are structural properties of closed Android–ROS service robots, not idiosyncrasies of this unit; we make the mechanism explicit for each so the observation transfers to other robots.

TABLE II
REVERSE-ENGINEERING EFFORT (CASE STUDY)

Metric	Value
APKs statically analyzed (JADX)	2
Distinct ROS topics discovered	416
Distinct ROS services discovered	299
MQTT topics observed (all telemetry)	1 (<code>test_mul</code>)
Hypotheses tested (confirmed / rejected)	2 / 2 (H1, H4 / H2, H3)
Elapsed wall-clock time, phases 1–6	2 weeks
Elapsed wall-clock time, phase 7 (field)	1 week
Distinct field sessions on physical robot	[TODO: N — <i>computer sessions terrain</i>]

Why H4 (transport $\neq$ execution) had to be formulated. ROSBRIDGE is a generic message router; it acknowledges anything that parses as a valid ROS message on an advertised topic, regardless of whether any node downstream actually consumes it meaningfully. On this chassis, a manual-mode safety gate (`control_state==30`, Section V) silently drops teleop commands published before the gate is set, while ROSBRIDGE still reports success. Any closed ROS robot with a safety or mode-gating layer between the message bus and actuation will reproduce this failure mode.

Why ROSBRIDGE responds without motion. Same mechanism as above, applied specifically to the WebSocket path: the JSON-RPC style response in ROSBRIDGE’s protocol confirms message delivery to the ROS graph, not physical execution, because ROSBRIDGE has no visibility past the topic it published to.

Why MQTT was a plausible but false lead (H2). The chassis exposes an MQTT broker on port 1883, and MQTT is a common command-and-telemetry bus in commercial IoT/robotics stacks, making it a reasonable first hypothesis. JADX audit later showed the vendor uses MQTT purely as a one-way telemetry export (for fleet dashboards), with all control logic hard-wired to ROSBRIDGE; without that audit, this would have appeared as an intermittent, unexplained non-responsiveness rather than a structurally closed channel.

Why multiple IPs appear for what looks like one robot. The Android head and the ROS chassis are two independent Linux network stacks bridged by an internal Ethernet link (Fig. 2), and the head additionally joins the lab Wi-Fi for deployment. A robot marketed and documented as a single product is, at the network layer, at least two hosts; conflating the head’s DHCP address with the chassis’s static address is the single most common operator error we observed and is why we document all three segments explicitly rather than a single "robot IP."

Why TTS was inaccessible from every standard channel. The vendor’s speech pipeline is implemented entirely inside the Android application layer (opaque IPC to a bundled Iflytek TTS engine), with no bridge exposed back down to ROS, HTTP, or MQTT (Table IV); speech was never designed to be a robot-level capability, only an application-level one. This explains why exhaustive protocol-level search (phases 2–3) could not find it, and why the eventual fix (Section VI) operates at the Android application layer instead.

TABLE III
NAVIGATION MODES AND PREREQUISITES

Mode	Mechanism	Gate
Coordinates (S1)	/navi_goal	loc. $\geq 60\%$, status 601
Named POI (S3)	/tag_manager/navi $\rightarrow$ /poi	POI in map

V. ROSBRIDGE PROTOCOL RECONSTRUCTION

A. Transport and client

ROSBRIDGE v2 over WebSocket TCP 9090 [6], [7]; JSON operations subscribe, publish, advertise, call_service. Our RosbridgeClient (transport module of the CYBEL SDK) uses three connection retries (20s timeout), 20s ping keepalive, and automatic reconnect.

B. Teleoperation

Manufacturer-confirmed topic:

```
/cmd_vel_mux/input/teleop
(geometry_msgs/Twist)
```

Sequence: advertise then periodic publish (~ 10 Hz). Sentrymove ramps linear velocity $\pm 0.025/100$ ms with $\omega_z \times 0.8$ scaling.

Gap E1: early CYBEL builds blocked teleop unless manual mode was active (control_state==30); Sentrymove does not require this step because it always sets the mode implicitly on session start a vendor convention discoverable only via APK audit (H1), not via wire traffic alone. **Fix:** auto-enable manual mode on first move().

C. Autonomous navigation

Two modes coexist on the chassis:

nav_status codes gate CYBEL commands: 600 not localized, 601 ready, 602 navigating, 603 arrived, 604 error. Cancellation chain: /move_base/cancel, /path_follower/cancel, /poi{command:stop}, zero velocity on mux.

D. Telemetry throttling

Subscriptions use throttle_rate (ms): /robot_pose 200 (~ 5 Hz), /navi_status 500, LiDAR /scan_filter 100 limiting ROSBRIDGE saturation on constrained Wi-Fi.

VI. CYBEL ARCHITECTURE: VALIDATION PLATFORM

This section presents CYBEL strictly as the reference implementation used to validate the methodology of Section IV; the architectural choices below follow directly from H1–H4 and from the edge constraint discussed in Section II.

A. Three-layer stack

Presentation: the visitor-facing kiosk web UI; a thin Android WebView wrapper for autonomous kiosk mode; the TTS bridge module handling speech (Section VI-C).

Application: a FastAPI development server on PC (port 8000); a lightweight Starlette-based standalone server on Termux (port 8001, POI variant) for a kiosk that needs no PC.




Fig. 3. Logical architecture (edge-first, no vendor cloud).

Domain: a RobotBackend protocol with MockRobot/RealRobot implementations 83 unit tests pass without the physical robot, directly operationalizing principle P5.

B. Edge deployment pattern

Termux on the tablet runs Python, serves the kiosk over 0.0.0.0:8001, connects to 192.168.20.22:9090, and triggers TTS via local am broadcast. The visitor session requires no PC after deployment (standalone Termux deployment or ADB bundle).

C. Conversational layer

The vendor welcomepatrol app couples Iflytek TTS via opaque IPC and a proprietary cloud knowledge API. CYBEL offers an *open, edge-only alternative*, whose scope we state precisely because the title places emphasis on it: the layer below is a validated set of primitives (speak, navigate, answer-from-local-knowledge) rather than a full dialogue system, and LLM-based reasoning over these primitives is future work (Section VIII).

- 1) **Input:** kiosk touch, operator text, or browser Web Speech API (PC only).
- 2) **KnowledgeEngine:** keyword scoring over a local JSON knowledge base and FAQ threshold ≥ 2.0 ; deterministic, offline-capable, and inspectable (unlike the vendor’s cloud API, which is opaque by construction).
- 3) **ReceptionService:** matched answer $\rightarrow$ speech output + optional navigation to a point of interest.
- 4) **TourEngine:** ordered stops from a tour definition file, with speech/navigation ordering fixed to relocalize *before* TTS (this ordering bug produced the “speaks but does not move” symptom during development, itself a direct instance of the H4 transport/execution gap).

1) **TTS channel discovery:** No ROS topic, service, HTTP port, or MQTT payload exposed TTS on TY1251D (Table IV) [12]; Section IV-E explains why this search was exhaustive yet unsuccessful at the protocol level.

The TTS bridge (~ 50 KB APK) implements a BroadcastReceiver that forwards to Android’s native TextToSpeech (Google engine, French locale):

```
am broadcast -n com.cybel.ttsbridge/.SpeakReceiver
-a com.cybel.ttsbridge.SPEAK --es text "Welcome."
```

TABLE IV
TTS INVESTIGATION SUMMARY

Channel tested	Result
ROS publish topics	No subscribers
ROS services	Absent in <code>rosapi</code>
HTTP head (80, 8080, 8888)	Closed
MQTT	Odometry only
ADB broadcast	Working (TTS bridge APK)

The speech module tries ROS, HTTP, ADB-from-PC, then local Termux broadcast a documented fallback chain, reflecting principle P3 (triangulate, then fall back gracefully rather than assume a single channel).

LLM extensibility. A single knowledge-query endpoint accepts the same contract as the local KnowledgeEngine; an LLM backend in the style of [10], [11] can call the validated CYBEL navigation/speech primitives without itself rediscovering ROSBRIDGE or the TTS bridge this is the concrete sense in which the conversational layer is “LLM-ready” rather than already LLM-based.

VII. EXPERIMENTAL EVALUATION

A. Hybrid navigation case study

1) *Coordinate-only strategy (S1):* Publishing `/navi_goal` with coordinates from a JSON knowledge base often failed in the field: robot spoke but `nav_status` remained 601 (planner never entered 602), wrong destinations due to map drift, slow relocalization. Representative trace (session `tour_20260623_142601`): goal published, no 601→602 transition.

2) *POI-reuse strategy (S3), testing H3:* The vendor Deployment Tool navigates reliably via named POIs (the chassis localization stack accepts them with vendor-controlled tolerance). H3 hypothesized that the CYBEL backend could exploit this by calling `/tag_manager/navi` the service `SelfChassis.sendMoveByMarkerName` identifies in the compiled APK. The designed flow was:

- 1) Create POIs in Deployment Tool (consistent naming convention).
- 2) Sync ROS markers into the CYBEL POI store (POI-sync module).
- 3) Kiosk auto-syncs on destination grid load; tour engine references POIs by name.
- 4) CYBEL calls `/tag_manager/navi` with POI name; monitors `nav_status`.

Runtime testing (Section below) showed the service call is silently ignored by the chassis: H3 is rejected.

3) *Navigation outcomes (S1 vs. S3):* Table V reports outcomes from 5 trials per strategy (same target POI, robot reset to a distant landmark between trials). S1 achieved 80% (4/5) with mean arrival time 3.5 s; the single failure occurred because the robot was mid-navigation during inter-trial reset. S3 triggered *no* confirmed navigations: two apparent successes (0.5 s and 0.6 s) were stale `nav_status=603` reads the chassis retains the terminal code of the *previous* navigation until a new goal is accepted. This result rejects H3 and directly

TABLE V
NAVIGATION OUTCOMES BY STRATEGY (5 TRIALS EACH, LAB ROBOT, JULY 2026)

Strategy	Success	Avg. arrival	Main failure mode	Obs. timeout
S1 (<code>/navi_goal</code>)	80% (4/5)	3.5 s	trial 1: mid-reset state	60 s
S3 (<code>/tag_manager/navi</code>)	0% (0/5) [†]	—	service non-functional	N/A

[†]Two apparent successes (0.5 s, 0.6 s) were stale `nav_status=603` reads.

TABLE VI
OBSERVED PERFORMANCE INDICATORS (JUNE 2026, LAB ROBOT)

Metric	Value
Local REST latency	<100 ms
ROSBIDGE connect	2–60 s (3×20 s retry)
Session reliability	~90% (Wi-Fi dependent)
Wi-Fi RTT	89–1654 ms
Unit tests	110/110 passed
Teleoperation success rate	100% (10 trials)
Guided-tour completion rate	[TODO: XX%] ([TODO: N] trials)
TTS bridge latency (ADB broadcast, 5 trials)	651–1555 ms (mean 923 ms)
Termux kiosk autonomous uptime	[TODO: X hours]

TABLE VII
FEATURE COMPARISON: VENDOR APPLICATION VS. CYBEL

Feature	Vendor app	CYBEL
Teleoperation	✓	✓
Guided tour	✓	✓
Local FAQ / knowledge base	✓ (cloud)	✓ (local, offline)
Speech synthesis	✓	✓ (bridge, Sec. VI-C)
Works without Internet	×	✓
Source-inspectable logic	×	✓
Extensible / self-hostable	×	✓
Cloud-independent	×	✓
Vendor support required	✓	×
LLM-backend ready	×	✓ (API contract)

reinforces H4: `/tag_manager/navi` is documented at the APK layer but is not a functional navigation trigger on this firmware.

B. Reverse-engineering and field metrics

Table VI reports system-level indicators; Table II (Section IV-D) reports the reverse-engineering effort that produced them.

Validation script (Validation Framework, phase 7): connects on `192.168.20.22`, exercises teleop, commands navigation to a named POI, and triggers TTS in a single scripted session, logging `/robot_pose` deltas per principle P2/H4.

C. Comparison with the vendor application

Table VII makes the “match or exceed” claim in the introduction concrete and falsifiable at the feature level; a quantitative user-study comparison (task completion time, error rate under identical scripted visits) is identified as future work in Section VIII rather than claimed here.

VIII. DISCUSSION

A. Lessons for closed-robot integration

- **Transport lies (H4):** ROSBRIDGE accepts publishes without motor effect; telemetry is ground truth, not the transport acknowledgment.

- **Vendor APK as spec (H1):** JADX audit of the vendor’s own application accelerated discovery versus generic ROS documentation, and is the only channel that revealed implicit preconditions (e.g. manual-mode gating).
- **Not every plausible channel is real (H2):** a structurally reasonable hypothesis (MQTT as command bus) can be architecturally false; documenting the rejection has value for other integrators of the same vendor family.
- **Dual/triple-IP is normal:** document head vs. chassis addresses explicitly rather than treating the robot as a single network endpoint.
- **APK presence $\neq$ runtime function (H3, rejected):** the `/tag_manager/navi` service documented in the vendor APK triggered no navigations at runtime; coordinate-based `/navi_goal` (S1) is the reliable path. Runtime validation is non-optional even when the APK source is clear.
- **Edge-first is not optional:** closed robot Wi-Fi precludes cloud LLM/TTS dependencies, which shaped every architectural choice in Section VI.

B. Generalization: what transfers to other robots

The four hypotheses are stated at a level intended to transfer beyond this specific unit. H1 and H3 should hold for any vendor robot where an Android or mobile companion app is the primary control surface, since the app must itself speak the true protocol. H4 should hold for any robot whose message bus is decoupled from a safety/mode layer, which is common practice in commercial mobile bases. H2’s rejection is more vendor-specific: another robot could plausibly use MQTT for commands; the contribution here is the *triangulation method* (P3) that would detect this quickly, not the specific rejection. What remains vendor-specific in CYBEL itself: exact topic names, the manual-mode gate semantics, the POI naming convention, and the TTS broadcast contract these must be rediscovered per vendor, using the same seven-phase pipeline.

C. Ethical considerations

All reverse engineering reported here was performed on hardware owned or lawfully operated by our institution, for interoperability purposes, without redistributing vendor code or bypassing any DRM/licensing mechanism; APK analysis was limited to recovering message schemas, not to extracting or republishing proprietary assets. Principle P4 (non-destructive, no root, no firmware modification) was also an ethical commitment: it keeps the vendor’s warranty and update path intact and avoids creating a fork of vendor firmware that could not be maintained. We did not attempt to circumvent the chassis SSH lockout beyond passive discovery of its existence.

D. Limitations

Chassis shell inaccessible; no native ROS TTS; Android 7.1 WebView constraints; DHCP head IP variability; on-robot ASR not yet implemented; the vendor comparison in Section VII-C is feature-level, not a controlled user study; quantitative values marked **[TODO: TODO]** in this draft must be filled from the lab’s field logs before submission.

IX. CONCLUSION

We presented a non-destructive reverse-engineering methodology for closed Android–ROS service robots, structured around four falsifiable hypotheses (H1–H4), and validated it end-to-end on the CIOT TY1251D-03195 via CYBEL, an open edge platform with reconstructed ROSBRIDGE protocol, a mock/real SDK, an Android TTS bridge, and a local conversational layer. Two hypotheses were confirmed (H1: APK-as-spec; H4: transport $\neq$ execution) and two were rejected with mechanistic explanations (H2: MQTT is telemetry-only; H3: `/tag_manager/navi` non-functional at runtime), each rejection carrying transferable diagnostic value. The main claim of the paper is methodological: the seven-phase, triangulation-based pipeline and the transport-versus-execution discipline (H4) generalize to other closed Android–ROS robots, while the specific protocol details recovered for CYBEL are this vendor’s instantiation of that method.

Future work: a controlled comparison against the vendor application beyond the feature table of Table VII; LLM/RAG reasoning behind the knowledge-query API; on-device ASR; presence-triggered kiosk wake-up; and publication of the exploration scripts as reproducible artifacts for other closed Android–ROS robots, to test H1–H4 on a second vendor.

ACKNOWLEDGMENT

This work was conducted at HESTIM Engineering & Business School under supervision of Dr. Sridath Tula. We thank the HESTIM robotics lab for robot access and field testing support.

REFERENCES

- [1] C. Lusamote Kimfuta and S. Tula, “CYBEL project: Architecture and APK audit notes,” 2026, internal technical documentation, HESTIM robotics lab.
- [2] P. M. Comparetti, G. Wondracek, C. Kruegel, and E. Kirda, “Prospex: Protocol specification extraction,” in *Proceedings of the IEEE Symposium on Security and Privacy*, 2009.
- [3] W. Enck, P. Gilbert, B.-G. Chun, L. P. Cox, J. Jung, P. McDaniel, and A. N. Sheth, “TaintDroid: An information-flow tracking system for realtime privacy monitoring on smartphones,” *ACM Transactions on Computer Systems*, vol. 32, no. 2, 2014.
- [4] C. Lusamote Kimfuta and S. Tula, “CYBEL: Reproducible artifacts and exploration scripts,” 2026, project repository, HESTIM robotics lab.
- [5] Skylot, “JADX: Dex to java decompiler,” <https://github.com/skylot/jadx>, GitHub repository, accessed 2026.
- [6] C. Crick, G. Jay, S. Osentoski, B. Pitzer, and O. C. Jenkins, “Rosbridge: ROS for non-ROS users,” in *Proceedings of the 15th International Symposium on Robotics Research (ISRR)*, 2012.
- [7] Open Source Robotics Foundation, “rosbridge_suite,” http://wiki.ros.org/rosbridge_suite, rOS Wiki, accessed 2026.
- [8] J. West, “How open is open enough? melding proprietary and open source platform strategies,” *Research Policy*, vol. 32, no. 7, pp. 1259–1285, 2003.
- [9] B. Kehoe, S. Patil, P. Abbeel, and K. Goldberg, “A survey of research on cloud robotics and automation,” *IEEE Transactions on Automation Science and Engineering*, vol. 12, no. 2, pp. 398–409, 2015.
- [10] M. Ahn *et al.*, “Do as I can, not as I say: Grounding language in robotic affordances,” *arXiv preprint arXiv:2204.01691*, 2022.
- [11] D. Driess *et al.*, “PaLM-E: An embodied multimodal language model,” *arXiv preprint arXiv:2303.03378*, 2023.
- [12] C. Lusamote Kimfuta and S. Tula, “CYBEL project: TTS channel investigation log,” 2026, internal technical documentation, HESTIM robotics lab.

- [13] M. Quigley, K. Conley, B. Gerkey, J. Faust, T. Foote, J. Leibs, R. Wheeler, and A. Y. Ng, "ROS: an open-source Robot Operating System," in *ICRA Workshop on Open Source Software*, 2009.
- [14] S. Thrun, W. Burgard, and D. Fox, *Probabilistic Robotics*. MIT Press, 2005.
- [15] C. Bartneck, T. Belpaeme, F. Eysel, T. Kanda, M. Keijsers, and S. Šabanović, *Human-Robot Interaction: An Introduction*. Cambridge University Press, 2020.