

File Number: **DRAFT-SAT-LOA-20260108-00016**

Call Sign:

S1. Satellite Information

a. Space Station or Satellite Network Name	b. Orbit Type	c. Estimated Operational Lifetime of Space Station(s) From Date of Launch (yrs)	d. Will the space station(s) operate on a Common Carrier basis?	e. Application Description
SpaceX Orbital Data Center System	Non-Geostationary (NGSO)	5	No	Application for authority to launch and operate a constellation of solar-powered orbital data centers.

S2. Operating Frequency Bands

a. Type of Service	b. If a. is Other, provide a service description	c. Satellite Frequency Band (MHz)	d. Satellite Frequency (Lower Band Edge) (MHz)	e. Satellite Frequency (Upper Band Edge) (MHz)	f. Direction of Transmission	g. Non Conforming Indicator
FSS		18800 - 19300	18800	19300	Space-to-Earth (Transmit)	No
FSS		28600 - 29100	28600	29100	Earth-to-Space (Receive)	No

S3. NGSO Orbital Information

a. Total Number of Simultaneously Operating Satellites in Constellation	b. Total Number of Satellites Deployed During the License Term	c. Orbit Epoch Date	d. Celestial Reference Body	e. If d. is "Other", provide the name of celestial body being referenced	f. Total Number of Orbital Planes
3	3	2024-04-01	Earth		3

g. Orbital Plane Information

(i) Orbital Plane No.	(ii) Number of Satellites in Plane	(iii) Inclination Angle (°)	(iv) Inclination Angle Tolerance (+/- °)	(v) Orbital Period (seconds)	(vi) Apogee (km)	(vii) Apogee Tolerance (+/- km)	(viii) Perigee (km)	(ix) Perigee Tolerance (+/- km)	(x) Argument of Perigee (°)	(xi) Right Ascension of Ascending Node (°)	(xii) Right Ascension of Ascending Node Tolerance (+/- °)	(xiii) Active Service Arc Begin Angle with Respect to Ascending Node (°)	(xiv) Active Service Arc End Angle with Respect to Ascending Node (°)	(xv) Is additional info on the active service arc provided in the application?	(xvi) Satellite Spacing	(xvii) Phase Angle Spacing (°)	(xviii) First Satellite Initial Phase Angle (°)	(xix) Maximum Orbital Eccentricity
1	1	97.4	2	5,677	500	100	500	100	90	0	30	0	0	No	Evenly-Spaced	360	90	
2	1	99.5	2	6,307	1,000	100	1,000	100	90	0	30	0	360	No	Evenly-Spaced	360	90	
3	1	104.9	2	7,632	2,000	100	2,000	100	90	0	30	0	360	No	Evenly-Spaced	360	90	

h. Initial Phase Angle Information

(i) Orbital Plane No.	(i) Satellite No.	(ii) Initial Phase Angle (°)
1	1	90
2	1	90
3	1	90

S4. Earth-to-Space (Receive) Beams

a. Beam ID:	Rx1	n. Beam Peak Flux Density at Command Threshold (dBW/m ²):	-68.9
b. Beam Frequency (Lower Band Edge) (MHz):	28600	o. Peak Isotropic Antenna Gain (dBi):	46.3
c. Beam Frequency (Upper Band Edge) (MHz):	29100	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	Yes	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum G/T (dB/K):	19.3	w. What information will be provided with the predicted antenna gain contours?:	
k. Minimum G/T (dB/K):	19.3		
l. Maximum Saturation Flux Density (dBW/m ²):			
m. Minimum Saturation Flux Density (dBW/m ²):			

a. Beam ID:	Rx3	n. Beam Peak Flux Density at Command Threshold (dBW/m ²):	-68.9
b. Beam Frequency (Lower Band Edge) (MHz):	28600	o. Peak Isotropic Antenna Gain (dBi):	43.6
c. Beam Frequency (Upper Band Edge) (MHz):	29100	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	No	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	Yes	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum G/T (dB/K):	16.6	w. What information will be provided with the predicted antenna gain contours?:	
k. Minimum G/T (dB/K):	16.6		
l. Maximum Saturation Flux Density (dBW/m ²):			
m. Minimum Saturation Flux Density (dBW/m ²):			

a. Beam ID:	Rx2	n. Beam Peak Flux Density at Command Threshold (dBW/m ²):	-68.9
b. Beam Frequency (Lower Band Edge) (MHz):	28600	o. Peak Isotropic Antenna Gain (dBi):	46.3
c. Beam Frequency (Upper Band Edge) (MHz):	29100	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.1

e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	Yes	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum G/T (dB/K):	19.3	w. What information will be provided with the predicted antenna gain contours?:	
k. Minimum G/T (dB/K):	19.3		
l. Maximum Saturation Flux Density (dBW/m²):			
m. Minimum Saturation Flux Density (dBW/m²):			

a. Beam ID:	Rx4	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	-68.9
b. Beam Frequency (Lower Band Edge) (MHz):	28600	o. Peak Isotropic Antenna Gain (dBi):	43.6
c. Beam Frequency (Upper Band Edge) (MHz):	29100	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	No	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	Yes	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	Yes
j. Maximum G/T (dB/K):	16.6	w. What information will be provided with the predicted antenna gain contours?:	
k. Minimum G/T (dB/K):	16.6		
l. Maximum Saturation Flux Density (dBW/m²):			
m. Minimum Saturation Flux Density (dBW/m²):			

S5. Space-to-Earth (Transmit) Beams

a. Beam ID:	Tx7	n. Beam Peak Flux Density at Command Threshold (dBW/m²):				
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	40			
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):				
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.1			
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1			
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:				
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:				
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:				
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:				
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-57.7	w. What information will be provided with the predicted antenna gain contours?:				
k. Maximum Transmit EIRP (dBW):	29.3					
x. Transmit Channels						
(i) Channel ID	(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)	(iv) Channel Frequency (Lower Band Edge) (MHz)	(v) Channel Frequency (Upper Band Edge) (MHz)	(vi) Channel Type	(vii) Point of Communication
TX001	5	18802.5	18800	18805		
y. Max. Power-Flux Densities						

			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-163.9	-162.3	-153.8	-150.3	-129	-129					

a. Beam ID:	Tx8	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	40
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-57.7	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	29.3		

x. Transmit Channels						
(i) Channel ID	(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)	(iv) Channel Frequency (Lower Band Edge) (MHz)	(v) Channel Frequency (Upper Band Edge) (MHz)	(vi) Channel Type	(vii) Point of Communication
TX001	5	18802.5	18800	18805		

y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-163.9	-162.3	-153.8	-150.3	-129	-129					

a. Beam ID:	Tx9	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	40
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-51.5	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	35.5		

x. Transmit Channels						
(i) Channel ID	(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)	(iv) Channel Frequency (Lower Band Edge) (MHz)	(v) Channel Frequency (Upper Band Edge) (MHz)	(vi) Channel Type	(vii) Point of Communication
TX001	5	18802.5	18800	18805		

y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-159	-157.8	-151.1	-150	-129	-129					

a. Beam ID:	Tx3	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	42.6
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-51.5	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	35.5		

x. Transmit Channels						
(i) Channel ID	(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)	(iv) Channel Frequency (Lower Band Edge) (MHz)	(v) Channel Frequency (Upper Band Edge) (MHz)	(vi) Channel Type	(vii) Point of Communication
TX001	5	18802.5	18800	18805		

y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-162.3	-161.1	-153.8	-150	-129	-129					

a. Beam ID:	Tx5	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	42.6
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-46.7	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	40.3		

x. Transmit Channels						
(i) Channel ID	(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)	(iv) Channel Frequency (Lower Band Edge) (MHz)	(v) Channel Frequency (Upper Band Edge) (MHz)	(vi) Channel Type	(vii) Point of Communication

TX001	5	18802.5	18800	18805									
y. Max. Power-Flux Densities													
			Angles of Arrival PFD					Geographic Region PFD					
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-157.3	-156.3	-150.5	-149.7	-129	-129					

a. Beam ID:	Tx1	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	42.6
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-57.7	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	29.3		

x. Transmit Channels						
(i) Channel ID	(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)	(iv) Channel Frequency (Lower Band Edge) (MHz)	(v) Channel Frequency (Upper Band Edge) (MHz)	(vi) Channel Type	(vii) Point of Communication
TX001	5	18802.5	18800	18805		

y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-167.2	-165.6	-157	-150.3	-129	-129					

a. Beam ID:	Tx2	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	42.6
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-57.7	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	29.3		

x. Transmit Channels			
----------------------	--	--	--

(i) Channel ID		(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)		(iv) Channel Frequency (Lower Band Edge) (MHz)		(v) Channel Frequency (Upper Band Edge) (MHz)		(vi) Channel Type		(vii) Point of Communication		
TX001		5	18802.5		18800		18805						
y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-167.2	-165.6	-157	-150.3	-129	-129					

a. Beam ID:	Tx4	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	42.6
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-51.5	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	35.5		

x. Transmit Channels													
(i) Channel ID		(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)		(iv) Channel Frequency (Lower Band Edge) (MHz)		(v) Channel Frequency (Upper Band Edge) (MHz)		(vi) Channel Type		(vii) Point of Communication		
TX001		5	18802.5		18800		18805						
y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-162.3	-161.1	-153.8	-150	-129	-129					

a. Beam ID:	Tx12	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	40
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-46.7	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	40.3		

x. Transmit Channels													
(i) Channel ID		(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)		(iv) Channel Frequency (Lower Band Edge) (MHz)		(v) Channel Frequency (Upper Band Edge) (MHz)		(vi) Channel Type		(vii) Point of Communication		
TX001		5	18802.5		18800		18805						
y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-154	-153	-150.5	-141.2	-129	-129					

a. Beam ID:	Tx6	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	42.6
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-46.7	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	40.3		

x. Transmit Channels													
(i) Channel ID		(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)		(iv) Channel Frequency (Lower Band Edge) (MHz)		(v) Channel Frequency (Upper Band Edge) (MHz)		(vi) Channel Type		(vii) Point of Communication		
TX001		5	18802.5		18800		18805						
y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-157.3	-156.3	-150.5	-149.7	-129	-129					

a. Beam ID:	Tx10	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	40
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	LHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-51.5	w. What information will be provided with the predicted antenna gain contours?:	

k. Maximum Transmit EIRP (dBW):				35.5									
x. Transmit Channels													
(i) Channel ID		(ii) Channel Bandwidth (MHz)		(iii) Center Frequency (MHz)		(iv) Channel Frequency (Lower Band Edge) (MHz)		(v) Channel Frequency (Upper Band Edge) (MHz)		(vi) Channel Type		(vii) Point of Communication	
TX001		5		18802.5		18800		18805					
y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-159	-157.8	-151.1	-150	-129	-129					

a. Beam ID:	Tx11	n. Beam Peak Flux Density at Command Threshold (dBW/m²):	
b. Beam Frequency (Lower Band Edge) (MHz):	18800	o. Peak Isotropic Antenna Gain (dBi):	40
c. Beam Frequency (Upper Band Edge) (MHz):	19300	p. Isotropic Antenna Gain at 3 dB Beamwidth (dBi):	
d. Polarization:	RHCP	q. Antenna Pointing Error (°):	0.1
e. Can the space station vary the channel bandwidth with on-board processing?:	Yes	r. Antenna Rotational Error (°):	0.1
f. Is this a command beam? (Check box if Yes):	No	s. Will a GIMS container file containing all antenna contour data be provided?:	
g. Is the beam shapeable? (Check box if Yes):	No	t. Under what rules will the associated antenna contours be submitted?:	
h. Is the beam steerable? (Check box if Yes):	Yes	u. Provide a list of each orbital plane in which this antenna beam is used.:	
i. Is the beam fed into transponders? (Check box if Yes):	No	v. Are all space stations in the NGSO constellation identical?:	
j. Maximum Transmit EIRP Density (dBW/Ref BW):	-46.7	w. What information will be provided with the predicted antenna gain contours?:	
k. Maximum Transmit EIRP (dBW):	40.3		

x. Transmit Channels													
(i) Channel ID		(ii) Channel Bandwidth (MHz)	(iii) Center Frequency (MHz)		(iv) Channel Frequency (Lower Band Edge) (MHz)		(v) Channel Frequency (Upper Band Edge) (MHz)		(vi) Channel Type		(vii) Point of Communication		
TX001		5	18802.5		18800		18805						
y. Max. Power-Flux Densities													
			Angles of Arrival PFD						Geographic Region PFD				
(i) Beam Sub-Frequency (Lower Band Edge) (MHz)	(ii) Beam Sub-Frequency (Upper Band Edge) (MHz)	(iii) Reference Bandwidth (BW)	(iv) 0-2° (dBW/m²/BW)	(v) 2-5° (dBW/m²/BW)	(vi) 5-15° (dBW/m²/BW)	(vii) 15-20° (dBW/m²/BW)	(viii) 20-25° (dBW/m²/BW)	(ix) 25-90° (dBW/m²/BW)	(x) Southeastern Region (dBW/m²/BW)	(xi) Northeastern Region (dBW/m²/BW)	(xii) Western Region (dBW/m²/BW)	(xiii) Other Region (dBW/m²/BW)	(xiv) Energy Dispersal Bandwidth (kHz)
		1 MHz	-154	-153	-150.5	-141.2	-129	-129					

S6. Space-to-Space (Receive) Beams

S7. Space-to-Space (Transmit) Beams

S8. Attachments

Beam ID	Direction of Transmission	(i) Document Type	(ii) If Document Type is "Other", provide short description	(iii) File Name
---------	---------------------------	-------------------	---	-----------------

Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_500-PHI0.00.gxt
Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_500-PHI25.00.gxt
Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_2000-PHI0.00.gxt
Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_2000-PHI43.60.gxt
Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_500-PHI57.20.gxt
Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_1000-PHI0.00.gxt
Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_2000-PHI25.00.gxt
Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_1000-PHI25.00.gxt
Rx1	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_1000-PHI51.60.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_2000-PHI25.00.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_1000-PHI25.00.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_1000-PHI0.00.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_500-PHI25.00.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_500-PHI0.00.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_2000-PHI43.60.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_1000-PHI51.60.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_2000-PHI0.00.gxt
Rx2	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX1RX2_500-PHI57.20.gxt
Rx3	Earth-to-Space (Receive)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_500-PHI57.20.gxt
Rx3	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_1000-PHI51.60.gxt
Rx3	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_2000-PHI25.00.gxt
Rx3	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_1000-PHI25.00.gxt
Rx3	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_2000-PHI43.60.gxt
Rx3	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_500-PHI0.00.gxt
Rx3	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_2000-

				PHI0.00.gxt
Rx3	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_1000-PHI0.00.gxt
Rx3	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_500-PHI25.00.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_500-PHI25.00.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_1000-PHI25.00.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_500-PHI0.00.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_2000-PHI25.00.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_2000-PHI43.60.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_1000-PHI51.60.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_1000-PHI0.00.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_2000-PHI0.00.gxt
Rx4	Earth-to-Space (Receive)	Receive Antenna Gain Contour Diagram		SPACEX-NGSO-KA-RX3RX4_500-PHI57.20.gxt
Tx1	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX1TX2_500-PHI25.00.gxt
Tx1	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX1TX2_500-PHI0.00.gxt
Tx1	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX1TX2_500-PHI57.20.gxt
Tx10	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX9TX10_1000-PHI51.60.gxt
Tx10	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX9TX10_1000-PHI0.00.gxt
Tx10	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX9TX10_1000-PHI25.00.gxt
Tx11	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX11TX12_2000-PHI0.00.gxt
Tx11	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX11TX12_2000-PHI25.00.gxt
Tx11	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX11TX12_2000-PHI43.60.gxt
Tx12	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX11TX12_2000-PHI43.60.gxt
Tx12	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX11TX12_2000-PHI0.00.gxt
Tx12	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX11TX12_2000-PHI25.00.gxt
Tx2	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX1TX2_500-PHI25.00.gxt

Tx2	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX1TX2_500-PHI57.20.gxt
Tx2	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX1TX2_500-PHI0.00.gxt
Tx3	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX3TX4_1000-PHI25.00.gxt
Tx3	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX3TX4_1000-PHI0.00.gxt
Tx3	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX3TX4_1000-PHI51.60.gxt
Tx4	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX3TX4_1000-PHI0.00.gxt
Tx4	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX3TX4_1000-PHI51.60.gxt
Tx4	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX3TX4_1000-PHI25.00.gxt
Tx5	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX5TX6_2000-PHI43.60.gxt
Tx5	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX5TX6_2000-PHI25.00.gxt
Tx5	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX5TX6_2000-PHI0.00.gxt
Tx6	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX5TX6_2000-PHI25.00.gxt
Tx6	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX5TX6_2000-PHI0.00.gxt
Tx6	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX5TX6_2000-PHI43.60.gxt
Tx7	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX7TX8_500-PHI25.00.gxt
Tx7	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX7TX8_500-PHI0.00.gxt
Tx7	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX7TX8_500-PHI57.20.gxt
Tx8	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX7TX8_500-PHI25.00.gxt
Tx8	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX7TX8_500-PHI0.00.gxt
Tx8	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX7TX8_500-PHI57.20.gxt
Tx9	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX9TX10_1000-PHI0.00.gxt
Tx9	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX9TX10_1000-PHI51.60.gxt
Tx9	Space-to-Earth (Transmit)	Transmit Antenna Gain Contour Diagram		SPACEX-NGSO-KA-TX9TX10_1000-PHI25.00.gxt