Chapter 3

Arithmetic operations on Integers

Datapath



Arithmetic Operations on Integers

- Operations on integers
  - Addition and subtraction
  - Multiplication and division
  - Dealing with overflow

Integer Addition

- Example: 7 + 6



- Overflow
  - please write down the 8-bit signed integer addition:
  - $0100\ 0000_{bin}+0100\ 0000_{bin}=?$ 1000 0000 = -128 ≠ 128
  - $1000\ 0000_{bin}+1000\ 0000_{bin}=?$ 0000 0000 = 0 ≠ -256

  } overflow

  - $0100\ 0000_{bin}+1100\ 0000_{bin}=?$ 0000 0000 = 0 = 0 (-128 +64)
  - $1100\ 0000_{bin}+1100\ 0000_{bin}=?$ 1000 0000 = -128 = -128

Please write down the equations in binary and decimal.

[-128, 127] 不在该范围内即 overflow

Overflow

- Examples in last page:
  - 8-bit signed integer range: -128 ~ 127
  - $0100\ 0000_{bin}+0100\ 0000_{bin}=1000\ 0000_{bin}$ 64 + 64= -128 Overflow
  - $1000\ 0000_{bin}+1000\ 0000_{bin}=(1)0000\ 0000_{bin}$ -128 + (-128) = 0 Overflow
  - $0100\ 0000_{bin}+1100\ 0000_{bin}=(1)0000\ 0000_{bin}$ 64+ (-64)= 0 No overflow
  - $1100\ 0000_{bin}+1100\ 0000_{bin}=(1)1000\ 0000_{bin}$ -64+(-64)=-128 No overflow
- Overflow if result out of range
  - no overflow, if ddding +ve and –ve operands
  - Overflow, if
    - Adding two +ve operands, get –ve operand $p + p \xrightarrow{0} n$
    - Adding two -ve operands, get +ve operand $n + n \xrightarrow{0} p$

1-bit adder



$$\text{Sum} = (a \cdot \overline{b} \cdot \overline{\text{CarryIn}}) + (\overline{a} \cdot b \cdot \overline{\text{CarryIn}}) + (\overline{a} \cdot \overline{b} \cdot \text{CarryIn}) + (a \cdot b \cdot \text{CarryIn})$$

$$\text{CarryOut} = (b \cdot \text{CarryIn}) + (a \cdot \text{CarryIn}) + (a \cdot b)$$

Inputs			Outputs		
a	b	CarryIn	CarryOut	Sum	Comments
0	0	0	0	0	$0 + 0 + 0 = 00_{two}$
0	0	1	0	1	$0 + 0 + 1 = 01_{two}$
0	1	0	0	1	$0 + 1 + 0 = 01_{two}$
0	1	1	1	0	$0 + 1 + 1 = 10_{two}$
1	0	0	0	1	$1 + 0 + 0 = 01_{two}$
1	0	1	1	0	$1 + 0 + 1 = 10_{two}$
1	1	0	1	0	$1 + 1 + 0 = 10_{two}$
1	1	1	1	1	$1 + 1 + 1 = 11_{two}$

1-bit Adder



$$\text{Sum} = (a \cdot \overline{b} \cdot \overline{\text{CarryIn}}) + (\overline{a} \cdot b \cdot \overline{\text{CarryIn}}) + (\overline{a} \cdot \overline{b} \cdot \text{CarryIn}) + (a \cdot b \cdot \text{CarryIn})$$

$$\text{CarryOut} = (b \cdot \text{CarryIn}) + (a \cdot \text{CarryIn}) + (a \cdot b)$$



1-bit adder – version 1



1-bit adder – version 2

1-bit ALU and 32-bit ALU

- ALU: arithmetic logical unit
- 1-bit ALU and 32-bit ALU
  - If op = 0, o = a & b (and)
  - If op = 1, o = a | b (or)
  - If op = 2, o = a + b (add)





Integer Subtraction

- Add negation of second operand
- Example: 7 – 6 = 7 + (–6)

+7:	0000 0000 … 0000 0111
–6:	1111 1111 … 1111 1010
+1:	0000 0000 … 0000 0001

- Overflow if result out of range
  - No overflow, if subtracting two +ve or two –ve operands
  - Overflow, if:
    - Subtracting +ve from –ve operand, and the result sign is 0 (+ve)
    - Subtracting –ve from +ve operand, and the result sign is 1 (-ve)

Dealing with Overflow

- Some languages (e.g., C) ignore overflow
  - Use MIPS `addu, addiu, subu` instructions
- Other languages (e.g., Ada, Fortran) require raising an exception
  - Use MIPS `add, addi, sub` instructions
  - On overflow, invoke exception handler
    - Save PC in exception program counter (EPC) register
    - Jump to predefined handler address
    - `mfc0` (move from coprocessor reg) instruction can retrieve EPC value, to return after corrective action
- Note: addiu: "u" means it doesn't generate overflow exception, but the immediate can be a signed number

Arithmetic for Multimedia-SIMD

- Graphics and media processing operates on vectors of 8-bit and 16-bit data
  - Use 64-bit adder, with partitioned carry chain
    - Operate on 8×8-bit, 4×16-bit, or 2×32-bit vectors
  - SIMD (single-instruction, multiple-data)
  - addv rd, rs, rt



Arithmetic for Multimedia – Saturating Operation

- Pixel representation:
  - RGB, each using 8 bit to represent, range: 0-255
- Saturating operations
  - On overflow, result is largest representable value
    - Instead of 2s-complement modulo arithmetic
  - E.g., change the volume and brightness in audio or video
  - Original brightness of three pixels: 100, 150, 200, make them brighter by adding 100, the result should be 200, 250, 44? Or 200, 250, 255?

Multiplication

- Start with long-multiplication approach

multiplicand

multiplier

product

```
  1000
× 1001
------
  1000
 0000
0000
1000
-------
1001000
```

Length of product is the sum of operand lengths



Multiplication

- Start with long-multiplication approach



Length of product is the sum of operand lengths



Multiplication

- Start with long-multiplication approach



Length of product is the sum of operand lengths



Multiplication

- Start with long-multiplication approach



Length of product is the sum of operand lengths



Multiplication

- Start with long-multiplication approach



Length of product is the sum of operand lengths



Multiplication

- Start with long-multiplication approach



Length of product is the sum of operand lengths



Finish!

Multiplication Hardware





In every step:

- ✓ multiplicand is shifted
- ✓ next bit of multiplier is examined (also a shifting step)
- ✓ if this bit is 1, shifted multiplicand is added to the product

Optimized Multiplier

- Perform steps in parallel: add/shift



- ✓ The multiplier is initially stored in the right half of product register
- ✓ check the 0^{th} bit in Product register, if 1, add left half of product with multiplicand
- ✓ the sum keeps shifting right
- ✓ at every step, number of bits in product + multiplier = 64, hence, they share a single 64-bit register
- ✓ for signed multiplication, it also works

Faster Multiplier



- The previous algorithm requires a clock to ensure that the earlier addition has completed before shifting
- This algorithm can quickly set up most inputs – it then has to wait for the result of each add to propagate down – faster because no clock is involved
- high transistor cost

Faster Multiplier

- Uses multiple pipelined adders
  - Cost/performance tradeoff

32 bit, 16 ALUs (可复用)
5 time slot



- Can be pipelined
  - Several multiplication performed in parallel

MIPS Multiplication

- Two 32-bit registers for product
  - HI: most-significant 32 bits
  - LO: least-significant 32 bits
- Instructions
  - `mult rs, rt  /  multu rs, rt`
    - 64-bit product in HI/LO
  - `mfhi rd  /  mflo rd`
    - Move from HI/LO to rd
    - Can test HI value to see if product overflows 32 bits
  - `mul rd, rs, rt`
    - Least-significant 32 bits of product –> rd

Division



n-bit operands yield *n*-bit quotient and remainder

- Check for 0 divisor
- Long division approach
  - If divisor ≤ dividend bits
    - 1 bit in quotient, subtract
  - Otherwise
    - 0 bit in quotient, bring down next dividend bit
- Restoring division
  - Do the subtract, and if remainder goes < 0, add divisor back
- Signed division
  - Divide using absolute values
  - Adjust sign of quotient and remainder as required

Divide Example

- Divide 7_{dec} ($0000\ 0111_{bin}$) by 2_{dec} (0010_{bin})

Iter	Step	Quot	Divisor	Remainder
0	Initial values	0000	0010 0000	0000 0111
1	Rem = Rem – Div	0000	0010 0000	1110 0111
	Rem < 0 ➔ +Div, shift 0 into Q	0000	0010 0000	0000 0111
	Shift Div right	0000	0001 0000	0000 0111
2	Same steps as 1	0000	0001 0000	1111 0111
		0000	0001 0000	0000 0111
		0000	0000 1000	0000 0111
3	Same steps as 1	0000	0000 0100	0000 0111
4	Rem = Rem – Div	0000	0000 0100	0000 0011
	Rem >= 0 ➔ shift 1 into Q	0001	0000 0100	0000 0011
	Shift Div right	0001	0000 0010	0000 0011
5	Same steps as 4	0011	0000 0001	0000 0001

除数后补零 被除数前补零

shift = # divisor 位数 + 1

Division Hardware





Division Hardware



Division Hardware



Division Hardware



Division Hardware



Division Hardware



Division Hardware



Optimized Divider



- One cycle per partial-remainder subtraction
- Looks a lot like a multiplier!
  - Same hardware can be used for both

Signed Division

- (+7) ÷ (-2) = (-3) ⋯ (+1)
- (-7) ÷ (-2) = (+3) ⋯ (-1)
- The quotient is +, if the signs of divisor and dividend agrees, otherwise, quotient is –
- The sign of the remainder matches that of the dividend.

Faster Division

- Can’t use parallel hardware as in multiplier
  - Subtraction is conditional on sign of remainder
- Faster dividers (e.g. SRT devision) generate multiple quotient bits per step
  - Still require multiple steps

MIPS Division

- Use HI/LO registers for result
  - HI: 32-bit remainder
  - LO: 32-bit quotient
- Instructions
  - `div rs, rt  /  divu rs, rt`
  - No overflow or divide-by-0 checking
    - Software must perform checks if required
  - Use `mfhi, mflo` to access result

Summary

- Operations on integers
  - Addition and subtraction
  - Multiplication and division
  - Dealing with overflow