Deep Ensembles for Predictive Uncertainty

Nicole Lacey Christopher Lawton

1 Introduction

Neural network classifier performance is typically evaluated by its accuracy, however in many scenarios the probabilities a network assigns to its predictions matters as much as the predictions and raw accuracy. It is frequently observed that a model's assigned probability is a poor descriptor to a model's true confidence of a given prediction (i.e. when a model is poorly calibrated). A simple approach to provide insight into model uncertainty is through ensembling, by averaging the predictions of several models, the ensemble becomes less confident when the members disagree. In this report we compare two different methods of ensembling. A standard deep ensemble which consists of several networks trained separately from different random initializations, and MC dropout where a single network with dropout is trained and each stochastic forward pass at test time represents a single member of the ensemble. We first evaluate both models on a simple two-dimensional problem where predictive uncertainty can be visualized directly and then evaluate them on Fashion-MNIST. For each method we examine the full ensemble and its individual members with respect to accuracy, predictive uncertainty and calibration, as well as the diversity of their predictions.

2 Setup

2.1 Data

[Two moons: 500 train / 1,000 test points, noise 0.12; 2-D, so predictions can be plotted over the whole input plane. Fashion-MNIST: 60,000 train / 10,000 test 28×28 grayscale images, 10 classes; several classes look alike (shirt, T-shirt, pullover, coat), which gives real aleatoric uncertainty.]

2.2 Model and training

[Both methods use the same MLP (Flatten, two hidden ReLU layers of width 64 for two moons / 256 for Fashion-MNIST, linear output), Adam with learning rate 10^{-3}, and 200 / 20 epochs with batch size 128 / 256. State the L2 term: weight decay 10^{-4}, equivalent to a zero-mean isotropic Gaussian prior on the weights. The only differences between the methods are dropout and how members are produced.]

2.3 Standard deep ensembles

[$M = 10$ networks, member m seeded `seed`$+m$ (initialization and data order), no dropout.] The ensemble prediction averages the members' predicted probabilities,

$$\bar{p}(y \mid x) = \frac{1}{M} \sum_{m=1}^{M} p_m(y \mid x), \tag{1}$$

a Monte Carlo estimate of the predictive distribution $p(y \mid x, \mathcal{D})$.

2.4 MC dropout

[One network with dropout $p = 0.1$ after each hidden layer, trained with the same objective (approximate variational inference, Gal & Ghahramani). Dropout stays on at test time; $T = 10$ stochastic passes are each treated as a member and averaged as in Eq. (1). Masks use a fixed seed, so results are reproducible.]

2.5 Evaluation metrics

[One sentence each on what the metric captures; definitions and code pointers are in `notes.md`.] All metrics except the entropy decomposition and disagreement are computed on $\bar{p}$.

- **Error rate**: fraction of inputs where $\arg\max_c \bar{p}(c \mid x) \neq y$.
- **Negative log-likelihood** (nats): $\mathrm{NLL} = -\frac{1}{N}\sum_n \ln \bar{p}(y_n \mid x_n)$.
- **Expected calibration error**: with confidence $\max_c \bar{p}(c \mid x)$ split into $B = 15$ equal-width bins, $\mathrm{ECE} = \sum_b \frac{n_b}{N} |\mathrm{acc}(b) - \mathrm{conf}(b)|$, shown in full by reliability diagrams.
- **Entropy decomposition**: predictive entropy (total) splits into expected entropy (aleatoric) and mutual information (epistemic),

$$\underbrace{H[\bar{p}]}_{\text{predictive}} = \underbrace{\frac{1}{M}\sum_m H[p_m]}_{\text{expected}} + \underbrace{\mathrm{MI}}_{\text{epistemic}}, \qquad H[p] = -\sum_c p_c \ln p_c. \tag{2}$$

- **Pairwise disagreement**: fraction of test inputs on which two members predict a different class; a PCA of each member's test predictions (*function space*) shows the same diversity visually.

2.6 Ensemble-size protocol

[Train $M = 10$ once; evaluate subsets of size $k \in \{1, 2, 5, 10\}$ (every subset when there are at most 20, else 20 random ones). Error bars are ± 1 sd over subsets; they shrink at large k partly because subsets overlap, and $k = 10$ is a single subset. The test set is used for evaluation only, never for model selection.]


3 Evaluation

Figures show the deep ensemble (a) and MC dropout (b) side by side; each panel has its own y-axis range, so compare values rather than curve heights.

3.1 Two moons

3.1.1 Training curves

[Both converge by about epoch 75 (99.4% test accuracy); test NLL keeps falling slowly to epoch 200 with no overfitting. Ensemble and member-mean curves overlap from about epoch 10: the final gain from ensembling is -0.04% (DE) and $+0.07\%$ (MC), i.e. nothing.]




(a) Deep ensemble (b) MC dropout

Figure 1: Two moons training curves: member mean ± 1 sd and the averaged prediction, on train and test.

3.1.2 Ensemble size

[Flat for both methods. Test error is 0.5% (5 of 1,000 points), and changes with k are under one test point (e.g. 0.46%→0.50%); the auto-scaled axes make noise look like trends. Values are tiny because nearly every point gets confidence ≈ 0.998: entropy ≈ 0.02 nats vs. a maximum of $\ln 2 = 0.693$. MI at $k = 10$: DE 0.0003 vs. MC 0.0046, so DE members are nearly identical on the test points.]




(a) Deep ensemble (b) MC dropout

Figure 2: Two moons metrics vs. number of members; error bars are ±1 sd over k-member subsets. Note the very small y-axis ranges.

3.1.3 Uncertainty surfaces

[Both draw the same boundary through the data. MI near data vs. away from it: DE 0.003 vs. 0.038 (12×), MC 0.022 vs. 0.053 (2.4×). The DE's uncertainty is concentrated away from the data; MC dropout's is spread everywhere, including on the data. Optional sentence on reliability (not shown): 97% of test points have confidence above 0.93; both methods are slightly underconfident (ECE < 0.01).]



(a) Deep ensemble (b) MC dropout

Figure 3: Two moons: predictive probability (left of each pair) and mutual information (right) over the input plane. [Describe where each method is uncertain.]

3.1.4 Function space

[MC dropout spreads more and disagrees more (0.5% vs. 0.1%), but 0.001 is one test point: DE pairs disagree on 0–4 points, MC pairs on 2–7. Only 4 test points ever change class under any DE member, all on the boundary (averaged confidence ≈ 0.55); each dropout pass shifts the boundary slightly, so 14 boundary points change class in at least one pass. Don't read structure into the DE heatmap; the differences are 1–3 points.]





Figure 4: Two moons function space: members of both methods in one PCA of their test predictions (left) and pairwise top-1 disagreement (right).

3.2 Fashion-MNIST

3.2.1 Training curves

[DE 90.1% vs. MC 88.7% test accuracy; test NLL 0.276 vs. 0.318. Gain over the member mean: DE up to +1.46% (final +1.18%), MC +0.47%. Member spread is larger for the DE in NLL (sd 0.0067 vs. 0.0018) but similar in accuracy; the bands mean different things (10 networks vs. 10 passes of one). Train–test accuracy gap: DE 4.3 points, MC 3.6 points (dropout regularizes).]



(a) Deep ensemble


(b) MC dropout

Figure 5: Fashion-MNIST training curves: member mean ±1 sd and the averaged prediction, on train and test.

3.2.2 Ensemble size

[Every metric improves with k, more for the DE (error 11.1%→9.9% vs. 11.8%→11.3%; ECE 0.025→0.008 vs. 0.029→0.018; MI 0.035 vs. 0.016 at $k = 10$); most of the gain comes by $k = 5$. Context: uniform-guess NLL and maximum entropy are $\ln 10 = 2.30$; MI is about 13% of predictive entropy for the DE. Train ECE rises with k while test ECE falls: averaging lowers confidence, which fixes overconfident test predictions but makes already slightly underconfident train predictions more so.]


3.2.3 Reliability



(a) Deep ensemble (b) MC dropout

Figure 6: Fashion-MNIST metrics vs. number of members; error bars are ±1 sd over k-member subsets.

[Single members of both methods are overconfident (mean confidence − accuracy: DE +2.6, MC +2.9 points). The DE ensemble ends almost exactly calibrated (−0.06 points, ECE −69%); MC dropout stays overconfident (+1.7 points, ECE −38%). Averaging lowers confidence most where members disagree, which is where errors concentrate.]



(a) Deep ensemble (b) MC dropout

Figure 7: Fashion-MNIST test reliability: single member vs. full ensemble. Points below the diagonal are overconfident; the histogram shows each bin's share of inputs.

3.2.4 Function space

[DE members spread widely; the 10 MC passes almost coincide. Mean disagreement DE 7.1% vs. MC 4.4%, matching the MI gap. PC1 mostly separates the methods (they trained different networks); diversity is the spread within each group. Contrast with two moons (Fig. 4), where the order is reversed.]




Figure 8: Fashion-MNIST function space: members of both methods in one PCA of their test predictions (left) and pairwise top-1 disagreement (right).

4 Discussion

[Where diversity comes from: random initialization sends DE members to different solutions on both datasets; what matters is whether the test inputs force them to agree. On two moons (2-D, test points on the training data) every solution draws the same boundary; on Fashion-MNIST (784-D, ambiguous images) they differ. MC dropout samples around one solution on both datasets (Fort et al., 2019).]

[The same averaging fixes calibration on test and worsens it on train.]

[Cost: the DE trains 10 networks; MC dropout trains one and pays only at test time.]

[Limitations: one training seed per configuration; dropout rate 0.1 not tuned; MLPs only; no out-of-distribution or dataset-shift evaluation.]

5 Conclusion

[Both methods improve on a single network, and the improvement grows with k. The DE improves more on accuracy, NLL and especially calibration, because its members differ more (2× MI, 1.6× disagreement). In-distribution diversity depends on whether the data leaves room for it; on two moons it does not.]