SESSION 2 · SUPPORT L1

# From a ticket to the logs

User support and qualifying user needs —
one app, five tickets, hands-on

Horacio Gonzalez · October 26, 2026 · 2 hours, mostly hands-on

AGENDA

# One app, five tickets

| Time | Scenario | Ticket |
|---|---|---|
| 0:00 | 0 · Setup | Is your setup working? — and the support mindset |
| 0:10 | 1 · Normal | A Python app and its PostgreSQL database |
| 0:35 | 2 | “My change isn’t online” |
| 0:50 | 3 | “It works, then it errors” |
| 1:10 | — | Break |
| 1:15 | 4 | “My files disappear” — add an FS Bucket |
| 1:35 | 5 | “Files vanish again” |
| 1:50 | — | Debrief, key messages, what’s next |

SCENARIO 0 · 10 MIN

# Is your setup working?

```
git --version
clever version
clever profile
clever applications list \
--org {{ORG}}
```

And the Console in your browser, on the training organisation.

You also need this session's repository: **demos/** and **handouts/**.

**Blocked?** Say it now: it's your first support ticket of the day.

THE SUPPORT MINDSET

# Understand before you fix

**Ticket**
a symptom, in the user's words

→

**Qualify**
what, who, where, since when, what changed

→

**Look**
logs, Console, configuration

→

**Explain**
cause and fix, in the user's words

→

**Write**
a ticket someone else can take over

Handouts: **qualification checklist** to ask the right questions, **ticket template** to write it down.

WHERE TO LOOK

# Each kind of problem has its place

| Symptom | Look at | How |
|---|---|---|
| Didn’t deploy, didn’t start | Deployment log | clever activity · clever logs --deployment-id |
| Errors once running | Runtime logs | clever logs --since 30m --until now |
| Slow, HTTP errors | Access logs, metrics | clever accesslogs --since 30m --until now · Console → Metrics |
| Limits, data, storage | The add-on | plan, dashboard · clever addon env |
| “It should work” | Configuration | clever env · the repository |

**Always first:** the identifiers — organisation, app or add-on ID, environment, time range.

SCENARIO 1 · 25 MIN

# The normal case: how things should go

```
export LAB=<session-folder>
cp -r $LAB/demos/1-base ~/cc-support-<name>
cd ~/cc-support-<name>
git init && git add . && git commit -m v1

clever create --type python \
--org {{ORG}} support-<name>
clever addon create postgresql-addon \
pg-<name> --plan dev --org {{ORG}}
clever service link-addon pg-<name>
clever env set CC_PYTHON_MODULE app:app
clever deploy
```

Then **/**, **/db**, **clever activity**, **clever logs**.

The add-on is linked **before** the first deploy: its variables are there at start.

Note your **organisation, app and add-on IDs**: every ticket needs them.

SCENARIO 2 · 15 MIN

# “My change isn’t online”

> “I pushed version 2 of the app an hour ago and it still shows version 1! Is the platform down?”

- Qualify: what, where, since when, what changed?
- Is the platform down? Is the app down?
- Where is the explanation?
- Why does the app still answer?

```
cd ~/cc-support-<name>
cp -R $LAB/demos/2-no-deploy/files/. .
git add -A && git commit -m v2
clever deploy
```

SCENARIO 3 · 20 MIN

# “It works, then it errors”

> “Since this morning’s release, /db works for a few calls, then only returns errors. Restarting fixes it for a minute. Is the database broken?”

- Does the deployment log help this time?
- Where is the error? Who says it?
- What are the add-on’s limits?
- Why does a restart “fix” it?

```
cd ~/cc-support-<name>
cp -R $LAB/demos/3-connections/files/. .
git add -A && git commit -m v3
clever deploy
# then call /db ten times
```

SCENARIO 4 · 20 MIN

# “My files disappear”: add an FS Bucket

### 1 · SEE THE PROBLEM

Upload a file, **clever restart**, list again. Where did it go — and why?

### 2 · ADD PERSISTENT STORAGE

```
clever addon create fs-bucket \
fs-<name> --org {{ORG}}
clever service link-addon fs-<name>
clever addon env <addon-id>
clever env set CC_FS_BUCKET \
/uploads:<bucket-host>
clever restart
```

### 3 · PROVE IT

Mount line in the deployment log · upload, restart, list · the add-on’s **File explorer**.

The mount folder is relative to the app, and **must not exist** in the repository.

SCENARIO 5 · 15 MIN · STRETCH

# “Files vanish again”

> “Since the last release, uploaded files disappear after every deployment again. And the bucket looks empty in the Console. The FS Bucket is broken!”

- Is the bucket broken? Is it mounted?
- Where is the app writing?
- What changed — code **and** configuration?
- More than one problem: find them all.

```
cd ~/cc-support-<name>
cp -R $LAB/demos/5-fs-bucket-config/files/. .
git add -A && git commit -m v5
bash $LAB/demos/5-fs-bucket-config/configure.sh
clever deploy
```

WHAT MUST STICK

# Eight reflexes for the next ticket

1. Understand before you fix: “the platform is down” rarely is.
2. No identifiers, no ticket: organisation, resource ID, environment, time range.
3. Ask “what changed?” — a deployment, a variable, a dependency, the traffic.
4. Look in the right log: deployment, runtime, access — or the add-on.
5. A failed deployment doesn’t take the app down: the previous version keeps serving.
6. A restart is not a fix: if it “helps for a minute”, something accumulates.
7. No error is also a symptom: compare the configuration with reality.
8. One user or everyone? Scope decides priority — escalate with a package.

WHAT'S NEXT

# From cases to a method

Next session — **Troubleshooting methodology**: turning today's cases into a repeatable method, then more runtimes and Clever Kubernetes Engine.

Before you leave: clean up (end of lab.md) — unless we keep your app for the next session.