

Packet Tracer - Configuración de OSPFv2 de área única

Tabla de asignación de direcciones

Dispositivo	Interfaz	Dirección IP / Prefijo
P2P-1	S0/1/0	10.0.0.1/30
	S0/1/1	10.0.0.9/30
	S0/2/0	10.0.0.13/30
P2P-2	S0/1/0	10.0.0.2/30
	S0/1/1	10.0.0.5/30
	G0/0/0	192.168.1.1/24
	G0/0/1	192.168.2.1/24
P2P-3	S0/1/0	10.0.0.6/30
	S0/1/1	10.0.0.10/30
	G0/0/0	192.168.3.1/28
BC-1	S0/1/0	10.0.0.14/30
	S0/1/1	64.0.100.2/30
	G0/0/0	10.0.1.1/29
BC-2	G0/0/0	192.168.4.1/30
	G0/0/1	10.0.1.2/29
BC-3	G0/0/0	192.168.5.1/24
	G0/0/1	10.0.1.3/29
Servidor de Internet	NIC	203.0.113.100/24
PC 1	NIC	192.168.1.10/24
Laptop 1	NIC	192.168.2.20/24
Servidor Workgroup	NIC	192.168.3.14/28
PC 2	NIC	192.168.4.40/24
PC 3	NIC	192.168.5.50/24

Objetivos

Implemente el OSPFv2 de área única en redes difusión de acceso múltiple de punto a punto.

Aspectos básicos

Está ayudando a un ingeniero de red a probar una configuración de OSPF mediante la creación de la red en el laboratorio donde trabaja. Ha interconectado los dispositivos y configurado las interfaces y tiene conectividad dentro de las LAN locales. Su trabajo consiste en completar la configuración OSPF de acuerdo con los requisitos dejados por el ingeniero.

Utilice la información proporcionada y la lista de requisitos para configurar la red de prueba. Cuando la tarea se haya completado correctamente, todos los hosts deberían poder hacer ping al servidor de Internet.

Instrucciones

Configure la red para cumplir con los requisitos.

Requisitos

Use el ID process 10 para la activación de OSPF en todos los routers.

- Active OSPF mediante instrucciones de red y máscaras inversas en los routers de la red de la Sede.
- Active OSPF configurando las interfaces de los dispositivos de red en la red del servicio de datos, cuando sea necesario.
- Configure los router IDs en los routers de red multiacceso de la siguiente manera:
 - BC-1: 6.6.6.6
 - BC-2: 5.5.5.5
 - BC-3: 4.4.4.4
- Configure OSPF para que las actualizaciones de enrutamiento no se envíen a las redes donde no sean necesarias.
- Configure el router BC-1 con la prioridad de interfaz OSPF más alta para que siempre sea el router designado de la red multiacceso.
- Configure una ruta predeterminada a la nube de ISP mediante el argumento de comando exit interface.
- Distribuya automáticamente la ruta predeterminada a todos los routers de la red.
- Configure los routers OSPF para que el costo de la interfaz Gigabit Ethernet sea 10 y el costo Fast Ethernet sea 100.
- Configure el valor de costo OSPF de la interfaz P2P-1 Serial0/1/1 a 50.
- Configure los valores tiempo de saludo y muerto en las interfaces que conectan P2P-1 y BC-1 para que sean el doble de los valores predeterminados.

P2P-1		P2P-1		P2P-1	
Physical Config CLI Attributes		Physical Config CLI Attributes		Physical Config CLI Attributes	
<pre>interface Serial0/2/1 no ip address clock rate 2000000 shutdown ! interface Vlan1 no ip address shutdown ! router ospf 10 log-adjacency-changes auto-cost reference-bandwidth 10000 network 10.0.0.12 0.0.0.3 area 0 network 10.0.0.0 0.0.0.3 area 0 network 10.0.0.8 0.0.0.3 area 0 ! ip classless ! ip flow-export version 9 ! line con 0 ! line aux 0 ! line vty 0 4 login ! end --More-- </pre>		<pre>! ! interface GigabitEthernet0/0/0 no ip address duplex auto speed auto shutdown ! interface GigabitEthernet0/0/1 no ip address duplex auto speed auto shutdown ! interface Serial0/1/0 ip address 10.0.0.1 255.255.255.252 clock rate 2000000 ! interface Serial0/1/1 ip address 10.0.0.9 255.255.255.252 ip ospf cost 50 clock rate 2000000 ! interface Serial0/2/0 ip address 10.0.0.13 255.255.255.252 ip ospf hello-interval 20 ip ospf dead-interval 80 ! interface Serial0/2/1 no ip address clock rate 2000000 shutdown ! interface Vlan1 no ip address shutdown ! --More-- </pre>		<pre>Building configuration... Current configuration : 1103 bytes ! version 15.4 no service timestamps log datetime msec no service timestamps debug datetime msec no service password-encryption ! hostname P2P-1 ! ! ! ! ! ! no ip cef no ipv6 cef ! ! ! ! ! ! spinning-tree mode pvst ! ! !--More--</pre>	
P2P-1		P2P-1		P2P-1	
Physical Config CLI Attributes		Physical Config CLI Attributes		Physical Config CLI Attributes	
<pre>P2P-l#show ip ospf interface Serial0/2/0 is up, line protocol is up Internet address is 10.0.0.13/30, Area 0 Process ID 10, Router ID 10.0.0.13, Network Type POINT-TO-POINT, Cost: 6476 Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 20, Dead 80, Wait 80, Retransmit 5 Hello due in 00:00:00 Index 1/L, Flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 1 , Adjacent neighbor count is 1 Adjacent with neighbor 6.6.6.6 Suppress hello for 0 neighbor(s) Serial0/1/0 is up, line protocol is up Internet address is 10.0.0.1/30, Area 0 Process ID 10, Router ID 10.0.0.13, Network Type POINT-TO-POINT, Cost: 6476 Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 Hello due in 00:00:00 Index 2/2, Flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 1 , Adjacent neighbor count is 1 Adjacent with neighbor 192.168.2.1 Suppress hello for 0 neighbor(s) Serial0/1/1 is up, line protocol is up Internet address is 10.0.0.9/30, Area 0 Process ID 10, Router ID 10.0.0.13, Network Type POINT-TO-POINT, Cost: 50 Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 Hello due in 00:00:05 Index 3/3, Flood queue length 0 Next 0x0(0)/0x0(0) --More-- </pre>		<pre>Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 20, Dead 80, Wait 80, Retransmit 5 Hello due in 00:00:00 Index 1/L, Flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 1 , Adjacent neighbor count is 1 Adjacent with neighbor 6.6.6.6 Suppress hello for 0 neighbor(s) Serial0/1/0 is up, line protocol is up Internet address is 10.0.0.1/30, Area 0 Process ID 10, Router ID 10.0.0.13, Network Type POINT-TO-POINT, Cost: 6476 Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 Hello due in 00:00:00 Index 2/2, Flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 1 , Adjacent neighbor count is 1 Adjacent with neighbor 192.168.2.1 Suppress hello for 0 neighbor(s) Serial0/1/1 is up, line protocol is up Internet address is 10.0.0.9/30, Area 0 Process ID 10, Router ID 10.0.0.13, Network Type POINT-TO-POINT, Cost: 50 Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 Hello due in 00:00:05 Index 3/3, Flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 1 , Adjacent neighbor count is 1 Adjacent with neighbor 192.168.3.1 Suppress hello for 0 neighbor(s) P2P-l# P2P-l#</pre>			

Router P2P-2

The image displays two side-by-side screenshots of a network device's configuration interface, specifically for a device named P2P-2.

Left Screenshot:

- Menu Bar:** Physical | Config | CLI | Attributes
- Command Prompt:** P2P-2#show running
- Status:** Building configuration...
- Configuration Summary:** Current configuration : 1010 bytes
- Version:** version 15.4
- Services:** no service timestamps log datetime msec, no service timestamps debug datetime msec, no service password-encryption
- Hostname:** hostname P2P-2
- IP Settings:** no ip cef, no ipv6 cef
- Spanning Tree:** spanning-tree mode pvst
- Footer:** --More--

Right Screenshot:

- Menu Bar:** Physical | Config | CLI | Attributes
- Interface Configuration:**

```
interface GigabitEthernet0/0/0
ip address 192.168.1.1 255.255.255.0
duplex auto
speed auto
!
interface GigabitEthernet0/0/1
ip address 192.168.2.1 255.255.255.0
duplex auto
speed auto
!
interface Serial0/1/0
ip address 10.0.0.2 255.255.255.252
!
interface Serial0/1/1
ip address 10.0.0.5 255.255.255.252
!
interface Vlan1
no ip address
shutdown
!
router ospf 10
log-adjacency-changes
passive-interface GigabitEthernet0/0/0
passive-interface GigabitEthernet0/0/1
auto-cost reference-bandwidth 10000
network 10.0.0.0 0.0.0.3 area 0
network 10.0.0.4 0.0.0.3 area 0
network 192.168.1.0 0.0.0.255 area 0
network 192.168.2.0 0.0.0.255 area 0
!
ip classless
!
ip flow-export version 9
!
```
- Footer:** --More--

P2P-2#	P2P-2#
Physical Config CLI Attributes	Physical Config CLI Attributes
<pre> P2P-2# P2P-2#show ip ospf interface GigabitEthernet0/0/0 is up, line protocol is up Internet address is 192.168.1.1/24, Area 0 Process ID 10, Router ID 192.168.2.1, Network Type BROADCAST, Cost: 10 Transmit Delay is 1 sec, State DR, Priority 1 Designated Router (ID) 192.168.2.1, Interface address 192.168.1.1 No backup designated router on this network Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 No Hellos (Passive interface) Index 1/1, flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 0, Adjacent neighbor count is 0 Suppress hello for 0 neighbor(s) GigabitEthernet0/0/1 is up, line protocol is up Internet address is 192.168.2.1/24, Area 0 Process ID 10, Router ID 192.168.2.1, Network Type BROADCAST, Cost: 10 Transmit Delay is 1 sec, State DR, Priority 1 Designated Router (ID) 192.168.2.1, Interface address 192.168.2.1 No backup designated router on this network Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 No Hellos (Passive interface) Index 2/2, flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 0, Adjacent neighbor count is 0 Suppress hello for 0 neighbor(s) Serial0/1/0 is up, line protocol is up Internet address is 10.0.0.2/30, Area 0 Process ID 10, Router ID 192.168.2.1, Network Type POINT-TO-POINT, Cost: 6476 Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 Hello due in 00:00:07 --More-- </pre>	<pre> Transmit Delay is 1 sec, State DR, Priority 1 Designated Router (ID) 192.168.2.1, Interface address 192.168.2.1 No backup designated router on this network Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 No Hellos (Passive interface) Index 2/2, flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 0, Adjacent neighbor count is 0 Suppress hello for 0 neighbor(s) Serial0/1/0 is up, line protocol is up Internet address is 10.0.0.2/30, Area 0 Process ID 10, Router ID 192.168.2.1, Network Type POINT-TO-POINT, Cost: 6476 Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 Hello due in 00:00:07 Index 3/3, flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Neighbor Count is 1, Adjacent neighbor count is 1 Adjacent with neighbor 10.0.0.13 Suppress hello for 0 neighbor(s) Serial0/1/1 is up, line protocol is up Internet address is 10.0.0.5/30, Area 0 Process ID 10, Router ID 192.168.2.1, Network Type POINT-TO-POINT, Cost: 6476 Transmit Delay is 1 sec, State POINT-TO-POINT, Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5 Hello due in 00:00:07 Index 4/4, flood queue length 0 Next 0x0(0)/0x0(0) Last flood scan length is 1, maximum is 1 Last flood scan time is 0 msec, maximum is 0 msec Suppress hello for 0 neighbor(s) P2P-2# P2P-2# P2P-2# </pre>

Página 5 de 8

[illegible]

Router BC-1

BC-1

Physical Config CLI Attributes

IOS Con

BC-1#show running
Building configuration...

Current configuration : 1047 bytes
!
version 15.4
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname BC-1
!
!
!
!
!
no ip cef
no ipv6 cef
!
!
!
!
!
!
!
!
!
!
spanning-tree mode pvst
!
!
--More--

BC-1

Physical Config CLI Attributes

IOS

interface GigabitEthernet0/0/0
ip address 10.0.1.1 255.255.255.248
ip ospf priority 255
ip ospf 10 area 0
duplex auto
speed auto
!
interface GigabitEthernet0/0/1
no ip address
duplex auto
speed auto
shutdown
!
interface Serial0/1/0
ip address 10.0.0.14 255.255.255.252
ip ospf hello-interval 20
ip ospf dead-interval 80
ip ospf 10 area 0
clock rate 2000000
!
interface Serial0/1/1
ip address 64.0.100.2 255.255.255.252
ip ospf 10 area 0
!
interface Vlan1
no ip address
shutdown
!
router ospf 10
router-id 6.6.6.6
log-adjacency-changes
passive-interface Serial0/1/1
auto-cost reference-bandwidth 10000
default-information originate
!
ip classless
--More--

BC-1

Physical Config CLI Attributes

IOS

interface Serial0/1/1
ip address 64.0.100.2 255.255.255.252
ip ospf 10 area 0
!
interface Vlan1
!
router ospf 10
router-id 6.6.6.6
log-adjacency-changes
passive-interface Serial0/1/1
auto-cost reference-bandwidth 10000
default-information originate
!
ip classless
ip route 0.0.0.0 0.0.0.0 Serial0/1/1
!
ip flow-export version 9
!
!
!
!
line con 0
!
line aux 0
!
line vty 0 4
login
!
!
end
--More--

BC-1

Physical Config CLI Attributes

IOS Command Line Interface

BC-1#show ip ospf interface

GigabitEthernet0/0/0 is up, line protocol is up
Internet address is 10.0.1.1/29, Area 0
Process ID 10, Router ID 6.6.6.6, Network Type BROADCAST, Cost: 10
Transmit Delay is 1 sec, State DR, Priority 255
Designated Router (ID) 6.6.6.6, Interface address 10.0.1.1
Backup Designated Router (ID) 4.4.4.4, Interface address 10.0.1.3
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
Hello due in 00:00:08
Index 1/1, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 2, Adjacent neighbor count is 2
Adjacent with neighbor 5.5.5.5
Adjacent with neighbor 4.4.4.4 (Backup Designated Router)
Suppress hello for 0 neighbor(s)
Serial0/1/1 is up, line protocol is up
Internet address is 64.0.100.2/30, Area 0
Process ID 10, Router ID 6.6.6.6, Network Type POINT-TO-POINT, Cost: 6476
Transmit Delay is 1 sec, State POINT-TO-POINT,
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
No Hellos (Passive interface)
Index 2/2, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Suppress hello for 0 neighbor(s)
Serial0/1/0 is up, line protocol is up
Internet address is 10.0.0.14/30, Area 0
Process ID 10, Router ID 6.6.6.6, Network Type POINT-TO-POINT, Cost: 6476
Transmit Delay is 1 sec, State POINT-TO-POINT,
Timer intervals configured, Hello 20, Dead 80, Wait 80, Retransmit 5
Hello due in 00:00:17
Index 3/3, flood queue length 0
--More--

BC-1

Physical Config CLI Attributes

IOS Command Line Interface

Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
Hello due in 00:00:08
Index 1/1, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 2, Adjacent neighbor count is 2
Adjacent with neighbor 4.4.4.4 (Backup Designated Router)
Suppress hello for 0 neighbor(s)
Serial0/1/1 is up, line protocol is up
Internet address is 64.0.100.2/30, Area 0
Process ID 10, Router ID 6.6.6.6, Network Type POINT-TO-POINT, Cost: 6476
Transmit Delay is 1 sec, State POINT-TO-POINT,
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
No Hellos (Passive interface)
Index 2/2, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Suppress hello for 0 neighbor(s)
Serial0/1/0 is up, line protocol is up
Internet address is 10.0.0.14/30, Area 0
Process ID 10, Router ID 6.6.6.6, Network Type POINT-TO-POINT, Cost: 6476
Transmit Delay is 1 sec, State POINT-TO-POINT,
Timer intervals configured, Hello 20, Dead 80, Wait 80, Retransmit 5
Hello due in 00:00:17
Index 3/3, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1, Adjacent neighbor count is 1
Adjacent with neighbor 10.0.0.13
Suppress hello for 0 neighbor(s)
BC-1#
BC-1#
BC-1#

Router BC-2

The image displays two side-by-side screenshots of a Cisco IOS CLI interface, showing the configuration of two routers, BC-2 and BC-3.

Router BC-2 Configuration:

```

BC-2#show running
Building configuration...

Current configuration : 899 bytes
!
version 15.4
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname BC-2
!
!
!
!
!
!
!
no ip cef
no ipv6 cef
!
!
!
!
!
!
!
!
!
!
spanning-tree mode pvst
!
!
--More--

```

Router BC-3 Configuration:

```

interface GigabitEthernet0/0/0
ip address 192.168.4.1 255.255.255.0
ip ospf 10 area 0
duplex auto
speed auto
!
interface GigabitEthernet0/0/1
ip address 10.0.1.2 255.255.255.248
ip ospf 10 area 0
duplex auto
speed auto
!
interface Serial10/1/0
no ip address
clock rate 2000000
shutdown
!
interface Serial10/1/1
no ip address
clock rate 2000000
shutdown
!
interface Vlan1
no ip address
shutdown
!
router ospf 10
router-id 5.5.5.5
log-adjacency-changes
passive-interface GigabitEthernet0/0/0
auto-cost reference-bandwidth 10000
!
ip classless
!
ip flow-export version 9
!
!
--More--

```

```
BC-2-
end

BC-2-#
BC-2-#show ip ospf interface

GigabitEthernet0/0/0 is up, line protocol is up
Internet address is 192.168.4.1/24, Area 0
Process ID 10, Router ID 5.5.5.5, Network Type BROADCAST, Cost: 10
Transmit Delay is 1 sec, State DR, Priority 1
Designated Router (ID) 5.5.5.5, Interface address 192.168.4.1
No backup designated router on this network
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
  No Hellos (Passive interface)
Index 1/1, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 0, Adjacent neighbor count is 0
Suppress hello for 0 neighbor(s)

GigabitEthernet0/0/1 is up, line protocol is up
Internet address is 10.0.1.2/25, Area 0
Process ID 10, Router ID 5.5.5.5, Network Type BROADCAST, Cost: 10
Transmit Delay is 1 sec, State DROTHER, Priority 1
Designated Router (ID) 6.6.6.6, Interface address 10.0.1.1
Backup Designated Router (ID) 4.4.4.4, Interface address 10.0.1.3
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
Hello due in 00:00:00
Index 2/2, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 2, Adjacent neighbor count is 2
  Adjacent with neighbor 6.6.6.6 (Designated Router)
  Adjacent with neighbor 4.4.4.4 (Backup Designated Router)
Suppress hello for 0 neighbor(s)
```

Router BC-3

BC-3

Physical Config **CLI** Attributes

Building configuration...
Current configuration : 899 bytes
!
version 15.4
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname BC-3
!
!
!
!
!
!
no ip cef
no ipv6 cef
!
!
!
!
!
!
!
spanning-tree mode pvst
!
!
!
--More--

BC-3

Physical Config **CLI** Attributes

interface GigabitEthernet0/0/0
ip address 192.168.5.1 255.255.255.0
ip ospf 10 area 0
duplex auto
speed auto
!
interface GigabitEthernet0/0/1
ip address 10.0.1.3 255.255.255.248
ip ospf 10 area 0
duplex auto
speed auto
!
interface Serial0/1/0
no ip address
clock rate 2000000
shutdown
!
interface Serial0/1/1
no ip address
clock rate 2000000
shutdown
!
interface Vlan1
no ip address
shutdown
!
router ospf 10
router-id 4.4.4.4
log-adjacency-changes
passive-interface GigabitEthernet0/0/0
auto-cost reference-bandwidth 10000
!
ip classless
!
ip flow-export version 9
!
!
--More--

BC-3

Physical Config **CLI** Attributes

!
end

BC-3#show ip ospf interface

GigabitEthernet0/0/0 is up, line protocol is up
Internet address is 192.168.5.1/24, Area 0
Process ID 10, Router ID 4.4.4.4, Network Type BROADCAST, Cost: 10
Transmit Delay is 1 sec, State DR, Priority 1
Designated Router (ID) 4.4.4.4, Interface address 192.168.5.1
No backup designated router on this network
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
No Hellos (Passive interface)
Index 1/1, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 0, Adjacent neighbor count is 0
Suppress hello for 0 neighbor(s)
GigabitEthernet0/0/1 is up, line protocol is up
Internet address is 10.0.1.3/29, Area 0
Process ID 10, Router ID 4.4.4.4, Network Type BROADCAST, Cost: 10
Transmit Delay is 1 sec, State BDR, Priority 1
Designated Router (ID) 6.6.6.6, Interface address 10.0.1.1
Backup Designated Router (ID) 4.4.4.4, Interface address 10.0.1.3
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
Hello due in 00:00:07
Index 2/2, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 2, Adjacent neighbor count is 2
Adjacent with neighbor 6.6.6.6 (Designated Router)
Adjacent with neighbor 5.5.5.5
Suppress hello for 0 neighbor(s)
BC-3#
BC-3#