

# Test report - Deployment of Arktos Cluster without Mizar CNI on AWS

This document captures the steps to deploy an Arktos cluster lab without Mizar CNI. The machine in this lab used are t2.2xlarge, 128 GB storage and Ubuntu 18.04 LTS.

Date-17 Dec. 2021

## Step-1: Update kernel (If required)

To check kernel, run following command `uname`

`-a`

```
ubuntu@ip-172-31-35-226:~$ uname -a
Linux ip-172-31-35-226 5.4.0-1060-aws #63~18.04.1-Ubuntu SMP Mon Nov 15 14:31:31 UTC 2021 x86_64 x86_64 x86_64 GNU/Linux
ubuntu@ip-172-31-35-226:~$
```

Here kernel version is 5.4.0-1051-aws which is less than the required kernel version, so to update the kernel version to 5.6.0-rc2, we used the following steps :

`wget https://raw.githubusercontent.com/CentaurusInfra/mizar/dev-next/kernelupdate.sh`

`sudo bash kernelupdate.sh`

```
fetches 74.6 kB in 0s (637 kB/s)
Reading package lists... Done
ubuntu@ip-172-31-35-226:/src/github.com/arktos$ sudo apt-get install ubuntu-make
Reading package lists... Done
Building dependency tree
Reading state information... Done
The following additional packages will be installed:
  python3-argcomplete python3-bs4 python3-gnupg python3-html5lib python3-lxml python3-progressbar python3-webencodings python3-xdg
Suggested packages:
  python3-genshi python3-lxml-doc python3-lxml-doc
The following NEW packages will be installed:
  python3-argcomplete python3-bs4 python3-gnupg python3-html5lib python3-lxml python3-progressbar python3-webencodings python3-xdg ubuntu-make
0 upgraded, 9 newly installed, 0 to remove and 13 not upgraded.
Need to get 1400 kB of archives.
After this operation, 5950 kB of additional disk space will be used.
Do you want to continue? [Y/n] Y
Get:1 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic/universe amd64 python3-argcomplete all 1.8.1-1ubuntu1 [26.9 kB]
Get:2 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic/main amd64 python3-bs4 all 4.6.0-1 [67.8 kB]
Get:3 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic-updates/universe amd64 python3-gnupg all 0.4.1-1ubuntu1.18.04.1 [17.1 kB]
Get:4 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic/main amd64 python3-webencodings all 0.5.2 [10.4 kB]
Get:5 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic/main amd64 python3-html5lib all 0.99999999-1 [81.9 kB]
Get:6 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic-updates/main amd64 python3-lxml amd64 4.2.1-1ubuntu0.4 [1097 kB]
Get:7 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic/universe amd64 python3-progressbar all 2.3-4 [9630 B]
Get:8 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic-updates/main amd64 python3-xdg all 0.25-4ubuntu1.1 [31.3 kB]
Get:9 http://us-east-2.ec2.archive.ubuntu.com/ubuntu bionic/universe amd64 ubuntu-make all 16.11.1ubuntu1 [57.6 kB]
Fetched 1400 kB in 0s (6300 kB/s)
Selecting previously unselected package python3-argcomplete.
(Reading database ... 92801 files and directories currently installed.)
Preparing to unpack .../0-python3-argcomplete_1.8.1-1ubuntu1_all.deb ...
Unpacking python3-argcomplete (1.8.1-1ubuntu1) ...
Selecting previously unselected package python3-bs4.
Preparing to unpack .../1-python3-bs4_4.6.0-1_all.deb ...
Unpacking python3-bs4 (4.6.0-1) ...
Selecting previously unselected package python3-gnupg.
Preparing to unpack .../2-python3-gnupg_0.4.1-1ubuntu1.18.04.1_all.deb ...
Unpacking python3-gnupg (0.4.1-1ubuntu1.18.04.1) ...
Selecting previously unselected package python3-webencodings.
Preparing to unpack .../3-python3-webencodings_0.5-2_all.deb ...
Unpacking python3-webencodings (0.5-2) ...
Selecting previously unselected package python3-html5lib.
Preparing to unpack .../4-python3-html5lib_0.99999999-1_all.deb ...
Unpacking python3-html5lib (0.99999999-1) ...
Selecting previously unselected package python3-lxml:amd64.
Preparing to unpack .../5-python3-lxml_4.2.1-1ubuntu0.4_amd64.deb ...
Unpacking python3-lxml:amd64 (4.2.1-1ubuntu0.4) ...
Selecting previously unselected package python3-progressbar.
Preparing to unpack .../6-python3-progressbar_2.3-4_all.deb ...
Unpacking python3-progressbar (2.3-4) ...
Selecting previously unselected package python3-xdg.
Preparing to unpack .../7-python3-xdg_0.25-4ubuntu1.1_all.deb ...
Unpacking python3-xdg (0.25-4ubuntu1.1) ...
Selecting previously unselected package ubuntu-make.
Preparing to unpack .../8-ubuntu-make_16.11.1ubuntu1_all.deb ...
Unpacking ubuntu-make (16.11.1ubuntu1) ...
Setting up python3-webencodings (0.5-2) ...
Setting up python3-progressbar (2.3-4) ...
Setting up python3-lxml:amd64 (4.2.1-1ubuntu0.4) ...
Setting up python3-gnupg (0.4.1-1ubuntu1.18.04.1) ...
```

`mkdir -p $GOPATH/src/github.com`

```
cd $GOPATH/src/github.com
```

```
git clone https://github.com/CentaurusInfra/arktos
```

```
cd arktos
```

```
bash hack/setup-dev-node.sh
```

```
make
```

```
root@ip-172-31-35-226:/src/github.com/arktos# make
+++ [1217 07:35:57] Building go targets for linux/amd64:
./vendor/k8s.io/code-generator/cmd/deepcopy-gen
+++ [1217 07:36:08] Building go targets for linux/amd64:
./vendor/k8s.io/code-generator/cmd/defaulter-gen
+++ [1217 07:36:12] Building go targets for linux/amd64:
./vendor/k8s.io/code-generator/cmd/conversion-gen
+++ [1217 07:36:22] Building go targets for linux/amd64:
./vendor/k8s.io/kube-openapi/cmd/openapi-gen
+++ [1217 07:36:33] Building go targets for linux/amd64:
./vendor/github.com/go-bindata/go-bindata/go-bindata
Running copyright check for repo: /src/github.com/arktos, logging to _output/ArktosCopyrightTool.log
/src/github.com/arktos /src/github.com/arktos
warning: inexact rename detection was skipped due to too many files.
warning: you may want to set your diff.renameLimit variable to at least 3067 and retry the command.
/src/github.com/arktos /src/github.com/arktos
warning: inexact rename detection was skipped due to too many files.
warning: you may want to set your diff.renameLimit variable to at least 3067 and retry the command.
/src/github.com/arktos
Inspecting copyright files, writing logs to _output/ArktosCopyrightTool.log
Done:
+++ [1217 07:36:44] Building go targets for linux/amd64:
cmd/kube-proxy
cmd/kube-apiserver
cmd/kube-controller-manager
cmd/cloud-controller-manager
cmd/workload-controller-manager
cmd/kubeadm
cmd/hypkube
cmd/kube-scheduler
vendor/k8s.io/apiextensions-apiserver
cluster/gce/mounter
cmd/kubectrl
cmd/gendocs
cmd/genkubedocs
cmd/genman
cmd/genyaml
cmd/genswagertypedocs
cmd/linkcheck
vendor/github.com/onsi/ginkgo/ginkgo
test/e2e/e2e.test
cmd/kubemark
vendor/github.com/onsi/ginkgo/ginkgo
test/e2e/e2e_node.test
```

## Run Arktos

The easiest way to run Arktos is to bring up a single-node cluster in your local development box:

```
cd $GOPATH/src/github.com/arktos
```

```
hack/arktos-up.sh
```

```
Arktos Setup done.
*****
Setup Kata Containers components ...
* Install Kata components
kata-containers 2.3.0 from Kata Containers (katacontainers-) installed
* Checking Kata compatibility
time="2021-12-17T07:42:49Z" level=warning msg="Not running network checks as super user" arch=amd64 name=kata-runtime pid=4109 source=runtime time="2021-12-17T07:42:49Z" level=error msg="CPU property not found
rch=amd64 description="Virtualization support" name=vmx pid=4109 source=runtime type=flag time="2021-12-17T07:42:49Z" level=warning msg="modprobe insert module failed" arch=amd64 error="exit status 1" module=k
intel name=kata-runtime output=modprobe: ERROR: could not insert 'kvm_intel': Operation not supported\n" pid=4109 source=runtime time="2021-12-17T07:42:49Z" level=error msg="kernel property kvm_intel not foun
rch=amd64 description="Intel KVM" name=kvm_intel pid=4109 source=runtime type=module time="2021-12-17T07:42:49Z" level=error msg="ERROR: System is not capable of running Kata Containers" arch=amd64 name=kata-
time pid=4109 source=runtime ERROR: System is not capable of running Kata Containers
Aborted. Current system does not support Kata Containers.
Kata Setup done.
*****
Local Kubernetes cluster is running. Press Ctrl-C to shut it down.

Logs:
/tmp/kube-apiserver0.log
/tmp/kube-controller-manager.log

/tmp/kube-proxy.log
/tmp/kube-scheduler.log
/tmp/kubectl.log

To start using your cluster, you can open up another terminal/tab and run:

export KUBECONFIG=/var/run/kubernetes/admin.kubeconfig
Or
export KUBECONFIG=/var/run/kubernetes/admin(N=0,1,...).kubeconfig
cluster/kubectl.sh

Alternatively, you can write to the default kubeconfig:

export KUBERNETES_PROVIDER=local

cluster/kubectl.sh config set-cluster local --server=https://ip-172-31-35-226:6443 --certificate-authority=/var/run/kubernetes/server-ca.crt
cluster/kubectl.sh config set-credentials myself --client-key=/var/run/kubernetes/client-admin.key --client-certificate=/var/run/kubernetes/client-admin.crt
cluster/kubectl.sh config set-context local --cluster=local --user=myself
cluster/kubectl.sh config use-context local
cluster/kubectl.sh
```

## 1) Check nodes status:

`./cluster/kubectl.sh get nodes`

```
ubuntu@ip-172-31-35-226:/src/github.com/arktos$ ./cluster/kubectl.sh get nodes
NAME                STATUS    ROLES    AGE      VERSION
ip-172-31-35-226    Ready    <none>    3m30s    v0.9.0
```

2) Check pods status:

`./cluster/kubectl.sh get pods -Ao wide`

```
ubuntu@ip-172-31-35-226:/src/github.com/arktos$ ./cluster/kubectl.sh get pods -Ao wide
NAMESPACE   NAME                                HASHKEY          READY    STATUS    RESTARTS   AGE    IP             NODE                NOMINATED NODE   READINESS GATES
kube-system  coredns-default-db947ddb8-x4vlc    559470266915271949  1/1     Running    0          3m31s  10.88.0.2      ip-172-31-35-226    <none>           <none>
kube-system  kube-dns-554c5866fc-h96z8        5242146391675538656  3/3     Running    0          3m31s  10.88.0.3      ip-172-31-35-226    <none>           <none>
kube-system  virtlet-824zm                     2722049154141057340  3/3     Running    0          3m32s  172.31.35.226  ip-172-31-35-226    <none>           <none>
```

Command:

`./cluster/kubectl.sh apply -f`

[https://github.com/Click2CloudCentaurus/Documentation/blob/main/test-yamls/test\\_pods.yaml](https://github.com/Click2CloudCentaurus/Documentation/blob/main/test-yamls/test_pods.yaml)

Check deployed pods:

Command:

`./cluster/kubectl.sh get pods -Ao wide Output`

Output

```
ubuntu@ip-172-31-35-226:/src/github.com/arktos$ ./cluster/kubectl.sh get pods -Ao wide
NAMESPACE   NAME                                HASHKEY          READY    STATUS    RESTARTS   AGE    IP             NODE                NOMINATED NODE   READINESS GATES
default      netpod1                             8087990749736038058  1/1     Running    0          64s  10.88.0.4      ip-172-31-35-226    <none>           <none>
default      netpod2                             6584546547910518947  1/1     Running    0          64s  10.88.0.5      ip-172-31-35-226    <none>           <none>
kube-system  coredns-default-db947ddb8-x4vlc    559470266915271949  1/1     Running    0          61m  10.88.0.2      ip-172-31-35-226    <none>           <none>
kube-system  kube-dns-554c5866fc-h96z8        5242146391675538656  3/3     Running    0          61m  10.88.0.3      ip-172-31-35-226    <none>           <none>
kube-system  virtlet-824zm                     2722049154141057340  3/3     Running    0          61m  172.31.35.226  ip-172-31-35-226    <none>           <none>
```

Check ping deployed pods:

`./cluster/kubectl.sh exec -it netpod1 ping 10.88.0.5`

```
ubuntu@ip-172-31-35-226:/src/github.com/arktos$ ./cluster/kubectl.sh exec -it netpod1 ping 10.88.0.5
PING 10.88.0.5 (10.88.0.5) 56(84) bytes of data:
64 bytes from 10.88.0.5: icmp_seq=1 ttl=64 time=0.106 ms
64 bytes from 10.88.0.5: icmp_seq=2 ttl=64 time=0.087 ms
64 bytes from 10.88.0.5: icmp_seq=3 ttl=64 time=0.075 ms
64 bytes from 10.88.0.5: icmp_seq=4 ttl=64 time=0.088 ms
64 bytes from 10.88.0.5: icmp_seq=5 ttl=64 time=0.076 ms
64 bytes from 10.88.0.5: icmp_seq=6 ttl=64 time=0.072 ms
^C
```

`./cluster/kubectl.sh exec -it netpod2 ping 10.88.0.4`

```
ubuntu@ip-172-31-35-226:/src/github.com/arktos$ ./cluster/kubectl.sh exec -it netpod2 ping 10.88.0.4
PING 10.88.0.4 (10.88.0.4) 56(84) bytes of data:
64 bytes from 10.88.0.4: icmp_seq=1 ttl=64 time=0.080 ms
64 bytes from 10.88.0.4: icmp_seq=2 ttl=64 time=0.077 ms
64 bytes from 10.88.0.4: icmp_seq=3 ttl=64 time=0.079 ms
64 bytes from 10.88.0.4: icmp_seq=4 ttl=64 time=0.094 ms
64 bytes from 10.88.0.4: icmp_seq=5 ttl=64 time=0.068 ms
^C
```