ClickHouse Jakarta Meetup



Tech Talks



An Introduction to ClickHouse and My Favourite Features

Tyler Hannan, Senior. Director, Developer Advocacy @ ClickHouse



Building the Backbone: Leveraging
ClickHouse for Real-Time Data in
High-Frequency Trading
Nahwin Rajan, Co-Founder & CEO In Stealth Mode



Driving Jakarta's Electric Motorcycle Transformation with ClickHouse

Andi Pangeran, Principal Software Engineer @ Electrum



An Introduction to ClickHouse

And my favourite features



What is ClickHouse?

Open source	column-oriented	distributed	OLAP database
Developed since	Best for aggregations	Replication	Analytics use cases
2009 - OSS 2016	Files per column	Sharding	Aggregations
31k+ Github stars	Sorting and indexing	Multi-master	Visualizations
1.3k+ contributors	Background merges	Cross-region	Mostly immutable data
500+ releases			



Key Features

Some of the cool things ClickHouse can do

1 Speaks SQL

Most SQL-compatible Uls, editors, applications, frameworks will just work!

2 Lots of writes

Up to several million writes per second - per server.

3 Distributed

Replicated and sharded, largest known cluster is 4000 servers.

4 Highly efficient storage

Lots of encoding and compression options - e.g. 20x from uncompressed CSV.

5 Very fast queries

Scan and process even billions of rows per second and use vectorized query execution.

Joins and lookups

Allows separating fact and dimension tables in a star schema.




Database for Interactive Experiences

Make any data fast









Benchmarks

- Our own at https://clickhouse.com/benchmark/dbms/
 - 6x faster than Vertical
 - 25x faster than Greenplum
 - 50x faster than TimescaleDB
- Others, see

https://github.com/ClickHouse/ClickHouse/issues/22398

e.g.:

- 3-5x faster than RedShift (sometimes 50x)
- 5-6x faster than Elasticsearch
- 6-10x faster than Druid
- Storage
 - Ebay: 90% less hardware than Druid
 - Contentsquare: 6x more data than Elasticsearch



Creating tables

ClickHouse SQL Basics

```
CREATE TABLE events
   timestamp DateTime,
            LowCardinality(String),
  tenant
            Enum8(...),
  type
  value
            Float64.
            Array(String),
  attr
            Map(String, Boolean)
  flags
ENGINE = MergeTree
ORDER BY (tenant, timestamp)
```

Other engines:

- ReplacingMergeTree
- CollapsingMergeTree
- AggregatingMergeTree

Integration engines:

- Kafka, RabbitMQ
- MySQL, PostgreSQL, MongoDB
- ♦ JDBC, ODBC
- ♦ S3, HDFS
- EmbeddedRocksDB
- Adding Replicating- in front makes an engine replicate data (e.g. ReplicatingMergeTree)



Inserting directly

ClickHouse SQL Basics

```
INSERT INTO people VALUES ('Obi-Wan Kenobi', 57, ...) ('Yoda', 900, ...)
(...)
```

Batching is important! Either batch yourself or turn on asynchronous inserts:

```
SET async_insert = true
INSERT INTO people VALUES ('Obi-Wan Kenobi', 57, ...)
INSERT INTO people VALUES ('Yoda', 900, ...)
INSERT INTO people VALUES (...)
```



Inserting from external sources

ClickHouse SQL Basics

ClickHouse has many built-in table functions to read external data:

```
INSERT INTO table SELECT * FROM s3(...)
INSERT INTO table SELECT * FROM file(...)
INSERT INTO table SELECT * FROM url(...)
INSERT INTO table SELECT * FROM mysql(...)
INSERT INTO table SELECT * FROM postgresql(...)
INSERT INTO table SELECT * FROM jdbc(...)
And more!
```

Read the docs at clickhouse.com/docs!



Reading data

ClickHouse SQL Basics

Don't do this! (at least not too often)

```
SELECT * FROM table
```

And also not this! (at least not too often)

```
SELECT ... FROM table WHERE id = '<uuid>'
```

The majority of your queries should be:

```
SELECT avg(something) FROM table WHERE toYear(timestamp) = 2022
```




Views

ClickHouse SQL Basics

Saving a query as a view (no data movement):



CREATE VIEW view AS SELECT ... FROM table ...



Continuously processing new data from a table into another table:

CREATE MATERIALIZED VIEW view AS SELECT avg(...) FROM table GROUP BY ...




Ecosystem and Integrations

- Interface
 - HTTP, native TCP, CLI
 - JDBC, ODBC
 - Client libraries: Go, Python, Javascript, etc.
- Data ingest
 - Kafka, S3, HDFS, RabbitMQ (native)
 - MySQL, PostgreSQL, MongoDB, Redis (native)
 - Vector (logs and metrics)
 - Airbyte (ELT)
 - JDBC, ODBC (Spark, Flink, etc.)
- Query editor
 - Open source: DBeaver, VS Studio
 - Proprietary: DataGrip
- Visualization
 - Open source: Grafana, Superset, Metabase
 - Proprietary: Tableau, Power BI



ClickHouse Cloud Architecture





For more, go to clickhouse.com/learn



OVERLAY

```
SELECT overlay('Hello, world!', 'test', 8, 5) AS res
1. Hello, test!
WITH 'Hello, world!' AS s,
     'test' AS replacement,
     8 AS pos,
     5 AS length
SELECT concat(substring(s, 1, pos - 1), replacement, substring(s, pos + length))
AS res
1. Hello, test!
```

JSON Object Format



Saved Queries as APIs

