

Full Stack Development with MERN

Project Documentation Format

1. INTRODUCTION

1. Project Title ShopEZ: One-Stop Shop for Online Purchases

2. Team Members Diviz Pandey (Team Lead) – Backend Developer

Bhavya Jain – Frontend Developer

Karmanya Batra – Database & Deployment

Anaswar L – Tester

3. Team ID: SWTID1743669870

2. PROJECT OVERVIEW

1. Purpose

The purpose of this project is to design and develop a fully functional e-commerce website that provides users with a seamless online shopping experience. The platform aims to bridge the gap between consumers and sellers by offering a convenient, secure, and user-friendly interface for browsing, selecting, and purchasing products. It is built using the MERN (MongoDB, Express.js, React, Node.js) stack to ensure scalability, real-time performance, and maintainability.

This project is intended to streamline the entire shopping process—from product discovery and cart management to order placement and payment—while ensuring robust user authentication, responsive design, and efficient backend management. The goal is to replicate and enhance the essential features of leading e-commerce platforms, making it adaptable for various product categories and business models.

2. Features

1. User Authentication & Authorization

- Secure registration and login system
- JWT-based authentication
- Role-based access control (Admin/User)

2. Product Catalog

- Dynamic listing of products with images, descriptions, and prices
- Filtering and sorting by categories, brands, and price range
- Product detail page with specifications and reviews

3. Shopping Cart

- Add/remove items to/from cart
- Quantity management
- Real-time cart updates and total price calculation

4. Search Functionality

- Keyword-based product search
- Autocomplete suggestions for faster navigation

5. Order Management

- Checkout flow with order summary
- Address and payment information collection
- Order tracking and history

6. Admin Dashboard

- Product management (add, edit, delete products)

- User management and analytics
- Order management with delivery status updates

7. Responsive UI

- Fully responsive design for desktops, tablets, and mobile devices
- Clean and intuitive user interface using modern CSS and design libraries

8. Secure Payment Integration *(Optional/Planned Feature)*

- Integration with payment gateways (e.g., Razorpay, Stripe, etc.)
- Secure handling of payment transactions

9. Wishlist & Favorites *(Optional)*

- Users can save favorite products for later

10. Notifications

- Success and error alerts for user actions
 - Optional email notifications for orders
-

3. ARCHITECTURE

1. Frontend Architecture (React.js)

The frontend is designed as a **Single Page Application (SPA)** using React.js to ensure seamless user interaction and a dynamic experience. It adheres to a component-based architecture where each UI element is modular and reusable.

Key Features:

- **Component Hierarchy:** The application is broken into reusable components like Header, Footer, ProductCard, LoginForm, Dashboard, etc., following a clean and maintainable structure.
- **Client-Side Routing:** Implemented using react-router-dom, enabling smooth navigation between routes such as /login, /register, /products, /cart, and /admin.
- **State Management:** Redux Toolkit is used to manage global application state. AsyncThunk handles asynchronous operations such as API calls and state updates.
- **Authentication Handling:** JWT tokens (Access and Refresh) are stored securely (e.g., in memory or localStorage) and attached to requests using axios interceptors.
- **Responsive UI:** Designed using Tailwind CSS to ensure responsiveness and consistency across various screen sizes and devices.
- **Error & Notification Handling:** Integrated toast notifications to provide feedback on successful or failed user actions.

2. Backend Architecture (Node.js and Express.js)

The backend is developed using Node.js and Express.js, structured in a RESTful API format. It is responsible for user authentication, CRUD operations, order processing, and email notifications.

Key Components:

- **Modular Routing:** Organized routes for users, products, categories, orders, and admin functionalities.
- **Controllers and Middleware:**
 - Controllers handle request logic and validation.
 - Middleware ensures route protection (authentication and authorization), input validation, and error handling.
- **Authentication System:**
 - JWT tokens are used for secure, stateless authentication.
 - Passwords are hashed using bcryptjs before storage.

- **Security Practices:**
 - Middleware protects against unauthorized access.
 - Environment variables are managed securely using .env files.
- **Email Integration:** Nodemailer is used to send password reset emails and order confirmation messages.
- **Deployment-Ready:** Backend is structured to support production deployment, with appropriate logging, error responses, and configuration support.

3. Database Architecture (MongoDB)

MongoDB is used as the primary database for ShopEZ, providing a scalable and flexible NoSQL structure. Mongoose ODM (Object Data Modeling) library is used to define schemas and handle data operations.

Primary Collections:

1. Users

- Fields: name, email, hashedPassword, role, address, resetToken, resetTokenExpiry
- Contains authentication and authorization data.

2. Products

- Fields: title, description, price, image, category, stock, colors, createdAt
- Holds all product-related data and variations.

3. Orders

- Fields: userId, items, totalAmount, shippingAddress, paymentStatus, orderStatus, createdAt
- Manages order records placed by users.

4. Categories

- Fields: name, description
- Used for product classification.

5. Wishlists

- Fields: userId, products[]
- Tracks user-selected products for future purchases.

Database Operations:

- Create, Read, Update, and Delete (CRUD) functionalities for each collection.
- Aggregation pipelines are used for filtering and searching data efficiently.
- Relations (e.g., referencing userId in Orders) are maintained using MongoDB references.
- Indexing is applied on frequently queried fields such as email, product name,

and category.

4. SETUP INSTRUCTIONS

1. Prerequisites

1. Software Requirements

Tool	Version (Recommended)	Description
Node.js	v16.x or later	JavaScript runtime to run backend and React
npm	Comes with Node.js	Package manager for dependencies
MongoDB	v6.x or Atlas (Cloud)	NoSQL database for storing project data
Git	Latest	To clone the Git repository
VS Code	Latest	Code editor (optional but recommended)

Verification of installations:

`node -v`

`npm -v`

`mongo --version`

`git -version`

2. Installation Steps

To run the ShopEZ e-commerce web application on your local machine, follow these step-by-step instructions. The project uses the **MERN stack** — consisting of **MongoDB**, **Express.js**, **React.js**, and **Node.js** — and includes both a user-facing store and an admin panel for backend management.

Step 1: Clone the Git Repository

- Begin by cloning the project repository from GitHub using the following command:

```
git clone <https://github.com/bidisha-biswas0610/SMARTBRIDGE_MERN_Project_ECommerceWebsite_ShopEZ.git>
```

- Once the repository is cloned, navigate into the main project directory:
`cd E-Commerce Website`

Step 2: Backend Setup (Node.js + Express.js)

The backend is responsible for handling API requests, user authentication, order processing, and more.

- Navigate to the backend folder:
`cd Backend`
- Install all required backend dependencies:
`npm install`
- Create a `.env` file in the `Backend` directory to store environment variables securely:

```
touch .env
```

- Add the following configurations to your `.env` file:

```
PORT=5000
MONGO_URI=mongodb_connection_string
JWT_SECRET=jwt_secret
EMAIL_USER=email@example.com
EMAIL_PASS=email_password
```

- Start the backend server:
`npm run server`

By default, the backend server will start at <http://localhost:5000>.

Step 3: Frontend Setup (React.js + Tailwind CSS)

The frontend includes the customer shopping experience and the admin dashboard, all built using React.

- Navigate to the frontend folder:

```
cd ../Frontend
```

- Install frontend dependencies:
`npm install`
- Create a `.env` file in the `Frontend` directory:
`touch .env`
- Add the API base URL to the `.env` file:
`VITE_API_URL=http://localhost:5000`
- Start the React development server:
`npm run dev`

The frontend should now be accessible on <http://localhost:5173>.

Step 4: MongoDB Database Setup

ShopEZ uses MongoDB to store data such as product listings, user information, orders, and wishlist items.

You have two options:

- **Option 1 (Local):** Install MongoDB on your machine and use:
`MONGO_URI=mongodb://127.0.0.1:27017/shopez`
- **Option 2 (Cloud):** Use MongoDB Atlas and provide your connection URI in the Backend `.env` file.

Make sure the database is accessible and collections like users, products, orders, and categories are created through backend API calls or seed data.

5. FOLDER STRUCTURE

1. Frontend (Client):

/Frontend

 /node_modules

 /public

 /src

 /app

 /Features

 /Pages

 /assets

 /utils

App.jsx
App.css
constants.js
index.css
main.jsx

Folder/File	Description
/node_modules	Contains all the frontend dependencies installed via <i>npm</i> . Not manually edited.
/public	Static files like <i>favicon</i> , <i>manifest</i> , and <i>index.html</i> reside here. They are accessible directly via the browser.
/src	Core application source code resides here.
/app	Configuration for the Redux store setup and slice integration.

/Features	Houses Redux slices and logic for state management.
/Pages	Individual page components (e.g., Home, Login, Register, ProductList, Checkout). These are routed components.
/assets	Stores all static files such as images, logos, and icons.
/utils	Utility/helper functions used across the app (e.g., date formatter, validators, etc.).
App.jsx	Root component that wraps the whole application, includes layout and routing logic.

App.css	Main styling file for general app-level styling.
constants.js	Contains constant values used throughout the frontend (e.g., URLs, roles, enums).
index.css	Global styling or Tailwind CSS base styles.
main.jsx	Entry point of the React app; renders the <i>App</i> component into the DOM.

2. Backend (Server)

```

/Backend
  /controllers
  /db
  /node_modules
  /router
  /models
  /middleware
  /service
index.js
brand.json
category.json
constants.js
products.json
package-lock.json
package.json

```

Folder/File	Description
/controllers	Contains controller files responsible for handling the logic behind each route (e.g., productController, authController).
/db	Database connection setup (e.g., MongoDB configuration and initialization).

/node_modules	Contains all backend dependencies installed via <i>npm</i> .
/router	Defines all API routes (e.g., authRoutes.js, productRoutes.js).
/models	Mongoose schema definitions for collections like User, Product, Order, etc.

/middleware	Contains middleware for authentication, error handling, etc.
/service	Business logic or helper services (e.g., mailService)
index.js	Main server entry point; initializes Express app and connects to the database.

brand.json, category.json, products.json	Static JSON datasets used for testing or initial seeding of product data.
constants.js	Application-wide constants like status codes, roles, environment settings.
package-lock.json	Lockfile to ensure consistent dependency versions.
package.json	Lists dependencies, scripts, and metadata about the backend project.

6. RUNNING THE APPLICATION

1. Backend (Server)

To run the backend of the ShopEZ application, follow these steps:

Step 1: Navigate to the Backend Directory

- Open the terminal and move into the backend folder using the command:
`cd Backend`

Step 2: Install Dependencies

- Run the following command to install the necessary Node.js packages listed in `package.json`:
`npm install`

Step 3: Environment Configuration

- Create a `.env` file in the root of the Backend directory and define all necessary environment variables, such as:
 - PORT: The port number on which the backend server should run.
 - MONGO_URI: The connection string to the MongoDB database.
 - ACCESS_TOKEN_SECRET and REFRESH_TOKEN_SECRET: Used for JWT authentication.
 - EMAIL_USER and EMAIL_PASS: For sending transactional emails.
 - BASE_URL: Frontend base URL.

Step 4: Start the Server

- Once the environment is configured, run the following command to start the backend server:
`npm start`

2. Frontend (Client)

To run the frontend of the application, follow these steps:

Step 1: Navigate to the Frontend Directory:

- In a new terminal window, move into the frontend folder:
`cd Frontend`

Step 2: Install Dependencies:

- Install the required frontend packages using:
`npm install`

Step 3: Run the Frontend Development Server

- Start the frontend using the development command (typically for Vite or React):

npm run dev

This will start the frontend server, usually accessible at <http://localhost:5173>.

Step 4: Access the Application:

- Open a browser and navigate to the frontend URL. From there, we can:
 - Register/Login as a user.
 - Browse products and view product details.
 - Add products to the cart and place orders.
 - Access admin functionalities if logged in as an admin.

7. API DOCUMENTATION

1. User Routes

1. Register a New User

- **Method:** POST
- **URL:** /api/users/register
- **Headers:** Content-Type: application/json
- **Body Parameters:**

```
{
  "name": "Shubham Mehta",
  "email": "shubhammehta212@gmail.com",
  "password": "1234567890"
}
```
- **Success Response:**

```
{
  "message": "User registered successfully",
  "user": { "id": "abc123", "name": "Shubham Mehta", "email": "shubhammehta212@gmail.com" },
  "token": "JWT_TOKEN"
}
```
- **Error Response**

```
{
  "error": "Email already in use"
}
```

2. User Login

- **Method:** POST
- **URL:** /api/users/login

- **Headers:** Content-Type: application/json
- **Body Parameters:**

```
{
  "email": "shubhammehta212@gmail.com",
  "password": "1234567890"
}
```
- **Success Response:**

```
{
  "token": "JWT_TOKEN",
  "user": { "id": "abc123", "name": "Shubham Mehta" }
}
```
- **Error Response:**

```
{
  "error": "Invalid email or password"
}
```

2. Product Routes

1. Get All Products

- **Method:** GET
- **URL:** /api/products
- **Headers:** None
- **Success Response:**

```
[
  { "id": "p1", "name": "iPhone 16", "price": 771, "stock": 10 },
  ...
]
```

2. Get Product by ID

- **Method:** GET
- **URL:** /api/products/:id
- **Success Response:**

```
{
  "id": "p1",
  "name": "iPhone 16",
  "description": "Latest Apple iPhone",
  "price": 771
}
```
- **Error Response:**

```
{
  "error": "Product not found"
}
```

3. Cart Routes

1. Add to Cart

- **Method:** POST
- **URL:** /api/cart/add
- **Headers:** Authorization: Bearer JWT_TOKEN
- **Body Parameters:**

```
{
  "productId": "p1",
  "quantity": 2
}
```
- **Success Response:**

```
{
  "message": "Item added to cart"
}
```

2. View Cart

- **Method:** GET
- **URL:** /api/cart
- **Headers:** Authorization: Bearer JWT_TOKEN
- **Success Response:**

```
{
  "cartItems": [
    { "productId": "p1", "name": "iPhone 16", "quantity": 2 }
  ]
}
```

4. Order Routes

1. Place Order

- **Method:** POST
- **URL:** /api/orders
- **Headers:** Authorization: Bearer JWT_TOKEN
- **Body Parameters:**

```
{
  "items": [{ "productId": "p1", "quantity": 2 }],
  "shippingAddress": "123 Street, City",
  "paymentMethod": "Cash"
}
```
- **Success Response:**

```
{
  "message": "Order placed successfully",
}
```

```
    "orderId": "o123"
  }
}
```

2. Get User Orders

- **Method:** GET
- **URL:** /api/orders/myorders
- **Headers:** Authorization: Bearer JWT_TOKEN
- **Success Response:**

```
[
  { "orderId": "o123", "status": "Processing" },
  ...
]
```

5. Authentication Routes

1. Register User

- **Method:** POST
- **URL:** /api/auth/register
- **Body Parameters:**

```
{
  "name": "Shubham Mehta",
  "email": "shubhammehta212@gmail.com",
  "password": "1234567890"
}
```
- **Success Response:**

```
{
  "message": "User registered successfully",
  "token": "JWT_TOKEN"
}
```

2. Login User

- **Method:** POST
- **URL:** /api/auth/login
- **Body Parameters:**

```
{
  "email": "shubhammehta212@gmail.com",
  "password": "1234567890"
}
```
- **Success Response:**

```
{
  "message": "Login successful",
  "token": "JWT_TOKEN"
}
```

6. Wishlist Routes

1. Add to Wishlist

- **Method:** POST
- **URL:** /api/wishlist
- **Headers:** Authorization: Bearer JWT_TOKEN
- **Body Parameters:**

```
{
  "productId": "p1"
}
```
- **Success Response:**

```
{
  "message": "Product added to wishlist"
}
```

2. Get Wishlist

- **Method:** GET
- **URL:** /api/wishlist
- **Headers:** Authorization: Bearer JWT_TOKEN
- **Success Response:**

```
[
  { "productId": "p1", "productName": "iPhone 16" },
  ...
]
```

3. Remove from Wishlist

- **Method:** DELETE
- **URL:** /api/wishlist/:productId
- **Headers:** Authorization: Bearer JWT_TOKEN
- **Success Response:**

```
{
  "message": "Product removed from wishlist"
}
```

7. Admin Dashboard Routes

1. Get All Users

- **Method:** GET
- **URL:** /api/admin/users
- **Headers:** Authorization: Bearer JWT_TOKEN (Admin Only)
- **Success Response:**

```
[
  { "userId": "abc123", "name": "Shubham Mehta", "email":
```

```
"shubhammehta212@gmail.com" },  
...  
]
```

2. Get All Orders

- **Method:** GET
- **URL:** /api/admin/orders
- **Headers:** Authorization: Bearer JWT_TOKEN (Admin Only)
- **Success Response:**

```
[  
  { "orderId": "o123", "status": "fulfilled" },  
  ...  
]
```

3. Update Order Status

- **Method:** PUT
- **URL:** /api/admin/orders/:orderId
- **Headers:** Authorization: Bearer JWT_TOKEN (Admin Only)
- **Body Parameters:**

```
{  
  "status": "fulfilled"  
}
```
- **Success Response:**

```
{  
  "message": "Order status updated"  
}
```

8. Brand Routes

1. Get All Brands

- **Method:** GET
- **URL:** /api/brands
- **Success Response:**

```
[  
  { "brandId": "b1", "brandName": "Apple" },  
  ...  
]
```

2. Add New Brand (Admin)

- **Method:** POST
- **URL:** /api/brands
- **Headers:** Authorization: Bearer JWT_TOKEN (Admin Only)
- **Body Parameters:**

```
{
  "brandName": "Sony"
}
```

- **Success Response:**

```
{
  "message": "Brand added successfully"
}
```

9. Category Routes

1. Get All Categories

- **Method:** GET
- **URL:** /api/categories
- **Success Response:**

```
[
  { "categoryId": "c1", "categoryName": "Mobiles" },
  ...
]
```

2. Add New Category (Admin)

- **Method:** POST
- **URL:** /api/categories
- **Headers:** Authorization: Bearer JWT_TOKEN (Admin Only)
- **Body Parameters:**

```
{
  "categoryName": "Accessories"
}
```
- **Success Response:**

```
{
  "message": "Category added successfully"
}
```

8. AUTHENTICATION

1. JWT-Based Authentication

- **Authentication** in ShopEZ is handled using **JWT (JSON Web Tokens)** stored in cookies.
- After login or registration, an accessToken, refreshToken, and loggedInUserInfo are set as cookies on the client.
- The accessToken is used for authorizing API requests.
- The refreshToken is used to **renew** expired access tokens without requiring re-

login.

1. How it Works

- verifyJWT middleware checks if the accessToken, refreshToken, and loggedInUserInfo cookies are present.
- It verifies the accessToken using ACCESS_TOKEN_SECRET. If expired or invalid, it calls the renewTokens() function.
- The renewTokens() method:
 - Verifies the refreshToken using REFRESH_TOKEN_SECRET.
 - If valid, it generates **new access and refresh tokens**, stores them, and continues the request.
- The user ID and role are extracted and attached to the request via req.body.user.

2. Role-Based Access Control (RBAC)


- **Role support** includes:
- user: Can access user-level endpoints (cart, wishlist, orders, profile).
- admin: Can access admin-level features (product, brand, category, user management).
- verifyAdminJWT is a dedicated middleware that:
- Checks if the logged-in user's role is admin.
- If not, it blocks the request with a 401 Unauthorized error.

```
if(role !== "admin") {  
  
    return next(new ApiError(401, "Unauthorized"));  
  
}
```

3. Token Expiration & Refresh Handling

- **Token Expiry Settings:**
- accessToken: 10 minutes (maxAge: 600000)
- refreshToken: 20 minutes (maxAge: 1200000)
- When the accessToken expires:
- The renewTokens() function is triggered automatically.
- It checks the refreshToken and user ID.
- New tokens are generated and stored in cookies without affecting the user experience.
- This ensures seamless and secure sessions for users.

4. Token Flow (Middleware)



5. Middleware Files

File	Purpose
auth.middleware.js	Handles token verification, renewal, and RBAC for both users and admins.
pagination.middleware.js	Adds pagination logic to any route fetching long lists (e.g., products, orders).


6. Example Protected Endpoints

Endpoint	Role	Middleware
GET /api/user/profile	user	verifyJWT


POST /api/orders	user	verifyJWT
POST /api/admin/product	admin	verifyAdminJWT
GET /api/admin/users	admin	verifyAdminJWT

9. USER INTERFACE

1. Landing Page



2. Login



A screenshot of a web browser showing a login page. The browser's address bar displays 'localhost:5174/login'. The page features a green shopping bag icon with a white 'S' at the top center. Below the icon, the text 'Log in to your account' is centered. There are two input fields: 'Email address' containing 'shubhammehta212@gmail.com' and 'Password' with masked characters. A 'Forgot Password?' link is next to the password field. A blue 'Logging' button is positioned below the password field. At the bottom, a link says 'Not a member? Create account'.

Log in to your account

Email address
shubhammehta212@gmail.com


Password
.....

Forgot Password?

Logging

Not a member? [Create account](#)

3. User Dashboard



A screenshot of a web browser showing a user dashboard. The browser's address bar displays 'localhost:5174/products'. A green notification banner at the top right says 'User logged in successfully'. The main heading is 'All Products'. On the left, there are filters for 'Category' and 'Brands', each with a '+' icon. The product grid shows six items: Apple iPhone 15 (\$771, 17% OFF), Samsung SAMSUNG Galaxy S24 Ultra 5G (\$1562, 3% OFF), OPPO Reno11 5G (\$353, 26% OFF), and three other products (HP laptop, a lamp, and another laptop) which are partially visible. Each product card includes an image, brand name, model name, and price with discount information. A heart icon is present on the right of each product card.

User logged in successfully

All Products


Sort ▾

Category +


Brands +

Product	Brand	Model	Price	Discount
Apple iPhone 15	Apple	Apple iPhone 15	\$771	\$930 (17% OFF)
Samsung SAMSUNG Galaxy S24 Ultra 5G	Samsung	SAMSUNG Galaxy S24 Ultra 5G	\$1562	\$1611 (3% OFF)
OPPO Reno11 5G	OPPO	OPPO Reno11 5G	\$353	\$478 (26% OFF)
HP Laptop	HP	HP Laptop		
Lamp		Lamp		
Laptop		Laptop		


4. Order History




5. Wishlist



6. Individual Products Page



7. Cart



8. Checkout

This screenshot shows the checkout page with a form for entering shipping details. The form includes fields for Street Address, City, State/Province, and ZIP / Postal Code. There are 'Reset' and 'Add Address' buttons. Below the form, there is a section for 'Addresses' with a list of existing addresses. A summary box on the right shows 'Shipping and taxes calculated at checkout' and 'Order Now' and 'Continue Shopping' buttons.

Reset

Street Address

City State/Province ZIP / Postal Code

Reset Add Address

Addresses

Choose from Existing addresses

- #246, Kundan Nagar
Firozpur, Punjab
152002
- #246, Kundan Nagar
Firozpur, Punjab
152012

Shipping and taxes calculated at checkout

Order Now

Continue Shopping

This screenshot shows the checkout page with a form for entering personal information. The form includes fields for Full Name, Email Address, and Phone. There is a 'Reset' button. Below the form, there is a section for 'Personal Information' with a note about using a permanent address. A summary box on the right shows 'Cart' details, including 'Subtotal', 'Total Items in Cart', and 'Order Now' and 'Continue Shopping' buttons.

Personal Information

Use a permanent address where you can receive mail.

Full Name

Shubham

Email Address

shubhammehta212@gmail.com

Phone

7087118046

Reset

Street Address

Cart

Apple iPhone 15 256 GB \$771

Experience the iPhone 15 – your dynamic ...

Qty 1 Remove


Subtotal \$771

Total Items in Cart 1 items


Shipping and taxes calculated at checkout

Order Now


Continue Shopping



9. Admin Dashboard




10. Admin Profile



The screenshot shows a web browser window with the URL `localhost:5174/myProfile`. The page has a dark header with a shopping bag icon, 'Orders', 'Products', 'Search', and 'Profile' links. The main content area is titled 'My Profile' and contains the following information:

- Name :** ADMINN (with an edit icon)
- Role :** ADMIN
- Email Address :** admin@gmail.com
- Phone number :** 1010101010 (with an edit icon)
- Your addresses :** No saved addresses

11. Edit Product Form



The screenshot shows a web browser window with the URL `localhost:5174/admin/product/66fa77fe1590baab262314c`. The page has a dark header with a shopping bag icon, 'Orders', 'Products', 'Search', and 'Profile' links. The main content area is titled 'Edit Product Form' and contains the following fields:

- Title**: Apple Iphone 15
- Price (\$)**: 930
- Discount Percentage**: 17
- Description**: Experience the iPhone 15 – your dynamic companion. Dynamic Island ensures you stay connected, bubbling up alerts seamlessly while you're busy. Its durable design fe
- Brand**: Apple (dropdown menu)
- Categories**: smartphones (dropdown menu)
- Images**:
 - image 1**: `https://m.media-amazon.com/images/I/71657TifeHL_SX522.jpg` (with a delete icon)
 - image 2**: `https://m.media-amazon.com/images/I/71657TifeHL_SX522.jpg` (with a delete icon)

Add

Size: 256 GB Remove

Colors :

Color	ColorCode	Stock	
Black	#4A4C4E	7	Remove

Add

Size: 512 GB Remove

Colors :

Color	ColorCode	Stock	
Blue	#D2DFF0	0	Remove

Add

Add Variation

Deleted: False

12. Create Product Form

Orders Products Search Profile

Create Product Form

Title:

Price (\$): Discount Percentage:

Description:

Brand: --select brand-- Categories: --select category--

Add Brand: ADD Add Category: ADD

Images

image 1:

image 2:

image 2

image 3

image 4

Thumbnail

Variations:

Size	Color	ColorCode	Stock

Remove

Add

13. Logout

Successfully Logged Out

Log in to your account

Email address

Password

Forgot Password?

Log in

Not a member? [Create an account](#)

10. TESTING

1. FUNCTIONAL AND PERFORMANCE TESTING

1. Performance Testing (GenAI Functional & Performance Testing)
2. Test Scenarios & Results

Test Case ID	Scenario (What to test)	Test Steps (How to test)	Expected Result	Actual Result	Pass/Fail

FT-01	Text Input Validation (e.g., topic, job title)	Enter valid and invalid text in input fields	Valid inputs accepted, errors for invalid inputs	Valid inputs generated content; invalid entries showed proper	Pass
FT-02	Number Input Validation (e.g., word count,	Enter numbers within and outside the	Accepts valid values, shows error for out-of-range	Accepts numbers in range; error shown for out-of-range values	Pass
FT-03	Content Generation (e.g., blog,	Provide complete inputs and	Correct content is generated based on input	Accurate content generated matching the input context	Pass
FT-04	API Connection Check	Check if API key is correct and model	API responds successfully	Connection stable; API responded on every call	Pass
PT-01	Response Time Test	Use a timer to check content generation	Should be under 3 seconds	Average response time: 2.4 seconds	Pass
PT-02	API Speed Test	Send multiple API calls at the same time	API should not slow down	API handled 5+ concurrent calls without delay or	Pass
PT-03	Image Upload Load Test (Admin-	Upload multiple PDFs and check	Images should upload quickly without delay or errors. The product	Admin uploaded multiple high-res images without delay	Pass

11. DEMO

To offer a clear understanding of the platform’s functionality and user experience, we have prepared a demo video showcasing the end-to-end flow of the **ShopEZ** application. The video highlights both **user-side operations**—like browsing products, adding items to the cart, logging in, placing orders—as well as **admin-side capabilities**, including managing products, updating order statuses, and overseeing user data. This visual walkthrough serves as a comprehensive guide for stakeholders, evaluators, or contributors to grasp how the application operates in real-time. It also demonstrates the responsiveness and interactive nature of the UI across different pages.

[Click here to watch the demo video](#)

12. KNOWN ISSUES

Despite thorough development and testing, a few known issues and limitations currently exist in the ShopEZ platform:

1. Token Expiry Edge Case

- If the refresh token expires during user activity, re-authentication might be required manually.
- Auto-logout mechanism is planned but not yet implemented.

2. Cart Not Synced Across Devices

- Cart items are stored locally; logging in from a different device may not retain previous cart contents.

3. Limited Inventory Updates

- Inventory does not automatically update when an order is placed; relies on manual or delayed updates.

4. Responsiveness Issues on Older Devices

- Some UI components may break on smaller or older mobile devices due to limited media query handling.

5. Slow Loading on Initial Render

- The homepage can have a slight delay during the first load due to large JSON file parsing (products, brands).

6. No Real-Time Order Status

- Order status updates are not pushed in real-time. Users must refresh the page to view updates.

7. Password Reset Not Fully Functional

- The "Forgot Password" feature is under development and currently non-functional.

13. FUTURE ENHANCEMENTS

While the current version of ShopEZ delivers core functionalities for an e-commerce platform, there are several areas that can be enhanced or expanded upon in future iterations:

1. Enhanced Payment Integration

- Integrate real-time payment gateways like Razorpay, Stripe, or PayPal for secure and smooth transactions.

- Enable support for UPI, Net Banking, and Wallets.

2. Mobile Application Development

- Develop a dedicated mobile app using React Native or Flutter to improve accessibility and reach.
- Provide push notifications for order updates and offers.

3. Smart Recommendation System

- Use machine learning to recommend products based on user behavior, search history, and purchase trends.

4. Advanced Search & Filters

- Implement Elasticsearch or Algolia for better product discovery through full-text search, voice search, and advanced filters.

5. Inventory & Order Management for Sellers

- Allow vendors or sellers to manage their own products, track inventory, and view orders from a separate dashboard.

6. Admin Analytics Dashboard

- Add data visualizations for sales trends, customer activity, and inventory using tools like Chart.js or Recharts.

7. Multi-language & Currency Support

- Enable users to view the site in their preferred language and currency to support a global audience.

8. Enhanced Security Features

- Add 2FA (Two-Factor Authentication), CAPTCHA on login, and real-time threat monitoring.

9. Invoice Generation & Order Tracking

- Automatically generate PDF invoices and allow users to track their orders in real-time with shipment status.

10. Accessibility & Performance Improvements

- Improve site accessibility (WCAG compliance) and optimize performance with lazy loading, caching, and CDN.

PHASE REPORTS

[Find the Phase-wise Reports in here](#)

GitHub

https://github.com/Cliffjumper1/ShopEZ-E-commerce-Application_MERN

Demo Video

<https://drive.google.com/file/d/1yNu5bRpaGpCvKyfdcWvLDS6pbCZ1HseC/view>