

• Create Campaign

POST /campaigns

Creates a new campaign with the specified characteristics.

Request

```
curl -location -request POST '{gatewayURL}/campaigns' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'x-lx-user: {LX-USER}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw '{
```

"name": "string",	Campaign name; restricted to 40 characters
"codePrefix": "string",	Prefix appended to campaign code; defined at tenant-level
"codeSuffix": "string",	Campaign code; restricted to 30 characters without spaces, unique identifier that cannot be repeated across campaigns
"tags": [	(Optional) tags
"string"	Up to 10 tags can be added to a campaign as free-form text
],	
"startDate": "string",	Campaign start datetime; must be after current system time when passed in a creation or update request. Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 00:00:00 in the tenant time zone.
"endDate": "string",	Campaign end datetime; must be after current system time when passed in a creation or update request. Null value indicates Ongoing end date Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 23:59:59 in the tenant time zone.
"partnerCode": "string",	Partner code; can be found using Retrieve lookup type API
"triggerFrequencyCode": "string",	Audience Targeting Refresh Mode Code REFRESHABLE NONREFRESHABLE
"targetingLevelCode": "string",	Audience Target Level Code

	MEMBER PRODUCT
"timeZoneOffset": number	Tenant time zone UTC offset
}	
"offerName": "string",	Offer name, restricted to 100 characters.
"offerCodePrefix": "string",	Offer code prefix, defined at tenant-level.
"offerCodeSuffix": "string",	Offer code suffix, restricted to 30 characters without spaces. Cannot be repeated within a campaign.
"requireOptIn": boolean,	Opt-in indicator, indicates whether eligible members are required to opt-in to receive an offer.
"startDate": "string",	Offer start date, must be on or after campaign start date. Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 00:00:00 in the tenant time zone.
"endDate": "string",	Fixed offer end date. Null value for Ongoing or Dynamic end dates. Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 23:59:59 in the tenant time zone.
"endDateOffset": number,	Dynamic end date offset, number of days after behaviour criteria is met for given member. Null value for Fixed or Ongoing end dates.
"timeZoneOffset": number,	Tenant time zone UTC offset
"displayChannels": [	(Optional) Offer channels where offers are displayed to eligible members
"string"	Offer channel code
],	
"descriptions": "string",	(Optional) description of the offer
"keyValues": [	Key value pairs assigned to the offer (see Key Configuration Use Case and Key Configuration APIs)
{	
"keyName": "string",	Key name
"keyValue": "string"	Key value
}	
],	

"campaignId": "string",	Campaign identifier; auto-generated GUID from campaign creation
}	
"behavior": {	Behavior assigned to the offer.
"offerId": "string",	Offer identifier; auto-generated GUID from offer creation.
"processorType": "string",	Evaluation processor type: REALTIME BATCH
"behaviorType": {	Real-time behavior type: SINGLE CUMULATIVE Empty array for Batch processorType.
"code": "string",	Behavior type code
"name": "string"	Behavior type name
},	
"behaviorCriteriaType": {	Real-time Cumulative Behavior Criteria Type; defined at tenant-level. Empty array for Batch processorType and Real-Time Single behaviorType.
"code": "string",	Behavior criteria type code
"name": "string"	Behavior criteria type name
},	
"threshold": number,	The minimum numerical value of the criteria that must be reached. Null for Batch processorType and Real-Time Single behaviorType.
"buffer": number,	Optional interval, or multiplier, of the Threshold value at which a member becomes eligible for the offer. Null for Batch processorType and Real-Time Single behaviorType.
"sections": [	Behavior scenarios and associated rules (see Retrieve offer behavior list API)
{	
"priority": number,	Order of the offer behavior scenario. If a member meets the rules of multiple behavior scenarios in a specified transaction, they are included in the scenario with the highest order (1 being the highest).
"behaviorSelectedRules": [	Behavior scenario rules (see Retrieve offer behavior list API)
{	
"ruleTypeCode": "string",	Code of the behavior rule data type
"ruleTypeName": "string",	Name of the behavior rule data type



Confidential

"behaviorRuleValue": {	Behavior rule data elements
"ruleValueTypeCode": "string",	Code of the behavior rule data element
"ruleValueTypeName": "string",	Name of the behavior rule data element
"operator": "string",	Operator applied to the behavior rule.
"selectedValues": [	Values assigned to the behavior rule.
"string"	
]	
}	
}	
]	
}	
]	
},	
"reward": {	Points reward assigned to the offer
"pointType": "string",	Point reward type: BONUS ACCELERATOR BASE
"value": "string",	Bonus points rewarded. Null for Accelerator and Base pointType.
"multiplier": "string",	Accelerator multiplying factor applied to base points. Null for Bonus and Base pointType.
"maxCap": "string",	Total maximum points that can be rewarded (across all eligible members) as part of the offer
"memberPointCap": number,	Maximum number of points that can be rewarded to a member as part of the offer.
"ratio": number,	Base points rewarded for each dollar of the eligible purchase amount. Null for Bonus and Accelerator pointType.
"issuanceType": "string",	Takes the value 'Unlimited' if the offer can be used unlimited times, else it is 'DefinedValue'.
"issuanceNumber": number,	Populated if issuance type is 'DefinedValue'. Represents how many issuances the offer can have.
"quantityAdjustedFl": boolean	Quantity adjusted flag; indicates whether bonus points are rewarded per qualifying item. Null for Accelerator and Base pointType.
"offerId": "string",	Offer identifier; auto-generated GUID from offer creation.
}	

[	
{	
"contentName": "string",	Content name
"contentCode": "string",	Unique content key exposed to external content management systems; cannot be repeated within an offer or contain spaces.
"startDate": "yyyy-MM-ddTHH:mm:ss.fffZ",	Content start date; restricted by campaign start date.
"endDate": "yyyy-MM-ddTHH:mm:ss.fffZ"	Content end date. Null value for Ongoing or Dynamic end dates.
"endDateOffset": number,	Dynamic end date: number of days after behaviour criteria is met for given member
"webFl": boolean,	Indicates if content displayed in Web channel.
"mobileFl": boolean,	Indicates if content displayed in Mobile channel
"contentTypeCode": "string"	Content type code
}	
}	

Sample Request

```
{
  "name": "Campaign Name",
  "codePrefix": "CMP_",
  "codeSuffix": "Cmp_CZZ",
  "tags": [
    "Integration_Test"
  ],
  "startDate": "2024-01-01",
  "endDate": "2024-02-02",
  "partnerCode": "SCENE",
  "triggerFrequencyCode": "REFRESHABLE",
  "targetingLevelCode": "MEMBER",
  "timeZoneOffset": null
}
```

Response

```
{
  "campaignId": "cmp_c14b3b0cb76c43b884e2e8aadf676324",
  "name": "BCG Test Create Campaign",
  "codePrefix": "CMP_",
  "codeSuffix": "Cmp_CZZ",
  "favorite": false,
  "tags": [
    "Integration_Test",
    "BCG_Test"
  ],
  "approvalStatus": {
```

```

    "code": "AUTHORING",
    "name": "Authoring"
  },
  "processStatus": {
    "code": "PENDING",
    "name": "Pending"
  },
  "status": {
    "code": "PENDING",
    "name": "Pending"
  },
  "startDate": "2022-06-20T00:00:00",
  "endDate": "2022-08-20T23:59:59",
  "triggerFrequency": {
    "code": "REFRESHABLE",
    "name": "Refreshable"
  },
  "audienceGroups": [],
  "files": [],
  "globalFl": false,
  "totalAudienceCount": 0,
  "startDateTimeZoneOffset": 0,
  "endDateTimeZoneOffset": 0,
  "externalTargetingFl": false
}

```

- Fulfill transaction.

POST /member-offers/{memberId}/fulfill-transaction

Fulfills the transaction of a specified basket for an identified member. And this includes process and calculate point issuance, redeem, voucher and reward, etc...

Offer issuances and/or voucher redemptions are generated using this API.

memberId: Member identifier

Request

```

curl --location --request POST '{gatewayURL}/member-offers/{memberId}/fulfill-transaction' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw '{

```

- Re-fulfill Transaction.

POST /member-offers/{memberId}/transactions/re-fulfill

Given that a transaction that resulted in an offer issuance of an additive (i.e., points) or non-additive (i.e., tier) reward has changed, and a new transaction is fulfilled, this endpoint publishes a reversed offer issuance of the offer issuance from the original transaction, revoking the additive or non-additive reward given by this offer issuance (this offer issuance reversal cannot be reversed) and reverts cumulative offer measures. If the new transaction satisfies offer behavior of an offer assigned to them, an offer issuance will be given for each offer satisfied. This endpoint will return any errors that may have happened with individual offer issuances and/or publishing events to the event hub. This endpoint only reverses offers that are configured with real-time single **(cumulative reversal to be included in release 3.7.0)** transaction behavior and an additive (i.e., points) or non-additive (i.e., tier, badge) reward.

Re-fulfillment essentially has 2 parts:

1. Cancel the original fulfilled transaction, reverses any associated offer issuance (this offer issuance reversal cannot be reversed), and reverts any cumulative offer measures
 - Reversed offer issuance results in a decrease in issue count, a new offer issuance reversal document, and an offer issuance event is published. The original transaction fulfilment is marked as cancelled.
2. Fulfill the new transaction provided and issue reward if applicable

memberId: Unique member identifier

Request

```
curl --location --request POST '{gatewayURL}/member-offers/{memberId}/transactions/re-fulfill' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'Content-Type: application/json' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}'
```

- Evaluate transaction.

POST /member-offers/{memberId}/evaluate-transaction

Evaluates a transaction for a specified member, returning eligible rewards that would result from the transaction.

No offer issuances are generated using this API.

memberId: Member identifier

Request

```
curl --location --request POST '{gatewayURL}/member-offers/{memberId}/evaluate-transaction' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
```

- Cancel transaction.

POST /member-offers/{memberId}/transactions/cancel

Cancels a previously fulfilled transaction, reverses any associated offer issuances (this offer issuance reversal cannot be reversed), and reverts cumulative offer measures. This endpoint only reverses offers that are configured with real-time single transaction behavior and an additive (i.e., points) or non-additive (i.e., tier, badge) reward.

Reversed offer issuance results in a decrease in issue count, a new offer issuance reversal document, and an offer issuance event is published. The original transaction fulfilment is marked as cancelled.

memberId: Unique member identifier

Request

```
curl --location --request POST '{gatewayURL}/member-offers/{memberId}/transactions/cancel' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
```

```
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
\
--data-raw '{
  "transactionId": "string",
  "productId": "string",
  "cancellationReason": "string"
}'
```

"transactionId": "string",	Unique identifier of the transaction that is being cancelled
"productId": "string",	Unique identifier of product; only applicable to product-targeting campaigns
"cancellationReason": "string"	(Optional) Free-form text to describe the reason for cancelling the transaction

- Retrieve transaction.

[GET](#) /member-offers/{memberId}/transactions/{transactionId}

Retrieves transaction with the specified identifiers.

memberId: Member identifier

transactionId: Transaction identifier received from caller for real-time evaluation.

Request

```
curl --location --request GET '{gatewayURL}/member-offers/{memberId}/transactions/{transactionId}' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw ''
```

- Search member transactions

[POST](#) /member-transactions/search

Searches member transactions using the specified filter criteria.

Request

```
curl --location --request POST '{gatewayURL}/member-transactions/search' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw '{
```

"filter": {	Search filters
"fromCreatedDate": "string",	(Optional) Minimum transaction date Formats: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If not specified, considered unlimited.
"toCreatedDate": "string",	(Optional) Maximum transaction date Formats: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If not specified, considered unlimited.
"minPoints": number,	(Optional) Minimum points issued If not specified, considered unlimited.
"maxPoints": number	(Optional) Maximum points issued If not specified, considered unlimited.
},	
"limit": number	The page size to retrieve. If limit is not specified, default value is 25.
}	

- Update member offer.

PUT /member-offers/{targetLevelGroupOfferId}

Updates the provided fields for a specified member offer. If an optional field is not provided in the request, it will not be updated.

targetLevelGroupOfferId: unique identifier of the member or product offer assignment

Request

```
curl --location --request PUT '{gatewayURL}/member-offers/{targetLevelGroupOfferId}' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
```

```
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw '{
```

"targetReferenceId": "string",	*Unique identifier of the associated member or product
"startDate": "string",	Start date of the member offer; updated value must be after current datetime Format: "yyyy-MM-ddTHH:mm:ssZ" "yyyy-MM-ddTHH:mm:ss.fffZ" "yyyy-MM-dd"
"endDate": "string",	End date of the member offer; must be after start date and current datetime Format: "yyyy-MM-ddTHH:mm:ssZ" "yyyy-MM-ddTHH:mm:ss.fffZ" "yyyy-MM-dd"
"setOpenEndDate": Boolean	true: ongoing end date (no end date) false: defined end date

```
}'
```

- Other Member and Offer related transactions.

Search member offers.

Retrieve Offer

Evaluate Offer.

Example:

- Evaluate Offer:** Insert members into an active campaign given the member is not already enrolled.

POST /member-offers/offers/evaluate

Request

```
curl --location --request POST '{gatewayURL}/member-offers/offers/evaluate' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'Content-Type: application/json' \
--data-raw '{
```

"campaignId": "string",	Campaign identifier of the campaign the member will be added to
"campaignName": "string",	
"audienceGroupId": "string",	(optional) Name of the campaign

	(optional) Audience group identifier
"audienceGroupName": "string",	(optional) Name of the audience group
"targetReferenceId": "string",	Member identifier or product identifier of the object to be injected into the campaign
"targetingLevelCode": "string",	"MEMBER" or "PRODUCT"
"offerIds": [	(optional) Offer identifiers
"string"	
],	
"eventId": "string",	(optional) Event identifier
"eventTime": number	(optional) Time the event was created
}	

Response

JSON Fields	Description
{	
"memberId": "string",	Campaign identifier of the campaign the member will be added to
"targetReferenceId": "string",	Member identifier or product identifier of the object to be injected into the campaign
"offerId": "string",	Offer identifiers
"newAssignmentFl": Boolean,	True if injection was successful, false otherwise
"errors": [	If a member is already in the campaign, an error will be thrown
{	
"message": "string",	Message describing the error
"type": "string",	Error type, e.g., BusinessException, ValidationException, UserNotFoundException, NullReferenceException, etc.
"code": number,	Error code, e.g., 400, 404, 500, etc.
"source": "string",	Application service returning the error
"index": number	Index of the error
}	
]	
}	



Confidential