

• Create Campaign

POST /campaigns

Creates a new campaign with the specified characteristics.

Request

```
curl -location -request POST '{gatewayURL}/campaigns' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'x-lx-user: {LX-USER}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw '{
```

"name": "string",	Campaign name; restricted to 40 characters
"codePrefix": "string",	Prefix appended to campaign code; defined at tenant-level
"codeSuffix": "string",	Campaign code; restricted to 30 characters without spaces, unique identifier that cannot be repeated across campaigns
"tags": [	(Optional) tags
"string"	Up to 10 tags can be added to a campaign as free-form text
],	
"startDate": "string",	Campaign start datetime; must be after current system time when passed in a creation or update request. Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 00:00:00 in the tenant time zone.
"endDate": "string",	Campaign end datetime; must be after current system time when passed in a creation or update request. Null value indicates Ongoing end date Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 23:59:59 in the tenant time zone.
"partnerCode": "string",	Partner code; can be found using Retrieve lookup type API
"triggerFrequencyCode": "string",	Audience Targeting Refresh Mode Code REFRESHABLE NONREFRESHABLE
"targetingLevelCode": "string",	Audience Target Level Code

	MEMBER PRODUCT
"timeZoneOffset": number	Tenant time zone UTC offset
}	
"offerName": "string",	Offer name, restricted to 100 characters.
"offerCodePrefix": "string",	Offer code prefix, defined at tenant-level.
"offerCodeSuffix": "string",	Offer code suffix, restricted to 30 characters without spaces. Cannot be repeated within a campaign.
"requireOptIn": boolean,	Opt-in indicator, indicates whether eligible members are required to opt-in to receive an offer.
"startDate": "string",	Offer start date, must be on or after campaign start date. Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 00:00:00 in the tenant time zone.
"endDate": "string",	Fixed offer end date. Null value for Ongoing or Dynamic end dates. Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 23:59:59 in the tenant time zone.
"endDateOffset": number,	Dynamic end date offset, number of days after behaviour criteria is met for given member. Null value for Fixed or Ongoing end dates.
"timeZoneOffset": number,	Tenant time zone UTC offset
"displayChannels": [	(Optional) Offer channels where offers are displayed to eligible members
"string"	Offer channel code
],	
"descriptions": "string",	(Optional) description of the offer
"keyValues": [	Key value pairs assigned to the offer (see Key Configuration Use Case and Key Configuration APIs)
{	
"keyName": "string",	Key name
"keyValue": "string"	Key value
}	
],	

"campaignId": "string",	Campaign identifier; auto-generated GUID from campaign creation
}	
"behavior": {	Behavior assigned to the offer.
"offerId": "string",	Offer identifier; auto-generated GUID from offer creation.
"processorType": "string",	Evaluation processor type: REALTIME BATCH
"behaviorType": {	Real-time behavior type: SINGLE CUMULATIVE Empty array for Batch processorType.
"code": "string",	Behavior type code
"name": "string"	Behavior type name
},	
"behaviorCriteriaType": {	Real-time Cumulative Behavior Criteria Type; defined at tenant-level. Empty array for Batch processorType and Real-Time Single behaviorType.
"code": "string",	Behavior criteria type code
"name": "string"	Behavior criteria type name
},	
"threshold": number,	The minimum numerical value of the criteria that must be reached. Null for Batch processorType and Real-Time Single behaviorType.
"buffer": number,	Optional interval, or multiplier, of the Threshold value at which a member becomes eligible for the offer. Null for Batch processorType and Real-Time Single behaviorType.
"sections": [	Behavior scenarios and associated rules (see Retrieve offer behavior list API)
{	
"priority": number,	Order of the offer behavior scenario. If a member meets the rules of multiple behavior scenarios in a specified transaction, they are included in the scenario with the highest order (1 being the highest).
"behaviorSelectedRules": [	Behavior scenario rules (see Retrieve offer behavior list API)
{	
"ruleTypeCode": "string",	Code of the behavior rule data type
"ruleTypeName": "string",	Name of the behavior rule data type

"behaviorRuleValue": {	Behavior rule data elements
"ruleValueTypeCode": "string",	Code of the behavior rule data element
"ruleValueTypeName": "string",	Name of the behavior rule data element
"operator": "string",	Operator applied to the behavior rule.
"selectedValues": [	Values assigned to the behavior rule.
"string"	
]	
}	
}	
]	
}	
]	
}	
]	
},	
"reward": {	Points reward assigned to the offer
"pointType": "string",	Point reward type: BONUS ACCELERATOR BASE
"value": "string",	Bonus points rewarded. Null for Accelerator and Base pointType.
"multiplier": "string",	Accelerator multiplying factor applied to base points. Null for Bonus and Base pointType.
"maxCap": "string",	Total maximum points that can be rewarded (across all eligible members) as part of the offer
"memberPointCap": number,	Maximum number of points that can be rewarded to a member as part of the offer.
"ratio": number,	Base points rewarded for each dollar of the eligible purchase amount. Null for Bonus and Accelerator pointType.
"issuanceType": "string",	Takes the value 'Unlimited' if the offer can be used unlimited times, else it is 'DefinedValue'.
"issuanceNumber": number,	Populated if issuance type is 'DefinedValue'. Represents how many issuances the offer can have.
"quantityAdjustedFI": boolean	Quantity adjusted flag; indicates whether bonus points are rewarded per qualifying item. Null for Accelerator and Base pointType.
"offerId": "string",	Offer identifier; auto-generated GUID from offer creation.
}	



[	
{	
"contentName": "string",	Content name
"contentCode": "string",	Unique content key exposed to external content management systems; cannot be repeated within an offer or contain spaces.
"startDate": "yyyy-MM-ddTHH:mm:ss.fffZ",	Content start date; restricted by campaign start date.
"endDate": "yyyy-MM-ddTHH:mm:ss.fffZ"	Content end date. Null value for Ongoing or Dynamic end dates.
"endDateOffset": number,	Dynamic end date: number of days after behaviour criteria is met for given member
"webFl": boolean,	Indicates if content displayed in Web channel.
"mobileFl": boolean,	Indicates if content displayed in Mobile channel
"contentTypeCode": "string"	Content type code
}	
}	

Sample Request

```
{
  "name": "Campaign Name",
  "codePrefix": "CMP_",
  "codeSuffix": "Cmp_CZZ",
  "tags": [
    "Integration_Test"
  ],
  "startDate": "2024-01-01",
  "endDate": "2024-02-02",
  "partnerCode": "SCENE",
  "triggerFrequencyCode": "REFRESHABLE",
  "targetingLevelCode": "MEMBER",
  "timeZoneOffset": null
}
```

Response

```
{
  "campaignId": "cmp_c14b3b0cb76c43b884e2e8aadf676324",
  "name": "Test Create Campaign",
  "codePrefix": "CMP_",
  "codeSuffix": "Cmp_CZZ",
  "favorite": false,
  "tags": [
    "Integration_Test",
    "Test"
  ],
  "approvalStatus": {
```

```

    "code": "AUTHORING",
    "name": "Authoring"
  },
  "processStatus": {
    "code": "PENDING",
    "name": "Pending"
  },
  "status": {
    "code": "PENDING",
    "name": "Pending"
  },
  "startDate": "2022-06-20T00:00:00",
  "endDate": "2022-08-20T23:59:59",
  "triggerFrequency": {
    "code": "REFRESHABLE",
    "name": "Refreshable"
  },
  "audienceGroups": [],
  "files": [],
  "globalFl": false,
  "totalAudienceCount": 0,
  "startDateTimeZoneOffset": 0,
  "endDateTimeZoneOffset": 0,
  "externalTargetingFl": false
}

```

• Add Offer

POST /campaigns/{campaignId}/offers

Adds an offer to a specified campaign with identifiers, dates, opt-in indicator, channels, key value pairs, and optional description.

campaignId: Campaign identifier; auto-generated GUID from campaign creation

Request

```

curl --location --request POST '{gatewayURL}/campaigns/{campaignId}/offers' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'x-lx-user: {LX-USER}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw '{

```

"offerName": "string",	Offer name, restricted to 100 characters.
------------------------	---

"offerCodePrefix": "string",	Offer code prefix, defined at tenant-level.
------------------------------	---

"offerCodeSuffix": "string",	Offer code suffix, restricted to 30 characters without spaces. Cannot be repeated within a campaign.
"requireOptIn": boolean,	Opt-in indicator, indicates whether eligible members are required to opt-in to receive an offer.
"startDate": "string",	Offer start date, must be on or after campaign start date. Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 00:00:00 in the tenant time zone.
"endDate": "string",	Fixed offer end date. Null value for Ongoing or Dynamic end dates. Format: yyyy-MM-dd yyyy-MM-ddTHH:mm:ssZ yyyy-MM-ddTHH:mm:ss.fffZ If time is not specified, automatically set as 23:59:59 in the tenant time zone.
"endDateOffset": number,	Dynamic end date offset, number of days after behaviour criteria is met for given member. Null value for Fixed or Ongoing end dates.
"timeZoneOffset": number,	Tenant time zone UTC offset
"displayChannels": [	(Optional) Offer channels where offers are displayed to eligible members
"string"	Offer channel code
],	
"descriptions": [	(Optional) description of the offer
{	
"text": "string",	Text description of the offer
"locale": "string"	Language of the offer description
}	
],	
"termsAndConditions": [	(Optional) terms and conditions of the offer

{	
"text": "string",	Text for terms and conditions
"locale": "string"	Language of the offer terms and conditions
}	
],	
"keyValues": [	Key value pairs assigned to the offer (see Key Configuration Use Case and Key Configuration APIs)
{	
"keyName": "string",	Key name
"keyValue": "string"	Key value
}	
]	
}	

Sample API Request

```
{
  "offerName": "Test_Offer",
  "offerCodePrefix": "BOGO_",
  "offerCodeSuffix": "OI",
  "requireOptIn": true,
  "startDate": "2022-06-21",
  "endDate": "2022-08-20",
  "endDateOffset": null,
  "timeZoneOffset": null,
  "displayChannels": [
    "WEB"
  ],
  "descriptions": [
    {
```

```

    "text": "This is Test Offer",
    "locale": "en"
  },
],
"termsAndConditions": [
  {
    "text": "Terms and Conditions for the offer",
    "locale": "en"
  }
],
"keyValues": [
  {
    "keyName": "OfferCategory",
    "keyValue": "ABC"
  }
]
}

```

Sample API Response

```

{
  "offerId": "ofr_08b80acbca8347cc9799528413aebd3d",
  "campaignId": "cmp_c14b3b0cb76c43b884e2e8aadf676324",
  "name": "Test_Offer",
  "offerCodePrefix": "BOGO_",
  "offerCodeSuffix": "OI",
  "requireOptIn": true,
  "startDate": "2022-06-21T00:00:00",

```

```
"endDate": "2022-08-20T23:59:59",
"endDateOffset": null,
"displayChannel": [
  {
    "code": "WEB",
    "name": "Web"
  }
],
"descriptions": [
  {
    "text": "This is Test Offer",
    "locale": "en"
  }
],
"terms": [
  {
    "text": "Teram and Conditions for the offer",
    "locale": "en"
  }
],
"reward": null,
"voucher": null,
"redemption": null,
"behavior": {
  "processorType": "BATCH",
  "behaviorType": null,
  "behaviorCriteriaType": null,
  "threshold": null,
  "buffer": null,
```

```

    "sections": [],
  },
  "percentageAssignment": 50,
  "keyValues": [
    {
      "keyName": "OfferCategory",
      "keyValue": "ABC"
    }
  ],
  "startDateTimeZoneOffset": 0.0,
  "endDateTimeZoneOffset": 0.0,
  "contents": [],
  "rewards": []
}

```

- Add Offer Behavior

POST /offers/{offerId}/behavior

Adds behavior scenario(s) and associated rule(s) to specified offer.

offerId: Offer identifier, auto-generated GUID from offer creation

Request

```

curl --location --request POST '{gatewayURL}/offers/{offerId}/behavior' \
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'x-lx-user: {LX-USER}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw '{

```

"processorType": "string",	Evaluation processor type: REALTIME BATCH
"behaviorType": "string",	Real-time behavior type: SINGLE CUMULATIVE Empty array for Batch processorType.
"behaviorCriteriaType": "string",	Real-time Cumulative Behavior Criteria Code; defined at tenant-level. Empty array for Batch processorType and Real-Time Single behaviorType.
"threshold": number,	The minimum numerical value of the criteria that must be reached. Null for Batch processorType and Real-Time Single behaviorType.
"buffer": number,	Optional interval, or multiplier, of the Threshold value at which a member begins receiving an offer. Null for Batch processorType and Real-Time Single behaviorType.
"sections": [	Behavior scenarios and associated rules (see Retrieve offer behavior list API)
{	
"priority": number,	Order of the offer behavior scenario. If a member meets the rules of multiple behavior scenarios in a specified transaction, they are included in the scenario with the highest order (1 being the highest).
"behaviorSelectedRules": [	Behavior scenario rules (see Retrieve offer behavior list API)
{	
"behaviorRuleValue": {	Behavior rule data elements, operator, and values
"ruleValueTypeCode": "string",	Code of the behavior rule data element
"operator": "string",	Operator code applied to the behavior rule
"selectedValues": [	Values assigned to the behavior rule
"string"	

]	
}	
}	
]	
}	
]	
}	

Sample API Request

```
{
  "processorType": "BATCH",
  "behaviorType": "",
  "behaviorCriteriaType": "",
  "threshold": null,
  "buffer": null,
  "sections": [
    {
      "priority": 1,
      "behaviorSelectedRules": [
        {
          "behaviorRuleValue": {
            "ruleValueTypeCode": "Age",
            "operator": "EQUALS",
            "selectedValues": [
              "30"
            ]
          }
        }
      ]
    }
  ]
}
```

```
    ]
  }
]
}
```

Sample API Response

```
{
  "offerId": "ofr_08b80acbca8347cc9799528413aebd3d",
  "campaignId": "cmp_c14b3b0cb76c43b884e2e8aadf676324",
  "name": "Test_Offer",
  "offerCodePrefix": "BOGO_",
  "offerCodeSuffix": "OI",
  "requireOptIn": true,
  "startDate": "2022-06-21T00:00:00",
  "endDate": "2022-08-20T23:59:59",
  "endDateOffset": null,
  "displayChannel": [
    {
      "code": "WEB",
      "name": "Web",
      "priority": null
    }
  ],
  "descriptions": [
    {
      "text": "This is Test Offer",
      "locale": "en"
    }
  ]
}
```

```
],
"terms": [
  {
    "text": "Teram and Conditions for the offer",
    "locale": "en"
  }
],
"content": null,
"reward": null,
"voucher": null,
"redemption": null,
"behavior": {
  "processorType": "BATCH",
  "behaviorType": null,
  "behaviorCriteriaType": null,
  "threshold": null,
  "buffer": null,
  "sections": [
    {
      "priority": 1,
      "behaviorSelectedRules": [
        {
          "ruleTypeCode": "DEMOGRAPHIC",
          "ruleTypeName": "Demographic",
          "behaviorRuleValue": {
            "ruleValueTypeCode": "AGE",
            "ruleValueTypeName": "Age",
            "operator": "EQUALS",
            "selectedValues": [
```

```
        "30"
      ]
    }
  }
]
},
"behaviorSelectedRules": null
},
"percentageAssignment": 50,
"keyValues": [
  {
    "keyName": "OfferCategory",
    "keyValue": "ABC"
  }
],
"startDateTimeZoneOffset": 0.0,
"endDateTimeZoneOffset": 0.0,
"contents": [],
"rewards": []
}
```

- Add Points Reward

POST /offers/{offerId}/rewards/point

Adds points rewards to specified offer.

offerId: Offer identifier, auto-generated GUID from offer creation

Request

```
curl --location --request POST '{gatewayURL}/offers/{offerId}/rewards/point \
```

```
--header 'Content-Type: application/json' \
--header 'lx-api-client-key: {AUTHENTICATION-KEY}' \
--header 'api-version: {API-VERSION}' \
--header 'x-lx-user: {LX-USER}' \
--header 'Cookie: ARRAffinity={AUTOGEN-COOKIE}; ARRAffinitySameSite={AUTOGEN-COOKIE}' \
--data-raw '{
```

"pointRewardId": "string",	Points reward identifier; auto-generated GUID from points reward creation.
"pointType": "string",	Point reward type: BONUS ACCELERATOR BASE
"value": "string",	Bonus points rewarded. Null for Accelerator and Base pointType.
"multiplier": "string",	Accelerator multiplying factor applied to base points. Null for Bonus and Base pointType.
"maxCap": "string",	Total maximum points that can be rewarded (across all eligible members) as part of the offer
"memberPointCap": number,	Maximum number of points that can be rewarded to a member as part of the offer.
"ratio": number,	Base points rewarded for each dollar of the eligible purchase amount. Null for Bonus and Accelerator pointType.
"issuanceType": "string",	Takes the value 'Unlimited' if the offer can be used unlimited times, else it is 'DefinedValue'.
"issuanceNumber": number,	Populated if issuance type is 'DefinedValue'. Represents how many issuances the offer can have.
"quantityAdjustedFl": boolean	Quantity adjusted flag; indicates whether bonus points are rewarded per qualifying item. Null for Accelerator and Base pointType.
}'	



Confidential

Sample API Request

```
{
  "pointType": "BONUS",
  "value": "560",
  "multiplier": null,
  "maxCap": null,
  "memberPointCap": 1234,
  "ratio": null,
  "issuanceType": "DEFINEDVALUE",
  "issuanceNumber": 1,
  "maxUses": 1,
  "quantityAdjustedFl": false
}
```

Sample API Response

```
{
  "offerId": "ofr_08b80acbca8347cc9799528413aebd3d",
  "campaignId": "cmp_c14b3b0cb76c43b884e2e8aadf676324",
  "name": "Test_Offer",
  "offerCodePrefix": "BOGO_",
  "offerCodeSuffix": "OI",
  "requireOptIn": true,
  "startDate": "2022-06-21T00:00:00",
  "endDate": "2022-08-20T23:59:59",
  "endDateOffset": null,
  "displayChannel": [
    {

```

```
        "code": "WEB",
        "name": "Web"
    }
],
"descriptions": [
    {
        "text": "This is Test Offer",
        "locale": "en"
    }
],
"terms": [
    {
        "text": "Terms and Conditions for the offer",
        "locale": "en"
    }
],
"reward": {
    "pointRewardId": "pr_124dd1baecce4a22938d053c20370e4c",
    "pointType": "BONUS",
    "value": 560.00,
    "multiplier": null,
    "maxCap": null,
    "memberPointCap": 1234.00,
    "ratio": null,
    "issuanceType": "DEFINEDVALUE",
    "issuanceNumber": 1,
    "quantityAdjustedFl": false
},
"voucher": null,
```

```
"redemption": null,
"behavior": {
  "processorType": "BATCH",
  "behaviorType": null,
  "behaviorCriteriaType": null,
  "threshold": null,
  "buffer": null,
  "sections": [
    {
      "priority": 1,
      "behaviorSelectedRules": [
        {
          "ruleTypeCode": "DEMOGRAPHIC",
          "ruleTypeName": "Demographic",
          "behaviorRuleValue": {
            "ruleValueTypeCode": "AGE",
            "ruleValueTypeName": "Age",
            "operator": "EQUALS",
            "selectedValues": [
              "30"
            ]
          }
        }
      ]
    }
  ]
},
"percentageAssignment": 50,
"keyValues": [
```

```

    {
      "keyName": "OfferCategory",
      "keyValue": "ABC"
    }
  ],
  "startDateTimeZoneOffset": 0.0,
  "endDateTimeZoneOffset": 0.0,
  "contents": [],
  "rewards": []
}

```

- Offer Assignment / Evaluate Offer

Insert members into an active campaign given the member is not already enrolled.

POST /member-offers/offers/evaluate

Request

"campaignId": "string",	-
"campaignName": "string",	-
"audienceGroupId": "string",	-
"audienceGroupName": "string",	-
"memberId": "string",	-
"offerIds": ["string"],	-
"eventId": "string",	-
"eventTime": number,	-
"targetReferenceId": "string",	-

"targetLevelCode": "string"	-
"audienceClassCode": "string"	-
}'	

Sample API Request

```
{
  "campaignId": "cmp_c14b3b0cb76c43b884e2e8aadf676324",
  "campaignName": "Test Create Campaign",
  "audienceGroupId": null,
  "audienceGroupName": null,
  "memberId": "N92F7D36-0D45-4CJE-9E17-B41091C03953",
  "offerIds": [
    "ofr_08b80acbca8347cc9799528413aebd3d"
  ],
  "eventId": "12345",
  "eventTime": 1636129549,
  "targetReferenceId": "N92F7D36-0D45-4CJE-9E17-B41091C03953",
  "targetingLevelCode": "MEMBERS"
}
```

Sample API Response

```
{
  "memberId": "N92F7D36-0D45-4CJE-9E17-B41091C03953",
  "targetReferenceId": null,
  "offerId": "ofr_08b80acbca8347cc9799528413aebd3d",
  "newAssignmentFl": true
}
```



Confidential