KOOKABURRA

⌘1-9 ws | ⌘T new tile | ⌘⇧T new ws | Z zen | ⌘F find

auth refactor ⌘1 ~/api 3x2
benchmarks ⌘2 ~/api 2x2
docs · playground ⌘3 ~/docs 2x1
shell ⌘4 no repo 1x1
+

search all tiles… ⌘⇧F

1 claude claude · implementing auth mid… wt claude/auth-mw-a7f

```
● Reading src/middleware/auth.rs
  └ 412 lines, identified 3 hook points

● Writing src/middleware/auth.rs
  ● added verify_jwt() at L34
  ● added extract_claims() at L58
  ○ refactoring middleware_chain()

● Running cargo test --lib auth
   Compiling api v0.3.2 (~/code/api)
    Finished `test` profile in 3.84s
     Running unittests src/lib.rs

running 7 tests
test auth::tests::rejects_expired_token     ... ok
test auth::tests::rejects_missing_header    ... ok
test auth::tests::accepts_valid_hs256       ... ok
test auth::tests::accepts_valid_rs256       ... ok
test auth::tests::claims_round_trip         ... ok
test auth::tests::refresh_token_rotation    ... ok
```

2 claude claude · exploring zod vs valibot wt claude/auth-mw-b22

```
● Thinking…

  The user wants to compare runtime validation libraries
  for the request body. Three candidates:

  1. zod — mature, large bundle, great DX
  2. valibot — tree-shakeable, smaller, newer
  3. arktype — fastest but unfamiliar syntax

  Given the handoff constraint about bundle size,
  valibot looks strongest. Let me check their pars
```

3 claude claude · zero-dep approach wt claude/auth-mw-c19

```
● Writing src/middleware/auth.rs
  ● implemented base64_url_decode
  ● implemented hmac_sha256
  ○ implementing verify_signature

  writing constant-time comparison
```

4 pnpm pnpm dev

```
[10:42:18] GET  /health           200  2ms
[10:42:18] GET  /api/session      200  18ms
[10:42:19] POST /api/auth/login   200  124ms
[10:42:19] GET  /api/me           200  6ms
[10:42:20] POST /api/items        422  3ms
  → body missing "title"
[10:42:21] POST /api/items        201  42ms
[10:42:21] GET  /api/items        200  8ms
[10:42:22] DELETE /api/items/42   204  14ms
[10:42:23] GET  /api/items        200  7ms
[10:42:23] POST /api/auth/logout  200  11ms
[10:42:24] GET  /health           200  1ms
[10:42:24] GET  /api/session      401  3ms
[10:42:25] POST /api/auth/refresh 200  22ms
[10:42:26] GET  /api/me           200  5ms
[10:42:27] GET  /api/items        200  9ms

~ watching for changes
```

▼ FOLLOW

5 zsh git ⎇ main

```
~/code/api (main) $ git worktree list
/Users/j/code/api                  a7f3c09 [main]
/Users/j/.kookaburra/wt/api-a7f    b2e4111 [claude/auth-mw-a7f]
/Users/j/.kookaburra/wt/api-b22    71cd890 [claude/auth-mw-b22]
/Users/j/.kookaburra/wt/api-c19    3fa2187 [claude/auth-mw-c19]

~/code/api (main) $ git log --oneline -10
a7f3c09 (HEAD → main, origin/main) handoff: strip UX final
8fc2d40 rename: mod.rs → lib.rs
1b90ae1 feat: pty resize propagation
9fe7c22 fix: glyphon atlas race on resize
d340a88 chore: bump alacritty_terminal to 0.24
2cd1f89 feat: tokyo night theme
55aa02e feat: 3x2 grid default layout
3ca9e02 feat: egui strip integration
0d887f1 chore: cargo workspace scaffold
ff01241 init

~/code/api (main) $
```

6 nvim nvim · NOTES.md

```
1  # Auth middleware — comp
2
3  Three branches, three ap
4
5  - **a7f**: jsonwebtoken
6  - **b22**: biscuit-auth,
7  - **c19**: hand-rolled,
8
9  ## Scoring
10
11 |           | perf | dep
12 |-----------|------|----
13 | a7f       | B+   | C
14 | b22       | A    | B
15 | c19       | A+   | A+
16
17 Leaning b22. Will wait f
18
~
~
```

TWEAKS

CHAOS
lively

DENSITY
normal | dense

ACCENT HUE 68°

HELPER FRIEND (KOOKA)

HELPER CHATTY

SHOW WALKER BIRD

auth refactor | tile 1/6 | ~/code/api | wt claude/auth-mw-a7f | 2 generating | 120×32 | zen □ | ready