

# Smart Header Detection Implementation Summary

---

## Branch: fix/smart-header-detection

---

**Commit:** c3eec68f4ef0eb6541793d5cb18b1665c3e08242

**Status:**  Pushed to GitHub

**Repository:** <https://github.com/CliveCaseley/soldcomp-analyser2>

## Problem Statement

---

The CSV parser was failing to handle files where:

- Row 1 contained TARGET metadata instead of headers
- Headers appeared on row 3 or later (within first 10 rows)
- Files had varying structures with metadata, empty rows, or formatting rows before the actual headers

### Example file structure:






```
Row 1: "TARGET is Hawthorns, Horncastle Road, Goulceby, LOUTH LN11 9WB",,,,,,1152,,,
Row 2: ,,,,,,,,,,
Row 3: Date,Address,Postcode,Type,Tenure,Age at sale,Price,Sq. ft,£/
sqft,Bedrooms,Distance,URL
Row 4: 15/05/2025,"Badger's Holt, Horncastle Road, Goulceby",LN11 9WB,Detached
house,Freehold,...
```

## Solution Implemented

---

### 1. Smart Header Row Detection ( `detectHeaders` function)

#### Key improvements:

-  Scans first 10 rows instead of assuming row 1 is the header
-  Uses fuzzy matching with scoring algorithm to identify the best header row
-  Prioritizes rows containing core columns: `date`, `address`, `postcode`, `price`
-  Requires at least 2 core columns matched before considering a row as header
-  Exact match detection (100% priority) before fuzzy matching (70% threshold)

#### Scoring algorithm:

```
Row Score = (Number of matched columns) + (Core columns matched × 2)
```

#### Core column detection:

- A row must match at least 2 of: `date`, `address`, `postcode`, `price`
- This prevents false positives from data rows

## 2. Enhanced Column Mapping

### Header variations supported:

- Date: date, sale date, sold date, transaction date
- Address: address, property address, full address
- Postcode: postcode, post code, postal code
- Price: price, sale price, sold price, amount
- Type: type, property type, house type
- And many more...

### Special handling:

- ✓ £/sqft checked BEFORE Sq. ft to prevent mismatches
- ✓ URL detection prevents URLs from being mapped to non-URL columns
- ✓ Preserves all standard headers with empty values for unmapped columns

## 3. Smart Data Normalization ( normalizeData function)

### Updates:

- ✓ Starts processing from row AFTER the detected header row
- ✓ Skips all metadata rows (TARGET info, empty rows, etc.)
- ✓ Properly handles URL-only rows
- ✓ Prevents data loss from rows before headers

## Test Results

### Test 1: data (3).csv - TARGET Metadata on Row 1

#### File structure:

```
Row 0: ,"TARGET is Hawthorns, Horncastle Road, Goulceby, LOUTH LN11 9WB",...
Row 1: ,,,,,,, (empty)
Row 2: Date,Address,Postcode,Type,Tenure,Age at sale,Price,Sq. ft,£/
sqft,Bedrooms,Distance,URL
Row 3: 15/05/2025,"Badger's Holt, Horncastle Road, Goulceby",LN11 9WB,...
```

#### Parser output:

- ✓ Header row detected at row 2
- ✓ Matched 12 columns (4 core columns)
- ✓ Processed 50 data rows (starting from row 3)
- ✓ No data loss

#### Sample parsed data:

```
{
  "Date of sale": "15/05/2025",
  "Address": "Badger's Holt, Horncastle Road, Goulceby",
  "Postcode": "LN11 9WB",
  "Type": "Detached house",
  "Tenure": "Freehold",
  "Price": "£315,000",
  "Sq. ft": "1130",
  "£/sqft": "£279",
  "Distance": "0.00mi",
  "URL": "https://propertydata.co.uk/transaction/38EDC0C3-0B84-0F63-E063-4704A8C00424"
}
```

## Test 2: output (22).csv - Standard Format

### File structure:

```
Row 0: Date of sale,Address,Postcode,Type,Tenure,Age at sale,Price,...
Row 1: ,EPC Lookup,DN9 3PT,,,,,,,,,https://...
Row 2: ,7 Fernbank Close,DN9 3PT,,,,,,,,,,,,,1,,
Row 3: 02 Jul 2025,"Pembroke House, Blakewood Drive, Blaxton, Doncaster DN9 3GX",DN9 3GX,...
```

### Parser output:

- ✓ Header row detected at row 0
- ✓ Matched 24 columns (4 core columns)
- ✓ Processed 20 data rows (starting from row 1)
- ✓ Correctly handled EPC lookup and target marker rows

## Code Changes

**File modified:** src/utils/csvParser.js

### Key changes:

#### 1. detectHeaders() function (lines 132-249)

- Added row scanning loop (first 10 rows)
- Implemented scoring algorithm
- Added core column requirement check
- Added exact match detection with 100% priority

#### 1. normalizeData() function (lines 268-332)

- Added headerRowIndex parameter
- Changed start index to headerRowIndex + 1
- Added logging for skipped rows

#### 2. HEADER\_VARIATIONS object (lines 44-67)

- Reordered entries to check specific headers first
- Added comment explaining priority

## Impact

---

- ✓ **Robustness:** Handles varying CSV structures without manual intervention
- ✓ **Accuracy:** 100% correct header detection across all test files
- ✓ **No Data Loss:** All data rows properly parsed, metadata properly skipped
- ✓ **Backward Compatible:** Still works with standard CSV files (headers on row 1)
- ✓ **Well Logged:** Detailed logging shows exact header detection process

## How to Create Pull Request

---

1. Visit: <https://github.com/CliveCaseley/soldcomp-analyser2/compare/fix/smart-header-detection>
2. Click "Create pull request"
3. Title: "Fix: Implement smart header detection for messy CSV files"
4. Description: Link to this summary document
5. Submit for review

## Pull Request URL

---

<https://github.com/CliveCaseley/soldcomp-analyser2/compare/master...fix/smart-header-detection>

---

**Implementation Date:** December 4, 2025

**Author:** Clive Caseley

**Branch:** fix/smart-header-detection

**Commit:** c3eec68