

STM32H7 CAN Sniffer

STM32H743I - Real-time CAN Bus Monitoring & Configuration



CAN Sniffer Control

Start or stop the CAN sniffer activity. Ensure configuration is applied before starting.

Start

Stop

Sniffer status

Stopped


Frames

No frame loss reported

Bus load

CAN1: 0.00 % (+/- 5 %)

CAN2: 0.00 % (+/- 5 %)



CAN Configuration

Configure CAN channel settings. Stop the sniffer before applying changes. Click **Apply** to use the new settings immediately and persist them to the SD card for use after restart.

SETTING	CURRENT VALUE	NEW VALUE
CAN1: Baudrate	1 Mbit/s	- ↕
CAN1: Operating Mode	listen only	- ↕
CAN2: Baudrate	1 Mbit/s	- ↕
CAN2: Operating Mode	listen only	- ↕

Apply Configuration

SD Card Management

Format the SD card to recover from file system corruption or to apply new logging parameters. The format request will be queued and executed on the next system restart.

Warning: This will erase all data on the SD card and reset the log ring.

Note: CAN logs are stored using file rotation.

SETTING	CURRENT VALUE	NEW VALUE
Cluster size	32 KiB	32 ↕ KiB Larger clusters improve write speed but waste more space for small files.
Log file size	10 MiB	10 ↕ MiB Size of each CAN log file; larger sizes mean fewer rotations.
Log file count	1000 files	1000 ↕ Number of log files kept in the ring buffer.

Format