




Ma(e)stering your identity security posture in Microsoft Entra

Thomas Naunheim
Cyber Security Architect @glueckkanja, Microsoft MVP





About Me



Thomas Naunheim

Cloud Security Architect @glueckkanja AG,
Microsoft Security MVP

Focus

Identity + Security
in Microsoft Cloud

From

Lahnstein/Koblenz, Germany

My Blog

www.cloud-architekt.net



Community

Cloud Inspires, Azure Meetup Bonn,
Cloud Identity Summit

Hobbies

Playing Bass Guitar, Hiking, Traveling

Contact

 ThomasNaunheim



Thank you sponsors



Gold Sponsors



PATCH MY PC

robopack 
empowered by **SOFTWARE**
CENTRAL



POINT: TAKEN

Community Sponsors



Silver Sponsors



bsure.
Fortytwo.io

 **CloudWay**
twoday

control 




AGENDA



Key takeaways:

- Critical configuration areas with high impact on tenant security.
- Built-in features and community tools to analyze security configurations.
- Automation for continuous review and improvement.

- Tenant (Security) Configuration
- Authentication and Conditional Access Policies
- Privileged Identity and Access Management
- Application and Workload Identities



Tenant (Security) Configuration



Tenant Configuration Blades



Dashboard > Security | Authentication methods >

Dashboard > CloudLab | Enterprise applications > Enterprise applications | User settings >

Consent and permissions | User consent settings ...

Dashboard > CloudLab | Groups > Groups

Groups | General ...

Dashboard > CloudLab

CloudLab | User settings ...

Microsoft Entra ID

Refresh | Got feedback?

Default user role permissions

[Learn more](#)

Users can register applications ① ☒ Yes

Restrict non-admin users from creating tenants ① ☒ Yes

Users can create security groups ① ☒ Yes

Guest user access

[Learn more](#)

Guest user access restrictions ① ☐ Guest users have the same access as members (most inclusive)

☐ Guest users have limited access to properties and memberships of directory objects

☒ Guest user access is restricted to properties and memberships of their own directory objects (most restrictive)

Users can create Microsoft 365 groups in Azure portals, API or PowerShell ☒ Yes ☐ No



Tenant Configuration As Code?



```
"@odata.context":  
"https://graph.microsoft.com/beta/$metadata#policies/authorizationPolicy",  
  
"value": [  
  {  
    "displayName": "Authorization Policy",  
    "id": "authorizationPolicy",  
    "allowInvitesFrom": "adminsAndGuestInviters",  
    "allowedToSignUpEmailBasedSubscriptions": true,  
    "allowedToUseSSPR": true,  
    "defaultUserRolePermissions": {  
      "allowedToCreateApps": true,  
      "allowedToCreateSecurityGroups": true,  
      "allowedToCreateTenants": false,  
      "allowedToReadBitlockerKeysForOwnedDevice": true,  
      "allowedToReadOtherUsers": true  
    }  
  }  
]
```




Monitoring your Tenant config



Entra ID Security Config Analyzer

EIDSCA



Tenant Configuration Checks As Code



```
"Name": "allowedToCreateApps",
"DisplayName": "Default User Role Permissions - Allowed to create Apps",
"CheckId": "EIDSCA.AP10",

"SkipCondition": "",
"SkipReason": "",

"CurrentValue": "defaultUserRolePermissions.allowedToCreateApps",
"DefaultValue": "true",
"RecommendedValue": "false",


"Recommendation": "CISA SCuBA 2.6: Only Administrators SHALL Be Allowed To Register 3rd Apps",
"Severity": "High",


"MitreTactic": ["TA0001 - Initial Access", ...],
"MitreTechnique": ["T1566.002", ...],
"MitreMitigation": ["M1017", ...],

"PortalDeepLink": "https://entra.microsoft.com/.../UserManagementMenuBlade/~/UserSettings",
"Description": "Controls if non-admin users may register custom-developed applications (...)",
"HowToFix": "Microsoft Graph PowerShell: Update-MgPolicyAuthorizationPolicy (...)"
```



EIDSCA Architecture





EIDSCA Integration for Sentinel ANR



Microsoft Azure

Search resources, services, and docs (G+)

Copilot



thomas@cloud-architek...
CLOUDLAB (CLOUD-ARCHITEKT...)

Dashboard > CloudLab

CloudLab | User settings

Refresh Got feedback?

- App registrations
- Identity Governance
- Application proxy
- Custom security attributes
- Licenses
- Cross-tenant synchronization
- Microsoft Entra Connect
- Custom domain names
- Mobility (MDM and WIP)
- Password reset
- Company branding
- User settings**
- Properties
- Security
- Monitoring
 - Sign-in logs
 - Audit logs
 - Provisioning logs
 - Health
 - Log Analytics

Default user role permissions

[Learn more](#)

Users can register applications ☐ No

Restrict non-admin users from creating tenants ☒ Yes

Users can create security groups ☒ Yes

Guest user access

[Learn more](#)

- Guest user access restrictions ☐ Guest users have the same access as members (most inclusive)
- ☐ Guest users have limited access to properties and memberships of directory objects
- ☒ Guest user access is restricted to properties and memberships of their own directory objects (most restrictive)

Administration center

[Learn more](#)

Restrict access to Microsoft Entra admin center ☐ No

LinkedIn account connections

[Learn more](#)

Allow users to connect their work or school account with LinkedIn ☐ Yes

☐ Selected group

Save

Cancel



Maester Framework

**Custom Tests authored by you.
Your org's security policy as code.**



196+ Tests → [CISA + CIS + EIDSCA + Maester]

Interactive Test Report

Maester PowerShell Module

Graph PowerShell commands
optimized for tests

Email + Report Gen
+ CI/CD Commands



Azure



Entra




Exchange

+ more...



EIDSCA + Maester






Demo: Tenant Hardening



Tenant Configuration Checks
with Maester

Integration of Maester in
Microsoft Sentinel






Authentication and Conditional Access Policies



Conditional Access Baseline Design



Ensure to protect every user and every app by minimal but strong baseline!
Avoid inconsistent or duplicated policies by smart policy design!
Closed CA policy!





**“Closed” policy design
cover all types of users**

**Exclusion Management
of policies**

**Effective Response
on risky sign-in**

**Tracking policy
changes and
evaluation**

Telemetry/analytics/assessment
JIT & Version Control



View CA Changes in Audit Logs



Dashboard > CloudLab

CloudLab | Audit logs

synchronization

Microsoft Entra Connect

Custom domain names

Mobility (MDM and WIP)

Password reset

Company branding

User settings

Properties

Security

Monitoring

Sign-in logs

Audit logs

Provisioning logs

Health

Log Analytics

Diagnostic settings

Workbooks

Usage & insights

Bulk operation results (Preview)

Troubleshooting + Support

Conditional Access policy changes

This editor feature is currently in (Preview).

Side-by-Side

```
1 {
2   "id": "4a64bb53-b36d-4a8d-8f2c-8b9156aeb09b",
3   "displayName": "208 - PILOT - Data/Workload Plane - Office 365",
4   "createdDateTime": "2024-08-03T19:44:55.2044505+00:00",
5   "modifiedDateTime": "2025-02-14T17:45:28.0195724+00:00",
6   "state": "enabled",
7   "conditions": {
8     "applications": {
9       "includeApplications": [
10        "00000002-0000-0ff1-ce00-000000000000",
11        "00000003-0000-0ff1-ce00-000000000000"
12      ],
13       "excludeApplications": [],
14       "includeUserActions": [],
15       "includeAuthenticationContextClassReferences": [],
16       "applicationFilter": null
17     },
18     "users": {
19       "includeUsers": [
20        "dc15cccec-73ad-48b1-8eb2-a4c4c1f1c73c",
21        "52284bc1-8bb2-4d44-9778-d02521f0adc3"
22      ],
23       "excludeUsers": [
24        "0e1e6c34-9d5c-4b24-bba6-aafb0995a6e0"
25      ],
26       "includeGroups": [],
27       "excludeGroups": [
28        "4f67e50e-bb87-4852-80ac-269bae72cb0e"
29      ],
30       "includeRoles": [],
31       "excludeRoles": []
32     },
33     "platforms": {
```

```
1 {
2   "id": "4a64bb53-b36d-4a8d-8f2c-8b9156aeb09b",
3   "displayName": "208 - PILOT - Data/Workload Plane - Office 365",
4   "createdDateTime": "2024-08-03T19:44:55.2044505+00:00",
5   "modifiedDateTime": "2025-06-06T15:40:25.2591682+00:00",
6   "state": "enabled",
7   "conditions": {
8     "applications": {
9       "includeApplications": [
10        "00000002-0000-0ff1-ce00-000000000000",
11        "00000003-0000-0ff1-ce00-000000000000"
12      ],
13       "excludeApplications": [],
14       "includeUserActions": [],
15       "includeAuthenticationContextClassReferences": [],
16       "applicationFilter": null
17     },
18     "users": {
19       "includeUsers": [
20        "dc15cccec-73ad-48b1-8eb2-a4c4c1f1c73c",
21        "52284bc1-8bb2-4d44-9778-d02521f0adc3",
22        "ec64f91d-54ce-4c59-b530-93d1287560bc"
23      ],
24       "excludeUsers": [
25        "0e1e6c34-9d5c-4b24-bba6-aafb0995a6e0"
26      ],
27       "includeGroups": [],
28       "excludeGroups": [
29        "4f67e50e-bb87-4852-80ac-269bae72cb0e"
30      ],
31       "includeRoles": [],
32       "excludeRoles": []
33     },
34     "platforms": {
```



CA Analysis with Entra Log data



Entra ID Security Config Analyzer (EIDSCA) | Workbook | ...

Azure Workbook

Policy display name	↑↓	State	↑↓	Cloud apps included	↑↓	Cloud apps excluded
100 - ALL - User Access - All apps: Block access When usi...		✔ On		["All"]		[]
101 - ALL - User Access - All apps: Block access When usi...		✔ On		["All"]		[]
102 - ALL - User Access - All apps: Block access When usi...		✔ On		["All"]		[]
103 - ALL - User Access - All apps: Require MFA		✔ On		["All"]		["372140e0-b3b7-4226-8ef9-d57986796201"]

Changes to the selected conditional access policy

The following table shows the changes made to the selected policy during the selected time period.

Note! You need to select a policy on the list above first.



ActivityDateTime	↑↓	InitiatedBy	↑↓	PolicyDisplayName	↑↓	ModifiedProperties
3/13/2025, 10:36:09.656 AM		thomas@cloud-architekt.net		104 - ALL - User Access - User Action/Register security inf...		[{"displayName":"ConditionalAccessPolicy","oldValue"
3/13/2025, 9:10:57.482 AM		thomas@cloud-architekt.net		104 - ALL - User Access - User Action/Register security inf...		[{"displayName":"ConditionalAccessPolicy","oldValue"
3/13/2025, 9:55:56.447 AM		thomas@cloud-architekt.net		104 - ALL - User Access - User Action/Register security inf...		[{"displayName":"ConditionalAccessPolicy","oldValue"
3/13/2025, 10:05:27.667 AM		thomas@cloud-architekt.net		104 - ALL - User Access - User Action/Register security inf...		[{"displayName":"ConditionalAccessPolicy","oldValue"




CA Analysis with Log data in Workbook



Number of sign-ins and the effect of the selected policy

The following pie chart shows the effect of the selected policy for sign-ins during the selected period.

Note! You need to select a policy on the list above first.



Unusual failure to the selected conditional access policy

The following table shows the unusual failure of users to selected policy during the selected time period. This requires to enable Microsoft Sentinel UEBA tables.

Note! You need to select a policy on the list above first.

UserDisplayName	UserPrincipalName	ConditionalAccessName
Spock	spock@corp.cloud-architekt.net	104 - ALL - User Access -
Spock	spock@corp.cloud-architekt.net	104 - ALL - User Access -
Spock	spock@corp.cloud-architekt.net	104 - ALL - User Access -



Conditional Access “WhatIf”



[Dashboard](#) > [Security](#) | [Conditional Access](#) > [Conditional Access | Policies](#) >

What If ...

Policies

[Info](#) [Preview features](#) | [Got feedback?](#)

Test the impact of Conditional Access on a user when signing in under certain conditions. [Learn more](#)

User or Workload identity [?](#)

[No user or service principal selected](#)

✗ User or Service principal required

Cloud apps, actions, or authentication context [?](#)

[Any cloud app](#)

IP address [?](#)

Enter IP address (ex: 40.77.182.32)

Country [?](#)

Select country...

Device platform [?](#)

Select device platform...

Client apps [?](#)

Select a client app...

Device state (deprecated) [?](#)

Select device state...

Sign-in risk [?](#)

Select sign-in risk...

User risk [?](#)

Select user risk...

Service principal risk [?](#)

Select service principal risk...

[Learn](#) / [Microsoft.Graph.Beta.Identity.SignIns](#) /

Test-MgBetaIdentityConditionalAccess

Reference

[Feedback](#)

Module: [Microsoft.Graph.Beta.Identity.SignIns](#)

Invoke action evaluate

Syntax

PowerShell

[Copy](#)

```
Test-MgBetaIdentityConditionalAccess
  [-ResponseHeadersVariable <String>]
  [-AdditionalProperties <Hashtable>]
  [-AppliedPoliciesOnly]
  [-ConditionalAccessContext <Hashtable>]
  [-ConditionalAccessWhatIfConditions
<IMicrosoftGraphConditionalAccessWhatIfConditions>]
  [-ConditionalAccessWhatIfSubject <Hashtable>]
  [-Headers <IDictionary>]
  [-ProgressAction <ActionPreference>]
  [-WhatIf]
  [-Confirm]
  [<CommonParameters>]
```




Maester Checks for CA "WhatIf"



```
Describe "Contoso.ConditionalAccess" {  
  It "SharePoint requires MFA" {  
  
    $userId = (Get-MgUser -UserId 'john@contoso.com').Id  
    $SharePointAppId = '67ad5377-2d78-4ac2-a867-6300cda00e85'  
  
    $policiesEnforced = Test-MtConditionalAccessWhatIf -UserId $userId `  
      -IncludeApplications $SharePointAppId  
  
    $policiesEnforced.grantControls.builtInControls | Should -Contain "mfa"  
  }  
}
```



CA Analysis with Security Copilot



Microsoft Entra Conditional Access optimization agent

The [Conditional Access optimization agent](#) ensures all users are protected by policy. It recommends policies and changes based on best practices aligned with [Zero Trust](#) and Microsoft's learnings. In preview, the agent evaluates policies requiring multifactor authentication (MFA), enforces device based controls (device compliance, app protection policies, and Domain Joined Devices), and blocks legacy authentication and device code flow.



Demo: Maester and Copilot for CA



WhatIf-based Gap analysis
in Maester

Checks for Exclusion
Management Groups in
Maester





Device Attestation Reports & Filters



Microsoft Intune admin center

Home > Reports

Reports | Device attestation status (preview)

Columns Export Restart Attest

Learn more about troubleshooting the attestation report here.

All attestation status All ownership

Generate again Cancel Report generated on: 8/13/2023

Not Started 191 Completed 17 Failed 10 Unknown 0

Search by Device Id, Device Name, or User

Showing 1 to 50 of 218 records

Select	Device Id	Device Attestation...	Status Detail
☐	06b6a727-	Failed	TPM is not ready
☐	2593ba72-	Failed	TPM is not ready
☐	ebbaa62e-	Failed	TPM is not ready
☐	92d25037-	Failed	Entra key cannot be attested
☐	0ba3b2d7-	Failed	Client did not provide all required param
☐	2ac46e8c-i	Failed	AIK certificate was not provided by client
☐	5a7c6b32-	Failed	AIK certificate was not provided by client
☐	7418b363-	Failed	AIK certificate was not provided by client
☐	d93f9067-i	Failed	AIK certificate was not provided by client

Microsoft Intune admin center

Home > Devices | Filters >

TPM Attested Devices

Properties Associated assignments

Summary

Basics Edit

Filter name TPM Attested Devices

Description No Description

Platform Windows 10 and later

Rules Edit

Rule syntax

```
(device.isTpmAttested -eq "True")
```



“Strong” Authentication

Mitigation of Post-Authentication

- | | | |
|--|---------------------------------|---|
| - Enforcement of TPM or Secure enclave | → HW-protected private keys | ⊖ PRT Replay |
| - No grace period of Intune compliance | → Verify TPM Health immediately | ⊖ TPM Bypass |
| - Require Passwordless (PIN or Biometrics) | → Device-bounded credentials | ⊖ Password Replay, Phishing |
| - Authentication via WAM | → Token Protection Capability | ⊖ Token Replay |
| - Integrated XDR to Identity Protection | | } ⚠ Incident and Response on
Post-Authentication Attacks |
| - Supported apps and signals to CAE | | |
| | → Anomaly & Endpoint Signals | |
| | → Revoke sessions and tokens | |



Device Attestation Reports & Filters



Microsoft Intune admin center

Home > Reports

Reports | Device attestation status (preview)

Columns Export Restart Attest

Learn more about troubleshooting the attestation report here.

All attestation status All ownership

Generate again Cancel Report generated on: 8/13/2023

Not Started 191 Completed 17 Failed 10 Unknown 0

Search by Device Id, Device Name, or User

Showing 1 to 50 of 218 records

Select	Device Id	Device Attestation...	Status Detail
☐	06b6a727-	Failed	TPM is not ready
☐	2593ba72-	Failed	TPM is not ready
☐	ebbaa62e-	Failed	TPM is not ready
☐	92d25037-	Failed	Entra key cannot be attested
☐	0ba3b2d7-	Failed	Client did not provide all required param
☐	2ac46e8c-i	Failed	AIK certificate was not provided by client
☐	5a7c6b32-	Failed	AIK certificate was not provided by client
☐	7418b363-	Failed	AIK certificate was not provided by client
☐	d93f9067-i	Failed	AIK certificate was not provided by client

Microsoft Intune admin center

Home > Devices | Filters >

TPM Attested Devices

Properties Associated assignments

Summary

Basics Edit

Filter name TPM Attested Devices

Description No Description

Platform Windows 10 and later

Rules Edit

Rule syntax

```
(device.isTpmAttested -eq "True")
```





Demo: Auth Method Insights



CAE-capable and
Device-Bounded Tokens





Privileged Identity and Access Management



5 Golden Rules for Privileged Accounts



Dedicated Privileged Account

Separated from workforce account, and productivity workloads



Phishing-resistant authentication

Cloud-only account with enforced use of device-bounded passkeys



Access from secured endpoint

Restricted logon on dedicated and secured endpoints (device filters)



Protection of privileged objects

Restricted management to avoid impact by lower privileged identities



Strong CA for privileged access

Strong CA policies to restrict sign-in frequency and access to cloud apps

Identify privileged accounts + assignment to security groups and (RM)AUs



How to identify privileges?

```
"EAMTierLevelName": "ControlPlane",
"EAMTierLevelTagValue": "0",
"TierLevelDefinition": [
  {
    "Category": "Microsoft.AzureAD",
    "Service": "Privileged User Management",
    "RoleAssignmentScopeName": [
      "/",
      "/administrativeUnits/<AzureAdmin>",
      "/administrativeUnits/<M365Admin>"
    ],
    "RoleDefinitionActions": [
      "microsoft.directory/users/authenticationMethods/create",
      "microsoft.directory/users/authenticationMethods/delete",
      "microsoft.directory/users/authenticationMethods/basic/update",
      "microsoft.directory/users/create",
      "microsoft.directory/users/disable",
      "microsoft.directory/users/delete",
      "microsoft.directory/users/enable",
      "microsoft.directory/users/basic/update",
      "microsoft.directory/users/manager/update",
      "microsoft.directory/users/userPrincipalName/update",
      "microsoft.directory/users/invalidateAllRefreshTokens",
      "microsoft.directory/users/restore",
      "microsoft.directory/users/password/update"
    ]
  }
]
```



Classification on actions and scopes



Definition of Actions and Scope


```
"EAMTierLevelName": "ControlPlane",
"EAMTierLevelTagValue": "0",
"TierLevelDefinition": [
  {
    "Category": "Microsoft.AzureAD",
    "Service": "Privileged User Management",
    "RoleAssignmentScopeName": [
      "/",
      "/administrativeUnits/<AzureAdmin>",
      "/administrativeUnits/<M365Admin>"
    ],
    "RoleDefinitionActions": [
      "microsoft.directory/users/authenticationMethods/create",
      "microsoft.directory/users/authenticationMethods/delete",
      "microsoft.directory/users/authenticationMethods/basic/update",
      "microsoft.directory/users/create",
      "microsoft.directory/users/disable",
      "microsoft.directory/users/delete",
      "microsoft.directory/users/enable",
      "microsoft.directory/users/basic/update",
      "microsoft.directory/users/manager/update",
      "microsoft.directory/users/userPrincipalName/update",
      "microsoft.directory/users/invalidateAllRefreshTokens",
      "microsoft.directory/users/restore",
      "microsoft.directory/users/password/update"
    ]
  }
]
```

Classified Privileged Access of User

```
"ObjectId": "ControlPlane",
"ObjectType": "0",
"ObjectDisplayName": "0",
"Classification": [
  {
    "AdminTierLevel": "Microsoft.AzureAD",
    "AdminTierLevelName": "User Management",
    "Service": "Privileged User Management",
  },
],
"RoleAssignments": [
  {
    "RoleAssignmentId": "18160c44-b052-45b3-9874-0f289d1d6cb4",
    "RoleAssignmentScopeId": "/administrativeUnits/<AzureAdmin>",
    "RoleAssignmentScopeName": "Tier0-ControlPlane.1.DevOps",
    "RoleAssignmentType": "Direct",
    "PIMAssignmentType": "Eligible",
    "RoleDefinitionName": "Authentication Administrator",
    "RoleDefinitionId": "fe930be7-5e62-47db-91af-98c3a49a38b1",
    "RoleType": "BuiltinRole",
    "Classification": [
      {
        "AdminTierLevel": "0",
        "AdminTierLevelName": "ControlPlane",
        "Service": "Privileged User Management",
        "TaggedBy": "JSONwithAction"
      }
    ]
  }
]
```



Who has direct/indirect privileges?





Identify critical assets


Critical asset management

Manage the criticality level of your organization's assets, either according to predefined classifications

+ Create a new classification

Classification	Status	Assets	Criticality level
Custom (5)			
Enterprise user	On	19	Low
Management Plane user	On	4	High
Control Plane user	On	2	Very high
Control Plane resources	On	0	Very high
PAW Devices	On	4	Very high
Predefined classifications (53)			
Azure AD Connect	On	0	High
Databases with Sensitive Data	On	1	High
Domain Admin Workstations	On	0	High

Attack surface map



Control Plane Assets
(direct or indirect impact)

KQL query via
Advanced Hunting API
in Microsoft Graph



**EntraOps
Privileged EAM**




Demo: Maester & EntraOps



EntraOps Classification Data
and Dashboard

Maester Checks for unused
PIM roles





Application and Workload Identities




5 Golden Rules for App Management



Visibility

App Inventory with details about non-human identity and their privileges




Delegation

Avoid privilege escalation by ownership on App and Service Principal objects



Policies

Restriction of allowed credential types and issuer by defined policies in Microsoft Azure and Entra ID



Lifecycle

Monitor usage of application and workload identities and their assigned permissions and health



Insights

Unusual activity or access by app or delegated permissions to sensitive data or APIs

Strictly monitoring and details on Application and Workload Identities



Demo: Workload Identity Posture



Maester checks for
Recommendation and App
Management Policies

KQL function to correlate data
from XDR hunting table



Active Directory & Entra Connect Sync



- Microsoft Defender for Endpoint (EDR and TVM) on all servers with hybrid identity components
- [Microsoft Defender for Identity \(MDI\) sensor health alerts](#) on AD DS and Connect servers
- [Configuration of Entra Connect sync rules](#) and scopes
- [ACEs and monitoring on Connect service accounts](#)
- Use app identity authentication (with TPM)

Tenant (Security) Configuration



- Use [Maester](#) to analyze security configs on regular basis or [track changes of test result in Sentinel](#)
- [Evaluate changes of critical policies](#) (e.g., Authorization or CA Policy) with results of EIDSCA/Maester checks
- Monitor and resolve findings in Entra ID [Recommendations](#), [XSPM Initiative](#) and [Identity Secure Score](#)
- Use [Health Monitoring](#) and Sign-in Analysis and other Operational Workbooks

Authentication and Conditional Access Policies



- Conditional Access [Insights](#), [Gap](#) and [Health Alerts](#)
- Policy Effectiveness ([WhatIf](#), Sign-in Logs), review with CA Optimization Agent
- [Analyze sign-in with strong authentication methods](#) and [protection of keys by TPM](#) or secure enclave
- Track [Authentication Methods Activity](#) (Register, Usage) and [SSPR Reports](#)
- Health status of [analytics rules](#), [playbooks](#) and data connector in Sentinel

Privileged Identity and Access Management



- Analyse and monitor high-privileged access with [EntraOps](#)
- Include privileged users in CA groups, Role-assignable groups or (R)MAUs
- Identify sensitive groups and their assignment to Access Packages and Catalogs
- [Classify and analyze your privileged assets](#) in Exposure Management
- Monitor PIM Alerts for [Entra ID roles](#) with Maester

Application and Workload Identities



- Identify high privileged workload identities and any potential attack paths in Exposure Management
- Monitor [MDA App Governance Policy Alerts](#) (for example, unused API permissions) and Entra Recommendations
- [Tracking changes](#) on assigned (API) permissions and delegations.
- [Usage & Insights Reports](#) about application, service principal sign-in and credential activity

Internal/External Configuration and Attack Analyses



- Security Awareness Training for Users (Attack Simulation, for example phishing)

- Penetration to validate security posture and ITDR detections (AADInternals, ROADtools,...)

- Attack Path Management (Exposure Management, BloodHound, Forest Druid)





Thank You