



AZ-300T02 Module 02: Implementing and Managing Storage

Ahmad Majeed Zahoory



1

Module 02: Implementing and Managing Storage

Lesson 01: Azure Storage Accounts



2

Azure Storage

Azure Storage serves as:

- **Storage for Azure VMs:**
 - operating system and data disks
 - file storage
- **Store for unstructured data:**
 - Blobs
 - Queues
 - Data Lake Store
- **Store for structured data:**
 - Tables
 - Cosmos DB
 - Azure SQL Database

3

Storage Account Endpoints

- Blob service: <http://mystorageaccount.blob.core.windows.net>
- Table service: <http://mystorageaccount.table.core.windows.net>
- Queue service: <http://mystorageaccount.queue.core.windows.net>
- File service: <http://mystorageaccount.file.core.windows.net>

4

Configuring Custom Domain Names

Direct CNAME mapping:

- **Create a CNAME record that points to the Azure storage account [storage account].blob.core.windows.net.**
- **This method can result in a brief downtime during registration of the custom domain with Azure.**

Intermediary mapping with asverify:

- **Step 1. Prepend asverify to your own CNAME record. This allows Azure to recognize your custom domain.**
- **Step 2. Modify the DNS record for the domain.**
- **This methods eliminates downtime.**

5

Pricing and Billing

Storage costs depend on:

- **The amount of data**
- **Performance level**
- **Access tier (per-gigabyte cost decreases as the tier gets cooler)**

Storage costs include:

- **Data access costs: increase as the tier gets cooler.**
- **Transaction costs: increases as the tier gets cooler. Delete is free.**
- **Geo-Replication data transfer costs (per GB): for GRS and RA-GRS storage accounts and charges for bandwidth used to replicate data to the second Azure region**
- **Outbound data transfer costs (per GB): transferred out of an Azure region**
- **Changing the storage tier:**
 - **Changing the account storage tier from cool to hot (warmer tier) incurs a charge equal to reading all the data existing in the storage account.**
 - **changing the account storage tier from hot to cool (cooler tier) incurs a charge equal to writing all the data into the cool tier (GPv2 accounts only).**
 - **Cool (30 days) and Archive (180 days) also attracts early deletion charges**

6

Storage Account Management

7

Azure Storage Services

- **Azure Blobs:** A massively scalable object store for text and binary data
- **Azure Files:** Managed file shares for cloud or on-premises deployments
- **Azure Tables:** A NoSQL store for schema less storage of structured data
- **Azure Queues:** A messaging store for reliable messaging between application components

**Blobs**

REST-based object storage for unstructured data

[Learn more](#)**Files**

File shares that use the standard SMB 3.0 protocol

[Learn more](#)**Tables**

Tabular data storage

[Learn more](#)**Queues**

Effectively scale apps according to traffic

[Learn more](#)

8

Standard and Premium Storage Accounts



- Standard:
 - Backed by magnetic drives (HDD)
 - Lowest cost per GB
- Premium:
 - Backed by solid state drives (SSD)
 - Can only be used with Azure VM disks

9

Storage Types

- Storage V2 – latest version, lowest price, supports all services, recommended
- Storage V1 – legacy account
- Blob Storage – specialized for storing unstructured object data




✓ You can easily upgrade a general-purpose v1 or Blob storage account to a general-purpose v2 account with no downtime and without the need to copy data

10

Azure Storage Explorer

- Access multiple accounts and subscriptions
- Create, delete, view, edit storage resources
- View and edit Blob, Queue, Table, File, Cosmos DB storage and Data Lake Storage
- Obtain shared access signature (SAS) keys
- Available for Windows, Mac, and Linux



11

Storage Explorer Connection Options

- Connect to an Azure subscription
- Work with local development storage (emulator)
- Attach to external storage
- Attach a storage account or storage service by using a shared access signature
- Connect to an Azure Cosmos DB account by using a connection string



12

Module 02: Implementing and Managing Storage


Lesson 02: Data Replication



13

Replication Options

- Locally-redundant storage (LRS):
 - **The only replication option when using Premium performance tier**
- Zone-redundant storage (ZRS):
- Geo-redundant storage (GRS)
- Read-access geo-redundant storage (RA-GRS)



14

Locally Redundant Storage

Copies:

- **3 in the same Azure facility**

Strategy:

- **Data replicated synchronously across 3 replicas in the same Azure facility**

Protection:

- **Localized hardware failures**

Additional considerations:

- **LRS is an economical option if your data can be easily reconstructed**
- **LRS is the only available option if you use the Premium performance tier**
- **When using LRS, you should plan for an alternative recovery strategy**

15

Geo-Redundant Storage

Copies:

- **Total of 6, with 3 per Azure region.**

Strategy:

- **Data replicated synchronously across 3 replicas in the same Azure facility**
- **Data replicated synchronously within each region and asynchronously across regions.**

Protection:

- **Localized hardware failures and region-wide disasters**

Additional considerations:

- **With GRS, data in the secondary region becomes available for reads and writes (via the primary endpoint) only after Microsoft initiates a failover from the primary region.**
- **With RA-GRS, data in the secondary region is always available for reads (via the secondary endpoint). It becomes available for writes (via the primary endpoint) only after Microsoft initiates a failover from the primary region.**

16

Zone Redundant Storage

Copies:

- **3 across different Azure facilities in separate zones in the same region.**

Strategy:

- **Data replicated synchronously across 3 replicas in separate zones in the same region.**

Protection:

- **Localized hardware failures and failures of individual facilities**

Additional considerations:

- **ZRS is not yet available in all regions.**
- **ZRS may not protect your data against a regional disaster where multiple zones are permanently affected.**
- **ZRS does not support Azure VM disk files**

17

Comparing Replication Strategies

Replication Option	LRS	ZRS	GRS	RA-GRS
Node unavailability within a data center	Yes	Yes	Yes	Yes
An entire data center (zonal or non-zonal) becomes unavailable	No	Yes	Yes	Yes
A region-wide outage	No	No	Yes	Yes
Read access to your data (in a remote, geo-replicated region) for region-wide unavailability	No	No	No	Yes
Available in storage account types	GPv1, GPv2, Blob	Standard, GPv2	GPv1, GPv2, Blob	GPv1, GPv2, Blob

18

Storage Account PowerShell Tasks

Task	Example
Check to see if a storage account name is available.	Get-AzureRmStorageAccountNameAvailability -Name 'mystorageaccount'
Create a storage account.	New-AzureRmStorageAccount -ResourceGroupName MyResourceGroup -AccountName mystorageaccount -Location westus -SkuName Standard_GRS
Retrieve a specific storage account or all the storage accounts in a resource group or subscription.	Get-AzureRmStorageAccount -ResourceGroupName "RG01" -AccountName "mystorageaccount"
Modify storage account properties, such as type.	Set-AzureRmStorageAccount -ResourceGroupName "MyResourceGroup" -AccountName "mystorageaccount" -Type "Standard_RAGRS"

19

Module 02: Implementing and Managing Storage

Lesson 03: Storing and Accessing Data



20

Import and Export Service

Transfers very large amounts of data between on-premises and Azure:

- **Import.** Securely transfers data to Azure Blob storage (block and page blobs) and Azure Files. You ship hard drives containing your data to an Azure data center.
- **Export.** Securely transfers data from Azure Blob storage (block, page, and append blobs) to your location. You ship empty hard drives to an Azure data center.

Scenarios:

- **Migrating data to the cloud**
- **Content distribution**
- **Backup and data recovery**

21

Import Jobs

Identify:


- data to be imported
- the number of drives
- destination blob or file

Run WAImportExport Tool:

- To copy data to hard disk drives
- To encrypt data with BitLocker

Create an import job:


- Via Azure portal (upload drive journal)
- Via Import/Export REST API
- **Provide shipping info**
- **Ship the hard disk drives**
- **Update tracking number**
- **Microsoft handles:**
 - Job processing
 - Shipment of drives back to you



22

Export Jobs

- **Identify:**
 - data to be exported
 - the number of drives
 - the source blobs
- **Create an export job:**
 - via the Azure portal
 - via Import/Export REST API
- **Provide shipping info**
- **Ship empty hard drives**
- **Update delivery tracking info**
- **Microsoft handles:**
 - job processing
 - shipment of drives back to you



23

AzCopy

a command-line utility for automating Azure Storage tasks:

- **Copy to/from Microsoft Azure Blob, File, and Table storage**
- **Copy between a file system and a storage account, or between storage accounts**

```

C:\Program Files (x86)\Microsoft SDKs\Azure\AzCopy>azcopy /? | more
AzCopy 5.0.0 Copyright (c) 2015 Microsoft Corp. All Rights Reserved.

AzCopy </Source> </Dest> [/SourceKey:] [/DestKey:] [/SourceSAS:] [/DestSAS:]
[/Pattern:] [/CheckMD5] [/L] [/MT] [/XO] [/XA] [/IA] [/XA]
[/SyncCopy] [/SetContentType] [/BlobType:] [/Delimiter:] [/Snapshot]
[/PKRS:] [/SplitSize:] [/EntityOperation:] [/Manifest:]
[/PayloadFormat:]
  
```

```

#1 - Download a blob from Blob storage to the file system, for example,
download 'https://myaccount.blob.core.windows.net/mycontainer/abc.txt'
to 'D:\test\'.
AzCopy /Source:https://myaccount.blob.core.windows.net/mycontainer/
/Dest:D:\test\ /SourceKey:key /Pattern:"abc.txt"

#2 - Copy a blob within a storage account
AzCopy /Source:https://myaccount.blob.core.windows.net/mycontainer1/
/Dest:https://myaccount.blob.core.windows.net/mycontainer2/
/SourceKey:key /Pattern:"abc.txt"


#3 - Upload files and subfolders in a directory to a container, recursively
AzCopy /Source:D:\test\
/Dest:https://myaccount.blob.core.windows.net/mycontainer/
/DestKey:key /S
  
```

24

How CDN Works

Azure content caching service:

- **Designed to expedite delivery of audio, video, images, etc. hosted by Azure services**
- **Utilizes the following data flow:**
 - 1. Alice requests a file using a URL pointing to a CDN location. DNS routes the request to the optimal POP
 - 2. If edge servers do not have the file cached, they request it from the origin.
 - 3. The origin returns the file, including its TTL.
 - 4. The server caches the file and returns it to Alice.
- **The file remains cached until the TTL expires.**
- 5. Subsequent requests are served from the cache.



25

CDN Profile

A collection of CDN endpoints with the same:

- **Pricing tier and provider:**
 - Premium Verizon
 - Standard Verizon
 - Standard Akamai

Pricing based on:

- **GBs of outbound data transfers**
- **Zone:**
 - Zone 1—North America, Europe, Middle East and Africa
 - Zone 2—Asia Pacific (including Japan)
 - Zone 3—South America
 - Zone 4—Australia
 - Zone 5—India

CDN profile

Name

CDNforStorage

Subscription

Visual Studio Enterprise

Resource group

☐ Create new
 ☒ Use existing

ASH

Resource group location

West Central US

Pricing tier (View full pricing details)

All Available Pricing

Premium Verizon

Standard Verizon

Standard Akamai

☐ Create a new CDN endpoint now

26

CDN Endpoints

Represent configuration of content origin:

- **CDN endpoint name**
- **Origin type:**
 - Storage
 - Cloud Service
 - Web App
 - Custom origin
- **Origin hostname**
- **CDN features that affect content delivery, such as:**
 - Compression
 - Query string
 - Geo filtering
 - Custom domains

CDN profile

☒ Create a new CDN endpoint now

* CDN endpoint name
ASHStorage ✓
azureedge.net

* Origin type
Storage
Storage
Cloud service
Web App
Custom origin

* Origin hostname ⓘ
ashdiag .core.windows.net
ashstorage .blob.core.windows.net

27

CDN Time-to-Live

CDN TTL can be:

- **Included in cache-directive headers in the HTTP response from the content origin**
- **Determined by Cache Expiration Duration, configurable by using:**
 - Global caching rules: affect all requests to the endpoint
 - Custom caching rules: match paths and file extensions
- **Custom caching rules override global ones**

Global caching rules

These rules affect the CDN caching behavior for all requests, and can be overridden using Custom Cache Rules below for certain scenarios. Note that the Query string caching behavior setting does not affect files that are not cached by the CDN.

Caching behavior ⓘ Set if missing

Cache expiration duration ⓘ Days: 10 Hours: 0 Minutes: 0 Seconds: 0

Query string caching behavior ⓘ Ignore query strings

Custom caching rules

Create caching rules based on specific match conditions. These rules override the default settings above, and are evaluated from top to bottom. This means that rules lower on the list can override rules above it in the list, as well as the global caching rules and default behavior. Therefore it makes more sense to have more specific rules towards the bottom of the list so they are not overwritten by a general rule under them. For example a rule for path '/folder/images/' should be below a rule for path '/folder/'.

↑ Move up ↓ Move down ↕ Move to top ↕ Move to bottom ➡ Insert ✖ Delete

MATCH CONDITION	MATCH VALUES	CACHING BEHAVIOR	DAYS	HOURS	MINUTES	SECONDS
Path	/images/*.jpg	Override	30	0	0	0
			0	0	0	0

28

CDN Compression

Improves file transfer speed and increases page-load performance:

Supports:

- **Enabling compression on the origin.** In this case, the CDN passes along the compressed files and delivers them to clients that request them.
- **Enabling compression directly on the CDN edge servers.** In this case, the CDN compresses the files and serves them to end users.
- **Enabling compression based on the MIME types list, allowing selection of the content formats to compress.**



29

Module 02: Implementing and Managing Storage

Lesson 04: Monitoring Storage




30

Monitor Metrics

Azure Monitor provides unified interface for monitoring Azure services

- Includes Azure Storage monitoring
- Offers access via the Azure portal and Monitor API (REST and .NET)
- Integrates with Log Analytics and Event Hubs
- Stores metrics for 30 days and allows long term retention in Azure Storage
- Supports consistent metrics filtering (resource, subservice) and aggregation criteria.






31

Capacity and Transaction Metrics

Available from the Azure portal:

- Select a Storage Account resource
- Select a sub-service: Account, Blob, File, Queue, or Table
- The sub-service selection determines Capacity metrics:
 - For example, for Blob sub-service, Capacity metrics include:
 - Blob Capacity
 - Blob Container Count
 - Blob Count
- Transaction metrics are available at:
 - account level
 - service level:
 - Blob storage
 - Table storage
 - Queue storage
 - Azure Files




32

Collect Across Subscriptions

You can collect Azure Activity Logs into a Log Analytics workspace using the Azure Log Analytics Data Collector connector for Logic Apps

- **This facilitates using a workspace in a subscription that has a different Azure AD tenant**
- **It offers a number of advantages, including:**
 - Low latency, since the Azure Activity Log is streamed into the Event Hub
 - Serverless services, with no infrastructure components to deploy
 - Minimal custom code



33


LAB [300TO01-M02-01]

1. Publish Static Website in Azure with Web Caching in High Availability.




34

Part A



35

Part B



36

LAB [300TO01-M02-01]

1. Publish Static Website in Azure with Web Caching in High Availability.

a. **Services, Tools & Code used**

- i. Azure Storage
- ii. Azure Blob
- iii. Azure Storage Explorer
- iv. HTML Code
- v. Azure CDN
- vi. AzCopy

Duration: 45 mnts.



37



38