

04-if语句、Python字典、用户输入和while循环

大纲

- if语句
- 字典
- 用户输入--input函数
- while循环
- 习题

if语句

```
In [2]: cars = ['audi', 'bmw', 'subaru', 'toyota']
for car in cars:
    if car == 'bmw':
        print(car.upper())
    else:
        print(car.title())
```

Audi
BMW
Subaru
Toyota

条件测试

if语句的核心是一个值为 True 或 False 的表达式

- == 和 is 操作符的区别
- 检测是否不相等
- 大于、小于
- 使用and检查多个条件
- 使用or检查多个条件
- 检查是否在列表中: in 操作符
- 检查某个数是不是为0, 不为0表示True, 0表示False

```
In [3]: car = 'bmw'
car == 'bmw'
```

Out[3]: True

== 操作符比较两个变量的值是否相等

```
In [5]: print(cars == cars[:])
print([1, 2, 3] == list(range(1, 4)))
print((1, 2, 3) == tuple(range(1, 4)))
print(1 == 1.0)
print(1+0j == 1)
print(1 == True)      # True == 1
print(0 == False)     # False == 0
```

```
True
True
True
True
True
True
True
```

is 操作符比较两个变量的id是否相同

```
In [ ]: print(cars is cars[:])
        print([1, 2, 3] is list(range(1, 4)))
        print((1, 2, 3) is tuple(range(1, 4)))
        print(1 is 1.0)
        print(1+0j is 1)
        print(1 is True)      # True == 1
        print(0 is False)     # False == 0
```

如果两个变量使用 `id()` 函数返回相同的结果，对他们使用 `is` 会返回 `True`（充分必要条件）

```
In [10]: cars = ['audi', 'bmw', 'subaru', 'toyota']
        print(cars == cars[:])
        print(cars is cars[:])

        my_cars = cars
        print(my_cars == cars)
        print(my_cars is cars)
```

```
True
False
True
True
```

```
In [8]: x = 1
        y = 1.0
        print(x == y)
        print(x is y)
```

```
True
False
```

检测是否不相等: `!=`

```
In [22]: requested_toppings = 'mushrooms'
        if requested_toppings != 'anchovies':
            print("Hold the anchovies!")
```

Hold the anchovies!

检测不是同一个对象: `is not`

```
In [25]: cars2 = cars[:]
        print(cars2 is not cars)
```

```
True
```

数值比较大小: `>`, `>=`, `<`, `<=`

```
In [26]: age = 18
        print(age > 18)
        print(age >= 18)
        print(age < 18)
        print(age <= 18)
```

```
print(age < 10)
```

False

True

False

True

使用 and 和 or 检查多个条件

In [28]:

```
age_0 = 22
age_1 = 18
print(age_0 >= 21 and age_1 >= 21)
print(age_0 >= 21 or age_1 >= 21)
```

False

True

- 使用 in 操作符检查特定值是否包含在列表、元组或者字符串中
- not in 检查特定值是否不包含在列表、元组或者字符串中
- 所有可迭代 (iterative) 的对象

In [34]:

```
requested_toppings = ['mushrooms', 'onions', 'pineapple']
print('mushrooms' in requested_toppings)
print('onions' not in requested_toppings)
```

True

False

简化多个条件

In [31]:

```
name = 'Jack'
pwd = '1234'
print((name, pwd) == ('Jack', '1234'))
```

True

In [33]:

```
x = 1
print(x == 0 or x == 1)
print(x in (0, 1))
```

True

True

if-else 语句

In [37]:

```
age = 17
if age >= 18:
    print("You are old enough to vote!")
    print("Have you registered to vote yet?")
else:
    print("Sorry, you are too young to vote.")
    print("Please register to vote as soon as you turn 18!")
```

Sorry, you are too young to vote.

Please register to vote as soon as you turn 18!

if...else 表达式

In [69]:

```
a, b = 10, 20
c = a if a else b
print(c)
```

if-elif-else 语句

In [38]:

```
age = 12
if age < 4:
    print("Your admission cost is $0.")
elif age < 18:
    print("Your admission cost is $5.")
else:
    print("Your admission cost is $10.")
```

Your admission cost is \$5.

:= 海象 (Walrus) 运算符(Python 3.8+)

- 先对运算符左边赋值
- 然后返回运算符左边的值

In [8]:

```
# 不使用海象运算符
x = 60
y = 50

diff = x-y
if diff > 0:
    print("Diff is positive.")
```

Diff is positive.

In [9]:

```
# 使用海象运算符
x = 60
y = 50

if (diff:= x-y) > 0:
    print("Diff is positive.")
```

Diff is positive.

判断列表是否为空

In [54]:

```
requested_toppings = []

if requested_toppings:
    for topping in requested_toppings:
        print(f"Adding {topping}.")
    print("\nFinished making your pizza!")
else:
    print("Are you sure you want a plain pizza?")
```

Finished making your pizza!

判断字符串是否为空

In [59]:

```
msg = ''

if msg:
    print("msg is not empty")
else:
    print("msg is empty")
```

msg is empty

判断数值是否为0

```
In [60]: x = 0.000

if x:
    print("x is not zero")
else:
    print("x is zero")
```

x is zero

```
In [65]: a = 0 + 0.00j
print(a == 0)
if a:
    print("a is not zero")
else:
    print("a is zero")
```

True

a is zero

字典

```
In [1]: alien_0 = {'color': 'green', 'points': 5}
print(alien_0['color'])
print(alien_0['points'])
```

green

5

添加键值对

```
In [2]: alien_0['x_position'] = 0
alien_0['y_position'] = 25
print(alien_0)
```

{'color': 'green', 'points': 5, 'x_position': 0, 'y_position': 25}

创建空字典

```
In [4]: alien_0 = {}
print(alien_0)
alien_0['color'] = 'green'
alien_0['points'] = 5
print(alien_0)
```

{}

{'color': 'green', 'points': 5}

修改字典中的值

```
In [5]: alien_0['color'] = 'yellow'
print(f"The alien is now {alien_0['color']}.")
```

The alien is now yellow.

删除键值对

```
In [6]: del alien_0['points']
print(alien_0)
```

{'color': 'yellow'}

由类似对象组成的字典

由类似对象组成的字典

```
In [7]: favorite_languages = {
        'jen': 'python',
        'sarah': 'c',
        'edward': 'ruby',
        'phil': 'python',
    }

    language = favorite_languages['sarah'].title()
    print(f"Sarah's favorite language is {language}.")
```

Sarah's favorite language is C.

使用get()方法来返回默认值

```
In [8]: alien_0 = {'color': 'green', 'speed': 'slow'}
        print(alien_0['points'])
```

```
-----
KeyError                                Traceback (most recent call last)
d:\workspaces\python_course\src\04-dictionaries-user-input-and-while-loops\04-
dictionaries-user-input-and-while-loops.ipynb Cell 49 in <cell line: 2>()
      1 <a href='vscode-notebook-cell:/d%3A/workspaces/python_course/src/04-dictionaries-u
      2 ser-input-and-while-loops/04-dictionaries-user-input-and-while-loops.ipynb#Y102sZmlsZQ%3
      3 D%3D?line=0'>1</a> alien_0 = {'color': 'green', 'speed': 'slow'}
----> <a href='vscode-notebook-cell:/d%3A/workspaces/python_course/src/04-di
      4 cictionaries-user-input-and-while-loops/04-dictionaries-user-input-and-while-loo
      5 ps.ipynb#Y102sZmlsZQ%3D%3D?line=1'>2</a> print(alien_0['points'])

KeyError: 'points'
```

```
In [10]: print(alien_0.get('points', 'No point value assigned.'))
```

No point value assigned.

遍历字典键值对

```
In [11]: user_0 = {
        'username': 'efermi',
        'first': 'enrico',
        'last': 'fermi',
    }

    for key, value in user_0.items():
        print(f'\nKey: {key}')
        print(f'Value: {value}')
```

Key:username
Value:efermi

Key:first
Value:enrico

Key:last
Value:fermi

```
In [12]: for name, language in favorite_languages.items():
        print(f"{name.title()}'s favorite language is {language.title()}.")
```

Jen's favorite language is Python.
Sarah's favorite language is C.
Edward's favorite language is Ruby.
Phil's favorite language is Python.

遍历字典的键

```
In [13]: for name in favorite_languages.keys():
          print(name.title())
```

Jen
Sarah
Edward
Phil

```
In [14]: print(sorted(favorite_languages.keys()))
```

['edward', 'jen', 'phil', 'sarah']

遍历字典中的值

```
In [15]: for language in favorite_languages.values():
          print(language.title())
```

Python
C
Ruby
Python

使用set()函数剔除重复项

```
In [16]: print(set(favorite_languages.values()))
```

{'ruby', 'c', 'python'}

set集合数据结构

- 不包含重复的元素
- 和dict同样使用 { } 来定义, 但不是键值对
- 空的集合用 set() 表示, {} 表示的是空的字典

嵌套的数据结构：字典列表

```
In [17]: alien_0 = {'color': 'green', 'points': 5}
          alien_1 = {'color': 'yellow', 'points': 10}
          alien_2 = {'color': 'red', 'points': 15}

          aliens = [alien_0, alien_1, alien_2]
          aliens
```

```
Out[17]: [{'color': 'green', 'points': 5},
          {'color': 'yellow', 'points': 10},
          {'color': 'red', 'points': 15}]
```

在字典中存储列表

```
In [1]: pizza = {
          'crust': 'thick',
          'toppings': ['mushrooms', 'extra cheese'],
          }

          print(pizza)
```

{'crust': 'thick', 'toppings': ['mushrooms', 'extra cheese']}

In [2]:

```

favorite_languages = {
    'jen': ['python', 'ruby'],
    'sarah': ['c'],
    'edward': ['ruby', 'go'],
    'phil': ['python', 'haskell'],
}

print(favorite_languages)

```

```

{'jen': ['python', 'ruby'], 'sarah': ['c'], 'edward': ['ruby', 'go'], 'phil': ['python', 'haskell']}

```

在字典中存储列表

```

In [3]: users = {
    'aeinstein': {
        'first': 'albert',
        'last': 'einstein',
        'location': 'princeton',
    },
    'mcurie': {
        'first': 'marie',
        'last': 'curie',
        'location': 'paris',
    },
}

print(users)

```

```

{'aeinstein': {'first': 'albert', 'last': 'einstein', 'location': 'princeton'}, 'mcurie': {'first': 'marie', 'last': 'curie', 'location': 'paris'}}

```

用户输入

- 使用input函数，用户可以在控制台进行输入。
- input()接受一个参数，要向用户显示的提示（prompt）或说明。
- input接受用户的输入后，将返回包含用户输入内容的字符串
- 用户输入的数字也是 str 类型，进行数值相关操作时必须转换成对应的数值类型，例如使用 int() 函数或 float() 函数

```

In [4]: message = input("Tell me something, and I will repeat it back to you: ")

```

```

In [5]: print(message)

```

Hello

```

In [6]: age = input("How old are you?")

```

```

In [7]: age >= 18

```

```

-----
TypeError                                Traceback (most recent call last)
d:\workspaces\python_course\src\04-dictionaries-user-input-and-while-loops\04-dictionaries-user-input-and-while-loops.ipynb Cell 74 in <cell line: 1>()
----> <a href='vscode-notebook-cell:/d%3A/workspaces/python_course/src/04-dictionaries-user-input-and-while-loops/04-dictionaries-user-input-and-while-loops.ipynb#Y140sZmlsZQ%3D%3D?line=0'>1</a> age >= 18

```

```

TypeError: '>=' not supported between instances of 'str' and 'int'

```



```
In [8]: int(age) >= 18
```

```
Out[8]: True
```

while循环

```
In [9]: unconfirmed_users = ['alice', 'brian', 'candace']
confirmed_users = []

while unconfirmed_users:
    current_user = unconfirmed_users.pop()
    print(f"Verifying user: {current_user.title()}")
    confirmed_users.append(current_user)

print("\nThe following users have been confirmed:")
for confirmed_user in confirmed_users:
    print(confirmed_user.title())
```

```
Verifying user: Candace
Verifying user: Brian
Verifying user: Alice
```

```
The following users have been confirmed:
Candace
Brian
Alice
```

习题

习题： 括号匹配

写一个函数，接收一串括号，并确定括号的顺序是否有效。如果字符串是有效的，它应该返回True，如果是无效的，它应该返回False。

例如：

```
"(){}[]" => True
"([{}])" => True
"{}" => False
"[]" => False
"[({})][]" => False
```

```
In [ ]: s1 = "()"
s2 = "{}"
s3 = "({}){}[]" # False
```

```
In [ ]: def match_brackets(s):
    stack = []
    brackets = {'(': ')', '[': ']', '{': '}' }
    for c in s:
        if c in brackets:
            stack.append(c)
        elif c in brackets.values():
            if not stack or brackets[stack.pop()] != c:
```