

入門指南

安裝

在 NuGet 安裝對應的資料庫 Client，例如：

```
dotnet add package Microsoft.Data.SqlClient
```

基本設定

在應用程式啟動時呼叫 `FacadeConfiguration.SetConfiguration`，至少需設定 `DbProviderFactory` 和連線字串。

```
using CloudyWing.DatabaseFacade;  
using Microsoft.Data.SqlClient;
```

```
FacadeConfiguration.SetConfiguration(SqlClientFactory.Instance, "your-connection-string");
```

基本查詢

```
using CloudyWing.DatabaseFacade;  
  
using CommandExecutor executor = new CommandExecutor();  
executor.CommandText = "SELECT * FROM Customers WHERE Id IN @Id";  
executor.Parameters.Add("Id", new int[] { 1, 2, 3 });  
DataTable dt = executor.CreateDataTable();
```

基本非同步查詢

```
using CloudyWing.DatabaseFacade;  
  
using CommandExecutor executor = new CommandExecutor();  
executor.CommandText = "SELECT * FROM Customers WHERE Id IN @Id";  
executor.Parameters.Add("Id", new int[] { 1, 2, 3 });  
DataTable dt = await executor.CreateDataTableAsync(cancellationToken);
```

If you need to process data sequentially, use `CreateDataReaderAsync` with `DbDataReader.ReadAsync`. See [Async Operations](#) for more examples.

執行非查詢指令

```
using CommandExecutor executor = new CommandExecutor();
executor.SetCommandText("INSERT INTO Customers (Id, Name) VALUES (@Id, @Name)")
    .Parameters.Add("Id", 1)
    .Add("Name", "小明")
    .GetCommandExecutor()
    .Execute();
```

Namespace CloudyWing.DatabaseFacade

Classes

[CommandExecutor](#)

Provides a fluent facade for executing ADO.NET commands with shared configuration and parameter handling.

[FacadeConfiguration](#)

Provides global defaults used when creating [CommandExecutor](#) instances.

[KeepConnectionRequiredException](#)

The exception that is thrown when an operation requires [KeepConnection](#) to be enabled.

[ParameterCollection](#)

Represents the parameters queued for the next [CommandExecutor](#) operation.

[ParameterMetadata](#)

Describes the values used to create and configure a provider-specific database parameter.

Enums

[ResetItems](#)

Specifies which parts of a [CommandExecutor](#) should be reset after an operation completes.