Welcome to CS61A!

Last modified: Wed Jan 18 13:30:53 2017

This week

- Yes, we don't all fit in Pauley Ballroom! Anyone who does not insist on seeing my face can use the screencasts and the posted lecture slides, and not actually come to lecture.
- Please see the course web site (http://cs61a.org), esp. the announcements and Course Info link. (Bear with us: the web site is under construction).
- If you did not complete the lab this week, you should try to to get it done offline (see http://cs61a.org/lab/lab00).
- Next week, labs (between Monday and Wednesday lecture) and discussions meet according to the published schedule.
- Try to find a lab and discussion section with the same TA, if possible. If enrolled, don't worry about changing things on CalCentral. If waitlisted, choose some discussion/lab if possible. Will try to resolve conflicts next week.

What's This Course About?

- This is a course about *programming*, which is the art and science of constructing artifacts ("programs") that perform computations or interact with the physical world.
- To do this, we have to learn a *programming language* (Python in our case), but programming means a great deal more, including
 - Design of what programs do.
 - Analysis of the performance of programs.
 - Confirmation of their correct operation.
 - Management of their complexity.
- This course is about the "big ideas" of programming. We expect most of what you learn to apply to any programming language.

Course Organization

- Readings cover the material. Try to do them before...
- Lectures summarize material, or present alternative "takes" on it.
- Laboratory exercises are "finger exercises" designed to introduce a new topic or certain practical skills. Unlimited collaboration.
- Homework assignments are more involved than lab exercises and often require some thought. Plan is to have them due on Monday. Feel free to discuss the homework with other students, but turn in your own solutions.
- Projects are four larger multi-week assignments intended to teach you how to combine ideas from the course in interesting ways. We'll be doing at least some of these in pairs.
- Use the discussion board (Piazza) for news, advice, etc.

Mandatory Warning

- We allow unlimited collaboration on labs.
- On homework, feel free to collaborate, but try to keep your work distinct from everyone else's.
- Likewise on projects, except that you and your partner submit a joint project.
- You can take small pieces of code within reason (ask if unsure), but you must attribute it!
- Otherwise, copying is against the Code of Conduct, and generally results in penalties.
- Most out-and-out copying is due to desparation and time pressure.
 Instead, see us if you're having trouble; that's what we're here for!

What's In A Programming Language?

- Values: the things programs fiddle with;
- Primitive operations (on values);
- Combining mechanisms, which glue operations together;
- Some predefined names (the "library");
- Definitional mechanisms, which allow one to introduce symbolic names and (in effect) to extend the library.

Python Values (I)

Python has a rich set of values, including:

Type	Values	Literals (Denotations)
Integers	$0 - 1 \ 16 \ 13$	0 -1 0o20 0b1101
	36893488147419103232	0x2000000000000000
Boolean (truth) values	true, false	True False
"Null"		None
Functions		operator.add, operator.mul,
		operator.lt, operator.eq

- Functions take values and return values (including functions). Thus, the definition of "value" is recursive: definition of function refers to functions.
- They don't look like much, perhaps, but with these values we can represent anything!

Python Values (II)

• ... but not conveniently. So now we add more complex types, including:

Type	Values	Literals (Denotations)
Strings	pear,	"pear"
	I ♥ NY	"I \u2661 NY"
	Say "Hello"	"Say \"Hello\""
Tuples		(), (1, "Hello", (3, 5))
Ranges	0-10, 1-5	range(10), range(1, 5)
Lists		[], [1, "Hello", (3, 5)]
		[x**3 for x in range(5)]
Dictionaries		{ "Paul" : 60, "Ann" : 59,
		"John" : 56 }
Sets	$\{\}, \{1, 2\},$	set([]), { 1, 2 },
	$ \{x \mid 0 \le x < 20$	{ x for x in range(20) if prime(x) }
	$\wedge x$ is prime	

What Values Can Represent

- The tuple type (as well as the list, dictionary, set class types) give
 Python the power to represent just about anything.
- In fact, we could get away with allowing just pairs: tuples with two elements:
 - Tuples can contain tuples (and lists can contain lists), which allows us to get as fancy as we want.
 - Instead of (1, 2, 7), could use (1, (2, (7, None))),
 - But while elegant, this would make programming tedious.

Python's Primitive Operations

- Literals are the base cases.
- Functions in particular are the starting point for creating programs: sub(truediv(mul(add(add(3, 7), 10), sub(1000, 8)), 992), 17)
- To evaluate a function call:
 - Evaluate the caller (left of the parentheses).
 - Evaluate the arguments (within the parentheses).
 - The caller then tells what to do and what value to produce from the operand's values
- For the convenience of the reader, though, Python employs a great deal of "syntactic sugar" to produce familiar notation:

$$(3 + 7 + 10) * (1000 - 8) / 992 - 17$$

Evaluating a Function Call

Consider

```
(3 + 7 + 10) * (1000 - 8) / 992 - 17

which "sugars"

sub(truediv(mul(add(add(3, 7), 10), sub(1000, 8)), 992), 17)
```

- The numerals all evaluate in the obvious way.
- Then proceed from the inside out:

3

Combining and Defining

Certain primitives are needed to allow conditional execution:

```
print(1 if x > 0 else -1 if x < 0 else 0)
# or equivalently
if x > 0:
    print(1)
elif x < 0:
    print(-1)
else:
    print(0)</pre>
```

Defining a new function:

```
def signum(x):
    return 1 if x > 0 else -1 if x < 0 else 0</pre>
```

Now signum denotes a function.

• Doesn't look like we have a lot, but in fact we already have enough to implement all the computable functions on the integers!

Getting repetition

- ullet Haven't explicitly mentioned any construct to "repeat X until ..." or "repeat X N times." Technically, none is needed.
- Suppose you'd like to compute $x + 2x^2 + 3x^3 + ... + Nx^N$ for any N:

```
def series(x, N):
    if N == 1:
        return x
    else:
        return N * x**N + series(x, N-1)
```

 But again, we have syntactic sugar (which is the usual approach in Python):

```
def series(x, N):
    S = 0
    for k in range(1, N+1):
        S += k * x**k
    return S
```

A Few General Rules

- Whatever the assignment, start now.
- "Yes, that's really all there is. Don't fight the problem."
- Practice is important. Don't just assume you can do it; do it!
- ALWAYS feel free to ask us for help.
- DBC
- RTFM
- Have fun!