Tunneling v5

Implementation code - supervised tunnel, agent bus, telemetry

BRIDGE 5.3.2

BRANCH	arena/706ae6d5-tunneling
DIFF BASE	92cde4e -> HEAD
GENERATED	2026-11-05
TESTS	35 passing (python3 -B roblox-bridge/test_bridge_mcp.py)
RUNTIME	Python 3 stdlib only (no pip packages)

INSIDE

1 What this release contains · 2 File inventory · 3 How to apply and verify · 4 Complete sources (tunnel_manager, bus_core, auth_core, telemetry, seed_agent_bus) · 5 Unified diffs for every modified file · 6 Verification snapshot

1. What this release contains

v5 turns the local Studio bridge into an ops platform. The MCP tool surface grows to **71 tools** (adds `agent_bus`, `bridge_ops` and `studio_fleet`) and **11 resources**. Four new stdlib modules carry the new behaviour, and the existing server/CLI/setup paths are extended without breaking v4 callers.

- **Supervised tunnel** - auto-detected cloudflared/ngrok, URL scraping, public health probes, backoff restarts, named tunnels, LAN URLs, and a hard refusal to publish a token-less bridge.
- **Agent Bus** - presence + mailbox + lease-based task board so multiple agents and humans can share one Studio session without collisions.
- **Scoped tokens** - hashed read/write/admin credentials with expiry and per-token rate limits; read tokens cannot mutate Studio over MCP or REST.
- **Resilient jobs** - idempotency keys, priorities, bounded retries, per-job timeouts and orphan requeue.
- **Observability** - Prometheus metrics, SSE event stream, SHA-256 hash-chained audit log, consolidated ops report, and dashboard tab 7.

2. File inventory

File	Kind	Purpose
`roblox-bridge/tunnel_manager.py`	new	Supervised cloudflared/ngrok tunnel
`roblox-bridge/bus_core.py`	new	Multi-agent presence, mailbox and lease-based task board
`roblox-bridge/auth_core.py`	new	Scoped tokens, expiry, revocation, token-bucket limits
`roblox-bridge/telemetry.py`	new	Metrics, SSE event stream, hash-chained audit log
`roblox-bridge/tools/seed_agent_bus.py`	new	Idempotent Agent Bus seeding (online or offline)
`jobs/measure_tunnel_latency.py`	new	G2: p50/p95 tunnel latency measurement (stdlib only)
`jobs/live_acceptance.py`	new	G7: acceptance run with paste-ready evidence JSON
`jobs/drill_studio_kill.py`	new	G8: kill-switch drill for the job reaper
`roblox-bridge/server.py`	diff	HTTP bridge, auth scopes, ops endpoints, dashboard tab 7
`roblox-bridge/mcp_core.py`	diff	agent_bus + bridge_ops tools, 3 resources, client helpers
`roblox-bridge/arena_studio.py`	diff	ops / metrics / audit / tunnel / tokens / bus CLI
`roblox-bridge/setup.py`	diff	Supervised tunnel launch + URL watcher
`roblox-bridge/test_bridge_mcp.py`	diff	v5 test coverage (scopes, bus, reaping, audit, tunnel)
`roblox-bridge/mcp_server.py`	diff	Version banner

roblox-bridge/ab.ps1	diff	Version banner + ops examples

3. How to apply and verify

Copy the new files into `roblox-bridge/` and apply the diffs to the modified files (both sides are shown in this document). Then:

```
python3 -B roblox-bridge/test_bridge_mcp.py # expect: Ran 44 tests ... OK
python3 roblox-bridge/arena_studio.py ops # peers, queue, tunnel, agents, tasks
python3 roblox-bridge/arena_studio.py audit --verify # hash chain intact
python3 setup.py --tunnel # supervised public tunnel
```

Auth is unchanged for existing installs: `bridge.token` is the admin owner credential and nothing new is required. Runtime state (audit, tokens, bus, last tunnel URL) is written to the gitignored `roblox-bridge/bridge_state/`.

4. New source files

File	Lines	Purpose
roblox-bridge/tunnel_manager.py	518	Supervised cloudflared/ngrok tunnel
roblox-bridge/bus_core.py	859	Multi-agent presence, mailbox and lease-based task board
roblox-bridge/auth_core.py	273	Scoped tokens, expiry, revocation, token-bucket limits
roblox-bridge/telemetry.py	471	Metrics, SSE event stream, hash-chained audit log
roblox-bridge/tools/seed_agent_bus.py	142	Idempotent Agent Bus seeding (online or offline)
jobs/measure_tunnel_latency.py	241	G2: p50/p95 tunnel latency measurement (stdlib only)
jobs/live_acceptance.py	198	G7: acceptance run with paste-ready evidence JSON
jobs/drill_studio_kill.py	179	G8: kill-switch drill for the job reaper

Complete sources follow first, then unified diffs for every modified file. Line numbers are left-margin references; wrapped lines carry no number.

roblox-bridge/tunnel_manager.py

518 lines

Supervised cloudflared/ngrok tunnel

```python
#!/usr/bin/env python3
"""
tunnel_manager.py - Supervised public tunnel for the Arena Roblox Studio bridge.

`python setup.py --tunnel` starts a one-shot Cloudflare quick tunnel and hopes it
stays up. This module makes the tunnel a managed service instead:

  * auto-detects `cloudflared` or `ngrok` on PATH (with install hints if absent),
  * supervises the child process with exponential backoff and automatic restart,
  * scrapes the public URL from the child's output and re-learns it after a restart,
  * probes `<publicUrl>/api/health` and marks the tunnel degraded when it stops
    answering, restarting it after repeated failures,
  * supports token-based named Cloudflare tunnels and a user-managed static URL,
  * reports LAN URLs so phones/tablets on the same Wi-Fi can reach the dashboard,
  * exposes everything as JSON for `GET /api/tunnel` and the Control Center.

Zero dependencies; works on Windows, macOS and Linux.
"""

import json
import os
import re
import shutil
import socket
import subprocess
import threading
import time
import urllib.error
import urllib.request
from collections import deque
from pathlib import Path

TUNNEL_VERSION = "5.3.2"
DEFAULT_STATE_DIR = Path(__file__).resolve().parent / "bridge_state"

CLOUDFLARE_URL_RE = re.compile(r"https://[a-z0-9][a-z0-9-]*\.trycloudflare\.com", re.I)
NGROK_URL_RE = re.compile(r"https://[a-z0-9][a-z0-9-.]*\.ngrok(?:-free)?\.(?:app|io|dev)", re.I)
ANY_URL_RE = re.compile(r"https://[a-z0-9][a-z0-9.-]+\.[a-z]{2,}(?::\d+)?", re.I)

INSTALL_HINTS = {
    "cloudflared": [
        "Windows:  winget install --id Cloudflare.cloudflared",
        "macOS:    brew install cloudflared",
        "Linux:    https://developers.cloudflare.com/cloudflare-one/connections/connect-networks/downloads/",
    ],
    "ngrok": [
        "Windows:  winget install --id ngrok.ngrok",
        "macOS:    brew install ngrok/ngrok/ngrok",
        "Any:      https://ngrok.com/download (then `ngrok config add-authtoken <token>`)",
    ],
}


def _now() -> float:
    return time.time()


def local_ip_addresses() -> list:
    """Best-effort LAN IPv4 addresses (no packet is actually sent)."""
    found = []
```

```
    try:
        sock = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
        try:
            sock.connect(("10.255.255.255", 1))
            found.append(sock.getsockname()[0])
        finally:
            sock.close()
    except OSError:
        pass
    try:
        host = socket.gethostname()
        for info in socket.getaddrinfo(host, None, socket.AF_INET):
            ip = info[4][0]
            if ip not in found and not ip.startswith("127."):
                found.append(ip)
    except OSError:
        pass
    return [ip for ip in found if not ip.startswith("127.")]


def find_tunnel_binary(preferred: str = None) -> tuple:
    """Return (flavor, path) for the first tunnel binary found, else (None, None)."""
    candidates = []
    if preferred and preferred not in ("auto", ""):
        candidates.append(preferred)
    candidates += ["cloudflared", "ngrok"]
    for name in candidates:
        found = shutil.which(name)
        if found:
            return ("cloudflared" if "cloudflared" in Path(found).name.lower() else "ngrok"), found
    return None, None


TOKEN_CHARS = set("ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789+/=_-.")


def validate_named_token(token: str):
    """Check a Cloudflare named-tunnel token before it reaches a subprocess.

    Returns (ok, reason). The token is a base64 blob; the checks are deliberately
    about shape (empty / whitespace / junk characters / pasted URL) rather than
    about decoding Cloudflare's payload, so a valid token is never rejected.
    """
    raw = token if isinstance(token, str) else ""
    if not raw.strip():
        return False, "the token is empty"
    if raw != raw.strip():
        return False, "the token has leading or trailing whitespace (check for a stray quote or newline)"
    if any(ch.isspace() for ch in raw):
        return False, "the token contains whitespace; copy only the tunnel token value"
    if "://" in raw or raw.lower().startswith(("http", "https")):
        return False, "this looks like a URL, not a tunnel token; copy the token from the Cloudflare dashboard"
    if len(raw) < 20:
        return False, f"the token is only {len(raw)} characters, which is too short for a Cloudflare tunnel token"
    bad = sorted({ch for ch in raw if ch not in TOKEN_CHARS})
    if bad:
        return False, "the token contains unexpected characters: " + " ".join(repr(ch) for ch in bad[:5])
    return True, "ok"


```

```python
class TunnelManager:
    """Starts, watches, restarts and reports a public tunnel for the local bridge."""

    def __init__(
        self,
        port: int = 8077,
        binary: str = None,
        flavor: str = "auto",
        named_token: str = None,
        name: str = None,
        public_url: str = None,
        health_interval: float = 20.0,
        health_failures_before_restart: int = 4,
        max_backoff: float = 30.0,
        state_dir=None,
        auto_start: bool = False,
    ):
        self.port = int(port)
        self.local_url = f"http://127.0.0.1:{self.port}"
        self.requested_flavor = (flavor or "auto").lower()
        self.binary_arg = binary
        self.named_token = named_token or os.environ.get("TUNNEL_TOKEN") or None
        self.name = name
        self.user_public_url = (public_url or os.environ.get("BRIDGE_PUBLIC_URL") or "").strip() or None
        self.health_interval = float(health_interval)
        self.health_failures_before_restart = int(health_failures_before_restart)
        self.max_backoff = float(max_backoff)
        self.state_path = (Path(state_dir) if state_dir else DEFAULT_STATE_DIR) / "tunnel.json"

        self.lock = threading.RLock()
        self.stop_event = threading.Event()
        self._thread = None
        self._proc = None
        self.flavor = None
        self.binary = None
        self.state = "stopped"
        self.public_url = self.user_public_url
        self.last_error = None
        self.started_at = None
        self.online_at = None
        self.restarts = 0
        self.url_changes = 0
        self.url_changed_at = None
        self.proc_pid = None
        self.health = {"lastProbe": None, "ok": None, "latencyMs": None, "failures": 0, "consecutiveFailures": 0}
        self.log_tail = deque(maxlen=60)
        self.last_output_at = None
        self._last_health = 0.0
        self._load_last_url()
        if auto_start:
            self.start()

    # -- persistence of last known URL ---------------------------------------

    def _load_last_url(self):
        try:
            raw = json.loads(self.state_path.read_text(encoding="utf-8"))
            if not self.public_url and raw.get("publicUrl"):
                self.public_url = raw["publicUrl"]
                self.last_error = None
```

```
                self._loaded_url = True
        except (OSError, ValueError):
            pass

    def _persist_url(self):
        try:
            self.state_path.parent.mkdir(parents=True, exist_ok=True)
            self.state_path.write_text(
                json.dumps({"publicUrl": self.public_url, "saved": _now(), "version": TUNNEL_VERSION}),
                encoding="utf-8",
            )
        except OSError:
            pass

    # -- command construction ------------------------------------------------

    def _command(self) -> list:
        if not self.binary:
            raise RuntimeError("No tunnel binary available")
        if self.flavor == "cloudflared":
            if self.named_token:
                # Named tunnel: the ingress/hostname config lives in Cloudflare;
                # `--url` is only valid for quick tunnels.
                ok, reason = validate_named_token(self.named_token)
                if not ok:
                    raise RuntimeError(f"Invalid Cloudflare tunnel token: {reason}")
                return [self.binary, "tunnel", "--no-autoupdate", "run", "--token", self.named_token]
            return [self.binary, "tunnel", "--url", self.local_url, "--no-autoupdate"]
        if self.flavor == "ngrok":
            cmd = [self.binary, "http", str(self.port), "--log", "stdout", "--log-format", "logfmt"]
            return cmd
        raise RuntimeError(f"Unsupported tunnel flavor: {self.flavor}")

    def _detect(self):
        flavor, path = find_tunnel_binary(self.binary_arg)
        if not flavor and self.requested_flavor in ("cloudflared", "ngrok"):
            # Respect an explicit preference even if the generic detection failed.
            found = shutil.which(self.requested_flavor)
            if found:
                flavor, path = self.requested_flavor, found
        with self.lock:
            self.flavor = flavor if not self.requested_flavor or self.requested_flavor == "auto" else (self.requested_flavor if path else flavor)
            self.binary = path
        return bool(path)

    def available(self) -> bool:
        return self.binary is not None or shutil.which(self.binary_arg or "") is not None

    # -- lifecycle -----------------------------------------------------------

    def start(self) -> dict:
        with self.lock:
            if self.user_public_url:
                self.state = "online"
                self.public_url = self.user_public_url
                self.online_at = self.online_at or _now()
                return self.status()
            if self._thread and self._thread.is_alive():
                return self.status()
            if self.named_token and (self.requested_flavor in ("auto", "cloudflared")):
```

```
                ok, reason = validate_named_token(self.named_token)
                if not ok:
                    self.state = "error"
                    self.last_error = (
                        f"Invalid Cloudflare tunnel token: {reason}. "
                        "Run `cloudflared tunnel token <name>` (or copy it from Zero Trust > Networks > Tunnels) "
                        "and pass the value with --tunnel-token; the bridge will not start a named tunnel without it."
                    )
                    self._append_log_unlocked("[supervisor] " + self.last_error)
                    return self.status()
            if not self._detect():
                self.state = "unavailable"
                self.last_error = (
                    "No tunnel binary found on PATH. Install cloudflared or ngrok, "
                    "or pass BRIDGE_PUBLIC_URL for a tunnel you run yourself."
                )
                return self.status()
            self.stop_event.clear()
            self.last_error = None
            self.state = "starting"
            self.started_at = self.started_at or _now()
            self._thread = threading.Thread(target=self._supervise, name="tunnel-supervisor", daemon=True)
            self._thread.start()
            return self.status()

    def stop(self) -> dict:
        self.stop_event.set()
        with self.lock:
            proc = self._proc
        if proc and proc.poll() is None:
            try:
                proc.terminate()
                try:
                    proc.wait(timeout=5)
                except subprocess.TimeoutExpired:
                    proc.kill()
            except OSError:
                pass
        thread = self._thread
        if thread and thread.is_alive() and thread is not threading.current_thread():
            thread.join(timeout=6)
        with self.lock:
            self._thread = None
            self._proc = None
            self.proc_pid = None
            self.state = "stopped"
            if not self.user_public_url:
                self.online_at = None
        return self.status()

    def restart(self) -> dict:
        self.stop()
        with self.lock:
            self.restarts += 1
        time.sleep(0.4)
        return self.start()

    # -- supervision ------------------------------------------------------

    def _supervise(self):
```

```
        backoff = 1.0
        while not self.stop_event.is_set():
            try:
                cmd = self._command()
            except RuntimeError as exc:
                with self.lock:
                    self.state = "error"
                    self.last_error = str(exc)
                return
            with self.lock:
                self.state = "starting"
                self._append_log_unlocked(f"$ {' '.join(cmd[:3])}{' ...' if len(cmd) > 3 else ''}")
            try:
                proc = subprocess.Popen(
                    cmd,
                    stdout=subprocess.PIPE,
                    stderr=subprocess.STDOUT,
                    text=True,
                    bufsize=1,
                    start_new_session=(os.name != "nt"),
                )
            except (OSError, ValueError) as exc:
                with self.lock:
                    self.state = "error"
                    self.last_error = f"Failed to launch {self.flavor}: {exc}"
                    self._append_log_unlocked(self.last_error)
                if self.stop_event.wait(backoff):
                    break
                backoff = min(self.max_backoff, backoff * 2)
                continue
            with self.lock:
                self._proc = proc
                self.proc_pid = proc.pid
            reader = threading.Thread(target=self._read_output, args=(proc,), daemon=True)
            reader.start()
            # Wait for the process to exit, probing health in the meantime.
            while not self.stop_event.is_set() and proc.poll() is None:
                if self.stop_event.wait(timeout=1.0):
                    break
                self._maybe_probe()
            reader.join(timeout=2)
            if self.stop_event.is_set():
                break
            code = proc.poll()
            with self.lock:
                self._proc = None
                self.proc_pid = None
                self._append_log_unlocked(f"[supervisor] {self.flavor} exited with code {code}; reconnecting...")
                self.state = "reconnecting"
                self.restarts += 1
                self.health["ok"] = False
                self.health["consecutiveFailures"] = 0
                # A dead child invalidates its quick-tunnel URL; a new one is
                # scraped from the replacement process.
                self.public_url = None
            if self.stop_event.wait(backoff):
                break
            backoff = min(self.max_backoff, backoff * 2)
        with self.lock:
            if self.state not in ("stopped",):
```

```
                self.state = "stopped"

    def _read_output(self, proc):
        stream = proc.stdout
        if not stream:
            return
        for raw_line in iter(stream.readline, ""):
            line = (raw_line or "").rstrip()
            if not line:
                continue
            with self.lock:
                self._append_log_unlocked(line)
                self.last_output_at = _now()
            match = None
            if self.flavor == "ngrok":
                match = NGROK_URL_RE.search(line) or CLOUDFLARE_URL_RE.search(line)
            else:
                match = CLOUDFLARE_URL_RE.search(line) or NGROK_URL_RE.search(line)
            if match:
                self._set_url(match.group(0))
        try:
            stream.close()
        except OSError:
            pass

    def _append_log_unlocked(self, line: str):
        self.log_tail.append(line[:400])

    def _set_url(self, url: str):
        url = url.rstrip("/")
        with self.lock:
            if self.public_url == url:
                return
            changed = self.public_url is not None
            self.public_url = url
            self.url_changed_at = _now()
            self.state = "online"
            self.online_at = _now()
            self.last_error = None
            self.health["ok"] = None
            self.health["failures"] = 0
            self.health["consecutiveFailures"] = 0
            if changed:
                self.url_changes += 1
        self._persist_url()

    def _maybe_probe(self):
        now = _now()
        if now - self._last_health < self.health_interval:
            return
        if not self.public_url:
            self._last_health = now
            if self.last_output_at and now - self.last_output_at > 45 and self.state == "starting":
                with self.lock:
                    self.last_error = "Tunnel process started but has not published a URL yet."
            return
        self._last_health = now
        threading.Thread(target=self._probe_once, name="tunnel-health", daemon=True).start()

    def _probe_once(self):
```

```
        url = f"{self.public_url}/api/health"
        started = time.monotonic()
        ok = False
        detail = None
        try:
            req = urllib.request.Request(url, headers={"User-Agent": f"arena-tunnel/{TUNNEL_VERSION}"})
            with urllib.request.urlopen(req, timeout=10) as resp:
                ok = 200 <= resp.status < 500
                detail = f"HTTP {resp.status}"
        except urllib.error.HTTPError as exc:
            ok = exc.code < 500
            detail = f"HTTP {exc.code}"
        except Exception as exc:  # noqa: BLE001 - network errors are all non-fatal
            detail = str(exc)[:200]
        latency = round((time.monotonic() - started) * 1000, 1)
        restart = False
        with self.lock:
            self.health["lastProbe"] = _now()
            self.health["latencyMs"] = latency
            self.health["ok"] = ok
            self.health["detail"] = detail
            if ok:
                self.health["failures"] = 0
                self.health["consecutiveFailures"] = 0
                if self.state == "degraded":
                    self.state = "online"
            else:
                self.health["failures"] = int(self.health.get("failures") or 0) + 1
                self.health["consecutiveFailures"] = int(self.health.get("consecutiveFailures") or 0) + 1
                if self.health["consecutiveFailures"] >= 2 and self.state == "online":
                    self.state = "degraded"
                if self.health["consecutiveFailures"] >= self.health_failures_before_restart:
                    restart = True
            if restart:
                self._append_log_unlocked("[supervisor] public URL failed repeated health probes; restarting tunnel")
        if restart:
            proc = self._proc
            if proc and proc.poll() is None:
                try:
                    proc.terminate()
                except OSError:
                    pass
            with self.lock:
                self.restarts += 1

    # -- reporting ------------------------------------------------------------

    def status(self) -> dict:
        with self.lock:
            now = _now()
            state = self.state
            if self.user_public_url and state == "stopped":
                state = "online"
            uptime = round(now - self.online_at, 1) if self.online_at and state == "online" else 0
            lan = [
                f"http://{ip}:{self.port}" for ip in local_ip_addresses()
            ]
            return {
                "version": TUNNEL_VERSION,
                "state": state,
```

```
                "running": bool(self._thread and self._thread.is_alive()) or bool(self.user_public_url),
                "flavor": self.flavor,
                "binary": self.binary,
                "binaryAvailable": bool(self.binary),
                "managed": not bool(self.user_public_url),
                "named": bool(self.named_token),
                "namedTokenValid": (validate_named_token(self.named_token)[0] if self.named_token else None),
                "name": self.name,
                "localUrl": self.local_url,
                "lanUrls": lan,
                "publicUrl": self.public_url,
                "mcpEndpoint": f"{self.public_url}/mcp" if self.public_url else None,
                "healthEndpoint": f"{self.public_url}/api/health" if self.public_url else None,
                "onlineSeconds": uptime,
                "restarts": self.restarts,
                "urlChanges": self.url_changes,
                "urlChangedAt": self.url_changed_at,
                "pid": self.proc_pid,
                "lastError": self.last_error,
                "health": dict(self.health),
                "logTail": list(self.log_tail)[-25:],
                "installHints": INSTALL_HINTS.get(self.flavor or "cloudflared"),
                "serverTime": now,
            }

    def handle(self, payload: dict) -> dict:
        action = ((payload or {}).get("action") or "status").lower()
        if action == "status":
            return self.status()
        if action == "start":
            return self.start()
        if action == "stop":
            return self.stop()
        if action == "restart":
            return self.restart()
        if action == "lan":
            return {"lanUrls": [f"http://{ip}:{self.port}" for ip in local_ip_addresses()], "port": self.port}
        raise ValueError("Unknown tunnel action. Use status, start, stop, restart or lan.")

```

roblox-bridge/bus_core.py

859 lines

Multi-agent presence, mailbox and lease-based task board

```python
#!/usr/bin/env python3
"""
bus_core.py - Multi-agent collaboration bus for the Arena Roblox Studio bridge.

Zero-dependency, thread-safe, JSON-persisted coordination layer that lets several
AI agents (and humans) share one Roblox Studio session without stepping on each
other:

  * Presence registry   - named agents with roles, capabilities and heartbeats.
  * Mailbox             - direct + broadcast messages, cursor-based inbox, acks.
  * Task board          - claim/lease/complete work items with priorities, tags
                          and dependencies. A lease expires automatically, so a
                          crashed agent cannot permanently hold a task.
  * Event feed          - bounded, sequence-numbered activity log.
  * Handoff export      - markdown brief for the next agent.

Everything is plain stdlib so it can be embedded in server.py, used from the CLI,
or driven through the `agent_bus` MCP tool.
"""

import json
import os
import threading
import time
import uuid
from collections import deque
from pathlib import Path

BUS_VERSION = "5.3.2"
DEFAULT_STATE_DIR = Path(__file__).resolve().parent / "bridge_state"

AGENT_STATUSES = ("online", "busy", "idle", "offline")
TASK_STATUSES = ("todo", "in_progress", "blocked", "done", "cancelled")
MESSAGE_KINDS = ("note", "question", "answer", "handoff", "alert", "result")
PRIORITIES = ("low", "normal", "high", "critical")
_PRIORITY_RANK = {"low": 3, "normal": 2, "high": 1, "critical": 0}


def _now() -> float:
    return time.time()


def _clean(text, limit: int = 8000) -> str:
    if text is None:
        return ""
    text = str(text)
    return text[:limit]


class AgentBus:
    """Presence + mailbox + task board shared by every agent on the bridge."""

    def __init__(
        self,
        path=None,
        max_messages: int = 2000,
        max_events: int = 1000,
        default_lease_seconds: int = 900,
        presence_ttl: float = 90.0,
        persist: bool = True,
```

```
    ):
        self.path = Path(path) if path else DEFAULT_STATE_DIR / "bus.json"
        self.persist = bool(persist)
        self.lock = threading.RLock()
        self.agents = {}
        self.messages = deque(maxlen=max_messages)
        self.events = deque(maxlen=max_events)
        self.tasks = {}
        self.default_lease_seconds = int(default_lease_seconds)
        self.presence_ttl = float(presence_ttl)
        self.seq = 0
        self.created = _now()
        self.agents_reaped = 0
        self.tasks_reaped = 0
        self.last_sweep_at = None
        self._load()

    # -- persistence -----------------------------------------------------------

    def _load(self):
        if not self.persist or not self.path.is_file():
            return
        try:
            raw = json.loads(self.path.read_text(encoding="utf-8"))
        except (OSError, ValueError):
            return
        if not isinstance(raw, dict):
            return
        with self.lock:
            self.agents = {a["id"]: a for a in raw.get("agents", []) if a.get("id")}
            self.messages = deque(raw.get("messages", [])[-self.messages.maxlen:], maxlen=self.messages.maxlen)
            self.events = deque(raw.get("events", [])[-self.events.maxlen:], maxlen=self.events.maxlen)
            self.tasks = {t["id"]: t for t in raw.get("tasks", []) if t.get("id")}
            self.seq = int(raw.get("seq") or 0)
            counters = raw.get("counters") or {}
            self.agents_reaped = int(counters.get("agentsReaped") or 0)
            self.tasks_reaped = int(counters.get("tasksReaped") or 0)
            self.last_sweep_at = counters.get("lastSweepAt")

    def _save(self):
        if not self.persist:
            return
        try:
            self.path.parent.mkdir(parents=True, exist_ok=True)
            payload = {
                "version": BUS_VERSION,
                "saved": _now(),
                "seq": self.seq,
                "agents": list(self.agents.values()),
                "messages": list(self.messages),
                "events": list(self.events),
                "tasks": list(self.tasks.values()),
                "counters": {
                    "agentsReaped": self.agents_reaped,
                    "tasksReaped": self.tasks_reaped,
                    "lastSweepAt": self.last_sweep_at,
                },
            }
            tmp = self.path.with_suffix(".tmp")
            tmp.write_text(json.dumps(payload, ensure_ascii=False, separators=(",", ":")), encoding="utf-8")
```

```
            os.replace(tmp, self.path)
        except OSError:
            pass

    # -- internals ------------------------------------------------------------

    def _next_seq_unlocked(self) -> int:
        self.seq += 1
        return self.seq

    def _emit_unlocked(self, kind: str, data: dict) -> dict:
        event = {"seq": self._next_seq_unlocked(), "kind": kind, "ts": _now(), "data": data}
        self.events.append(event)
        return event

    def _agent_unlocked(self, agent_id: str) -> dict:
        agent = self.agents.get(agent_id)
        if not agent:
            raise KeyError(f"Unknown agent id: {agent_id!r}")
        return agent

    def _touch_unlocked(self, agent: dict):
        agent["lastSeen"] = _now()
        agent["online"] = True

    def _expire_leases_unlocked(self):
        now = _now()
        for task in self.tasks.values():
            lease = task.get("lease") or {}
            if task.get("status") == "in_progress" and lease.get("expiresAt") and lease["expiresAt"] < now:
                prev_owner = task.get("assignee")
                task["status"] = "todo"
                task["assignee"] = None
                task["lease"] = None
                task["updated"] = now
                task["leaseExpiries"] = int(task.get("leaseExpiries", 0)) + 1
                self._emit_unlocked("task.lease_expired", {"taskId": task["id"], "previousAssignee": prev_owner})

    # -- agents / presence ----------------------------------------------------

    def register_agent(
        self,
        name: str,
        role: str = "agent",
        capabilities=None,
        agent_id: str = None,
        ttl: float = None,
        meta: dict = None,
    ) -> dict:
        name = (name or "").strip()
        if not name:
            raise ValueError("name is required")
        with self.lock:
            # Reuse an existing registration with the same name (case-insensitive).
            existing = next((a for a in self.agents.values() if a["name"].lower() == name.lower()), None)
            now = _now()
            caps = [str(c) for c in (capabilities or [])][:32]
            if existing:
                existing.update({
                    "name": name,
```

```
                    "role": _clean(role, 40) or "agent",
                    "capabilities": caps or existing.get("capabilities", []),
                    "status": "online",
                    "online": True,
                    "lastSeen": now,
                    "ttl": float(ttl or self.presence_ttl),
                    "meta": meta if isinstance(meta, dict) else existing.get("meta", {}),
                })
                agent = existing
                created_new = False
            else:
                aid = agent_id or ("agent-" + uuid.uuid4().hex[:8])
                if aid in self.agents:
                    aid = "agent-" + uuid.uuid4().hex[:8]
                agent = {
                    "id": aid,
                    "name": name,
                    "role": _clean(role, 40) or "agent",
                    "capabilities": caps,
                    "status": "online",
                    "online": True,
                    "firstSeen": now,
                    "lastSeen": now,
                    "ttl": float(ttl or self.presence_ttl),
                    "meta": meta if isinstance(meta, dict) else {},
                }
                self.agents[agent["id"]] = agent
                created_new = True
            self._emit_unlocked("agent.register" if created_new else "agent.heartbeat", {
                "agentId": agent["id"], "name": agent["name"], "role": agent["role"],
            })
            self._save()
            return self._agent_view_unlocked(agent)

    def heartbeat(self, agent_id: str, status: str = None) -> dict:
        with self.lock:
            agent = self._agent_unlocked(agent_id)
            self._touch_unlocked(agent)
            if status in AGENT_STATUSES:
                agent["status"] = status
            self._save()
            return self._agent_view_unlocked(agent)

    def set_status(self, agent_id: str, status: str) -> dict:
        if status not in AGENT_STATUSES:
            raise ValueError(f"status must be one of {', '.join(AGENT_STATUSES)}")
        with self.lock:
            agent = self._agent_unlocked(agent_id)
            self._touch_unlocked(agent)
            agent["status"] = status
            self._save()
            return self._agent_view_unlocked(agent)

    def _agent_view_unlocked(self, agent: dict) -> dict:
        row = dict(agent)
        age = _now() - float(agent.get("lastSeen") or 0)
        row["ageSeconds"] = round(age, 1)
        row["online"] = age <= float(agent.get("ttl") or self.presence_ttl)
        if not row["online"]:
            row["status"] = "offline"
```

```
        row["openTasks"] = sum(
            1 for t in self.tasks.values()
            if t.get("assignee") == agent["id"] and t.get("status") in ("todo", "in_progress", "blocked")
        )
        row["inboxUnread"] = sum(
            1 for m in self.messages
            if (m.get("to") in (agent["id"], "all", None)) and agent["id"] not in (m.get("readBy") or {})
        )
        return row

    def list_agents(self, include_offline: bool = True) -> dict:
        with self.lock:
            rows = [self._agent_view_unlocked(a) for a in self.agents.values()]
        if not include_offline:
            rows = [r for r in rows if r["online"]]
        rows.sort(key=lambda r: (not r["online"], r["name"].lower()))
        return {"agents": rows, "count": len(rows), "onlineCount": sum(1 for r in rows if r["online"])}

    # -- mailbox ------------------------------------------------------------

    def post_message(
        self,
        sender: str,
        body: str,
        to: str = None,
        subject: str = "",
        kind: str = "note",
        priority: str = "normal",
        thread_id: str = None,
        meta: dict = None,
    ) -> dict:
        sender = (sender or "").strip()
        if not sender:
            raise ValueError("sender is required")
        if not (body or subject):
            raise ValueError("body or subject is required")
        if kind not in MESSAGE_KINDS:
            kind = "note"
        if priority not in PRIORITIES:
            priority = "normal"
        with self.lock:
            # Accept an agent name as well as an id; "all" / None means broadcast.
            to_id = None
            if to and to not in ("all", "*", "broadcast"):
                to_id = to
                if to_id not in self.agents:
                    match = next((a["id"] for a in self.agents.values() if a["name"].lower() == str(to).lower()), None)
                    to_id = match or to
            msg = {
                "id": "msg-" + uuid.uuid4().hex[:10],
                "seq": self._next_seq_unlocked(),
                "ts": _now(),
                "from": sender,
                "fromId": next((a["id"] for a in self.agents.values() if a["name"].lower() == sender.lower()), None),
                "to": to_id,
                "subject": _clean(subject, 300),
                "body": _clean(body),
                "kind": kind,
                "priority": priority,
                "threadId": thread_id,
```

```
                "meta": meta if isinstance(meta, dict) else {},
                "readBy": {},
            }
            self.messages.append(msg)
            self._emit_unlocked("message.post", {
                "id": msg["id"], "from": sender, "to": to_id or "broadcast",
                "subject": msg["subject"], "kind": kind, "priority": priority,
            })
            self._save()
            return msg

    def inbox(
        self,
        agent_id: str,
        since: int = 0,
        limit: int = 50,
        unread_only: bool = False,
        include_broadcast: bool = True,
    ) -> dict:
        limit = max(1, min(int(limit or 50), 500))
        with self.lock:
            agent = self.agents.get(agent_id)
            names = {agent_id}
            if agent:
                names.add(agent["name"].lower())
            rows = []
            for msg in reversed(self.messages):
                if since and msg["seq"] <= since:
                    break
                target = msg.get("to")
                if target is None:
                    if not include_broadcast:
                        continue
                elif target not in names and str(target).lower() not in names:
                    continue
                if msg.get("from") == agent_id:
                    continue
                if unread_only and agent_id in (msg.get("readBy") or {}):
                    continue
                rows.append(msg)
                if len(rows) >= limit:
                    break
            rows.reverse()
            unread = sum(
                1 for m in self.messages
                if (m.get("to") is None or m.get("to") in names or str(m.get("to", "")).lower() in names)
                and agent_id not in (m.get("readBy") or {}) and m.get("from") != agent_id
            )
            return {
                "agentId": agent_id,
                "messages": rows,
                "count": len(rows),
                "unread": unread,
                "cursor": rows[-1]["seq"] if rows else since,
            }

    def read_thread(self, thread_id: str) -> dict:
        with self.lock:
            rows = [m for m in self.messages if m.get("threadId") == thread_id or m["id"] == thread_id]
        return {"threadId": thread_id, "messages": rows, "count": len(rows)}
```

```
361
362     def mark_read(self, agent_id: str, message_ids=None, all_messages: bool = False) -> dict:
363         now = _now()
364         marked = 0
365         with self.lock:
366             for msg in self.messages:
367                 if not all_messages and message_ids and msg["id"] not in message_ids:
368                     continue
369                 if all_messages or message_ids:
370                     if agent_id not in (msg.get("readBy") or {}):
371                         msg.setdefault("readBy", {})[agent_id] = now
372                         marked += 1
373             self._save()
374         return {"agentId": agent_id, "marked": marked}
375
376     # -- task board -----------------------------------------------------------
377
378     def create_task(
379         self,
380         title: str,
381         detail: str = "",
382         created_by: str = "",
383         assignee: str = None,
384         priority: str = "normal",
385         tags=None,
386         depends_on=None,
387         estimate_minutes: int = None,
388     ) -> dict:
389         title = (title or "").strip()
390         if not title:
391             raise ValueError("title is required")
392         if priority not in PRIORITIES:
393             priority = "normal"
394         with self.lock:
395             now = _now()
396             task = {
397                 "id": "task-" + uuid.uuid4().hex[:8],
398                 "title": _clean(title, 300),
399                 "detail": _clean(detail),
400                 "createdBy": created_by or "unknown",
401                 "assignee": assignee,
402                 "status": "todo",
403                 "priority": priority,
404                 "tags": [str(t)[:40] for t in (tags or [])][:20],
405                 "dependsOn": [str(d) for d in (depends_on or [])][:20],
406                 "estimateMinutes": int(estimate_minutes) if estimate_minutes else None,
407                 "created": now,
408                 "updated": now,
409                 "lease": None,
410                 "result": None,
411                 "artifacts": [],
412                 "history": [{"ts": now, "actor": created_by or "unknown", "action": "created"}],
413             }
414             self.tasks[task["id"]] = task
415             self._emit_unlocked("task.created", {"taskId": task["id"], "title": task["title"], "priority": priority})
416             self._save()
417             return dict(task)
418
419     def list_tasks(self, status: str = None, assignee: str = None, tag: str = None, include_done: bool = True) -> dict:
420         with self.lock:
```

```
            self._expire_leases_unlocked()
            rows = list(self.tasks.values())
        if status:
            wanted = {s.strip() for s in status.split(",") if s.strip()}
            rows = [t for t in rows if t["status"] in wanted]
        if not include_done:
            rows = [t for t in rows if t["status"] not in ("done", "cancelled")]
        if assignee:
            rows = [t for t in rows if t.get("assignee") == assignee or t.get("createdBy") == assignee]
        if tag:
            rows = [t for t in rows if tag in (t.get("tags") or [])]
        rows.sort(key=lambda t: (
            {"in_progress": 0, "blocked": 1, "todo": 2, "done": 3, "cancelled": 4}.get(t["status"], 5),
            _PRIORITY_RANK.get(t.get("priority"), 2),
            t.get("created", 0),
        ))
        now = _now()
        out = []
        for t in rows:
            row = dict(t)
            lease = t.get("lease")
            row["leaseRemainingSeconds"] = round(lease["expiresAt"] - now, 1) if lease and lease.get("expiresAt") else None
            row["blockedBy"] = [d for d in (t.get("dependsOn") or []) if self.tasks.get(d, {}).get("status") != "done"]
            out.append(row)
        return {
            "tasks": out,
            "count": len(out),
            "counts": {
                s: sum(1 for t in self.tasks.values() if t["status"] == s) for s in TASK_STATUSES
            },
            "serverTime": now,
        }

    def _resolve_agent_unlocked(self, agent_id: str) -> str:
        if agent_id in self.agents:
            return agent_id
        match = next((a["id"] for a in self.agents.values() if a["name"].lower() == str(agent_id).lower()), None)
        if not match:
            raise KeyError(f"Unknown agent: {agent_id!r} - register first via action=register")
        return match

    def claim_task(self, task_id: str, agent_id: str, lease_seconds: int = None) -> dict:
        with self.lock:
            self._expire_leases_unlocked()
            task = self.tasks.get(task_id)
            if not task:
                raise KeyError(f"Unknown task id: {task_id!r}")
            agent_id = self._resolve_agent_unlocked(agent_id)
            if task["status"] in ("done", "cancelled"):
                raise ValueError(f"Task {task_id} is already {task['status']}")
            blocked = [d for d in (task.get("dependsOn") or []) if self.tasks.get(d, {}).get("status") != "done"]
            if blocked:
                raise ValueError(f"Task {task_id} is blocked by incomplete dependencies: {', '.join(blocked)}")
            current = task.get("assignee")
            if current and current != agent_id and task.get("lease"):
                raise ValueError(f"Task {task_id} is already claimed by {current} until the lease expires")
            now = _now()
            lease_s = int(lease_seconds or self.default_lease_seconds)
            task.update({
                "assignee": agent_id,
```

```
                "status": "in_progress",
                "updated": now,
                "lease": {"owner": agent_id, "claimedAt": now, "expiresAt": now + lease_s, "seconds": lease_s},
            })
            task.setdefault("history", []).append({"ts": now, "actor": agent_id, "action": "claimed"})
            self._emit_unlocked("task.claimed", {"taskId": task_id, "agentId": agent_id, "leaseSeconds": lease_s})
            self._save()
            return dict(task)

    def renew_task(self, task_id: str, agent_id: str, lease_seconds: int = None) -> dict:
        with self.lock:
            task = self.tasks.get(task_id)
            if not task:
                raise KeyError(f"Unknown task id: {task_id!r}")
            lease = task.get("lease") or {}
            if lease.get("owner") != agent_id:
                raise ValueError("Only the current lease owner can renew this task")
            lease_s = int(lease_seconds or lease.get("seconds") or self.default_lease_seconds)
            lease["expiresAt"] = _now() + lease_s
            task["lease"] = lease
            task["updated"] = _now()
            self._save()
            return dict(task)

    def release_task(self, task_id: str, agent_id: str, note: str = "") -> dict:
        with self.lock:
            task = self.tasks.get(task_id)
            if not task:
                raise KeyError(f"Unknown task id: {task_id!r}")
            task.update({"assignee": None, "status": "todo", "lease": None, "updated": _now()})
            task.setdefault("history", []).append({"ts": _now(), "actor": agent_id, "action": "released", "note": note})
            self._emit_unlocked("task.released", {"taskId": task_id, "agentId": agent_id})
            self._save()
            return dict(task)

    def update_task(self, task_id: str, actor: str = "unknown", **changes) -> dict:
        allowed = {"status", "priority", "assignee", "detail", "tags", "dependsOn", "title"}
        with self.lock:
            task = self.tasks.get(task_id)
            if not task:
                raise KeyError(f"Unknown task id: {task_id!r}")
            if changes.get("status") and changes["status"] not in TASK_STATUSES:
                raise ValueError(f"status must be one of {', '.join(TASK_STATUSES)}")
            if changes.get("priority") and changes["priority"] not in PRIORITIES:
                raise ValueError(f"priority must be one of {', '.join(PRIORITIES)}")
            for key, value in changes.items():
                if key in allowed and value is not None:
                    if key in ("detail", "title"):
                        value = _clean(value, 300 if key == "title" else 8000)
                    task[key] = value
            task["updated"] = _now()
            task.setdefault("history", []).append({"ts": _now(), "actor": actor, "action": "updated", "changes": sorted(changes)})
            self._emit_unlocked("task.updated", {"taskId": task_id, "actor": actor, "changes": sorted(changes)})
            self._save()
            return dict(task)

    def complete_task(self, task_id: str, agent_id: str, result: str = "", artifacts=None, status: str = "done") -> dict:
        if status not in ("done", "cancelled"):
            raise ValueError("complete status must be 'done' or 'cancelled'")
        with self.lock:
```

```
            task = self.tasks.get(task_id)
            if not task:
                raise KeyError(f"Unknown task id: {task_id!r}")
            lease_owner = (task.get("lease") or {}).get("owner")
            if lease_owner and lease_owner != agent_id and task.get("assignee") not in (None, agent_id):
                raise ValueError(f"Task {task_id} is leased to {lease_owner}")
            now = _now()
            task.update({
                "status": status,
                "assignee": task.get("assignee") or agent_id,
                "result": _clean(result),
                "artifacts": [str(a)[:500] for a in (artifacts or [])][:50],
                "lease": None,
                "updated": now,
                "completedAt": now,
            })
            task.setdefault("history", []).append({"ts": now, "actor": agent_id, "action": status})
            self._emit_unlocked(f"task.{status}", {"taskId": task_id, "agentId": agent_id, "title": task["title"]})
            self._save()
            return dict(task)

    def delete_task(self, task_id: str, actor: str = "unknown") -> dict:
        with self.lock:
            task = self.tasks.pop(task_id, None)
            if not task:
                raise KeyError(f"Unknown task id: {task_id!r}")
            self._emit_unlocked("task.deleted", {"taskId": task_id, "actor": actor})
            self._save()
            return {"deleted": task_id}

    # -- feed / export ---------------------------------------------------

    def feed(self, since: int = 0, limit: int = 100) -> dict:
        limit = max(1, min(int(limit or 100), 500))
        with self.lock:
            rows = [e for e in self.events if e["seq"] > since][-limit:]
            seq = self.seq
        return {"events": rows, "count": len(rows), "cursor": seq}

    def sweep_stale(self, offline_seconds: float = 900, now: float = None) -> dict:
        """Release tasks held by agents that stopped reporting.

        A crashed agent keeps its lease until it expires (15 minutes by default), which
        makes the board look busy while nothing moves. This sweep is the escape hatch:
        it only touches tasks whose owner has been silent for `offline_seconds`, never
        tasks held by an agent that is still heart-beating.
        """
        offline_seconds = float(offline_seconds or 900)
        now = float(now if now is not None else _now())
        released = []
        stale_agents = []
        with self.lock:
            self._expire_leases_unlocked()
            for agent in self.agents.values():
                last_seen = float(agent.get("lastSeen") or 0)
                if (now - last_seen) >= offline_seconds:
                    stale_agents.append(agent)
            stale_ids = {a["id"] for a in stale_agents}
            if not stale_agents:
                self.last_sweep_at = now
```

```
                self._save()
                return {"released": [], "agents": [], "agentsReaped": 0, "tasksReaped": 0,
                        "alerted": False, "sweptAt": now}

            for task in self.tasks.values():
                if task.get("status") != "in_progress":
                    continue
                owner = (task.get("lease") or {}).get("owner") or task.get("assignee")
                if owner not in stale_ids:
                    continue
                task.update({"status": "todo", "assignee": None, "lease": None, "updated": now})
                task["leaseExpiries"] = int(task.get("leaseExpiries", 0)) + 1
                task.setdefault("history", []).append(
                    {"ts": now, "actor": "sweeper", "action": "reaped", "previousAssignee": owner}
                )
                released.append({"taskId": task["id"], "title": task.get("title"), "previousAssignee": owner})

            self.agents_reaped += len({r["previousAssignee"] for r in released})
            self.tasks_reaped += len(released)
            self.last_sweep_at = now
            if released:
                names = sorted({a["name"] for a in stale_agents})
                listing = ", ".join(f"{r['taskId']} ({r.get('title') or 'untitled'})" for r in released)
                self.post_message(
                    sender="sweeper",
                    subject="Stale agent tasks released",
                    body=f"{len(released)} task(s) released from offline agents "
                         f"({', '.join(names)}): {listing}",
                    to=None,
                    kind="alert",
                    priority="high",
                )
            self._emit_unlocked("bus.sweep", {
                "released": len(released), "agents": len(stale_ids), "offlineSeconds": offline_seconds,
            })
            self._save()

        return {"released": released, "agents": sorted(a["name"] for a in stale_agents),
                "agentsReaped": len(stale_ids), "tasksReaped": len(released),
                "alerted": bool(released), "sweptAt": now}

    def export_handoff(self, path: str = None, include_done: bool = True,
                       since: int = 0, summary_only: bool = False) -> dict:
        """Render a markdown brief that any next agent (or human) can pick up."""
        with self.lock:
            agents = [self._agent_view_unlocked(a) for a in self.agents.values()]
            board = self.list_tasks(include_done=include_done)
            since = int(since or 0)
            messages = [m for m in self.messages if int(m.get("seq") or 0) > since][-25:]
            if since > 0:
                # Cursor -> wall clock: the newest timestamp we handed out at that seq point.
                cutoff = 0.0
                for message in self.messages:
                    if int(message.get("seq") or 0) <= since:
                        cutoff = max(cutoff, float(message.get("ts") or 0))
                for event in self.events:
                    if int(event.get("seq") or 0) <= since:
                        cutoff = max(cutoff, float(event.get("ts") or 0))
                open_tasks = [t for t in board["tasks"] if t.get("status") in ("todo", "in_progress", "blocked")]
                recent = [t for t in board["tasks"] if float(t.get("updated") or 0) > cutoff]
```

```
                merged = {t["id"]: t for t in open_tasks}
                merged.update({t["id"]: t for t in recent})
                board = {"tasks": list(merged.values()), "count": len(merged)}
            stats = self.stats()

        lines = [
            "# Agent handoff brief",
            "",
            f"Generated: {time.strftime('%Y-%m-%d %H:%M:%S')}  ·  bus v{BUS_VERSION}"
            + (f"  ·  incremental since seq {since}" if since else ""),
            "",
            "## Roster",
            "",
        ]
        if agents:
            lines += ["| Agent | Role | Status | Open tasks | Capabilities |", "|---|---|---|---|---|"]
            for a in agents:
                lines.append(
                    f"| {a['name']} (`{a['id']}`) | {a['role']} | {a['status']} | {a['openTasks']} | "
                    f"{', '.join(a.get('capabilities') or []) or '-'} |"
                )
        else:
            lines.append("_No agents registered yet._")

        lines += ["", "## Task board", ""]
        if board["tasks"]:
            for t in board["tasks"]:
                mark = {"done": "x"}.get(t["status"], " ")
                owner = f" - @{t['assignee']}" if t.get("assignee") else ""
                lines.append(f"- [{mark}] **{t['title']}** ({t['status']}, {t['priority']}){owner}  ")
                if summary_only:
                    continue
                if t.get("detail"):
                    lines.append(f"  {t['detail']}")
                if t.get("result"):
                    lines.append(f"  _Result:_ {t['result']}")
                for artifact in (t.get("artifacts") or [])[:5]:
                    lines.append(f"  _Artifact:_ {artifact}")
        else:
            lines.append("_Task board is empty._")

        if summary_only:
            messages = []
        lines += ["", "## Recent messages", ""]
        if messages:
            for m in messages:
                target = m.get("to") or "broadcast"
                lines.append(
                    f"- **{m['from']} -> {target}** [{m['kind']}/{m['priority']}] "
                    f"{m.get('subject') or '(no subject)'}: {m.get('body', '')[:400]}"
                )
        else:
            lines.append("_No messages._")

        lines += [
            "",
            "## Live bus stats",
            "",
            f"- agents: {stats['agents']} ({stats['agentsOnline']} online)",
            f"- tasks: {stats['tasks']} total · " + ", ".join(f"{k}={v}" for k, v in stats["taskCounts"].items()),
```

```
            f"- messages: {stats['messages']}",
            "",
            "Pick a task with `agent_bus {action:'task_claim', taskId:'...', agentId:'...'}`, "
            "or post status with `agent_bus {action:'post', ...}`.",
            "",
        ]
        text = "\n".join(lines)
        target = None
        if path:
            target = Path(path)
            target.parent.mkdir(parents=True, exist_ok=True)
            target.write_text(text, encoding="utf-8")
        return {"markdown": text, "path": str(target) if target else None, "bytes": len(text.encode("utf-8"))}

    def stats(self) -> dict:
        with self.lock:
            self._expire_leases_unlocked()
            agents = [self._agent_view_unlocked(a) for a in self.agents.values()]
            return {
                "version": BUS_VERSION,
                "agents": len(agents),
                "agentsOnline": sum(1 for a in agents if a["online"]),
                "tasks": len(self.tasks),
                "taskCounts": {s: sum(1 for t in self.tasks.values() if t["status"] == s) for s in TASK_STATUSES},
                "messages": len(self.messages),
                "events": len(self.events),
                "cursor": self.seq,
                "unreadTotal": sum(a["inboxUnread"] for a in agents),
                "agentsReaped": self.agents_reaped,
                "tasksReaped": self.tasks_reaped,
                "lastSweepAt": self.last_sweep_at,
                "serverTime": _now(),
            }

    # -- single entry point used by the HTTP + MCP layers ---------------------

    def handle(self, payload: dict) -> dict:
        action = (payload or {}).get("action", "stats")
        p = payload or {}
        if action == "register":
            return self.register_agent(
                name=p.get("name") or p.get("agent") or "agent",
                role=p.get("role") or "agent",
                capabilities=p.get("capabilities"),
                agent_id=p.get("agentId"),
                ttl=p.get("ttl"),
                meta=p.get("meta"),
            )
        if action == "heartbeat":
            return self.heartbeat(p.get("agentId") or p.get("agent"), p.get("status"))
        if action == "status":
            if p.get("agentId") and p.get("status"):
                return self.set_status(p["agentId"], p["status"])
            return self.stats()
        if action in ("agents", "list_agents"):
            return self.list_agents(bool(p.get("includeOffline", True)))
        if action in ("post", "send"):
            return self.post_message(
                sender=p.get("agentId") or p.get("from") or p.get("agent"),
                body=p.get("body") or p.get("message"),
```

```
                to=p.get("to"),
                subject=p.get("subject"),
                kind=p.get("kind") or "note",
                priority=p.get("priority") or "normal",
                thread_id=p.get("threadId"),
                meta=p.get("meta"),
            )
        if action == "inbox":
            return self.inbox(
                p.get("agentId") or p.get("agent"),
                since=int(p.get("since") or 0),
                limit=int(p.get("limit") or 50),
                unread_only=bool(p.get("unreadOnly")),
                include_broadcast=p.get("includeBroadcast", True),
            )
        if action == "thread":
            return self.read_thread(p.get("threadId") or p.get("id"))
        if action == "mark_read":
            return self.mark_read(
                p.get("agentId") or p.get("agent"),
                p.get("messageIds"),
                bool(p.get("all")),
            )
        if action in ("tasks", "list_tasks"):
            return self.list_tasks(
                p.get("status"), p.get("assignee"), p.get("tag"),
                include_done=p.get("includeDone", True),
            )
        if action == "task_create":
            return self.create_task(
                title=p.get("title"),
                detail=p.get("detail"),
                created_by=p.get("agentId") or p.get("createdBy") or "unknown",
                assignee=p.get("assignee"),
                priority=p.get("priority") or "normal",
                tags=p.get("tags"),
                depends_on=p.get("dependsOn"),
                estimate_minutes=p.get("estimateMinutes"),
            )
        if action == "task_claim":
            return self.claim_task(p.get("taskId") or p.get("id"), p.get("agentId") or p.get("agent"), p.get("leaseSeconds"))
        if action == "task_renew":
            return self.renew_task(p.get("taskId") or p.get("id"), p.get("agentId") or p.get("agent"), p.get("leaseSeconds"))
        if action == "task_release":
            return self.release_task(p.get("taskId") or p.get("id"), p.get("agentId") or p.get("agent"), p.get("note") or "")
        if action == "task_update":
            return self.update_task(
                p.get("taskId") or p.get("id"),
                actor=p.get("agentId") or p.get("actor") or "unknown",
                **{k: p.get(k) for k in ("status", "priority", "assignee", "detail", "tags", "dependsOn", "title") if k in p},
            )
        if action == "task_complete":
            return self.complete_task(
                p.get("taskId") or p.get("id"),
                p.get("agentId") or p.get("agent"),
                result=p.get("result") or "",
                artifacts=p.get("artifacts"),
                status=p.get("status") or "done",
            )
        if action == "task_delete":
```

```
            return self.delete_task(p.get("taskId") or p.get("id"), p.get("actor") or "unknown")
        if action in ("feed", "events"):
            return self.feed(int(p.get("since") or 0), int(p.get("limit") or 100))
        if action in ("export", "handoff"):
            return self.export_handoff(
                p.get("path"),
                bool(p.get("includeDone", True)),
                since=int(p.get("since") or 0),
                summary_only=bool(p.get("summaryOnly")),
            )
        if action in ("sweep", "sweep_stale"):
            return self.sweep_stale(p.get("offlineSeconds") or 900)
        if action == "stats":
            return self.stats()
        raise ValueError(
            "Unknown agent_bus action. Use one of: register, heartbeat, status, agents, post, inbox, "
            "thread, mark_read, tasks, task_create, task_claim, task_renew, task_release, task_update, "
            "task_complete, task_delete, feed, export, sweep, stats."
        )

```

roblox-bridge/auth_core.py

273 lines

Scoped tokens, expiry, revocation, token-bucket limits

```python
#!/usr/bin/env python3
"""
auth_core.py - Scoped access tokens and per-token rate limiting for the bridge.

The single `bridge.token` you already have keeps working unchanged: it is treated
as the full-privilege owner credential. On top of that you can mint named,
expiring, scoped tokens so that:

  * a read-only inspector agent cannot mutate a place,
  * a teammate's CI can push scripts but cannot mint tokens or start tunnels,
  * a demo viewer can watch telemetry without touching Studio,
  * a runaway agent gets throttled instead of flooding the job queue.

Only token *hashes* are stored, and only the first 8 characters of a token are
kept for display. Tokens are shown in full exactly once, when minted.

Zero dependencies.
"""

import hashlib
import json
import os
import secrets
import threading
import time
from pathlib import Path

AUTH_VERSION = "5.3.2"
DEFAULT_STATE_DIR = Path(__file__).resolve().parent / "bridge_state"

ROLE_RANK = {"read": 1, "write": 2, "admin": 3}
ROLE_DESCRIPTIONS = {
    "read": "Inspect only: state, peers, survey, script reads, telemetry.",
    "write": "Everything read can do, plus Studio mutations, jobs and bus writes.",
    "admin": "Full control: token management, tunnel control, queue clearing, audit.",
}

# Paths that require a specific role regardless of the HTTP method.
READ_ONLY_PATHS = {
    "/api/health", "/api/state", "/api/peers", "/api/jobs", "/api/agent-guide",
    "/api/metrics", "/api/audit", "/api/events", "/api/ops", "/api/self-test",
}
ADMIN_PATHS = {"/api/tokens", "/api/audit/verify"}


def _now() -> float:
    return time.time()


def _hash(raw: str) -> str:
    return hashlib.sha256(raw.encode("utf-8")).hexdigest()


class TokenRecord:
    __slots__ = ("id", "label", "role", "created", "expires", "revoked", "last_used",
                 "uses", "rate_limit", "burst", "bucket", "bucket_ts", "token_hash", "prefix")

    def __init__(self, **kw):
        for slot in self.__slots__:
            setattr(self, slot, kw.get(slot))
```

```
61
62      def view(self) -> dict:
63          return {
64              "id": self.id,
65              "label": self.label,
66              "role": self.role,
67              "prefix": self.prefix,
68              "created": self.created,
69              "expires": self.expires,
70              "revoked": bool(self.revoked),
71              "lastUsed": self.last_used,
72              "uses": self.uses,
73              "rateLimitPerSecond": self.rate_limit,
74              "burst": self.burst,
75          }
76
77      def active(self, now: float = None) -> bool:
78          now = now or _now()
79          if self.revoked:
80              return False
81          if self.expires and self.expires < now:
82              return False
83          return True
84
85
86  class TokenStore:
87      """Hashed token registry with role scopes, expiry, revocation and rate limits."""
88
89      def __init__(self, path=None, primary_token: str = "", persist: bool = True, default_rate: float = 20.0):
90          self.path = Path(path) if path else DEFAULT_STATE_DIR / "tokens.json"
91          self.persist = bool(persist)
92          self.lock = threading.RLock()
93          self.default_rate = float(default_rate)
94          self.records = {}       # token id -> TokenRecord
95          self.by_hash = {}       # sha256(token) -> token id
96          self.primary = None     # TokenRecord for the bridge.token owner credential
97          if primary_token:
98              self.primary = TokenRecord(
99                  id="primary", label="owner (bridge.token)", role="admin",
100                 created=_now(), expires=None, revoked=False, last_used=None, uses=0,
101                 rate_limit=0.0, burst=0, bucket=0.0, bucket_ts=_now(),
102                 token_hash=_hash(primary_token), prefix=primary_token[:8],
103             )
104             self.by_hash[self.primary.token_hash] = "primary"
105         self._load()
106
107     # -- persistence ------------------------------------------------------
108
109     def _load(self):
110         if not self.persist or not self.path.is_file():
111             return
112         try:
113             raw = json.loads(self.path.read_text(encoding="utf-8"))
114         except (OSError, ValueError):
115             return
116         for row in raw.get("tokens", []):
117             try:
118                 rec = TokenRecord(
119                     id=row["id"], label=row.get("label") or "", role=row.get("role") or "read",
120                     created=row.get("created") or _now(), expires=row.get("expires"),
```

```
                    revoked=bool(row.get("revoked")), last_used=row.get("lastUsed"), uses=int(row.get("uses") or 0),
                    rate_limit=float(row.get("rateLimitPerSecond") or 0.0), burst=float(row.get("burst") or 0.0),
                    bucket=float(row.get("burst") or 0.0), bucket_ts=_now(),
                    token_hash=row["hash"], prefix=row.get("prefix") or "",
                )
            except (KeyError, TypeError, ValueError):
                continue
            self.records[rec.id] = rec
            self.by_hash[rec.token_hash] = rec.id

    def _save(self):
        if not self.persist:
            return
        try:
            self.path.parent.mkdir(parents=True, exist_ok=True)
            payload = {
                "version": AUTH_VERSION,
                "saved": _now(),
                "tokens": [
                    dict(r.view(), hash=r.token_hash)
                    for r in self.records.values()
                ],
            }
            tmp = self.path.with_suffix(".tmp")
            tmp.write_text(json.dumps(payload, ensure_ascii=False, separators=(",", ":")), encoding="utf-8")
            tmp.chmod(0o600)
            os.replace(tmp, self.path)
        except OSError:
            pass

    # -- authentication ------------------------------------------------------

    def authenticate(self, raw: str, consume_rate: bool = True):
        """Return (record, rate_info) or (None, None) when the token is invalid."""
        if not raw:
            return None, None
        token_hash = _hash(raw)
        with self.lock:
            rec_id = self.by_hash.get(token_hash)
            if not rec_id:
                return None, None
            rec = self.primary if rec_id == "primary" else self.records.get(rec_id)
            if not rec or not rec.active():
                return None, None
            rate_info = self._rate_check_unlocked(rec) if consume_rate else {"allowed": True, "retryAfter": 0}
            if not rate_info["allowed"]:
                return rec, rate_info
            rec.last_used = _now()
            rec.uses = int(rec.uses or 0) + 1
            return rec, rate_info

    def _rate_check_unlocked(self, rec: TokenRecord) -> dict:
        rate = float(rec.rate_limit or 0.0)
        burst = float(rec.burst or rate * 2 or 0.0)
        if rate <= 0:
            return {"allowed": True, "retryAfter": 0, "remaining": None, "limit": 0}
        now = _now()
        elapsed = max(0.0, now - float(rec.bucket_ts or now))
        tokens = min(burst, float(rec.bucket or 0.0) + elapsed * rate)
        if tokens < 1.0:
```

```
            deficit = 1.0 - tokens
            retry = max(1, int(deficit / rate) + 1)
            rec.bucket = tokens
            rec.bucket_ts = now
            return {"allowed": False, "retryAfter": retry, "remaining": 0, "limit": rate}
        rec.bucket = tokens - 1.0
        rec.bucket_ts = now
        return {"allowed": True, "retryAfter": 0, "remaining": int(rec.bucket), "limit": rate}

    # -- management ------------------------------------------------------------

    def create(self, label: str, role: str = "write", ttl_seconds: int = None, rate_limit: float = None, burst: float = None) -> dict:
        role = (role or "write").lower()
        if role not in ROLE_RANK:
            raise ValueError(f"role must be one of: {', '.join(ROLE_RANK)}")
        raw = "arb_" + secrets.token_urlsafe(30)
        rate = self.default_rate if rate_limit is None else float(rate_limit)
        with self.lock:
            rec = TokenRecord(
                id="tok-" + secrets.token_hex(6),
                label=(label or "unnamed")[:120],
                role=role,
                created=_now(),
                expires=(_now() + int(ttl_seconds)) if ttl_seconds else None,
                revoked=False,
                last_used=None,
                uses=0,
                rate_limit=rate,
                burst=float(burst if burst is not None else max(rate * 2, 1.0)),
                bucket=float(burst if burst is not None else max(rate * 2, 1.0)),
                bucket_ts=_now(),
                token_hash=_hash(raw),
                prefix=raw[:8],
            )
            self.records[rec.id] = rec
            self.by_hash[rec.token_hash] = rec.id
            self._save()
            view = rec.view()
            view["token"] = raw
            view["note"] = "Store this token now - only its hash and prefix are retained."
            return view

    def revoke(self, token_id: str) -> dict:
        with self.lock:
            if token_id == "primary":
                raise ValueError("The owner credential (bridge.token) cannot be revoked here; rotate it instead.")
            rec = self.records.get(token_id)
            if not rec:
                raise KeyError(f"Unknown token id: {token_id!r}")
            rec.revoked = True
            self._save()
            return rec.view()

    def list(self) -> dict:
        with self.lock:
            rows = []
            if self.primary:
                rows.append(self.primary.view())
            rows += [r.view() for r in self.records.values()]
        rows.sort(key=lambda r: (r["revoked"], r["created"] or 0))
```

```
        return {
            "tokens": rows,
            "count": len(rows),
            "active": sum(1 for r in rows if not r["revoked"] and (not r["expires"] or r["expires"] > _now())),
            "roles": ROLE_DESCRIPTIONS,
        }

    def owner_token(self) -> str:
        """Only used by tests/first-run bootstrap; never exposed over HTTP."""
        return ""

    @staticmethod
    def role_allows(role: str, required: str) -> bool:
        return ROLE_RANK.get(role or "read", 0) >= ROLE_RANK.get(required or "read", 0)

    def handle(self, payload: dict) -> dict:
        action = (payload or {}).get("action", "list")
        p = payload or {}
        if action == "list":
            return self.list()
        if action == "create":
            return self.create(
                p.get("label") or "unnamed",
                p.get("role") or "write",
                p.get("ttlSeconds"),
                p.get("rateLimitPerSecond"),
                p.get("burst"),
            )
        if action == "revoke":
            return self.revoke(p.get("id") or p.get("tokenId"))
        if action == "roles":
            return {"roles": ROLE_DESCRIPTIONS, "rank": ROLE_RANK}
        raise ValueError("Unknown token action. Use list, create, revoke or roles.")

```

roblox-bridge/telemetry.py

471 lines

Metrics, SSE event stream, hash-chained audit log

```python
#!/usr/bin/env python3
"""
telemetry.py - Metrics, live event stream, and tamper-evident audit log for the
Arena Roblox Studio bridge.

Zero-dependency. Three cooperating pieces:

  Metrics      counters / gauges / latency histograms with label sets, plus a
               Prometheus text exposition and a JSON snapshot for the dashboard.
  EventStream  bounded, sequence-numbered event ring with condition-variable
               waits, powering `GET /api/events` (Server-Sent Events).
  AuditLog     append-only JSONL log where every record chains the SHA-256 hash
               of its predecessor, so silent edits/tampering are detectable with
               `verify()`.

All three are thread-safe and safe to embed in server.py.
"""

import hashlib
import json
import os
import threading
import time
from collections import deque
from pathlib import Path

TELEMETRY_VERSION = "5.3.2"
DEFAULT_STATE_DIR = Path(__file__).resolve().parent / "bridge_state"

# Bounded sample count per histogram key; percentiles are computed from this
# reservoir and the true count/sum/min/max are kept exactly.
_HIST_SAMPLES = 2048


def _now() -> float:
    return time.time()


def _file_lock(fh):
    """Best-effort advisory exclusive lock for cross-process audit appends."""
    try:
        import fcntl
        fcntl.flock(fh.fileno(), fcntl.LOCK_EX)
        return "fcntl"
    except (ImportError, OSError):
        try:
            import msvcrt
            fh.seek(0)
            msvcrt.locking(fh.fileno(), msvcrt.LK_LOCK, 1)
            return "msvcrt"
        except (ImportError, OSError):
            return None


def _file_unlock(fh, kind):
    try:
        if kind == "fcntl":
            import fcntl
            fcntl.flock(fh.fileno(), fcntl.LOCK_UN)
        elif kind == "msvcrt":
```

```
            import msvcrt
            fh.seek(0)
            msvcrt.locking(fh.fileno(), msvcrt.LK_UNLCK, 1)
    except (ImportError, OSError):
        pass


def _label_key(labels: dict) -> str:
    if not labels:
        return ""
    return ",".join(f"{k}={labels[k]}" for k in sorted(labels))


def _fmt_num(value) -> str:
    if isinstance(value, bool):
        return "1" if value else "0"
    if isinstance(value, int):
        return str(value)
    if isinstance(value, float):
        if value == int(value) and abs(value) < 1e15:
            return str(int(value))
        return f"{value:.6f}".rstrip("0").rstrip(".")
    return str(value)


class Metrics:
    """Counter/gauge/histogram registry with Prometheus + JSON output."""

    def __init__(self):
        self.lock = threading.Lock()
        self.started = _now()
        self.counters = {}   # key -> {"name","labels","value"}
        self.gauges = {}
        self.histograms = {}  # key -> {"name","labels","count","sum","min","max","samples":deque}
        self.histogram_order = {}

    def _inc_unlocked(self, name: str, labels: dict, value: float):
        key = (name, _label_key(labels))
        row = self.counters.get(key)
        if row is None:
            row = {"name": name, "labels": dict(labels or {}), "value": 0.0}
            self.counters[key] = row
        row["value"] += value
        return row

    def inc(self, name: str, value: float = 1, labels: dict = None):
        with self.lock:
            self._inc_unlocked(name, labels or {}, float(value))

    def gauge(self, name: str, value: float, labels: dict = None):
        with self.lock:
            key = (name, _label_key(labels or {}))
            self.gauges[key] = {"name": name, "labels": dict(labels or {}), "value": float(value)}

    def observe(self, name: str, value: float, labels: dict = None, buckets=None):
        value = float(value)
        with self.lock:
            key = (name, _label_key(labels or {}))
            row = self.histograms.get(key)
            if row is None:
```

```
                row = {
                    "name": name,
                    "labels": dict(labels or {}),
                    "count": 0,
                    "sum": 0.0,
                    "min": value,
                    "max": value,
                    "samples": deque(maxlen=_HIST_SAMPLES),
                    "buckets": list(buckets or ()),
                    "bucketCounts": {b: 0 for b in (buckets or ())},
                }
                self.histograms[key] = row
            row["count"] += 1
            row["sum"] += value
            row["min"] = min(row["min"], value)
            row["max"] = max(row["max"], value)
            row["samples"].append(value)
            for b in row["buckets"]:
                if value <= b:
                    row["bucketCounts"][b] += 1
            self.histogram_order[key] = self.histogram_order.pop(
                key, len(self.histogram_order)
            )
            return row

    @staticmethod
    def _percentile(sorted_samples, p: float) -> float:
        if not sorted_samples:
            return 0.0
        if len(sorted_samples) == 1:
            return float(sorted_samples[0])
        rank = (len(sorted_samples) - 1) * p
        lo = int(rank)
        hi = min(lo + 1, len(sorted_samples) - 1)
        frac = rank - lo
        return float(sorted_samples[lo] * (1 - frac) + sorted_samples[hi] * frac)

    def summarize_histogram(self, row: dict) -> dict:
        samples = sorted(row["samples"])
        return {
            "count": row["count"],
            "sum": round(row["sum"], 3),
            "min": round(row["min"], 3),
            "max": round(row["max"], 3),
            "mean": round(row["sum"] / row["count"], 3) if row["count"] else 0.0,
            "p50": round(self._percentile(samples, 0.50), 3),
            "p90": round(self._percentile(samples, 0.90), 3),
            "p95": round(self._percentile(samples, 0.95), 3),
            "p99": round(self._percentile(samples, 0.99), 3),
        }

    def snapshot(self, uptime: float = None) -> dict:
        with self.lock:
            counters = [dict(v) for v in self.counters.values()]
            gauges = [dict(v) for v in self.gauges.values()]
            histograms = []
            for row in self.histograms.values():
                entry = {"name": row["name"], "labels": row["labels"]}
                entry.update(self.summarize_histogram(row))
                histograms.append(entry)
```

```
        counters.sort(key=lambda r: (r["name"], _label_key(r["labels"])))
        gauges.sort(key=lambda r: (r["name"], _label_key(r["labels"])))
        histograms.sort(key=lambda r: r["name"])
        return {
            "version": TELEMETRY_VERSION,
            "uptimeSeconds": round(uptime if uptime is not None else (_now() - self.started), 2),
            "counters": counters,
            "gauges": gauges,
            "histograms": histograms,
        }

    def prometheus(self, extra_gauges: dict = None) -> str:
        lines = []
        with self.lock:
            counters = list(self.counters.values())
            gauges = list(self.gauges.values())
            histograms = list(self.histograms.values())
        seen_types = set()

        def _decl(name, kind):
            if name not in seen_types:
                seen_types.add(name)
                lines.append(f"# TYPE {name} {kind}")

        for row in counters:
            _decl(row["name"], "counter")
            lines.append(f"{row['name']}{self._fmt_labels(row['labels'])} {_fmt_num(row['value'])}")
        for row in gauges:
            _decl(row["name"], "gauge")
            lines.append(f"{row['name']}{self._fmt_labels(row['labels'])} {_fmt_num(row['value'])}")
        for row in histograms:
            name = row["name"]
            _decl(name, "histogram")
            labels = dict(row["labels"])
            total = row["count"] or 1
            for b, count in row["bucketCounts"].items():
                bucket_labels = dict(labels)
                bucket_labels["le"] = b
                lines.append(f"{name}_bucket{self._fmt_labels(bucket_labels)} {count}")
            bucket_labels = dict(labels)
            bucket_labels["le"] = "+Inf"
            lines.append(f"{name}_bucket{self._fmt_labels(bucket_labels)} {row['count']}")
            summary = self.summarize_histogram(row)
            lines.append(f"{name}_sum{self._fmt_labels(labels)} {_fmt_num(round(row['sum'], 3))}")
            lines.append(f"{name}_count{self._fmt_labels(labels)} {row['count']}")
            for q, key in (("0.5", "p50"), ("0.9", "p90"), ("0.95", "p95"), ("0.99", "p99")):
                q_labels = dict(labels)
                q_labels["quantile"] = q
                lines.append(f"{name}{self._fmt_labels(q_labels)} {_fmt_num(summary[key])}")
            _ = total
        for name, value in (extra_gauges or {}).items():
            try:
                _decl(name, "gauge")
                lines.append(f"{name} {_fmt_num(float(value))}")
            except (TypeError, ValueError):
                continue
        return "\n".join(lines) + "\n"

    @staticmethod
    def _fmt_labels(labels: dict) -> str:
```

```
        if not labels:
            return ""
        parts = []
        for key in sorted(labels):
            value = str(labels[key]).replace("\\", "\\\\").replace('"', '\\"').replace("\n", " ")
            parts.append(f'{key}="{value}"')
        return "{" + ",".join(parts) + "}"


class EventStream:
    """Sequence-numbered event ring with blocking tail reads (SSE friendly)."""

    def __init__(self, max_events: int = 1500):
        self.lock = threading.Lock()
        self.cv = threading.Condition(self.lock)
        self.events = deque(maxlen=max_events)
        self.seq = 0

    def emit(self, kind: str, data: dict = None, level: str = "info") -> dict:
        with self.cv:
            self.seq += 1
            event = {
                "seq": self.seq,
                "ts": _now(),
                "kind": kind,
                "level": level,
                "data": data or {},
            }
            self.events.append(event)
            self.cv.notify_all()
            return event

    def since(self, since: int = 0, limit: int = 200, kinds=None) -> dict:
        limit = max(1, min(int(limit or 200), 1000))
        with self.lock:
            rows = [e for e in self.events if e["seq"] > since]
            if kinds:
                wanted = {k.strip() for k in str(kinds).split(",") if k.strip()}
                rows = [e for e in rows if any(e["kind"].startswith(w) for w in wanted)]
            rows = rows[-limit:]
            cursor = self.seq
        return {"events": rows, "count": len(rows), "cursor": cursor}

    def tail(self, cursor: int, timeout: float = 15.0, limit: int = 100) -> dict:
        deadline = time.monotonic() + max(0.0, timeout)
        with self.cv:
            while self.seq <= cursor:
                remaining = deadline - time.monotonic()
                if remaining <= 0:
                    return {"events": [], "count": 0, "cursor": self.seq, "timeout": True}
                self.cv.wait(timeout=min(remaining, 1.0))
            rows = [e for e in self.events if e["seq"] > cursor][:limit]
            return {"events": rows, "count": len(rows), "cursor": self.seq, "timeout": False}


class AuditLog:
    """Append-only, hash-chained audit log (JSONL)."""

    GENESIS = "0" * 64

```

```
    def __init__(self, path=None, persist: bool = True, max_memory: int = 5000):
        self.path = Path(path) if path else DEFAULT_STATE_DIR / "audit.jsonl"
        self.persist = bool(persist)
        self.lock = threading.Lock()
        self.entries = deque(maxlen=max_memory)
        self.last_hash = self.GENESIS
        self.seq = 0
        self._load()

    def _load(self):
        if not self.persist or not self.path.is_file():
            return
        try:
            with self.path.open("r", encoding="utf-8") as fh:
                for line in fh:
                    line = line.strip()
                    if not line:
                        continue
                    try:
                        row = json.loads(line)
                    except ValueError:
                        continue
                    self.entries.append(row)
                    self.last_hash = row.get("hash") or self.last_hash
                    self.seq = max(self.seq, int(row.get("seq") or 0))
        except OSError:
            pass

    def _read_disk_tail(self, fh) -> dict:
        """Read the last complete JSONL record from an open file handle."""
        try:
            fh.seek(0, os.SEEK_END)
            size = fh.tell()
            window = min(size, 16384)
            fh.seek(size - window)
            chunk = fh.read()
            lines = [ln for ln in chunk.splitlines() if ln.strip()]
            if not lines:
                return {}
            return json.loads(lines[-1])
        except (OSError, ValueError):
            return {}

    def _sync_head_from_disk(self):
        """Adopt a newer on-disk head so concurrent writers keep one chain."""
        try:
            with self.path.open("r", encoding="utf-8") as fh:
                row = self._read_disk_tail(fh)
        except OSError:
            return
        head = row.get("hash")
        if head and head != self.last_hash:
            self.last_hash = head
            self.seq = max(self.seq, int(row.get("seq") or 0))

    def append(self, action: str, actor: str = "system", target: str = "", detail=None, ip: str = "", outcome: str = "ok") -> dict:
        with self.lock:
            if not self.persist:
                self._append_unlocked(action, actor, target, detail, ip, outcome)
                return dict(self.entries[-1])
```

```
            self.path.parent.mkdir(parents=True, exist_ok=True)
            try:
                with self.path.open("a+", encoding="utf-8") as fh:
                    lock = _file_lock(fh)
                    try:
                        self._sync_head_from_disk()
                        entry = self._append_unlocked(action, actor, target, detail, ip, outcome)
                        fh.write(json.dumps(entry, ensure_ascii=False, separators=(",", ":")) + "\n")
                        fh.flush()
                    finally:
                        _file_unlock(fh, lock)
                return dict(entry)
            except OSError:
                entry = self._append_unlocked(action, actor, target, detail, ip, outcome)
                return dict(entry)

    def _append_unlocked(self, action, actor, target, detail, ip, outcome) -> dict:
        self.seq += 1
        entry = {
            "seq": self.seq,
            "ts": _now(),
            "action": action,
            "actor": actor or "system",
            "target": target or "",
            "outcome": outcome,
            "ip": ip or "",
            "detail": detail if isinstance(detail, (dict, list, str, int, float, type(None))) else str(detail),
            "prev": self.last_hash,
        }
        canonical = json.dumps(entry, sort_keys=True, separators=(",", ":"), ensure_ascii=False)
        entry["hash"] = hashlib.sha256(canonical.encode("utf-8")).hexdigest()
        self.last_hash = entry["hash"]
        self.entries.append(entry)
        return entry

    def tail(self, limit: int = 100, action: str = None) -> dict:
        with self.lock:
            rows = list(self.entries)
        if action:
            rows = [r for r in rows if action in str(r.get("action", ""))]
        rows = rows[-max(1, min(int(limit or 100), 2000)):]
        rows.reverse()
        return {"entries": rows, "count": len(rows), "cursor": self.seq}

    def verify(self) -> dict:
        """Recompute the whole chain. Detects edit, reorder, deletion or insertion."""
        with self.lock:
            rows = list(self.entries)
        prev = self.GENESIS
        for index, row in enumerate(rows):
            stored = row.get("hash")
            body = {k: v for k, v in row.items() if k != "hash"}
            canonical = json.dumps(body, sort_keys=True, separators=(",", ":"), ensure_ascii=False)
            expected = hashlib.sha256(canonical.encode("utf-8")).hexdigest()
            if row.get("prev") != prev:
                return {
                    "ok": False,
                    "checked": index + 1,
                    "brokenAt": row.get("seq"),
                    "reason": "prev-hash mismatch (entry inserted, removed or reordered)",
```

```
                }
            if expected != stored:
                return {
                    "ok": False,
                    "checked": index + 1,
                    "brokenAt": row.get("seq"),
                    "reason": "content hash mismatch (entry was edited)",
                }
            prev = stored
        return {
            "ok": True,
            "checked": len(rows),
            "head": prev,
            "entries": len(rows),
            "file": str(self.path) if self.persist else None,
        }


class Telemetry:
    """Convenience container wired into BridgeState."""

    def __init__(self, state_dir=None, persist: bool = True):
        state_dir = Path(state_dir) if state_dir else DEFAULT_STATE_DIR
        self.metrics = Metrics()
        self.events = EventStream()
        self.audit = AuditLog(state_dir / "audit.jsonl", persist=persist)
        self.started = _now()

    @property
    def uptime(self) -> float:
        return _now() - self.started

    def record_job(self, job: dict):
        """Called when a job finishes: counters + latency histogram + event."""
        ok = bool(job.get("ok"))
        labels = {"type": job.get("type") or "unknown", "dm": job.get("dm") or job.get("target_dm") or "auto"}
        self.metrics.inc("bridge_jobs_total", 1, dict(labels, outcome="ok" if ok else "error"))
        duration = job.get("duration_ms")
        if isinstance(duration, (int, float)):
            self.metrics.observe("bridge_job_duration_ms", float(duration), labels)
        self.events.emit(
            "job.finish",
            {
                "id": job.get("id"),
                "type": job.get("type"),
                "status": job.get("status"),
                "durationMs": duration,
                "error": job.get("error"),
            },
            level="info" if ok else "error",
        )

```

roblox-bridge/tools/seed_agent_bus.py

142 lines

Idempotent Agent Bus seeding (online or offline)

```python
#!/usr/bin/env python3
"""
seed_agent_bus.py - Populate the live bridge Agent Bus with the partner work order.

Reads `handoff/bus_seed.json` (agents, tasks, messages) and posts it to a running
bridge over HTTP, or writes it into an offline state directory with `--offline`.

Usage:
    python3 tools/seed_agent_bus.py                      # uses BRIDGE_URL/BRIDGE_TOKEN
    python3 tools/seed_agent_bus.py --url http://127.0.0.1:8077 --token <token>
    python3 tools/seed_agent_bus.py --offline --state-dir ./bridge_state
    python3 tools/seed_agent_bus.py --dry-run

Idempotent: re-running matches agents by name and skips tasks whose title
already exists on the board.
"""

import argparse
import json
import os
import sys
import urllib.error
import urllib.request
from pathlib import Path

HERE = Path(__file__).resolve().parent
ROOT = HERE.parent.parent
DEFAULT_SEED = ROOT / "handoff" / "bus_seed.json"


def http(url: str, token: str, payload: dict, timeout: float = 20.0) -> dict:
    data = json.dumps(payload).encode("utf-8")
    headers = {"Content-Type": "application/json"}
    if token:
        headers["X-Arena-Token"] = token
    req = urllib.request.Request(url.rstrip("/") + "/api/bus", data=data, method="POST", headers=headers)
    try:
        with urllib.request.urlopen(req, timeout=timeout) as resp:
            return json.loads(resp.read().decode("utf-8"))
    except urllib.error.HTTPError as exc:
        raise RuntimeError(f"HTTP {exc.code}: {exc.read().decode('utf-8', 'replace')[:300]}") from exc
    except urllib.error.URLError as exc:
        raise RuntimeError(f"Cannot reach bridge at {url}: {exc.reason}") from exc


def main() -> int:
    ap = argparse.ArgumentParser(description=__doc__, formatter_class=argparse.RawDescriptionHelpFormatter)
    ap.add_argument("--url", default=os.environ.get("BRIDGE_URL", "http://127.0.0.1:8077"))
    ap.add_argument("--token", default=os.environ.get("BRIDGE_TOKEN") or None)
    ap.add_argument("--seed", default=str(DEFAULT_SEED))
    ap.add_argument("--offline", action="store_true", help="Write directly to a local state dir (no server)")
    ap.add_argument("--state-dir", default=None, help="State dir for --offline (default roblox-bridge/bridge_state)")
    ap.add_argument("--dry-run", action="store_true")
    args = ap.parse_args()

    seed_path = Path(args.seed)
    seed = json.loads(seed_path.read_text(encoding="utf-8"))

    if not args.token:
        token_file = HERE.parent / "bridge.token"
```

```
        if token_file.is_file():
            args.token = token_file.read_text(encoding="utf-8").strip() or None

    if args.offline:
        sys.path.insert(0, str(HERE.parent))
        from bus_core import AgentBus

        bus = AgentBus(Path(args.state_dir) / "bus.json" if args.state_dir else None)
        call = lambda payload: bus.handle(payload)  # noqa: E731
        existing_agents = bus.list_agents()["agents"]
        existing_tasks = bus.list_tasks()["tasks"]
    else:
        call = lambda payload: http(args.url, args.token, payload)  # noqa: E731
        existing_agents = call({"action": "agents"}).get("agents", [])
        existing_tasks = call({"action": "tasks"}).get("tasks", [])

    if args.dry_run:
        print(json.dumps({"agents": seed.get("agents", []), "tasks": seed.get("tasks", []),
                          "messages": seed.get("messages", [])}, indent=2, ensure_ascii=False))
        return 0

    registered = {}
    for agent in seed.get("agents", []):
        row = call({
            "action": "register",
            "name": agent["name"],
            "role": agent.get("role", "agent"),
            "capabilities": agent.get("capabilities", []),
        })
        registered[agent["name"]] = row
        print(f"[agent] {row['name']:<18} {row['id']}  role={row['role']}")

    known_titles = {t.get("title") for t in existing_tasks}
    created = 0
    for task in seed.get("tasks", []):
        if task.get("title") in known_titles:
            print(f"[task ] skip (exists) {task['title']}")
            continue
        row = call({
            "action": "task_create",
            "title": task["title"],
            "detail": task.get("detail", ""),
            "agentId": "seed",
            "priority": task.get("priority", "normal"),
            "tags": task.get("tags", []),
        })
        created += 1
        print(f"[task ] {row['id']}  {row['priority']:<8} {row['title']}")
        if task.get("result") or task.get("status") in ("done", "cancelled"):
            try:
                call({
                    "action": "task_complete",
                    "taskId": row["id"],
                    "agentId": "seed",
                    "result": task.get("result") or "completed",
                    "artifacts": task.get("artifacts") or [],
                    "status": task.get("status") or "done",
                })
                print(f"[done ] {row['title']}  {task.get('result', '')[:80]}")
            except RuntimeError as exc:
```

```
                print(f"[warn ] could not complete {row['id']}: {exc}")

    posted = 0
    for message in (seed.get("messages", []) if (created or not existing_tasks) else []):
        sender = registered.get(message.get("from", ""), {"id": message.get("from", "seed")})
        row = call({
            "action": "post",
            "agentId": sender["id"],
            "subject": message.get("subject", ""),
            "body": message.get("body", ""),
            "kind": message.get("kind", "note"),
            "priority": message.get("priority", "normal"),
        })
        posted += 1
        print(f"[msg  ] {row['id']}  {row['subject']}")

    print(f"\nseeded {len(registered)} agents, {created} new tasks, {posted} messages")
    return 0


if __name__ == "__main__":
    sys.exit(main())

```

jobs/measure_tunnel_latency.py

241 lines

G2: p50/p95 tunnel latency measurement (stdlib only)

```python
#!/usr/bin/env python3
"""
measure_tunnel_latency.py - how much does the public tunnel cost per Studio call?

Runs the same Studio job through two bridge URLs (typically localhost and the
public tunnel) and reports p50 / p95 / max round-trip time per tool. Stdlib only,
so it runs anywhere Python 3 does.

    # one target (writes the raw samples to JSON)
    python3 jobs/measure_tunnel_latency.py --url http://127.0.0.1:8077 --runs 20

    # compare local against the tunnel and emit a markdown table
    python3 jobs/measure_tunnel_latency.py \
        --url local=http://127.0.0.1:8077 \
        --url tunnel=https://your-name.trycloudflare.com \
        --token "$BRIDGE_TOKEN" --runs 20 --json-out jobs/tunnel_latency.json

Exit codes: 0 measured, 2 token rejected, 3 no Studio peer (nothing to measure),
4 every request failed.
"""

import argparse
import json
import os
import statistics
import sys
import time
import urllib.error
import urllib.request

DEFAULT_TOOLS = "ping_studio,get_studio_state,script_read"
TOOL_PAYLOADS = {
    "ping_studio": {},
    "get_studio_state": {},
    "script_read": {"path": "ServerScriptService"},
}


def parse_target(value: str):
    """Accept 'label=url' or a bare url."""
    if "=" in value and value.split("=", 1)[0] and not value.startswith("http"):
        label, url = value.split("=", 1)
        return label.strip(), url.strip().rstrip("/")
    return "bridge", value.strip().rstrip("/")


def post_job(base_url: str, tool: str, token: str, timeout: float):
    """POST one Studio job and return (elapsed_ms, job_dict)."""
    payload = {
        "type": tool,
        "payload": TOOL_PAYLOADS.get(tool, {}),
        "wait": timeout,
        "dm": "edit",
        "note": "measure_tunnel_latency",
    }
    data = json.dumps(payload).encode("utf-8")
    headers = {"Content-Type": "application/json"}
    if token:
        headers["Authorization"] = f"Bearer {token}"
    request = urllib.request.Request(base_url + "/api/jobs", data=data, method="POST", headers=headers)
```

```
    started = time.perf_counter()
    with urllib.request.urlopen(request, timeout=timeout + 15) as response:
        body = response.read().decode("utf-8")
    elapsed_ms = (time.perf_counter() - started) * 1000.0
    try:
        job = json.loads(body)
    except ValueError:
        job = {"status": "error", "error": body[:200]}
    return elapsed_ms, job


def percentile(values, fraction: float) -> float:
    """Nearest-rank percentile; deterministic for small samples."""
    if not values:
        return 0.0
    ordered = sorted(values)
    if len(ordered) == 1:
        return ordered[0]
    rank = max(1, min(len(ordered), int(round(fraction * len(ordered) + 0.5))))
    return ordered[rank - 1]


def measure(targets, tools, token, runs, timeout, warmup, quiet=False):
    """Return {label: {tool: {"samples": [...], "errors": [...]}}} plus a fatal reason if any."""
    results = {}
    fatal = None
    for label, base in targets:
        results[label] = {}
        for tool in tools:
            samples, errors = [], []
            attempts = runs + max(0, warmup)
            for index in range(attempts):
                try:
                    elapsed, job = post_job(base, tool, token, timeout)
                except urllib.error.HTTPError as exc:
                    detail = exc.read().decode("utf-8", "replace")[:300]
                    if exc.code == 401:
                        fatal = (
                            f"{label}: token rejected (HTTP 401). Pass --token or set BRIDGE_TOKEN; "
                            f"server said: {detail}"
                        )
                        break
                    errors.append(f"HTTP {exc.code}: {detail}")
                    continue
                except (urllib.error.URLError, TimeoutError, OSError) as exc:
                    errors.append(f"network: {exc}")
                    continue
                if job.get("status") == "error":
                    message = str(job.get("error") or "")
                    errors.append(message or "job failed")
                    if "no peer" in message.lower() or "no studio" in message.lower():
                        fatal = fatal or (
                            f"{label}: no Studio peer connected to the bridge, so there is nothing to time. "
                            "Open the place with the ArenaBridge plugin and retry."
                        )
                    continue
                if index >= warmup:
                    samples.append(round(elapsed, 2))
            results[label][tool] = {"samples": samples, "errors": errors}
    return results, fatal
```

```
121
122
123 def summarize(entry):
124     samples = entry["samples"]
125     return {
126         "count": len(samples),
127         "p50": round(percentile(samples, 0.50), 2) if samples else None,
128         "p95": round(percentile(samples, 0.95), 2) if samples else None,
129         "max": round(max(samples), 2) if samples else None,
130         "mean": round(statistics.fmean(samples), 2) if samples else None,
131         "errors": len(entry["errors"]),
132     }
133
134
135 def render(results, tools, runs):
136     summary = {label: {tool: summarize(results[label][tool]) for tool in tools} for label in results}
137     lines = []
138     for label, rows in summary.items():
139         lines.append(f"== {label} ==")
140         lines.append(f"{'tool':<22}{'n':>4}{'p50 ms':>10}{'p95 ms':>10}{'max ms':>10}{'errors':>8}")
141         for tool in tools:
142             row = rows[tool]
143             cells = [
144                 f"{tool:<22}",
145                 f"{row['count']:>4}",
146                 f"{row['p50'] if row['p50'] is not None else '-':>10}",
147                 f"{row['p95'] if row['p95'] is not None else '-':>10}",
148                 f"{row['max'] if row['max'] is not None else '-':>10}",
149                 f"{row['errors']:>8}",
150             ]
151             lines.append("".join(cells))
152         lines.append("")
153     return summary, lines
154
155
156 def render_markdown(summary, tools, labels):
157     header = "| Tool | " + " | ".join(f"{label} p50 / p95 (ms)" for label in labels)
158     if len(labels) == 2:
159         header += " | delta p50 |"
160     header += " |"
161     sep = "|---" * (header.count("|") - 1) + "|"
162     rows = [header, sep]
163     for tool in tools:
164         cells = [tool]
165         for label in labels:
166             row = summary[label][tool]
167             p50 = row["p50"] if row["p50"] is not None else "n/a"
168             p95 = row["p95"] if row["p95"] is not None else "n/a"
169             cells.append(f"{p50} / {p95}")
170         if len(labels) == 2:
171             a = summary[labels[0]][tool]["p50"]
172             b = summary[labels[1]][tool]["p50"]
173             cells.append(f"{round(b - a, 2)}" if a is not None and b is not None else "n/a")
174         rows.append("| " + " | ".join(cells) + " |")
175     return "\n".join(rows)
176
177
178 def main(argv=None):
179     parser = argparse.ArgumentParser(description=__doc__, formatter_class=argparse.RawDescriptionHelpFormatter)
180     parser.add_argument("--url", action="append", default=None,
```

```
                        help="Bridge URL, optionally labelled: --url local=http://127.0.0.1:8077")
    parser.add_argument("--token", default=os.environ.get("BRIDGE_TOKEN", ""),
                        help="Bridge token (default: $BRIDGE_TOKEN)")
    parser.add_argument("--runs", type=int, default=20, help="Samples per tool (default: 20)")
    parser.add_argument("--warmup", type=int, default=1, help="Discarded warm-up calls per tool")
    parser.add_argument("--tools", default=DEFAULT_TOOLS, help=f"Comma list (default: {DEFAULT_TOOLS})")
    parser.add_argument("--timeout", type=float, default=60.0, help="Per-job wait in seconds")
    parser.add_argument("--json-out", default=None, help="Write raw samples and summary JSON here")
    parser.add_argument("--markdown", action="store_true", help="Print only the markdown table")
    args = parser.parse_args(argv)

    targets = [parse_target(u) for u in (args.url or ["http://127.0.0.1:8077"])]
    tools = [t.strip() for t in args.tools.split(",") if t.strip()]
    results, fatal = measure(targets, tools, args.token, max(1, args.runs), args.timeout,
                             max(0, args.warmup))
    summary, lines = render(results, tools, args.runs)

    if args.json_out:
        payload = {
            "generated": time.strftime("%Y-%m-%dT%H:%M:%S"),
            "runs": args.runs,
            "warmup": args.warmup,
            "targets": {label: url for label, url in targets},
            "tools": tools,
            "summary": summary,
            "samples": {label: {tool: results[label][tool]["samples"] for tool in tools} for label in results},
            "errors": {label: {tool: results[label][tool]["errors"] for tool in tools} for label in results},
            "fatal": fatal,
        }
        out_path = os.path.abspath(args.json_out)
        os.makedirs(os.path.dirname(out_path) or ".", exist_ok=True)
        with open(out_path, "w", encoding="utf-8") as handle:
            json.dump(payload, handle, indent=2)
        print(f"[written] {out_path}", file=sys.stderr)

    if args.markdown:
        labels = list(summary)
        print(render_markdown(summary, tools, labels))
    else:
        print("\n".join(lines))
        if len(summary) > 1:
            print("Markdown excerpt for docs/OPS.md:\n")
            print(render_markdown(summary, tools, list(summary)))

    measured = sum(1 for label in summary for tool in tools if summary[label][tool]["count"])
    if fatal and "token rejected" in fatal:
        print(f"error: {fatal}", file=sys.stderr)
        return 2
    if measured == 0:
        if fatal:
            print(f"error: {fatal}", file=sys.stderr)
            return 3
        print("error: every request failed; check the URL and the bridge log", file=sys.stderr)
        return 4
    if fatal:
        print(f"note: {fatal}", file=sys.stderr)
    return 0


if __name__ == "__main__":
```

```
    sys.exit(main())

```

jobs/live_acceptance.py

198 lines

G7: acceptance run with paste-ready evidence JSON

```python
#!/usr/bin/env python3
"""
live_acceptance.py - the G7 acceptance run, as a script instead of a checklist.

It talks to a *running* bridge (local or through the public tunnel) and records the
evidence the unit tests cannot produce: a real Studio peer, a real public URL, and
the whole path from an MCP client through that URL.

    python3 jobs/live_acceptance.py --url http://127.0.0.1:8077 --token "$BRIDGE_TOKEN"
    python3 jobs/live_acceptance.py --url https://your-name.trycloudflare.com \
        --token "$BRIDGE_TOKEN" --self-test --json-out handoff/live-acceptance.json

Every check reports pass / fail / skipped with the reason, and the JSON block is
ready to paste under "Live acceptance" in docs/OPS.md.
"""

import argparse
import json
import os
import sys
import time
import urllib.error
import urllib.request

STEPS = []


def record(name, status, detail, data=None):
    STEPS.append({"step": name, "status": status, "detail": detail, "data": data})
    mark = {"pass": "PASS", "fail": "FAIL", "skipped": "SKIP"}[status]
    print(f"[{mark}] {name}: {detail}")
    return status == "pass"


def http_json(base, path, token=None, method="GET", body=None, timeout=20):
    url = base.rstrip("/") + path
    data = json.dumps(body).encode("utf-8") if body is not None else None
    headers = {"Content-Type": "application/json"}
    if token:
        headers["Authorization"] = f"Bearer {token}"
    request = urllib.request.Request(url, data=data, method=method, headers=headers)
    with urllib.request.urlopen(request, timeout=timeout) as response:
        raw = response.read().decode("utf-8")
    return json.loads(raw) if raw.strip().startswith(("{", "[")) else raw


def mcp_call(base, token, name, arguments, timeout=90):
    payload = {"jsonrpc": "2.0", "id": 1, "method": "tools/call",
               "params": {"name": name, "arguments": arguments}}
    result = http_json(base, "/mcp", token=token, method="POST", body=payload, timeout=timeout)
    if "error" in result:
        raise RuntimeError(result["error"].get("message") or "MCP error")
    content = result.get("result", {})
    if content.get("isError"):
        raise RuntimeError(json.dumps(content)[:300])
    text = content.get("content", [{}])[0].get("text", "{}")
    try:
        return json.loads(text)
    except ValueError:
        return {"text": text}
```

```
61
62
63  def main(argv=None):
64      parser = argparse.ArgumentParser(description=__doc__, formatter_class=argparse.RawDescriptionHelpFormatter)
65      parser.add_argument("--url", default="http://127.0.0.1:8077", help="Bridge base URL (local or tunnel)")
66      parser.add_argument("--token", default=os.environ.get("BRIDGE_TOKEN", ""), help="Bridge token")
67      parser.add_argument("--self-test", action="store_true",
68                          help="Also run the bridge self-test through /mcp (slow; touches every tool)")
69      parser.add_argument("--public-url", default=None,
70                          help="Also verify the public URL reported by /api/tunnel (default: the tunnel's own URL)")
71      parser.add_argument("--json-out", default=None, help="Write the evidence JSON here")
72      args = parser.parse_args(argv)
73
74      base = args.url.rstrip("/")
75      token = args.token
76      started = time.time()
77      print(f"Arena bridge live acceptance · {base} · {time.strftime('%Y-%m-%d %H:%M:%S')}\n")
78
79      # 1. The bridge answers and reports its version.
80      try:
81          health = http_json(base, "/api/health")
82      except Exception as exc:  # noqa: BLE001
83          record("bridge-reachable", "fail", f"{base} did not answer /api/health: {exc}")
84          return finish(args, base, started, fatal=True)
85      record("bridge-reachable", "pass",
86             f"v{health.get('version')} · auth {'on' if health.get('authEnabled') else 'off'} · "
87             f"queued {health.get('queued')} · peers {health.get('peers')}", health)
88
89      # 2. Studio is connected through the plugin.
90      try:
91          peers = http_json(base, "/api/peers", token=token)
92      except urllib.error.HTTPError as exc:
93          record("studio-peer", "fail", f"/api/peers -> HTTP {exc.code} (token rejected?)")
94          peers = {"peers": []}
95      peer_rows = peers.get("peers") or []
96      if peer_rows:
97          record("studio-peer", "pass", f"{len(peer_rows)} peer(s): " +
98                 ", ".join(str(p.get('peer') or p.get('id')) for p in peer_rows[:3]), peers)
99      else:
100         record("studio-peer", "fail",
101                "no Studio peer: open the place with the ArenaBridge plugin, then re-run")
102
103     # 3. Tunnel state and public URL.
104     try:
105         tunnel = http_json(base, "/api/tunnel", token=token)
106     except Exception as exc:  # noqa: BLE001
107         tunnel = {"state": "error", "lastError": str(exc)}
108     public_url = (tunnel.get("publicUrl") or "").rstrip("/")
109     if tunnel.get("state") == "online" and public_url:
110         record("tunnel-online", "pass", f"{tunnel.get('flavor')} · {public_url} · health.ok={tunnel.get('health', {}).get('ok')}", tunnel)
111     else:
112         record("tunnel-online", "fail",
113                f"state={tunnel.get('state')} url={public_url or 'none'} lastError={tunnel.get('lastError')}", tunnel)
114
115     # 4. The public URL serves the same bridge, with auth enforced.
116     if public_url:
117         try:
118             with urllib.request.urlopen(public_url + "/api/health", timeout=15) as response:
119                 public_health = json.loads(response.read().decode("utf-8"))
120             same = str(public_health.get("version")) == str(health.get("version"))
```

```
            record("public-health", "pass" if same else "fail",
                   f"public /api/health v{public_health.get('version')} "
                   f"({'matches' if same else 'differs from local ' + str(health.get('version'))})",
                   public_health)
        except Exception as exc:  # noqa: BLE001
            record("public-health", "fail", f"public URL unreachable: {exc}")

    # 5. An MCP client reaches the bridge through the tunnel and talks to Studio.
    mcp_base = args.public_url.rstrip("/") if args.public_url else (public_url or base)
    try:
        status = mcp_call(mcp_base, token, "bridge_ops", {"action": "status"})
        connected = bool(status.get("studio_connected") or status.get("studioConnected"))
        record("mcp-bridge-ops", "pass" if connected else "fail",
               f"studio_connected={connected} via {mcp_base}", status)
    except Exception as exc:  # noqa: BLE001
        record("mcp-bridge-ops", "fail", f"{mcp_base}/mcp: {exc}")

    # 6. A real Studio read through the tunnel (proves end-to-end, not just /api/health).
    if peer_rows:
        try:
            state = mcp_call(mcp_base, token, "get_studio_state", {})
            place = state.get("place") or state.get("placeName") or state.get("placeId")
            record("mcp-studio-read", "pass", f"get_studio_state returned place={place}", {"place": place})
        except Exception as exc:  # noqa: BLE001
            record("mcp-studio-read", "fail", str(exc))

    # 7. Optional: the full bridge self-test, including the Studio smoke test.
    if args.self_test:
        try:
            result = mcp_call(mcp_base, token, "self_test", {"includeStudioSmoke": True}, timeout=180)
            ok = bool(result.get("ok"))
            record("self-test", "pass" if ok else "fail",
                   f"ok={ok} tools={len(result.get('toolMatrix') or [])}", {"ok": ok})
        except Exception as exc:  # noqa: BLE001
            record("self-test", "fail", str(exc))
    else:
        record("self-test", "skipped", "pass --self-test to run every tool through the tunnel")

    # 8. Audit chain stays intact after all of that traffic.
    try:
        audit = http_json(base, "/api/audit?verify=1", token=token)
        record("audit-verify", "pass" if audit.get("ok") else "fail",
               f"chain {'intact' if audit.get('ok') else 'BROKEN'} · {audit.get('checked')} entries", audit)
    except Exception as exc:  # noqa: BLE001
        record("audit-verify", "fail", str(exc))

    return finish(args, base, started)


def finish(args, base, started, fatal=False):
    passed = sum(1 for s in STEPS if s["status"] == "pass")
    failed = sum(1 for s in STEPS if s["status"] == "fail")
    skipped = sum(1 for s in STEPS if s["status"] == "skipped")
    verdict = "pass" if failed == 0 and passed else ("blocked" if fatal else "fail")
    evidence = {
        "kind": "live-acceptance",
        "generated": time.strftime("%Y-%m-%dT%H:%M:%S"),
        "url": base,
        "verdict": verdict,
        "counts": {"pass": passed, "fail": failed, "skipped": skipped},
```

```
        "durationSec": round(time.time() - started, 2),
        "steps": STEPS,
    }
    print(f"\nverdict: {verdict} ({passed} pass / {failed} fail / {skipped} skip)")
    if args.json_out:
        path = os.path.abspath(args.json_out)
        os.makedirs(os.path.dirname(path) or ".", exist_ok=True)
        with open(path, "w", encoding="utf-8") as handle:
            json.dump(evidence, handle, indent=2)
        print(f"[written] {path}", file=sys.stderr)
    else:
        print("\nPaste this under 'Live acceptance' in docs/OPS.md:\n")
        print(json.dumps(evidence, indent=2))
    return 0 if verdict == "pass" else 1


if __name__ == "__main__":
    sys.exit(main())

```

jobs/drill_studio_kill.py

179 lines

G8: kill-switch drill for the job reaper

```python
#!/usr/bin/env python3
"""
drill_studio_kill.py - G8: prove the job reaper survives a Studio crash.

The unit tests exercise the reaper with synthetic peers. This drill does it for
real: it enqueues a job that Studio will sit on, waits for a peer to claim it,
tells you to kill Studio (close the place, kill the plugin, or unplug the network),
and then watches whether the bridge requeues the job instead of leaving it stuck
in `running` forever.

    python3 jobs/drill_studio_kill.py --token "$BRIDGE_TOKEN"
    python3 jobs/drill_studio_kill.py --url https://your-name.trycloudflare.com \
        --token "$BRIDGE_TOKEN" --json-out handoff/kill-switch-drill.json

Exit codes: 0 drill passed, 1 drill failed, 3 no Studio peer to drill with.
"""

import argparse
import json
import os
import sys
import time
import urllib.error
import urllib.request

DRILL_CODE = "task.wait(25) return 'drill-finished'"


def http_json(base, path, token=None, method="GET", body=None, timeout=30):
    data = json.dumps(body).encode("utf-8") if body is not None else None
    headers = {"Content-Type": "application/json"}
    if token:
        headers["Authorization"] = f"Bearer {token}"
    request = urllib.request.Request(base.rstrip("/") + path, data=data, method=method, headers=headers)
    with urllib.request.urlopen(request, timeout=timeout) as response:
        raw = response.read().decode("utf-8")
    return json.loads(raw) if raw.strip().startswith(("{", "[")) else raw


def reaped_total(base, token):
    """Read bridge_jobs_reaped_total from the metrics JSON (0 when absent)."""
    try:
        metrics = http_json(base, "/api/metrics", token=token)
    except Exception:  # noqa: BLE001
        return None
    counters = metrics.get("counters") or {}
    for key, value in counters.items():
        if key.startswith("bridge_jobs_reaped_total"):
            return value if isinstance(value, (int, float)) else (value.get("value") if isinstance(value, dict) else None)
    return 0


def main(argv=None):
    parser = argparse.ArgumentParser(description=__doc__, formatter_class=argparse.RawDescriptionHelpFormatter)
    parser.add_argument("--url", default="http://127.0.0.1:8077", help="Bridge base URL")
    parser.add_argument("--token", default=os.environ.get("BRIDGE_TOKEN", ""), help="Bridge token")
    parser.add_argument("--wait", type=float, default=90.0, help="How long to watch for the requeue (default 90s)")
    parser.add_argument("--json-out", default=None, help="Write the drill evidence here")
    args = parser.parse_args(argv)

```

```
    base = args.url.rstrip("/")
    timeline = []

    def note(event, **extra):
        entry = {"t": round(time.time() - started, 2), "event": event, **extra}
        timeline.append(entry)
        print(f"  [{entry['t']:>6.1f}s] {event}" + (f" {extra}" if extra else ""))
        return entry

    started = time.time()
    print(f"Arena bridge kill-switch drill · {base} · {time.strftime('%Y-%m-%d %H:%M:%S')}\n")

    try:
        peers = http_json(base, "/api/peers", token=args.token)
    except Exception as exc:  # noqa: BLE001
        print(f"error: cannot reach {base}/api/peers: {exc}", file=sys.stderr)
        return 3
    if not (peers.get("peers") or []):
        print("error: no Studio peer connected - open the place, then re-run the drill.", file=sys.stderr)
        print("       (the reaper only has something to do when a peer disappears mid-job)", file=sys.stderr)
        return 3
    note("peer-present", peers=len(peers.get("peers") or []))

    before = reaped_total(base, args.token)
    note("metrics-before", reapedTotal=before)

    try:
        job, _ = None, None
        job = http_json(base, "/api/jobs", token=args.token, method="POST", body={
            "type": "execute_luau",
            "payload": {"code": DRILL_CODE, "dm": "edit"},
            "wait": 0,
            "timeout": 600,
            "note": "drill_studio_kill",
        })
    except urllib.error.HTTPError as exc:
        print(f"error: cannot enqueue the drill job: HTTP {exc.code} {exc.read()[:200]!r}", file=sys.stderr)
        return 1
    job_id = job.get("id")
    note("job-enqueued", jobId=job_id)

    print("\n  >>> Stop Roblox Studio now (close the place or disable the plugin).")
    print("      The drill waits for the bridge to notice and requeue the job.\n")

    statuses = []
    last_status = None
    requeued = False
    saw_running = False
    killed_at = None
    while time.time() - started < args.wait:
        try:
            current = http_json(base, f"/api/jobs/{job_id}", token=args.token)
        except Exception as exc:  # noqa: BLE001
            note("poll-error", error=str(exc))
            time.sleep(2)
            continue
        status = current.get("status")
        if status != last_status:
            note("job-status", status=status, attempts=current.get("attempts"))
            statuses.append({"t": round(time.time() - started, 2), "status": status})
```

```
            last_status = status
            if status == "running":
                saw_running = True
                killed_at = killed_at or time.time()
        if status == "queued" and saw_running:
            requeued = True
            note("job-requeued", attempts=current.get("attempts"), note=current.get("note"))
            break
        if status in ("done", "error", "cancelled") and saw_running:
            note("job-finished", status=status, error=current.get("error"))
            break
        time.sleep(1.0)

    after = reaped_total(base, args.token)
    delta = (after - before) if (after is not None and before is not None) else None
    note("metrics-after", reapedTotal=after, delta=delta)

    # The job may also have been requeued and then re-claimed by a reconnected peer.
    try:
        final = http_json(base, f"/api/jobs/{job_id}", token=args.token)
    except Exception:  # noqa: BLE001
        final = {}
    final_status = final.get("status")
    attempts = int(final.get("attempts") or 0)

    passed = bool(requeued or (attempts > 0 and final_status in ("queued", "running", "done")) or (delta or 0) > 0)
    verdict = "pass" if passed else "fail"
    print(f"\nverdict: {verdict}  (final status={final_status}, attempts={attempts}, reaped delta={delta})")
    if not passed:
        print("  The job never left `running`. Check that the bridge is still alive, that the reaper is "
              "running (it starts with the server), and that Studio really stopped heart-beating.")

    evidence = {
        "kind": "kill-switch-drill",
        "generated": time.strftime("%Y-%m-%dT%H:%M:%S"),
        "url": base,
        "verdict": verdict,
        "jobId": job_id,
        "finalStatus": final_status,
        "attempts": attempts,
        "reapedTotal": {"before": before, "after": after, "delta": delta},
        "requeued": requeued,
        "timeline": timeline,
        "durationSec": round(time.time() - started, 2),
    }
    if args.json_out:
        path = os.path.abspath(args.json_out)
        os.makedirs(os.path.dirname(path) or ".", exist_ok=True)
        with open(path, "w", encoding="utf-8") as handle:
            json.dump(evidence, handle, indent=2)
        print(f"[written] {path}", file=sys.stderr)
    else:
        print("\nPaste this under 'Kill-switch drill' in docs/OPS.md:\n")
        print(json.dumps(evidence, indent=2))
    return 0 if passed else 1


if __name__ == "__main__":
    sys.exit(main())

```

5. Diffs against the previous release

Unified diffs produced with `git diff 92cde4e -- <file>`. Lines prefixed + are added, - removed; each file starts on its own page.

File	Added	Removed	Purpose
`roblox-bridge/server.py`	+2016	-118	HTTP bridge, auth scopes, ops endpoints, dashboard tab 7
`roblox-bridge/mcp_core.py`	+737	-58	agent_bus + bridge_ops tools, 3 resources, client helpers
`roblox-bridge/arena_studio.py`	+239	-1	ops / metrics / audit / tunnel / tokens / bus CLI
`roblox-bridge/setup.py`	+123	-29	Supervised tunnel launch + URL watcher
`roblox-bridge/test_bridge_mcp.py`	+1033	-6	v5 test coverage (scopes, bus, reaping, audit, tunnel)
`roblox-bridge/mcp_server.py`	+1	-1	Version banner
`roblox-bridge/ab.ps1`	+6	-1	Version banner + ops examples
Total	**+4155**	**-214**	

The diff sections carry the context lines needed to place each change; nothing outside these files is touched by the release.

roblox-bridge/server.py (diff)

2587 lines

HTTP bridge, auth scopes, ops endpoints, dashboard tab 7

```
diff --git a/roblox-bridge/server.py b/roblox-bridge/server.py
index 9bedc28..18a63c1 100644
--- a/roblox-bridge/server.py
+++ b/roblox-bridge/server.py
@@ -7,7 +7,7 @@ Simultaneously serves:
1. Roblox Studio local plugin peers (Edit + Play Server + Play Client bridge)
via fast long-polling (`GET /api/poll`, `POST /api/result`).
2. Native MCP Streamable HTTP endpoint (`POST /mcp`, `GET /mcp`, `DELETE /mcp`)
- implementing MCP 2025-06-18 / 2024-11-05 JSON-RPC 2.0 (68 tools, 5 live
+ implementing MCP 2025-06-18 / 2024-11-05 JSON-RPC 2.0 (70 tools, 8 live
resources, 2 resource templates, 4 workflow prompts).
3. REST API for CLI (`arena_studio.py` / `ab.ps1`) & remote cloud agents
(`GET /api/health`, `GET /api/state`, `GET /api/agent-guide`,
@@ -31,9 +31,22 @@ import time
from urllib.parse import parse_qs, urlparse
import uuid

-from mcp_core import BridgeClient, MCPDispatcher, TOOL_SPECS, run_bridge_self_test
-
-VERSION = "4.0.0"
+from mcp_core import (
+ BridgeClient,
+ MCPDispatcher,
+ MODERN_PROTOCOL_VERSION,
+ SUPPORTED_PROTOCOL_VERSIONS,
+ TOOL_MAP,
+ TOOL_SPECS,
+ is_tool_call_read_only,
+ run_bridge_self_test,
+)
+from auth_core import ROLE_RANK, TokenStore
+from bus_core import AgentBus
+from telemetry import Telemetry
+from tunnel_manager import TunnelManager
+
+VERSION = "5.3.2"
PEER_ONLINE_WINDOW = 5.0 # play DataModel peers are transient; do not route work to stale peers
HERE = Path(__file__).resolve().parent
SNAPSHOT_DIR = HERE / "snapshots"
@@ -120,10 +133,27 @@ def build_agent_guide(state_snapshot: dict, origin: str = "http://127.0.0.1:8077
# ---------------------------------------------------------------------------

class BridgeState:
- def __init__(self, token: str = "", read_only: bool = False, guard_place_id: int = None):
+ def __init__(
+ self,
+ token: str = "",
+ read_only: bool = False,
+ guard_place_id: int = None,
+ state_dir: str = None,
+ auto_tunnel: bool = False,
+ tunnel_flavor: str = "auto",
+ tunnel_token: str = None,
+ tunnel_name: str = None,
+ public_url: str = None,
+ tunnel_binary: str = None,
+ sweep_interval: float = 300.0,
+ sweep_offline_seconds: float = 900.0,
+ ):
self.token = token or ""
```

```
self.read_only = bool(read_only)
self.guard_place_id = int(guard_place_id) if guard_place_id else None
+ self.started = _now()
+ self.state_dir = Path(state_dir) if state_dir else (HERE / "bridge_state")
+ self.state_dir.mkdir(parents=True, exist_ok=True)

self.lock = threading.RLock()
self.poll_cv = threading.Condition(self.lock)
@@ -151,6 +181,419 @@ class BridgeState:
)
self.mcp_dispatcher = MCPDispatcher(self.mcp_client)

+ # --- v5 ops platform ------------------------------------------------
+ self.telemetry = Telemetry(self.state_dir)
+ self.bus = AgentBus(self.state_dir / "bus.json")
+ self.tokens = TokenStore(self.state_dir / "tokens.json", primary_token=self.token)
+ self.tunnel = TunnelManager(
+ port=int(os.environ.get("BRIDGE_PORT", 8077)),
+ binary=tunnel_binary,
+ flavor=tunnel_flavor,
+ named_token=tunnel_token,
+ name=tunnel_name,
+ public_url=public_url,
+ state_dir=self.state_dir,
+ auto_start=bool(auto_tunnel),
+ )
+ # Automatic stale-agent sweeping (0 disables the background sweep).
+ self.sweep_interval = max(0.0, float(sweep_interval or 0))
+ self.sweep_offline_seconds = max(60.0, float(sweep_offline_seconds or 900))
+ self._last_sweep = 0.0
+ self._sweeps = 0
+ # Multi-studio fleet: pinned peer (the "active studio"), labels, and the
+ # persisted fleet file. Routing prefers the pin, then falls back to auto
+ # so a closed Studio cannot silently stall the queue.
+ self._fleet_path = self.state_dir / "fleet.json"
+ self.studio_pin = None
+ self.peer_labels = {}
+ self._load_fleet()
+ # Maintenance switch: keep accepting work, stop handing it to Studio.
+ self.queue_paused = False
+ self.queue_paused_reason = None
+ self.queue_paused_at = None
+ # Job dedupe + retry bookkeeping
+ self.idempotency = {}
+ self._reaper_stop = threading.Event()
+ self._reaper = threading.Thread(target=self._reap_loop, name="job-reaper", daemon=True)
+ self._reaper.start()
+
+ self.telemetry.events.emit("bridge.start", {
+ "version": VERSION,
+ "readOnly": self.read_only,
+ "tools": len(TOOL_SPECS),
+ "authMode": "scoped" if self.token else "open",
+ })
+ self.telemetry.audit.append(
+ "bridge.start",
+ actor="system",
+ detail={"version": VERSION, "readOnly": self.read_only, "authMode": "scoped" if self.token else "open"},
+ )
+
```

```
+ # -- auth ------------------------------------------------------------
+
+ def authenticate(self, supplied: str = None, is_loopback: bool = False, required: str = "read"):
+ """Resolve a raw token into an auth context.
+
+ Returns (context, error). `error` is a dict with `code`/`error` when the
+ request must be rejected. Auth is disabled entirely when no token is set,
+ which preserves the historical zero-config localhost experience.
+ """
+ if not self.token and not self.tokens.records:
+ return {"role": "admin", "id": "open", "label": "auth-disabled"}, None
+ record, rate = self.tokens.authenticate(supplied)
+ if record is None:
+ # No anonymous bypass: a configured token is required for every path
+ # that is not explicitly public (dashboard HTML and /api/health).
+ return None, {"code": 401, "error": "bad token"}
+ if rate and not rate.get("allowed"):
+ return None, {
+ "code": 429,
+ "error": "rate limit exceeded for this token",
+ "retryAfter": rate.get("retryAfter", 1),
+ }
+ if not TokenStore.role_allows(record.role, required):
+ return None, {
+ "code": 403,
+ "error": f"token role '{record.role}' cannot perform '{required}' actions",
+ }
+ ctx = {
+ "role": record.role,
+ "id": record.id,
+ "label": record.label,
+ "remaining": (rate or {}).get("remaining"),
+ }
+ if record.id != "primary":
+ self.telemetry.metrics.inc("bridge_token_requests_total", 1, {"token": record.id, "role": record.role})
+ return ctx, None
+
+ # -- background reaper -----------------------------------------------
+
+ def _reap_loop(self):
+ while not self._reaper_stop.wait(2.0):
+ try:
+ self.reap_jobs()
+ except Exception: # noqa: BLE001 - the reaper must never die
+ continue
+ if self.sweep_interval <= 0:
+ continue
+ try:
+ if _now() - self._last_sweep >= self.sweep_interval:
+ self.auto_sweep()
+ except Exception: # noqa: BLE001 - the sweeper must never kill the reaper
+ continue
+
+ def auto_sweep(self) -> dict:
+ """Release tasks held by agents that stopped heart-beating.
+
+ Runs on the reaper thread every `sweep_interval` seconds. A no-op sweep is
+ cheap and deliberately silent; a sweep that releases work is broadcast on
+ the bus, recorded in the audit log and counted in metrics.
+ """
```

```
+ result = self.bus.sweep_stale(self.sweep_offline_seconds)
+ self._last_sweep = _now()
+ self._sweeps += 1
+ if result.get("tasksReaped"):
+ self.telemetry.metrics.inc("bridge_agents_reaped_total", len(result.get("agents") or []))
+ self.telemetry.metrics.inc("bridge_tasks_released_total", result["tasksReaped"])
+ self.telemetry.events.emit("bus.sweep", {
+ "released": result["tasksReaped"], "agents": result.get("agents", []),
+ }, level="warn")
+ self.telemetry.audit.append("bus.sweep", actor="sweeper",
+ detail={"released": result["tasksReaped"],
+ "agents": result.get("agents", [])})
+ return result
+
+ def pause_queue(self, reason: str = None) -> dict:
+ """Stop handing jobs to Studio; new work still queues (nothing is lost)."""
+ with self.lock:
+ self.queue_paused = True
+ self.queue_paused_reason = (reason or "paused by operator")[:200]
+ self.queue_paused_at = _now()
+ queued = len(self.pending)
+ self.telemetry.events.emit("queue.paused", {"reason": self.queue_paused_reason, "queued": queued}, level="warn")
+ self.telemetry.audit.append("queue.pause", actor="operator", detail={"reason": self.queue_paused_reason, "queued": queued})
+ return {"paused": True, "reason": self.queue_paused_reason, "queued": queued}
+
+ def resume_queue(self) -> dict:
+ with self.lock:
+ was_paused = self.queue_paused
+ paused_for = round(_now() - self.queue_paused_at, 1) if self.queue_paused_at else 0
+ self.queue_paused = False
+ self.queue_paused_reason = None
+ self.queue_paused_at = None
+ queued = len(self.pending)
+ with self.poll_cv:
+ self.poll_cv.notify_all()
+ if was_paused:
+ self.telemetry.events.emit("queue.resumed", {"queued": queued})
+ self.telemetry.audit.append("queue.resume", actor="operator", detail={"queued": queued, "pausedSeconds": paused_for})
+ return {"paused": False, "queued": queued, "pausedSeconds": paused_for}
+
+ def reap_jobs(self) -> dict:
+ """Fail timed-out jobs and re-queue work orphaned by a dead/absent peer."""
+ now = _now()
+ recovered = 0
+ timed_out = 0
+ with self.lock:
+ online = {p["peerId"] for p in self._active_peers_unlocked() if p["online"]}
+ for job in list(self.jobs.values()):
+ if job.get("status") != "running":
+ continue
+ claimed = job.get("claimed") or now
+ timeout = float(job.get("timeout") or 120.0)
+ owner = job.get("claimedBy")
+ orphaned = bool(owner) and owner not in online and (now - claimed) > 20.0
+ if orphaned:
+ job["status"] = "queued"
+ job["claimedBy"] = None
+ job["claimed"] = None
+ job["attempts"] = int(job.get("attempts") or 0) + 1
+ job["note"] = (job.get("note") or "") + f" [requeued: peer {owner} went away]"
```

```
+ if job["id"] not in self.pending:
+ self.pending.append(job["id"])
+ recovered += 1
+ self.poll_cv.notify_all()
+ self.telemetry.events.emit("job.requeued_orphan", {"id": job["id"], "type": job["type"], "peer": owner}, level="warn")
+ continue
+ if (now - claimed) > timeout:
+ job["status"] = "error"
+ job["ok"] = False
+ job["error"] = f"timeout after {timeout:.0f}s in {'peer ' + owner if owner else 'queue'}"
+ job["finished"] = now
+ job["duration_ms"] = round((now - claimed) * 1000, 1)
+ timed_out += 1
+ evt = self.job_events.get(job["id"])
+ if evt:
+ evt.set()
+ self.telemetry.record_job(job)
+ self.telemetry.audit.append("job.timeout", actor="reaper", target=job["id"],
+ detail={"type": job["type"], "peer": owner}, outcome="error")
+ self.telemetry.metrics.inc("bridge_jobs_reaped_total", recovered + timed_out)
+ return {"recovered": recovered, "timedOut": timed_out}
+
+ # -- multi-studio fleet ------------------------------------------------
+
+ def _load_fleet(self):
+ try:
+ raw = json.loads(self._fleet_path.read_text(encoding="utf-8"))
+ except (OSError, ValueError):
+ return
+ if isinstance(raw, dict):
+ self.studio_pin = raw.get("pinned") or None
+ labels = raw.get("labels")
+ if isinstance(labels, dict):
+ self.peer_labels = {str(k): str(v)[:60] for k, v in labels.items()}
+
+ def _save_fleet(self):
+ try:
+ self._fleet_path.write_text(
+ json.dumps({"pinned": self.studio_pin, "labels": self.peer_labels},
+ ensure_ascii=False, indent=2),
+ encoding="utf-8",
+ )
+ except OSError:
+ pass
+
+ def fleet_snapshot(self) -> dict:
+ """One entry per Studio DataModel the bridge can talk to."""
+ with self.lock:
+ peers = self._active_peers_unlocked()
+ queued_by_peer = {}
+ for job_id in self.pending:
+ job = self.jobs.get(job_id) or {}
+ target = job.get("target_peer")
+ if target:
+ queued_by_peer[target] = queued_by_peer.get(target, 0) + 1
+ pin = self.studio_pin
+ labels = dict(self.peer_labels)
+ online_count = sum(1 for p in peers if p["online"])
+ studios = []
+ pin_online = False
```

```
+ for p in peers:
+ entry = {
+ "peerId": p["peerId"],
+ "studioId": p["peerId"],
+ "label": labels.get(p["peerId"]) or f"{p['place']} ({p['dm']})",
+ "dm": p["dm"],
+ "place": p["place"],
+ "placeId": p["placeId"],
+ "gameId": p["gameId"],
+ "online": p["online"],
+ "ageSeconds": p["ageSeconds"],
+ "client": p["client"],
+ "playerCount": p["playerCount"],
+ "pluginVersion": p["pluginVersion"],
+ "studioVersion": p.get("studioVersion") or None,
+ "pinned": p["peerId"] == pin,
+ "queuedJobs": queued_by_peer.get(p["peerId"], 0),
+ "defaultTarget": False,
+ }
+ if entry["pinned"] and p["online"]:
+ pin_online = True
+ studios.append(entry)
+ # Mark which peer an untargeted job would actually reach.
+ if pin_online:
+ for entry in studios:
+ entry["defaultTarget"] = entry["pinned"] and entry["online"]
+ else:
+ for entry in studios:
+ entry["defaultTarget"] = bool(entry["online"] and entry["dm"] == "edit")
+ if entry["defaultTarget"]:
+ break
+ return {
+ "ok": True,
+ "count": len(studios),
+ "online": online_count,
+ "pinned": pin,
+ "pinOnline": pin_online,
+ "routing": "pinned" if pin_online else "auto",
+ "studios": studios,
+ "hint": (
+ "Target one with peerId on any tool, or POST /api/studios "
+ "{\"action\":\"set_active\",\"peerId\":\"...\"} to make it the default."
+ ),
+ }
+
+ def set_active_peer(self, peer_id: str = None, place_id: int = None) -> dict:
+ with self.lock:
+ peers = self._active_peers_unlocked()
+ chosen = None
+ if peer_id:
+ chosen = next((p for p in peers if p["peerId"] == peer_id), None)
+ if not chosen:
+ raise KeyError(f"No connected Studio with peerId {peer_id!r}")
+ elif place_id:
+ chosen = next((p for p in peers if p["placeId"] == int(place_id) and p["online"]), None) \
+ or next((p for p in peers if p["placeId"] == int(place_id)), None)
+ if not chosen:
+ raise KeyError(f"No connected Studio on placeId {place_id}")
+ else:
+ raise ValueError("set_active needs peerId or placeId")
```

```
+ self.studio_pin = chosen["peerId"]
+ self._save_fleet()
+ self.telemetry.audit.append("fleet.set_active", actor="operator",
+ detail={"peerId": chosen["peerId"], "place": chosen["place"]})
+ return {"ok": True, "active": chosen["peerId"], "place": chosen["place"], "dm": chosen["dm"]}
+
+ def clear_active_peer(self) -> dict:
+ with self.lock:
+ previous = self.studio_pin
+ self.studio_pin = None
+ self._save_fleet()
+ if previous:
+ self.telemetry.audit.append("fleet.clear_active", actor="operator", detail={"previous": previous})
+ return {"ok": True, "active": None, "previous": previous}
+
+ def label_peer(self, peer_id: str, label: str = None) -> dict:
+ with self.lock:
+ peers = self._active_peers_unlocked()
+ if not any(p["peerId"] == peer_id for p in peers):
+ raise KeyError(f"No connected Studio with peerId {peer_id!r}")
+ if label:
+ self.peer_labels[peer_id] = str(label)[:60]
+ else:
+ self.peer_labels.pop(peer_id, None)
+ self._save_fleet()
+ saved = self.peer_labels.get(peer_id)
+ return {"ok": True, "peerId": peer_id, "label": saved}
+
+ def fleet_action(self, payload: dict = None) -> dict:
+ body = dict(payload or {})
+ action = (body.get("action") or "list").lower()
+ if action in ("list", "status"):
+ return self.fleet_snapshot()
+ if action in ("set_active", "pin", "activate"):
+ return self.set_active_peer(body.get("peerId") or body.get("peer_id"),
+ body.get("placeId") or body.get("place_id"))
+ if action in ("clear_active", "unpin"):
+ return self.clear_active_peer()
+ if action == "label":
+ return self.label_peer(body.get("peerId") or body.get("peer_id"), body.get("label"))
+ raise ValueError(f"Unknown fleet action: {action}")
+
+ BROADCAST_TOOL_KINDS = {
+ "ping_studio": ("ping", {}),
+ "get_studio_state": ("studio_state", {}),
+ "survey_place": ("survey", {"includeSource": False}),
+ "inspect_instance": ("inspect", {"depth": 2}),
+ "script_read": ("read_script", {}),
+ "get_console_output": ("get_console", {}),
+ }
+
+ def broadcast(self, kind: str = "ping", payload: dict = None, timeout: float = 20.0,
+ dm: str = None, tool: str = None) -> dict:
+ """Fan one read-only job out to every online Studio and collect per-peer results."""
+ if tool:
+ mapped = self.BROADCAST_TOOL_KINDS.get(tool)
+ if not mapped:
+ raise ValueError(f"broadcast does not know tool {tool!r}; use one of "
+ f"{', '.join(self.BROADCAST_TOOL_KINDS)}")
+ kind, defaults = mapped
```

```
+ payload = {**defaults, **(payload or {})}
+ if kind not in self.BROADCAST_KINDS:
+ raise ValueError(
+ f"broadcast only runs read-only kinds ({', '.join(self.BROADCAST_KINDS)}); "
+ f"refusing {kind!r}"
+ )
+ with self.lock:
+ targets = [p for p in self._active_peers_unlocked()
+ if p["online"] and (not dm or dm == "auto" or p["dm"] == dm)]
+ if not targets:
+ return {"ok": False, "reason": "no_peer", "error": "No online Studio to broadcast to.",
+ "kind": kind, "results": []}
+
+ started = _now()
+ submitted = []
+ for peer in targets:
+ try:
+ job, event = self.enqueue_job(kind=kind, payload=payload, note=f"broadcast:{kind}",
+ peer_id=peer["peerId"], timeout=max(10.0, timeout))
+ except Exception as exc: # noqa: BLE001 - one bad peer must not kill the fan-out
+ submitted.append({"peer": peer, "job": None, "event": None, "error": str(exc)})
+ continue
+ submitted.append({"peer": peer, "job": job, "event": event, "error": None})
+
+ deadline = time.monotonic() + max(1.0, timeout)
+ results = []
+ for item in submitted:
+ peer, job, event, error = item["peer"], item["job"], item["event"], item["error"]
+ row = {
+ "peerId": peer["peerId"],
+ "place": peer["place"],
+ "placeId": peer["placeId"],
+ "dm": peer["dm"],
+ "label": self.peer_labels.get(peer["peerId"]) or f"{peer['place']} ({peer['dm']})",
+ }
+ if job is None:
+ row.update({"ok": False, "status": "error", "error": error})
+ results.append(row)
+ continue
+ event.wait(timeout=max(0.1, deadline - time.monotonic()))
+ with self.lock:
+ finished = dict(self.jobs.get(job["id"]) or job)
+ row.update({
+ "jobId": finished.get("id"),
+ "status": finished.get("status"),
+ "ok": finished.get("status") == "done" and bool(finished.get("ok", True)),
+ "durationMs": finished.get("duration_ms"),
+ "result": finished.get("result"),
+ "error": finished.get("error"),
+ })
+ results.append(row)
+
+ done = sum(1 for r in results if r.get("ok"))
+ summary = {
+ "ok": done > 0,
+ "kind": kind,
+ "peers": len(results),
+ "succeeded": done,
+ "failed": len(results) - done,
+ "elapsedMs": round((_now() - started) * 1000.0, 1),
```

```
+ "results": results,
+ }
+ self.telemetry.events.emit("fleet.broadcast", {"kind": kind, "peers": len(results), "ok": done})
+ return summary
+
# -- peer tracking ------------------------------------------------------------

def record_poll(self, qs: dict) -> dict:
@@ -246,10 +689,25 @@ class BridgeState:

# -- job routing & matching ---------------------------------------------------

+ # Read-only job kinds that are safe to fan out across every open Studio.
+ BROADCAST_KINDS = (
+ "ping", "studio_state", "survey", "inspect", "search_tree", "get_properties",
+ "compare_instances", "read_script", "read_scripts", "get_console", "snapshot_list",
+ )
+
def _peer_matches_job_unlocked(self, peer: dict, job: dict) -> bool:
req_peer = job.get("target_peer")
if req_peer and peer["peerId"] != req_peer:
return False
+ if not req_peer and job.get("target_dm") in (None, "", "auto") and not job.get("place_id"):
+ # An explicitly pinned Studio wins over "any edit peer", but only
+ # while it is actually online - a closed Studio must not stall work.
+ pin = self.studio_pin
+ if pin:
+ pinned = next((p for p in self._active_peers_unlocked()
+ if p["peerId"] == pin and p["online"]), None)
+ if pinned and peer["peerId"] != pin:
+ return False

req_place = job.get("place_id")
if req_place and peer["placeId"] != int(req_place):
@@ -284,23 +742,46 @@ class BridgeState:
deadline = time.monotonic() + wait_seconds
with self.poll_cv:
while True:
+ if self.queue_paused:
+ # Keep the peer alive (lastPoll still updates) but hand out nothing.
+ self.peers[peer_info["peerId"]]["lastPoll"] = _now()
+ if self.poll_cv.wait(timeout=max(0.1, min(0.5, deadline - time.monotonic()))):
+ continue
+ if time.monotonic() >= deadline:
+ return None
+ continue
self.peers[peer_info["peerId"]]["lastPoll"] = _now()
+ best = None
for job_id in list(self.pending):
job = self.jobs.get(job_id)
if not job or job["status"] != "queued":
self.pending.remove(job_id)
continue
- if self._peer_matches_job_unlocked(peer_info, job):
- self.pending.remove(job_id)
- job["status"] = "running"
- job["claimed"] = _now()
- job["claimedBy"] = peer_info["peerId"]
- job["dm"] = peer_info["dm"]
- return {
```

```
- "id": job["id"],
- "type": job["type"],
- "payload": job["payload"],
- }
+ if not self._peer_matches_job_unlocked(peer_info, job):
+ continue
+ # Priority first, then FIFO, so a critical agent probe is not
+ # stuck behind a long bulk-build job from another agent.
+ rank = (int(job.get("priority", 5)), job.get("created", 0))
+ if best is None or rank < best[0]:
+ best = (rank, job_id)
+ if best is not None:
+ job_id = best[1]
+ job = self.jobs[job_id]
+ self.pending.remove(job_id)
+ job["status"] = "running"
+ job["claimed"] = _now()
+ job["claimedBy"] = peer_info["peerId"]
+ job["dm"] = peer_info["dm"]
+ job["attempts"] = int(job.get("attempts") or 0) + 1
+ self.telemetry.events.emit("job.claim", {
+ "id": job["id"], "type": job["type"], "peer": peer_info["peerId"],
+ "priority": job.get("priority", 5),
+ })
+ return {
+ "id": job["id"],
+ "type": job["type"],
+ "payload": job["payload"],
+ }

remaining = deadline - time.monotonic()
if remaining <= 0:
@@ -325,6 +806,10 @@ class BridgeState:
dm: str = None,
peer_id: str = None,
place_id: int = None,
+ idempotency_key: str = None,
+ priority: int = 5,
+ max_retries: int = 0,
+ timeout: float = None,
):
payload_dict = dict(payload or {}) if isinstance(payload, dict) else {}

@@ -351,7 +836,28 @@ class BridgeState:

effective_place = place_id if place_id is not None else self.guard_place_id

+ priority = max(0, min(int(priority if priority is not None else 5), 9))
+ max_retries = max(0, min(int(max_retries or 0), 5))
+ idempotency_key = (idempotency_key or "").strip()[:200] or None
+
with self.poll_cv:
+ now = _now()
+ # Purge idempotency keys older than an hour so the map stays bounded.
+ if len(self.idempotency) > 512:
+ for key in [k for k, v in self.idempotency.items() if now - v.get("ts", 0) > 3600]:
+ self.idempotency.pop(key, None)
+
+ if idempotency_key:
+ prior = self.idempotency.get(idempotency_key)
```

```
+ prior_job = self.jobs.get(prior["id"]) if prior else None
+ if prior_job and prior_job.get("status") not in ("error", "cancelled"):
+ prior_job["deduplicated"] = int(prior_job.get("deduplicated") or 0) + 1
+ self.telemetry.metrics.inc("bridge_job_dedupe_total", 1, {"type": kind})
+ self.telemetry.events.emit("job.dedupe", {
+ "id": prior_job["id"], "type": kind, "key": idempotency_key,
+ })
+ return prior_job, self.job_events.setdefault(prior_job["id"], threading.Event())
+
jid = uuid.uuid4().hex[:12]
done_evt = threading.Event()
job = {
@@ -365,7 +871,7 @@ class BridgeState:
"dm": None,
"claimedBy": None,
"status": "queued",
- "created": _now(),
+ "created": now,
"claimed": None,
"finished": None,
"duration_ms": None,
@@ -373,29 +879,82 @@ class BridgeState:
"result": None,
"error": None,
"logs": [],
+ "priority": priority,
+ "maxRetries": max_retries,
+ "retries": 0,
+ "attempts": 0,
+ "timeout": float(timeout) if timeout else None,
+ "idempotencyKey": idempotency_key,
+ "deduplicated": 0,
}
self.jobs[jid] = job
self.job_events[jid] = done_evt
self.pending.append(jid)
self.history.append(jid)
+ if idempotency_key:
+ self.idempotency[idempotency_key] = {"id": jid, "ts": now}
while len(self.jobs) > 600:
oldest = next(iter(self.jobs))
if oldest == jid:
break
self.jobs.pop(oldest, None)
self.job_events.pop(oldest, None)
+ self.telemetry.metrics.inc("bridge_jobs_enqueued_total", 1, {"type": kind})
+ self.telemetry.events.emit("job.enqueue", {
+ "id": jid, "type": kind, "dm": effective_dm, "priority": priority,
+ "note": note, "idempotencyKey": idempotency_key,
+ })
+ if kind in self.MUTATING_JOB_TYPES:
+ self.telemetry.audit.append(
+ "job.enqueue", actor=note or "agent", target=jid,
+ detail={"type": kind, "dm": effective_dm, "priority": priority},
+ )
self.poll_cv.notify_all()
return job, done_evt

+ TRANSIENT_ERROR_HINTS = (
+ "timeout", "timed out", "time-out", "peer", "disconnect", "connection",
```

```
+ "econn", "temporarily", "busy", "try again", "socket", "network",
+ "unknown job type", "not ready",
+ )
+
+ def _is_transient_error(self, body: dict, job: dict) -> bool:
+ if body.get("retryable") is True:
+ return True
+ message = str(body.get("error") or "").lower()
+ if not message:
+ return False
+ return any(hint in message for hint in self.TRANSIENT_ERROR_HINTS)
+
def complete_job(self, body: dict) -> bool:
jid = body.get("id")
- with self.lock:
+ with self.poll_cv:
job = self.jobs.get(jid)
if not job:
return False
now = _now()
- job["status"] = "done" if body.get("ok") else "error"
- job["ok"] = bool(body.get("ok"))
+ ok = bool(body.get("ok"))
+ if not ok and int(job.get("retries") or 0) < int(job.get("maxRetries") or 0) \
+ and self._is_transient_error(body, job):
+ job["retries"] = int(job.get("retries") or 0) + 1
+ job["attempts"] = int(job.get("attempts") or 0)
+ job["status"] = "queued"
+ job["claimedBy"] = None
+ job["claimed"] = None
+ job["error"] = None
+ job["note"] = (job.get("note") or "") + f" [retry {job['retries']}: {str(body.get('error'))[:120]}]"
+ if jid not in self.pending:
+ self.pending.append(jid)
+ self.telemetry.metrics.inc("bridge_job_retries_total", 1, {"type": job["type"]})
+ self.telemetry.events.emit("job.retry", {
+ "id": jid, "type": job["type"], "retry": job["retries"],
+ "error": str(body.get("error"))[:200],
+ }, level="warn")
+ self.poll_cv.notify_all()
+ return True
+
+ job["status"] = "done" if ok else "error"
+ job["ok"] = ok
job["result"] = body.get("result")
job["error"] = body.get("error")
job["logs"] = body.get("logs") or []
@@ -409,6 +968,12 @@ class BridgeState:
evt = self.job_events.get(jid)
if evt:
evt.set()
+ self.telemetry.record_job(job)
+ if not ok:
+ self.telemetry.audit.append(
+ "job.error", actor=job.get("claimedBy") or "studio", target=jid,
+ detail={"type": job["type"], "error": str(job.get("error"))[:300]}, outcome="error",
+ )
return True

def cancel_job(self, jid: str) -> dict:
```

```
@@ -515,6 +1080,7 @@ class BridgeState:
with self.lock:
online, st = self.legacy_studio_summary_unlocked()
peers = self._active_peers_unlocked()
+ tunnel_state = self.tunnel.state
return {
"ok": True,
"version": VERSION,
@@ -525,6 +1091,29 @@ class BridgeState:
"peers": peers,
"queued": len(self.pending),
"jobs": len(self.jobs),
+ "uptimeSeconds": round(_now() - self.started, 1),
+ "authMode": "scoped" if self.token else "open",
+ "tunnel": {
+ "state": tunnel_state,
+ "publicUrl": self.tunnel.public_url,
+ "localUrl": self.tunnel.local_url,
+ },
+ "agents": self.bus.stats()["agents"],
+ "agentsOnline": self.bus.stats()["agentsOnline"],
+ "studios": {
+ "count": len(peers),
+ "online": sum(1 for p in peers if p["online"]),
+ "active": self.studio_pin,
+ "routing": "pinned" if self.studio_pin else "auto",
+ },
+ "queuePaused": self.queue_paused,
+ "queuePausedReason": self.queue_paused_reason,
+ "sweeper": {
+ "intervalSeconds": self.sweep_interval,
+ "offlineSeconds": self.sweep_offline_seconds,
+ "lastSweep": self._last_sweep or None,
+ "sweeps": self._sweeps,
+ },
}
if op == "state":
with self.lock:
@@ -542,7 +1131,15 @@ class BridgeState:
"snapshots": len(self.snapshots),
"recent": recent,
"server_time": _now(),
+ "uptimeSeconds": round(_now() - self.started, 1),
+ "bus": self.bus.stats(),
+ "tunnel": {
+ "state": self.tunnel.state,
+ "publicUrl": self.tunnel.public_url,
+ },
}
+ if op == "studios":
+ return self.fleet_snapshot()
if op == "peers":
with self.lock:
peers = self._active_peers_unlocked()
@@ -565,14 +1162,177 @@ class BridgeState:
dm=body.get("dm"),
peer_id=body.get("peer_id"),
place_id=body.get("place_id"),
+ idempotency_key=body.get("idempotencyKey") or body.get("idempotency_key"),
+ priority=body.get("priority", 5),
```

```
+ max_retries=body.get("maxRetries", body.get("max_retries", 0)),
+ timeout=body.get("timeout"),
)
wait = float(body.get("wait") or 0)
if wait > 0:
evt.wait(timeout=min(wait, 120.0))
with self.lock:
return dict(self.jobs[job["id"]])
+ if op == "bus":
+ return self.bus.handle(body)
+ if op == "fleet":
+ return self.fleet_action(body)
+ if op == "broadcast":
+ return self.broadcast(
+ kind=body.get("type") or body.get("kind") or "ping",
+ payload=body.get("payload"),
+ timeout=float(body.get("timeout") or 20.0),
+ dm=body.get("dm"),
+ tool=body.get("tool"),
+ )
+ if op == "tunnel":
+ return self.tunnel_action(body)
+ if op == "tokens":
+ return self.tokens.handle(body)
+ if op == "metrics":
+ return self.metrics_snapshot()
+ if op == "audit":
+ if body.get("verify"):
+ return self.telemetry.audit.verify()
+ return self.telemetry.audit.tail(int(body.get("limit") or 100), body.get("action"))
+ if op == "events":
+ if body.get("wait") is not None:
+ return self.telemetry.events.tail(int(body.get("cursor") or 0), float(body.get("wait") or 0), int(body.get("limit") or 100))
+ return self.telemetry.events.since(int(body.get("cursor") or 0), int(body.get("limit") or 200), body.get("kinds"))
+ if op in ("ops", "ops_report"):
+ return self.ops_report()
+ if op == "queue_pause":
+ return self.pause_queue(body.get("reason"))
+ if op == "queue_resume":
+ return self.resume_queue()
+ if op == "sweep":
+ return self.auto_sweep()
+ if op == "queue_clear":
+ cancelled = self.clear_queue()
+ self.telemetry.audit.append("queue.clear", actor="internal", detail={"cancelled": cancelled})
+ return {"cancelled": cancelled}
+ if op == "reap":
+ return self.reap_jobs()
raise ValueError(f"Unknown internal op: {op}")

+ # -- tunnel control ------------------------------------------------------
+
+ def tunnel_action(self, payload: dict) -> dict:
+ """Refuse to publish an unauthenticated bridge, then delegate."""
+ action = ((payload or {}).get("action") or "status").lower()
+ if action in ("start", "restart") and not self.token:
+ status = self.tunnel.status()
+ status.update({
+ "state": "blocked",
+ "running": False,
```

```
+ "lastError": (
+ "Refusing to expose the bridge publicly without a token. "
+ "Run `python setup.py` (it writes bridge.token) or start server.py with --token."
+ ),
+ "security": "blocked_no_token",
+ })
+ self.telemetry.events.emit("tunnel.blocked", {"reason": "no_token"}, level="warn")
+ self.telemetry.audit.append("tunnel.blocked", actor="system", detail={"reason": "no_token"}, outcome="denied")
+ return status
+ return self.tunnel.handle(payload)
+
+ # -- ops reporting ------------------------------------------------------
+
+ def metrics_snapshot(self) -> dict:
+ with self.lock:
+ online, _ = self.legacy_studio_summary_unlocked()
+ peers_online = sum(1 for p in self._active_peers_unlocked() if p["online"])
+ queued = len(self.pending)
+ running = sum(1 for j in self.jobs.values() if j.get("status") == "running")
+ jobs_total = len(self.jobs)
+ online_flag = online
+ bus_stats = self.bus.stats()
+ t = self.telemetry.metrics
+ t.gauge("bridge_peers_online", peers_online)
+ t.gauge("bridge_studio_connected", 1 if online_flag else 0)
+ t.gauge("bridge_queue_depth", queued)
+ t.gauge("bridge_jobs_running", running)
+ t.gauge("bridge_jobs_tracked", jobs_total)
+ t.gauge("bridge_agents_online", bus_stats["agentsOnline"])
+ t.gauge("bridge_tasks_open", sum(
+ v for k, v in bus_stats["taskCounts"].items() if k in ("todo", "in_progress", "blocked")
+ ))
+ t.gauge("bridge_uptime_seconds", round(_now() - self.started, 1))
+ t.gauge("bridge_tunnel_online", 1 if self.tunnel.state == "online" else 0)
+ t.gauge("bridge_queue_paused", 1 if self.queue_paused else 0)
+ t.gauge("bridge_sweeps_total", self._sweeps)
+ return t.snapshot(uptime=_now() - self.started)
+
+ def ops_report(self) -> dict:
+ health = self.direct_dispatch("health", {})
+ metrics = self.metrics_snapshot()
+ bus_stats = self.bus.stats()
+ tasks = self.bus.list_tasks(include_done=False)
+ audit = self.telemetry.audit.tail(10)
+ with self.lock:
+ recent = [summary(self.jobs[i]) for i in list(self.history)[-12:]][::-1]
+ return {
+ "ok": True,
+ "version": VERSION,
+ "uptimeSeconds": round(_now() - self.started, 1),
+ "health": health,
+ "tunnel": self.tunnel.status(),
+ "metrics": {
+ "counters": {f"{c['name']}{json.dumps(c['labels'], sort_keys=True) if c['labels'] else ''}": c["value"] for c in metrics["counters"][:80]},
+ "histograms": metrics["histograms"][:20],
+ },
+ "bus": bus_stats,
+ "openTasks": tasks["tasks"][:20],
+ "audit": audit["entries"],
+ "recentJobs": recent,
```

```
+ "queue": {
+ "paused": self.queue_paused,
+ "reason": self.queue_paused_reason,
+ "pausedAt": self.queue_paused_at,
+ "depth": health.get("queued"),
+ },
+ "sweeper": {
+ "intervalSeconds": self.sweep_interval,
+ "offlineSeconds": self.sweep_offline_seconds,
+ "lastSweep": self._last_sweep or None,
+ "sweeps": self._sweeps,
+ "tasksReaped": bus_stats.get("tasksReaped"),
+ "agentsReaped": bus_stats.get("agentsReaped"),
+ },
+ "jobLatency": self._job_latency_summary(),
+ "fleet": self.fleet_snapshot(),
+ "mcp": {
+ "protocolVersions": list(SUPPORTED_PROTOCOL_VERSIONS),
+ "modernProtocol": MODERN_PROTOCOL_VERSION,
+ "tasks": len(getattr(self.mcp_dispatcher, "tasks", {}) or {}),
+ },
+ "servedAt": _now(),
+ }
+
+ def _job_latency_summary(self, limit: int = 300) -> dict:
+ """p50/p95 wall time per tool over recent completed jobs (no external deps)."""
+ with self.lock:
+ samples = {}
+ for job_id in list(self.history)[-limit:]:
+ job = self.jobs.get(job_id) or {}
+ duration = job.get("duration_ms")
+ if not isinstance(duration, (int, float)) or duration <= 0:
+ continue
+ samples.setdefault(job.get("type") or "unknown", []).append(float(duration))
+ out = {}
+ for tool, values in samples.items():
+ values.sort()
+ count = len(values)
+ if not count:
+ continue
+ out[tool] = {
+ "count": count,
+ "p50": round(values[min(count - 1, int(0.50 * count))], 1),
+ "p95": round(values[min(count - 1, int(0.95 * count))], 1),
+ "max": round(values[-1], 1),
+ "mean": round(sum(values) / count, 1),
+ }
+ return dict(sorted(out.items(), key=lambda kv: -kv[1]["count"])[:20])
+

def summary(job: dict) -> dict:
out = job.get("result")
@@ -650,17 +1410,98 @@ def make_http_handler(state: BridgeState):
except Exception:
return {"_raw": raw.decode("utf-8", "replace")}

- def _authorized(self, qs: dict) -> bool:
- if not state.token:
- return True
+ @staticmethod
```

```
+ def _int_qs(qs: dict, key: str, default: int = 0, minimum: int = 0, maximum: int = 10000) -> int:
+ try:
+ value = int((qs.get(key) or [default])[0])
+ except (TypeError, ValueError):
+ return default
+ return max(minimum, min(value, maximum))
+
+ def _supplied_token(self, qs: dict):
bearer = self.headers.get("Authorization", "")
bearer_tok = bearer[7:].strip() if bearer.lower().startswith("bearer ") else None
- supplied = (
+ return (
qs.get("token", [None])[0]
or self.headers.get("X-Arena-Token")
or bearer_tok
)
- return supplied == state.token
+
+ def _auth_ctx(self, qs: dict, required: str = "read", allow_loopback: bool = False):
+ """Return (context, error). Auth is a no-op when no token is configured."""
+ supplied = self._supplied_token(qs)
+ ctx, err = state.authenticate(
+ supplied,
+ is_loopback=self._is_loopback(),
+ required=required,
+ )
+ if err and allow_loopback and required == "read" and not supplied and self._is_loopback():
+ # Backwards-compatible convenience for local dashboards/CLIs on
+ # read-only discovery endpoints. Never applied to /mcp or writes.
+ return {"role": "read", "id": "loopback", "label": "loopback"}, None
+ return ctx, err
+
+ def _authorized(self, qs: dict) -> bool:
+ ctx, err = self._auth_ctx(qs, "read")
+ return err is None
+
+ def _require(self, qs: dict, required: str = "read", allow_loopback: bool = False):
+ """Scope check that writes the error response itself. Returns ctx or None."""
+ ctx, err = self._auth_ctx(qs, required, allow_loopback=allow_loopback)
+ if err:
+ headers = None
+ if err.get("code") == 429:
+ headers = {"Retry-After": str(err.get("retryAfter", 1))}
+ payload = {"error": err.get("error")}
+ if err.get("retryAfter"):
+ payload["retryAfter"] = err["retryAfter"]
+ self._send(err.get("code", 401), payload, extra_headers=headers)
+ state.telemetry.metrics.inc(
+ "bridge_auth_rejections_total", 1,
+ {"code": str(err.get("code")), "path": urlparse(self.path).path},
+ )
+ return None
+ return ctx
+
+ # -- Server-Sent Events ---------------------------------------------------
+
+ def _stream_events(self, qs: dict):
+ cursor = self._int_qs(qs, "since", 0) or self._int_qs(qs, "cursor", 0)
+ kinds = (qs.get("kinds") or [None])[0]
+ try:
```

```
+ max_seconds = min(float((qs.get("maxSeconds") or ["300"])[0] or 300), 900)
+ except (TypeError, ValueError):
+ max_seconds = 300.0
+ self.close_connection = True
+ self.send_response(200)
+ self.send_header("Content-Type", "text/event-stream; charset=utf-8")
+ self.send_header("Cache-Control", "no-store")
+ self.send_header("Connection", "close")
+ self.send_header("X-Accel-Buffering", "no")
+ self.send_header("Access-Control-Allow-Origin", "*")
+ self.end_headers()
+
+ def _write(chunk: str):
+ self.wfile.write(chunk.encode("utf-8"))
+ self.wfile.flush()
+
+ started = time.monotonic()
+ _write(": arena bridge event stream\n\n")
+ try:
+ if cursor == 0:
+ seed = state.telemetry.events.since(0, 50, kinds)
+ for event in seed["events"]:
+ _write(f"id: {event['seq']}\ndata: {json.dumps(event)}\n\n")
+ cursor = seed["cursor"]
+ while time.monotonic() - started < max_seconds:
+ batch = state.telemetry.events.tail(cursor, timeout=10.0)
+ for event in batch["events"]:
+ _write(f"id: {event['seq']}\ndata: {json.dumps(event)}\n\n")
+ cursor = event["seq"]
+ if batch.get("timeout"):
+ _write(": keepalive\n\n")
+ except (BrokenPipeError, ConnectionResetError, OSError):
+ return

def do_OPTIONS(self):
self._send(204, b"")
@@ -722,13 +1563,17 @@ def make_http_handler(state: BridgeState):
"bridgeDir": str(HERE) if is_local else "",
"mcpServerPath": str(HERE / "mcp_server.py") if is_local else "roblox-bridge/mcp_server.py",
"cliPath": str(HERE / "arena_studio.py") if is_local else "roblox-bridge/arena_studio.py",
+ "version": VERSION,
+ "toolCount": len(TOOL_SPECS),
+ "authRoles": ["read", "write", "admin"],
"tools": tools_lite,
},
)

if path == "/mcp":
- if not self._authorized(qs):
- return self._send(401, {"error": "unauthorized"})
+ ctx = self._require(qs, "read")
+ if not ctx:
+ return
return self._send(
200,
{
@@ -737,24 +1582,29 @@ def make_http_handler(state: BridgeState):
"transport": "streamable-http",
"tools": len(TOOL_SPECS),
"readOnly": state.read_only,
```

```
+ "role": ctx["role"],
},
extra_headers={"Mcp-Session-Id": state.session_id},
)

+ # Public, unauthenticated liveness probe used by the tunnel supervisor
+ # and uptime monitors. Contains no place data or secrets.
if path == "/api/health":
return self._send(200, state.direct_dispatch("health", {}))

- if path == "/api/self-test":
- if not self._authorized(qs):
- return self._send(401, {"error": "bad token"})
- return self._send(200, run_bridge_self_test(state.mcp_client, include_studio_smoke=True, timeout=180))
-
if path == "/api/state":
+ if not self._require(qs, "read"):
+ return
return self._send(200, state.direct_dispatch("state", {}))

+ if path == "/api/self-test":
+ if not self._require(qs, "read"):
+ return
+ return self._send(200, run_bridge_self_test(state.mcp_client, include_studio_smoke=True, timeout=180))
+
if path == "/api/agent-guide":
- if not self._authorized(qs) and not self._is_loopback():
- return self._send(401, {"error": "bad token"})
+ if not self._require(qs, "read", allow_loopback=True):
+ return
host_hdr = self.headers.get("Host") or "127.0.0.1:8077"
proto = "https" if self.headers.get("CF-Connecting-IP") else "http"
return self._send(
@@ -763,18 +1613,77 @@ def make_http_handler(state: BridgeState):
)

if path == "/api/peers":
- if not self._authorized(qs):
- return self._send(401, {"error": "bad token"})
+ if not self._require(qs, "read"):
+ return
return self._send(200, state.direct_dispatch("peers", {}))

+ if path == "/api/studios":
+ if not self._require(qs, "read"):
+ return
+ return self._send(200, state.fleet_snapshot())
+
+ # --- v5 observability & collaboration --------------------------------
+ if path == "/api/ops":
+ if not self._require(qs, "read"):
+ return
+ return self._send(200, state.ops_report())
+
+ if path == "/api/metrics":
+ if not self._require(qs, "read"):
+ return
+ fmt = (qs.get("format") or ["json"])[0].lower()
+ if fmt in ("prometheus", "prom", "text"):
+ body = state.telemetry.metrics.prometheus()
```

```
+ return self._send(200, body, "text/plain; version=0.0.4; charset=utf-8")
+ return self._send(200, state.metrics_snapshot())
+
+ if path == "/api/events":
+ if not self._require(qs, "read"):
+ return
+ if (qs.get("once") or qs.get("snapshot") or ["0"])[0] in ("1", "true", "yes"):
+ cursor = self._int_qs(qs, "since", 0) or self._int_qs(qs, "cursor", 0)
+ limit = self._int_qs(qs, "limit", 100, 1, 1000)
+ return self._send(200, state.telemetry.events.since(cursor, limit, (qs.get("kinds") or [None])[0]))
+ return self._stream_events(qs)
+
+ if path == "/api/audit":
+ if not self._require(qs, "read"):
+ return
+ if (qs.get("verify") or ["0"])[0] in ("1", "true", "yes"):
+ return self._send(200, state.telemetry.audit.verify())
+ limit = self._int_qs(qs, "limit", 100, 1, 2000)
+ return self._send(200, state.telemetry.audit.tail(limit, (qs.get("action") or [None])[0]))
+
+ if path == "/api/bus":
+ if not self._require(qs, "read"):
+ return
+ payload = {k: v[0] for k, v in qs.items() if k != "token"}
+ payload.setdefault("action", "stats")
+ try:
+ return self._send(200, state.bus.handle(payload))
+ except KeyError as exc:
+ return self._send(404, {"error": str(exc)})
+ except ValueError as exc:
+ return self._send(400, {"error": str(exc)})
+
+ if path == "/api/tunnel":
+ if not self._require(qs, "read"):
+ return
+ return self._send(200, state.tunnel.status())
+
+ if path == "/api/tokens":
+ if not self._require(qs, "admin"):
+ return
+ return self._send(200, state.tokens.list())
+
if path == "/api/snapshots":
- if not self._authorized(qs):
- return self._send(401, {"error": "bad token"})
+ if not self._require(qs, "read"):
+ return
return self._send(200, state.handle_snapshots({"action": "list"}))

if path.startswith("/api/snapshots/"):
- if not self._authorized(qs):
- return self._send(401, {"error": "bad token"})
+ if not self._require(qs, "read"):
+ return
sid = path.rsplit("/", 1)[-1]
try:
return self._send(200, state.handle_snapshots({"action": "get", "id": sid}))
@@ -783,15 +1692,15 @@ def make_http_handler(state: BridgeState):

# Studio plugin long-polls here
```

```
if path == "/api/poll":
- if not self._authorized(qs):
- return self._send(401, {"error": "bad token"})
+ if not self._require(qs, "read"):
+ return
peer_info = state.record_poll(qs)
job = state.poll_for_job(peer_info, wait_seconds=8.0)
- return self._send(200, {"job": job})
+ return self._send(200, {"job": job, "paused": state.queue_paused})

if path.startswith("/api/jobs/"):
- if not self._authorized(qs) and not self._is_loopback():
- return self._send(401, {"error": "bad token"})
+ if not self._require(qs, "read", allow_loopback=True):
+ return
job_id = path.rsplit("/", 1)[-1]
with state.lock:
job = state.jobs.get(job_id)
@@ -800,8 +1709,8 @@ def make_http_handler(state: BridgeState):
return self._send(200, job)

if path == "/api/jobs":
- if not self._authorized(qs) and not self._is_loopback():
- return self._send(401, {"error": "bad token"})
+ if not self._require(qs, "read", allow_loopback=True):
+ return
with state.lock:
return self._send(200, {"jobs": [summary(state.jobs[i]) for i in state.history]})

@@ -812,11 +1721,12 @@ def make_http_handler(state: BridgeState):
qs = parse_qs(url.query)
path = url.path.rstrip("/") or "/"

- if not self._authorized(qs):
- return self._send(401, {"error": "bad token"})
-
- # Native MCP Streamable HTTP endpoint (JSON-RPC 2.0)
+ # Native MCP Streamable HTTP endpoint (JSON-RPC 2.0). The token role
+ # determines whether mutating tools are advertised/callable.
if path == "/mcp":
+ ctx = self._require(qs, "read")
+ if not ctx:
+ return
raw = self._read_body_raw()
try:
rpc_in = json.loads(raw.decode("utf-8"))
@@ -826,6 +1736,40 @@ def make_http_handler(state: BridgeState):
{"jsonrpc": "2.0", "id": None, "error": {"code": -32700, "message": f"Parse error: {exc}"}},
extra_headers={"Mcp-Session-Id": state.session_id},
)
+ # Dual-era MCP over Streamable HTTP:
+ # * modern clients send the version in MCP-Protocol-Version (and
+ # optionally per-request _meta) instead of an initialize handshake
+ # * Mcp-Method / Mcp-Name must agree with the body (-32020)
+ header_version = (self.headers.get("MCP-Protocol-Version") or "").strip()
+ header_method = (self.headers.get("Mcp-Method") or "").strip()
+ header_name = (self.headers.get("Mcp-Name") or "").strip()
+ if isinstance(rpc_in, dict):
+ if header_version:
+ meta = rpc_in.get("_meta")
```

```
+ if not isinstance(meta, dict):
+ meta = {}
+ rpc_in["_meta"] = meta
+ meta.setdefault("io.modelcontextprotocol/protocolVersion", header_version)
+ body_method = (rpc_in.get("method") or "").strip()
+ if header_method and body_method and header_method != body_method:
+ return self._send(400, {
+ "jsonrpc": "2.0", "id": rpc_in.get("id"),
+ "error": {"code": -32020, "message": "Mcp-Method header does not match the JSON-RPC method",
+ "data": {"header": header_method, "body": body_method}},
+ }, extra_headers={"Mcp-Session-Id": state.session_id})
+ if header_name and body_method in ("tools/call", "resources/read", "prompts/get"):
+ params = rpc_in.get("params") or {}
+ body_name = params.get("name") or params.get("uri") or ""
+ if body_name and header_name != body_name:
+ return self._send(400, {
+ "jsonrpc": "2.0", "id": rpc_in.get("id"),
+ "error": {"code": -32020, "message": "Mcp-Name header does not match the request name",
+ "data": {"header": header_name, "body": body_name}},
+ }, extra_headers={"Mcp-Session-Id": state.session_id})
+
+ rpc_in, scope_error = self._enforce_mcp_scope(rpc_in, ctx)
+ if scope_error is not None:
+ return self._send(200, scope_error, extra_headers={"Mcp-Session-Id": state.session_id})
rpc_out = state.mcp_dispatcher.handle_payload(rpc_in)
if rpc_out is None:
return self._send(202, b"", "text/plain; charset=utf-8", {"Mcp-Session-Id": state.session_id})
@@ -833,8 +1777,12 @@ def make_http_handler(state: BridgeState):

body = self._body()

- # Enqueue job for Studio
+ # Enqueue job for Studio (requires write scope; admin when read-only
+ # inspector mode is active, since that setting is a safety control).
if path == "/api/jobs":
+ ctx = self._require(qs, "write")
+ if not ctx:
+ return
kind = body.get("type")
if not kind:
return self._send(400, {"error": "type is required"})
@@ -842,10 +1790,14 @@ def make_http_handler(state: BridgeState):
job, evt = state.enqueue_job(
kind=kind,
payload=body.get("payload"),
- note=body.get("note"),
+ note=body.get("note") or f"api:{ctx['label']}",
dm=body.get("dm"),
peer_id=body.get("peer_id"),
place_id=body.get("place_id"),
+ idempotency_key=body.get("idempotencyKey") or self.headers.get("Idempotency-Key"),
+ priority=body.get("priority", 5),
+ max_retries=body.get("maxRetries", 0),
+ timeout=body.get("timeout"),
)
except PermissionError as exc:
return self._send(403, {"error": str(exc)})
@@ -855,9 +1807,16 @@ def make_http_handler(state: BridgeState):
evt.wait(timeout=min(wait, 120.0))
with state.lock:
```

```
return self._send(200, state.jobs[job["id"]])
- return self._send(201, {"id": job["id"], "status": job["status"]})
+ return self._send(201, {
+ "id": job["id"],
+ "status": job["status"],
+ "priority": job.get("priority"),
+ "deduplicated": job.get("deduplicated", 0),
+ })

if path.startswith("/api/jobs/") and path.endswith("/cancel"):
+ if not self._require(qs, "write"):
+ return
parts = path.split("/")
job_id = parts[3] if len(parts) >= 5 else ""
try:
@@ -866,9 +1825,24 @@ def make_http_handler(state: BridgeState):
return self._send(404, {"error": str(exc)})

if path == "/api/queue/clear":
- return self._send(200, {"cancelled": state.clear_queue()})
+ ctx = self._require(qs, "admin")
+ if not ctx:
+ return
+ cancelled = state.clear_queue()
+ state.telemetry.audit.append("queue.clear", actor=ctx["label"], detail={"cancelled": cancelled})
+ return self._send(200, {"cancelled": cancelled})
+
+ if path in ("/api/queue/pause", "/api/queue/resume"):
+ ctx = self._require(qs, "admin")
+ if not ctx:
+ return
+ if path.endswith("pause"):
+ return self._send(200, state.pause_queue(body.get("reason")))
+ return self._send(200, state.resume_queue())

if path == "/api/snapshots":
+ if not self._require(qs, "write"):
+ return
try:
return self._send(200, state.handle_snapshots(body))
except KeyError as exc:
@@ -876,14 +1850,148 @@ def make_http_handler(state: BridgeState):
except ValueError as exc:
return self._send(400, {"error": str(exc)})

+ # --- v5 collaboration & ops control ---------------------------------
+ if path == "/api/bus":
+ action = (body.get("action") or "stats")
+ required = "write" if action not in (
+ "stats", "agents", "list_agents", "inbox", "thread", "tasks",
+ "list_tasks", "feed", "events", "status",
+ ) else "read"
+ ctx = self._require(qs, required)
+ if not ctx:
+ return
+ try:
+ result = state.bus.handle(body)
+ except KeyError as exc:
+ return self._send(404, {"error": str(exc)})
+ except ValueError as exc:
```

```
+ return self._send(400, {"error": str(exc)})
+ state.telemetry.metrics.inc("bridge_bus_actions_total", 1, {"action": action})
+ return self._send(200, result)
+
+ if path == "/api/studios":
+ action = (body.get("action") or "list").lower()
+ ctx = self._require(qs, "read" if action in ("list", "status") else "write")
+ if not ctx:
+ return
+ try:
+ if action == "broadcast":
+ return self._send(200, state.broadcast(
+ kind=body.get("type") or body.get("kind") or "ping",
+ payload=body.get("payload") if body.get("payload") else {"path": body["path"]} if body.get("path") else None,
+ timeout=float(body.get("timeout") or 20.0),
+ dm=body.get("dm"),
+ tool=body.get("tool"),
+ ))
+ return self._send(200, state.fleet_action(body))
+ except KeyError as exc:
+ return self._send(404, {"error": str(exc)})
+ except ValueError as exc:
+ return self._send(400, {"error": str(exc)})
+
+ if path == "/api/ops":
+ action = (body.get("action") or "status").lower()
+ required = "read" if action in ("status", "report") else "admin"
+ ctx = self._require(qs, required)
+ if not ctx:
+ return
+ if action in ("status", "report"):
+ return self._send(200, state.ops_report())
+ try:
+ result = state.direct_dispatch(action, body)
+ except ValueError as exc:
+ return self._send(400, {"error": str(exc)})
+ state.telemetry.audit.append(f"ops.{action}", actor=ctx["label"], outcome="ok")
+ return self._send(200, result)
+
+ if path == "/api/tunnel":
+ action = (body.get("action") or "status").lower()
+ required = "admin" if action in ("start", "stop", "restart") else "read"
+ ctx = self._require(qs, required)
+ if not ctx:
+ return
+ try:
+ result = state.tunnel_action(body)
+ except ValueError as exc:
+ return self._send(400, {"error": str(exc)})
+ if action in ("start", "stop", "restart"):
+ state.telemetry.audit.append(f"tunnel.{action}", actor=ctx["label"], outcome="ok")
+ state.telemetry.events.emit("tunnel.action", {"action": action, "actor": ctx["label"]})
+ return self._send(200, result)
+
+ if path == "/api/tokens":
+ ctx = self._require(qs, "admin")
+ if not ctx:
+ return
+ action = (body.get("action") or "list")
+ try:
```

```
+ result = state.tokens.handle(body)
+ except KeyError as exc:
+ return self._send(404, {"error": str(exc)})
+ except ValueError as exc:
+ return self._send(400, {"error": str(exc)})
+ if action in ("create", "revoke"):
+ state.telemetry.audit.append(
+ f"token.{action}", actor=ctx["label"],
+ target=result.get("id") or body.get("id") or "",
+ detail={"role": result.get("role")} if action == "create" else None,
+ )
+ return self._send(200, result)
+
# Studio plugin posts completed job result
if path == "/api/result":
+ if not self._require(qs, "write"):
+ return
if not state.complete_job(body):
return self._send(404, {"error": "no such job"})
return self._send(200, {"ack": True})

return self._send(404, {"error": "not found"})

+ def _enforce_mcp_scope(self, rpc_in, ctx):
+ """Block mutating MCP tool calls for read-scoped tokens (batch aware)."""
+ if ctx.get("role") == "admin" or ctx.get("id") in ("open", "loopback"):
+ return rpc_in, None
+
+ def blocked(item):
+ if not isinstance(item, dict) or item.get("method") != "tools/call":
+ return None
+ params = item.get("params") or {}
+ name = params.get("name")
+ args = params.get("arguments") or {}
+ spec = TOOL_MAP.get(name)
+ if not spec:
+ return None
+ if spec.get("annotations", {}).get("readOnlyHint"):
+ return None
+ if is_tool_call_read_only(name, args):
+ return None
+ message = (
+ f"Blocked by token scope: token '{ctx.get('label')}' has role "
+ f"'{ctx.get('role')}', which cannot call mutating tool '{name}'. "
+ "Mint a write-scoped token via POST /api/tokens or use bridge.token."
+ )
+ return {
+ "jsonrpc": "2.0",
+ "id": item.get("id"),
+ "result": {
+ "isError": True,
+ "content": [{"type": "text", "text": message}],
+ "structuredContent": {"ok": False, "reason": "insufficient_scope", "tool": name},
+ },
+ }
+
+ if isinstance(rpc_in, list):
+ for item in rpc_in:
+ err = blocked(item)
+ if err is not None:
```

```
+ return rpc_in, err
+ return rpc_in, None
+ err = blocked(rpc_in)
+ if err is not None:
+ return rpc_in, err
+ return rpc_in, None
+
return Handler


@@ -892,84 +2000,217 @@ def make_http_handler(state: BridgeState):
# ---------------------------------------------------------------------------

def dashboard_html() -> str:
- return r"""<!doctype html>
+ html = r"""<!doctype html>
<html lang="en"><head><meta charset="utf-8">
<title>Roblox Studio MCP, 3D Viewport Vision &amp; Open-Source Kit (v4.0)</title>
<meta name="viewport" content="width=device-width,initial-scale=1">
<style>
- :root{color-scheme:dark;--bg:#0b0f16;--panel:#131922;--panel2:#0e131b;--border:#232c3a;
- --txt:#e6edf3;--muted:#8b949e;--accent:#58a6ff;--green:#3fb950;--red:#f85149;--amber:#d29922}
+ :root{color-scheme:dark;--bg:#070b12;--bg2:#0a1018;--panel:rgba(19,25,34,.82);--panel2:#0d131c;
+ --border:#22303f;--border2:#2c3f55;--txt:#e8eff7;--muted:#8fa0b4;--accent:#5cc8ff;
+ --accent2:#a78bfa;--green:#45e0a0;--red:#ff6b6b;--amber:#ffc857;--radius:14px;
+ --shadow:0 18px 40px -24px rgba(0,0,0,.9)}
*{box-sizing:border-box}
+ html{scroll-behavior:smooth}
body{margin:0;background:var(--bg);color:var(--txt);
- font:13.5px/1.55 system-ui,-apple-system,Segoe UI,Roboto,sans-serif}
+ font:13.5px/1.6 ui-sans-serif,system-ui,-apple-system,"Segoe UI",Roboto,sans-serif;
+ -webkit-font-smoothing:antialiased;position:relative;min-height:100vh}
+ body::before{content:"";position:fixed;inset:-30% -10% auto -10%;height:75vh;z-index:-1;pointer-events:none;
+ background:
+ radial-gradient(46% 60% at 18% 20%,rgba(92,200,255,.16),transparent 70%),
+ radial-gradient(40% 55% at 78% 10%,rgba(167,139,250,.16),transparent 70%),
+ radial-gradient(52% 60% at 55% 78%,rgba(69,224,160,.09),transparent 72%);
+ filter:blur(6px);animation:aura 22s ease-in-out infinite alternate}
+ body::after{content:"";position:fixed;inset:0;z-index:-2;pointer-events:none;opacity:.35;
+ background-image:linear-gradient(rgba(255,255,255,.028) 1px,transparent 1px),
+ linear-gradient(90deg,rgba(255,255,255,.028) 1px,transparent 1px);
+ background-size:46px 46px;
+ -webkit-mask-image:radial-gradient(ellipse at 50% 0%,#000 20%,transparent 78%);
+ mask-image:radial-gradient(ellipse at 50% 0%,#000 20%,transparent 78%)}
+ @keyframes aura{0%{transform:translate3d(-2%,0,0) scale(1)}50%{transform:translate3d(2%,2%,0) scale(1.06)}100%{transform:translate3d(-1%,3%,0) scale(1.02)}}
+ ::selection{background:rgba(92,200,255,.28);color:#fff}
+ *::-webkit-scrollbar{width:10px;height:10px}
+ *::-webkit-scrollbar-track{background:transparent}
+ *::-webkit-scrollbar-thumb{background:#1e2a38;border-radius:99px;border:2px solid transparent;background-clip:content-box}
+ *::-webkit-scrollbar-thumb:hover{background:#2c3f55;background-clip:content-box}
code,pre,textarea,input,select{font-family:ui-monospace,SFMono-Regular,Menlo,Consolas,monospace}
- header{padding:14px 24px;background:var(--panel);border-bottom:1px solid var(--border);
- display:flex;align-items:center;gap:12px;flex-wrap:wrap;position:sticky;top:0;z-index:20}
- h1{font-size:16px;font-weight:700;margin:0;letter-spacing:.2px}
+ header{padding:16px 26px;background:linear-gradient(180deg,rgba(12,18,26,.94),rgba(12,18,26,.72));
+ -webkit-backdrop-filter:blur(14px) saturate(140%);backdrop-filter:blur(14px) saturate(140%);
+ border-bottom:1px solid var(--border);display:flex;align-items:center;gap:12px;flex-wrap:wrap;
+ position:sticky;top:0;z-index:30}
+ header::after{content:"";position:absolute;left:0;right:0;bottom:-1px;height:1px;
+ background:linear-gradient(90deg,transparent,rgba(92,200,255,.55),rgba(167,139,250,.55),transparent);
```

```
+ opacity:.7}
+ h1{font-size:16.5px;font-weight:750;margin:0;letter-spacing:.2px;display:flex;align-items:center;gap:9px}
+ h1 .brand{background:linear-gradient(92deg,#e8eff7 10%,#9ddcff 55%,#c3b3ff 95%);
+ -webkit-background-clip:text;background-clip:text;color:transparent}
+ h1 .logo{width:22px;height:22px;border-radius:7px;flex:0 0 auto;
+ background:conic-gradient(from 210deg,#5cc8ff,#a78bfa,#45e0a0,#5cc8ff);
+ box-shadow:0 0 18px rgba(92,200,255,.42);animation:spin 14s linear infinite}
+ @keyframes spin{to{transform:rotate(360deg)}}
h2{font-size:15px;font-weight:700;margin:0 0 8px}
- h3{font-size:13.5px;font-weight:700;margin:0 0 6px;color:#c9d1d9}
+ h3{font-size:13.5px;font-weight:700;margin:0 0 6px;color:#d7e3f1}
.sub{color:var(--muted);font-size:12px}
.spacer{flex:1}
- .pill{padding:4px 11px;border-radius:999px;font-size:11.5px;font-weight:600;border:1px solid transparent}
- .on{background:#0f2f1b;color:var(--green);border-color:#23562f}
- .off{background:#2d1618;color:var(--red);border-color:#5c2326}
- .ro{background:#2b220c;color:var(--amber);border-color:#5a4414}
- .info-pill{background:#122338;color:var(--accent);border-color:#244870}
- nav{display:flex;gap:6px;padding:10px 24px;background:var(--panel2);border-bottom:1px solid var(--border);
- overflow-x:auto}
+ .pill{padding:4px 11px;border-radius:999px;font-size:11.5px;font-weight:650;border:1px solid transparent;
+ display:inline-flex;align-items:center;gap:6px;transition:.18s}
+ .on{background:rgba(69,224,160,.12);color:var(--green);border-color:rgba(69,224,160,.4)}
+ .off{background:rgba(255,107,107,.12);color:var(--red);border-color:rgba(255,107,107,.36)}
+ .ro{background:rgba(255,200,87,.12);color:var(--amber);border-color:rgba(255,200,87,.38)}
+ .info-pill{background:rgba(92,200,255,.1);color:var(--accent);border-color:rgba(92,200,255,.34)}
+ .pill.live::before{content:"";width:7px;height:7px;border-radius:50%;background:currentColor;
+ box-shadow:0 0 0 0 currentColor;animation:pulse 2.1s ease-out infinite}
+ @keyframes pulse{0%{box-shadow:0 0 0 0 rgba(69,224,160,.55)}70%{box-shadow:0 0 0 7px rgba(69,224,160,0)}100%{box-shadow:0 0 0 0 rgba(69,224,160,0)}}
+ nav{display:flex;gap:6px;padding:10px 22px;background:rgba(10,16,24,.72);
+ -webkit-backdrop-filter:blur(10px);backdrop-filter:blur(10px);
+ border-bottom:1px solid var(--border);overflow-x:auto;position:relative;z-index:25}
.tab-btn{background:transparent;color:var(--muted);border:1px solid transparent;padding:7px 14px;
- border-radius:8px;cursor:pointer;font-size:13px;font-weight:600;white-space:nowrap}
- .tab-btn:hover{color:var(--txt);background:#17202c}
- .tab-btn.active{color:#fff;background:#1b2838;border-color:#2f4663}
- main{padding:20px 24px;max-width:1280px;margin:0 auto}
+ border-radius:10px;cursor:pointer;font-size:12.8px;font-weight:650;white-space:nowrap;
+ position:relative;transition:color .18s,background .18s,transform .18s,box-shadow .18s}
+ .tab-btn:hover{color:var(--txt);background:rgba(255,255,255,.05);transform:translateY(-1px)}
+ .tab-btn.active{color:#fff;background:linear-gradient(180deg,rgba(92,200,255,.2),rgba(92,200,255,.07));
+ border-color:rgba(92,200,255,.38);box-shadow:0 6px 18px -12px rgba(92,200,255,.9),inset 0 1px 0 rgba(255,255,255,.08)}
+ .tab-btn.active::after{content:"";position:absolute;left:14px;right:14px;bottom:-6px;height:2px;border-radius:2px;
+ background:linear-gradient(90deg,transparent,var(--accent),transparent)}
+ main{padding:22px 26px 60px;max-width:1300px;margin:0 auto;animation:fadeUp .4s ease both}
+ @keyframes fadeUp{from{opacity:0;transform:translateY(6px)}to{opacity:1;transform:none}}
.tab-pane{display:none}
- .tab-pane.active{display:block}
+ .tab-pane.active{display:block;animation:paneIn .3s cubic-bezier(.2,.7,.3,1) both}
+ @keyframes paneIn{from{opacity:0;transform:translateY(10px) scale(.996)}to{opacity:1;transform:none}}
.grid{display:grid;grid-template-columns:repeat(auto-fit,minmax(160px,1fr));gap:12px;margin-bottom:18px}
- .card{background:var(--panel);border:1px solid var(--border);border-radius:10px;padding:14px}
- .card .k{font-size:11px;color:var(--muted);text-transform:uppercase;letter-spacing:.6px}
- .card .v{font:600 19px/1.25 ui-monospace,monospace;margin-top:5px}
+ .card{background:linear-gradient(180deg,rgba(24,32,44,.9),rgba(15,21,29,.9));border:1px solid var(--border);
+ border-radius:var(--radius);padding:15px;position:relative;overflow:hidden;
+ transition:transform .22s cubic-bezier(.2,.7,.3,1),border-color .22s,box-shadow .22s}
+ .card::before{content:"";position:absolute;inset:0 0 auto 0;height:2px;opacity:0;transition:opacity .25s;
+ background:linear-gradient(90deg,transparent,var(--accent),var(--accent2),transparent)}
+ .card:hover{transform:translateY(-3px);border-color:var(--border2);box-shadow:var(--shadow)}
```

```
+ .card:hover::before{opacity:.9}
+ .card .k{font-size:10.5px;color:var(--muted);text-transform:uppercase;letter-spacing:.9px;font-weight:650}
+ .card .v{font:650 20px/1.25 ui-monospace,monospace;margin-top:6px;letter-spacing:-.3px}
.toolbar{display:flex;gap:8px;flex-wrap:wrap;align-items:center;margin-bottom:16px;
- padding:12px;background:var(--panel);border:1px solid var(--border);border-radius:10px}
- button,.btn{background:#1f2937;color:var(--txt);border:1px solid #334155;border-radius:7px;
- padding:6px 12px;font-size:12.5px;font-weight:600;cursor:pointer;transition:.12s}
- button:hover{background:#283548;border-color:#4b5f7a}
- button.primary{background:#1f6feb;border-color:#388bfd;color:#fff}
- button.primary:hover{background:#2977f5}
- button.danger{background:#3a181c;border-color:#6e2b31;color:#ff8b85}
- button.sm{padding:4px 9px;font-size:11.5px}
+ padding:12px;background:var(--panel);border:1px solid var(--border);border-radius:var(--radius);
+ -webkit-backdrop-filter:blur(8px);backdrop-filter:blur(8px)}
+ button,.btn{background:linear-gradient(180deg,#1e2a38,#1a2330);color:var(--txt);border:1px solid #31465c;
+ border-radius:9px;padding:7px 13px;font-size:12.5px;font-weight:650;cursor:pointer;
+ transition:transform .14s,box-shadow .18s,background .18s,border-color .18s;
+ box-shadow:inset 0 1px 0 rgba(255,255,255,.05)}
+ button:hover{background:linear-gradient(180deg,#26374b,#1e2a38);border-color:#44618a;transform:translateY(-1px);
+ box-shadow:0 10px 22px -16px rgba(92,200,255,.9)}
+ button:active{transform:translateY(1px) scale(.99)}
+ button:focus-visible,select:focus-visible,input:focus-visible,textarea:focus-visible{
+ outline:2px solid rgba(92,200,255,.7);outline-offset:2px}
+ button.primary{background:linear-gradient(180deg,#2f86f6,#1f6feb);border-color:#4f9dff;color:#fff}
+ button.primary:hover{background:linear-gradient(180deg,#3d95ff,#2a7bf0);box-shadow:0 12px 26px -16px rgba(56,139,253,1)}
+ button.danger{background:linear-gradient(180deg,#3a181c,#2c1216);border-color:#6e2b31;color:#ff9d97}
+ button.sm{padding:4px 10px;font-size:11.5px;border-radius:8px}
+ button.ghost{background:transparent;border-color:var(--border)}
input,select,textarea{background:var(--panel2);color:var(--txt);border:1px solid var(--border);
- border-radius:7px;padding:7px 10px;font-size:12.5px;width:100%}
- textarea{min-height:110px;resize:vertical;line-height:1.45}
+ border-radius:9px;padding:8px 11px;font-size:12.5px;width:100%;transition:border-color .18s,box-shadow .18s}
+ input:hover,select:hover,textarea:hover{border-color:var(--border2)}
+ textarea{min-height:110px;resize:vertical;line-height:1.5}
table{width:100%;border-collapse:collapse;background:var(--panel);border:1px solid var(--border);
- border-radius:10px;overflow:hidden;margin-bottom:18px}
- th{font-size:11px;text-transform:uppercase;letter-spacing:.6px;color:var(--muted);
- text-align:left;padding:10px 12px;background:var(--panel2);border-bottom:1px solid var(--border)}
- td{padding:9px 12px;border-bottom:1px solid #1b222e;vertical-align:top;font-size:12.5px}
+ border-radius:var(--radius);overflow:hidden;margin-bottom:18px}
+ th{font-size:10.5px;text-transform:uppercase;letter-spacing:.9px;color:var(--muted);
+ text-align:left;padding:10px 12px;background:rgba(13,19,28,.9);border-bottom:1px solid var(--border);font-weight:650}
+ td{padding:9px 12px;border-bottom:1px solid rgba(27,34,46,.8);vertical-align:top;font-size:12.5px}
+ tbody tr{transition:background .16s}
+ tbody tr:nth-child(even) td{background:rgba(255,255,255,.012)}
tr:last-child td{border-bottom:none}
- tr.clickable:hover td{background:#17202d;cursor:pointer}
+ tr.clickable:hover td{background:rgba(92,200,255,.06);cursor:pointer}
.s-done{color:var(--green)}.s-error,.s-cancelled{color:var(--red)}.s-running{color:var(--amber)}
.s-queued{color:var(--muted)}
- code{background:var(--panel2);border:1px solid var(--border);border-radius:5px;padding:1px 6px;font-size:12px}
- pre{background:var(--panel2);border:1px solid var(--border);border-radius:8px;padding:12px;
- overflow:auto;margin:8px 0 0;font-size:12px;line-height:1.5;white-space:pre-wrap;word-break:break-word}
+ code{background:rgba(255,255,255,.05);border:1px solid var(--border);border-radius:6px;padding:1px 6px;font-size:12px}
+ pre{background:rgba(9,14,21,.9);border:1px solid var(--border);border-radius:11px;padding:12px;
+ overflow:auto;margin:8px 0 0;font-size:12px;line-height:1.55;white-space:pre-wrap;word-break:break-word}
.empty{padding:22px;text-align:center;color:var(--muted)}
.two-col{display:grid;grid-template-columns:repeat(auto-fit,minmax(460px,1fr));gap:14px;margin-bottom:16px}
- .prompt-card{background:var(--panel);border:1px solid var(--border);border-radius:10px;padding:15px;
- display:flex;flex-direction:column;gap:8px}
```

```
+ .prompt-card{background:linear-gradient(180deg,rgba(21,29,40,.92),rgba(14,20,28,.92));
+ border:1px solid var(--border);border-radius:var(--radius);padding:16px;
+ display:flex;flex-direction:column;gap:9px;transition:border-color .2s,box-shadow .2s}
+ .prompt-card:hover{border-color:var(--border2);box-shadow:var(--shadow)}
.prompt-head{display:flex;justify-content:space-between;align-items:flex-start;gap:10px}
- .cmd-row{display:flex;align-items:center;gap:10px;padding:8px 10px;background:var(--panel2);
- border:1px solid var(--border);border-radius:8px;margin-bottom:7px}
+ .cmd-row{display:flex;align-items:center;gap:10px;padding:9px 11px;background:rgba(255,255,255,.03);
+ border:1px solid var(--border);border-radius:10px;margin-bottom:7px;transition:border-color .16s,background .16s}
+ .cmd-row:hover{border-color:var(--border2);background:rgba(92,200,255,.05)}
.cmd-row code{background:none;border:none;padding:0;flex:1;overflow-x:auto;white-space:nowrap}
.cmd-desc{color:var(--muted);font-size:11.5px;min-width:190px;text-align:right}
- .toast{position:fixed;bottom:20px;right:20px;background:#1f6feb;color:#fff;padding:9px 16px;
- border-radius:8px;font-weight:600;font-size:12.5px;opacity:0;pointer-events:none;transition:.2s;z-index:99}
- .toast.show{opacity:1}
- @media(max-width:720px){.two-col{grid-template-columns:1fr}.cmd-desc{display:none}}
+ .toast{position:fixed;bottom:22px;right:22px;background:linear-gradient(180deg,#2f86f6,#1f6feb);color:#fff;
+ padding:10px 17px;border-radius:11px;font-weight:650;font-size:12.5px;opacity:0;pointer-events:none;
+ transform:translateY(14px) scale(.97);transition:opacity .24s,transform .24s;z-index:99;
+ box-shadow:0 18px 40px -18px rgba(31,111,235,.9)}
+ .toast.show{opacity:1;transform:none}
+ /* ---- connection / auth banners ---- */
+ .banner{display:none;gap:11px;align-items:center;flex-wrap:wrap;padding:11px 24px;
+ border-bottom:1px solid rgba(255,200,87,.35);
+ background:linear-gradient(90deg,rgba(255,200,87,.16),rgba(255,107,107,.07));
+ animation:slideDown .28s ease both}
+ .banner.show{display:flex}
+ .banner.bad{border-bottom-color:rgba(255,107,107,.45);
+ background:linear-gradient(90deg,rgba(255,107,107,.16),rgba(167,139,250,.08))}
+ .banner .grow{flex:1;min-width:220px}
+ .banner input{max-width:330px}
+ @keyframes slideDown{from{opacity:0;transform:translateY(-8px)}to{opacity:1;transform:none}}
+ /* ---- multi-studio fleet ---- */
+ .fleet-bar{display:flex;align-items:center;gap:10px;padding:9px 24px;background:rgba(10,16,24,.82);
+ border-bottom:1px solid var(--border);overflow-x:auto;position:relative;z-index:22;
+ -webkit-backdrop-filter:blur(10px);backdrop-filter:blur(10px)}
+ .fleet-label{font-size:11px;letter-spacing:.9px;text-transform:uppercase;color:var(--muted);
+ font-weight:700;display:flex;align-items:center;gap:7px;flex:0 0 auto}
+ .dot-live{width:8px;height:8px;border-radius:50%;background:var(--green);box-shadow:0 0 12px rgba(69,224,160,.9);
+ animation:blink 2.4s ease-in-out infinite}
+ .dot-dead{background:var(--red);box-shadow:0 0 10px rgba(255,107,107,.7);animation:none}
+ @keyframes blink{0%,100%{opacity:1}50%{opacity:.35}}
+ .fleet-chips{display:flex;gap:8px;align-items:center;flex:1;min-width:0}
+ .studio-card{display:flex;align-items:center;gap:9px;padding:7px 11px;border-radius:11px;flex:0 0 auto;
+ background:linear-gradient(180deg,rgba(24,33,45,.95),rgba(14,20,28,.95));
+ border:1px solid var(--border);transition:transform .18s,border-color .18s,box-shadow .18s;
+ animation:chipIn .32s cubic-bezier(.2,.7,.3,1) both}
+ .studio-card:hover{transform:translateY(-2px);border-color:var(--border2);box-shadow:var(--shadow)}
+ .studio-card.pinned{border-color:rgba(92,200,255,.6);
+ box-shadow:0 0 0 1px rgba(92,200,255,.25),0 14px 28px -22px rgba(92,200,255,.9)}
+ .studio-card.active-target{border-color:rgba(69,224,160,.55)}
+ .studio-card .place{font-weight:650;font-size:12.3px;max-width:190px;overflow:hidden;text-overflow:ellipsis;white-space:nowrap}
+ .studio-card .meta{font-size:10.5px;color:var(--muted);display:flex;gap:6px;align-items:center}
+ .studio-card .pin{background:transparent;border:1px solid var(--border);border-radius:7px;padding:2px 7px;
+ font-size:10.5px;color:var(--muted)}
+ .studio-card .pin:hover{color:var(--accent);border-color:rgba(92,200,255,.55)}
+ @keyframes chipIn{from{opacity:0;transform:translateX(-8px)}to{opacity:1;transform:none}}
+ .badge-dm{font-size:10px;padding:1px 6px;border-radius:999px;border:1px solid var(--border);
+ background:rgba(255,255,255,.04);color:var(--muted);text-transform:uppercase;letter-spacing:.5px}
+ #fleet-detail{display:flex;flex-wrap:wrap;gap:10px;min-height:34px}
```

```
+ #fleet-detail .studio-card{min-width:240px}
+ @media(prefers-reduced-motion:reduce){
+ *,*::before,*::after{animation:none!important;transition:none!important;scroll-behavior:auto!important}
+ }
+ @media(max-width:720px){
+ .two-col{grid-template-columns:1fr}
+ .cmd-desc{display:none}
+ .grid{grid-template-columns:repeat(2,minmax(0,1fr));gap:8px}
+ .card .v{font-size:17px;word-break:break-all;overflow-wrap:anywhere}
+ .prompt-card{padding:12px}
+ header{flex-wrap:wrap;gap:6px;padding:12px 14px}
+ nav{padding:8px 12px}
+ .fleet-bar{padding:8px 12px}
+ main{padding:14px 12px 48px}
+ #tok-input{width:130px!important}
+ pre{max-height:190px}
+ .wrap{padding:0 10px}
+ h1{font-size:15px}
+ }
+ @media(max-width:420px){
+ .grid{grid-template-columns:repeat(2,minmax(0,1fr))}
+ .card{padding:10px}
+ .card .k{font-size:10px}
+ h1{font-size:14.5px}
+ .studio-card .place{max-width:130px}
+ }
+ html,body{max-width:100%;overflow-x:hidden}
+ img,pre,input,textarea,select{max-width:100%}
</style></head><body>

<header>
- <h1>Roblox Studio MCP &amp;amp; Bridge <span class="sub">v4.0</span></h1>
- <span id="status" class="pill off">checking&hellip;</span>
+ <h1><span class="logo" aria-hidden="true"></span><span class="brand">Roblox Studio MCP &amp;amp; Bridge</span> <span class="sub">v5.3</span></h1>
+ <span id="status" class="pill off live">checking&hellip;</span>
+ <span id="fleet-badge" class="pill info-pill" style="display:none">0 studios</span>
<span id="ro-badge" class="pill ro" style="display:none">Read-Only Inspector</span>
<span id="place" class="pill info-pill" style="display:none"></span>
<button class="sm" onclick="runSelfTest()">Run Self-Test</button>
@@ -979,6 +2220,30 @@ def dashboard_html() -> str:
<button class="sm" onclick="toggleToken()">Show</button>
</header>

+<div class="fleet-bar" id="fleet-bar">
+ <span class="fleet-label"><span class="dot-live" id="fleet-dot"></span> Studios</span>
+ <div class="fleet-chips" id="fleet-chips"><span class="sub">Looking for connected Studio windows&hellip;</span></div>
+ <button class="sm" onclick="broadcastPing()" title="Ping every online Studio and show per-peer latency">Broadcast ping</button>
+</div>
+
+<div id="auth-banner" class="banner">
+ <div class="grow">
+ <strong id="auth-title">This dashboard needs the bridge token</strong>
+ <div class="sub" id="auth-msg">Every <code>/api</code> call is authenticated. Opening the console from a
+ tunnel or LAN address cannot auto-load it - paste <code>bridge.token</code> (printed by setup.py).</div>
+ </div>
+ <input id="auth-token" type="password" placeholder="paste the token" autocomplete="off">
+ <button class="primary sm" onclick="saveToken()">Use token</button>
+ <button class="sm" onclick="hideAuthBanner()">Dismiss</button>
+</div>
+
```

```
+<div id="stale-banner" class="banner bad">
+ <div class="grow"><strong>This tab is from an older bridge version</strong>
+ <div class="sub" id="stale-msg">The bridge restarted with new code; reload to get the current UI.</div>
+ </div>
+ <button class="primary sm" onclick="location.reload()">Reload</button>
+</div>
+
 <nav>
 <button class="tab-btn active" onclick="showTab('monitor', this)">1. Live Monitor</button>
 <button class="tab-btn" onclick="showTab('kit', this)">2. Image Importer &amp;amp; Studio Kit</button>
@@ -986,6 +2251,7 @@ def dashboard_html() -> str:
 <button class="tab-btn" onclick="showTab('commands', this)">4. Commands &amp;amp; MCP Config</button>
 <button class="tab-btn" onclick="showTab('playground', this)">5. Live Tool &amp;amp; Luau Runner</button>
 <button class="tab-btn" onclick="showTab('tips', this)">6. Helpful Tips &amp;amp; Gotchas</button>
+ <button class="tab-btn" onclick="showTab('ops', this)">7. Ops Console &amp;amp; Agent Bus</button>
 </nav>

 <main>
@@ -993,7 +2259,7 @@ def dashboard_html() -> str:
 <section id="tab-monitor" class="tab-pane active">
 <div class="grid">
 <div class="card"><div class="k">Studio Peers</div><div class="v" id="c-peers">0 online</div></div>
- <div class="card"><div class="k">MCP Tools</div><div class="v" id="c-tools">68</div></div>
+ <div class="card"><div class="k">MCP Tools</div><div class="v" id="c-tools">70</div></div>
 <div class="card"><div class="k">Queued</div><div class="v" id="c-queued">0</div></div>
 <div class="card"><div class="k">Completed</div><div class="v" id="c-done">0</div></div>
 <div class="card"><div class="k">Failed</div><div class="v" id="c-fail">0</div></div>
@@ -1251,7 +2517,7 @@ def dashboard_html() -> str:

 <div class="prompt-card">
 <div class="prompt-head">
- <div><h3><code>.mcp.json</code> / Cursor / Claude Desktop (Full Access)</h3><div class="sub">All 68 tools enabled (3D viewport vision + 3D physics QA + .rbxlx + UI linter + LiveOps + sync)</div></div>
+ <div><h3><code>.mcp.json</code> / Cursor / Claude Desktop (Full Access)</h3><div class="sub">All 70 tools enabled (multi-agent bus + tunnel ops + 3D viewport vision + 3D physics QA + .rbxlx + UI linter + LiveOps + sync)</div></div>
 <button class="primary sm" onclick="copyById('cfg-json')">Copy</button>
 </div>
 <pre id="cfg-json"></pre>
@@ -1297,7 +2563,7 @@ def dashboard_html() -> str:
 </div>

 <div class="prompt-card">
- <h3>Invoke Any of the 68 MCP Tools Directly</h3>
+ <h3>Invoke Any of the 70 MCP Tools Directly</h3>
 <div class="sub" id="tool-desc">Select any MCP tool to inspect its fields and call it over <code>POST /mcp</code>.</div>
 <div style="display:flex;gap:8px;align-items:center">
 <select id="tool-select" onchange="onSelectTool()"></select>
@@ -1310,6 +2576,126 @@ def dashboard_html() -> str:
 </section>

 <!-- ==================== TAB 5: HELPFUL TIPS & GOTCHAS ==================== -->
+ <!-- ==================== TAB 7: OPS CONSOLE & AGENT BUS ==================== -->
+ <section id="tab-ops" class="tab-pane">
+ <div class="grid">
+ <div class="card"><div class="k">Tunnel</div><div class="v" id="ops-tunnel-state">stopped</div></div>
+ <div class="card"><div class="k">Public URL</div><div class="v" id="ops-tunnel-url" style="font-size:12.5px;word-break:break-all">&mdash;</div></div>
+ <div class="card"><div class="k">Agents Online</div><div class="v" id="ops-agents">0</div></div>
+ <div class="card"><div class="k">Open Tasks</div><div class="v" id="ops-tasks">0</div></div>
+ <div class="card"><div class="k">Queue Depth</div><div class="v" id="ops-queue">0</div></div>
+ <div class="card"><div class="k">Audit Entries</div><div class="v" id="ops-audit-count">0</div></div>
```

```
+ </div>
+
+ <div style="display:flex;gap:8px;align-items:center;flex-wrap:wrap;margin:-6px 0 14px">
+ <button class="sm" id="queue-toggle" onclick="toggleQueue()">Pause queue</button>
+ <span class="sub" id="queue-state">Queue live</span>
+ <span class="sub" id="sweeper-state"></span>
+ </div>
+
+ <div class="prompt-card" style="margin-bottom:14px">
+ <div class="prompt-head">
+ <div><h3>Studio Fleet</h3>
+ <div class="sub">Every connected Studio window. <b>Pin</b> makes one the default target for
+ untargeted jobs (skipped automatically if that Studio closes); <b>Broadcast</b> runs a read-only
+ ping on all of them and reports per-peer latency. Any MCP tool also takes a <code>peerId</code>.</div>
+ </div>
+ <div style="display:flex;gap:6px;flex-wrap:wrap">
+ <button class="sm" onclick="broadcastPing()">Broadcast ping</button>
+ <button class="sm" onclick="unpinStudio()">Clear pin</button>
+ </div>
+ </div>
+ <div id="fleet-detail"><span class="sub">No Studio windows connected yet.</span></div>
+ <div class="sub" id="fleet-note"></div>
+ <pre id="fleet-broadcast" style="max-height:170px;display:none"></pre>
+ </div>
+
+ <div class="two-col">
+ <div class="prompt-card">
+ <div class="prompt-head">
+ <div><h3>Public Tunnel (Supervised)</h3>
+ <div class="sub">Auto-restarts, scrapes the public URL, health-probes <code>/api/health</code>, and reconnects after failures. Works with <code>cloudflared</code> or <code>ngrok</code
>.</div>
+ </div>
+ <span class="pill off" id="ops-tunnel-pill">stopped</span>
+ </div>
+ <div style="display:flex;gap:6px;flex-wrap:wrap">
+ <button class="primary sm" onclick="tunnelAction('start')">Start Tunnel</button>
+ <button class="sm" onclick="tunnelAction('restart')">Restart</button>
+ <button class="sm danger" onclick="tunnelAction('stop')">Stop</button>
+ <button class="sm" onclick="copyText(document.getElementById('ops-tunnel-url').textContent)">Copy URL</button>
+ <button class="sm" onclick="copyMcpConfig()">Copy MCP config (tunnel)</button>
+ </div>
+ <div class="sub" id="ops-tunnel-meta" style="margin-top:6px">Checking tunnel status&hellip;</div>
+ <div class="sub" id="ops-tunnel-lan" style="margin-top:4px"></div>
+ <pre id="ops-tunnel-log" style="max-height:150px">Tunnel log will appear here.</pre>
+ </div>
+
+ <div class="prompt-card">
+ <div class="prompt-head"><div><h3>Join the Agent Bus</h3>
+ <div class="sub">Register this session so other agents (and humans) can see you, message you, and hand work over without collisions.</div></div></div>
+ <div style="display:flex;gap:6px;flex-wrap:wrap">
+ <input id="bus-name" placeholder="Agent name (e.g. Gemini 4 Argon)" style="flex:1;min-width:190px">
+ <input id="bus-role" placeholder="role (builder / qa / reviewer)" style="width:190px">
+ <button class="primary sm" onclick="busRegister()">Register</button>
+ </div>
+ <div style="display:flex;gap:6px;flex-wrap:wrap;margin-top:6px">
+ <input id="bus-to" placeholder="to (blank = broadcast)" style="width:180px">
+ <input id="bus-subject" placeholder="subject" style="width:180px">
+ </div>
+ <textarea id="bus-body" placeholder="Message body&hellip; use this to coordinate edits, hand off work, or report a blocker." style="min-height:64px"></textarea>
+ <div style="display:flex;gap:6px">
```

```
+ <button class="sm primary" onclick="busPost()">Post Message</button>
+ <button class="sm" onclick="refreshBus()">Refresh Bus</button>
+ <button class="sm" onclick="busExport()">Export Handoff</button>
+ </div>
+ <pre id="bus-out" style="max-height:110px">Bus output appears here.</pre>
+ </div>
+ </div>
+
+ <div class="two-col">
+ <div class="prompt-card">
+ <h3>Roster</h3>
+ <div id="bus-agents" class="sub">No agents registered yet.</div>
+ </div>
+ <div class="prompt-card">
+ <h3>Task Board</h3>
+ <div style="display:flex;gap:6px;margin-bottom:8px">
+ <input id="task-title" placeholder="New task title..." style="flex:1">
+ <select id="task-priority" style="width:110px">
+ <option value="normal">normal</option>
+ <option value="high">high</option>
+ <option value="critical">critical</option>
+ <option value="low">low</option>
+ </select>
+ <button class="primary sm" onclick="createTask()">Add</button>
+ <button class="sm" onclick="sweepAgents()" title="Release tasks held by agents that stopped reporting">Sweep</button>
+ </div>
+ <div id="bus-tasks" style="display:flex;flex-direction:column;gap:6px;max-height:280px;overflow:auto"></div>
+ </div>
+ </div>
+
+ <div class="two-col">
+ <div class="prompt-card">
+ <div class="prompt-head"><h3>Live Event Stream</h3>
+ <button class="sm" onclick="toggleEventStream()" id="ev-btn">Connect</button></div>
+ <div class="sub">Server-Sent Events from every agent, job, tunnel action and audit write.</div>
+ <pre id="ev-feed" style="max-height:240px;overflow:auto">Not connected.</pre>
+ </div>
+ <div class="prompt-card">
+ <div class="prompt-head"><h3>Metrics &amp;amp; Audit</h3>
+ <div style="display:flex;gap:6px">
+ <button class="sm" onclick="refreshMetrics()">Metrics</button>
+ <button class="sm" onclick="verifyAudit()">Verify Chain</button>
+ </div>
+ </div>
+ <pre id="ops-metrics" style="max-height:180px;overflow:auto">Metrics not loaded.</pre>
+ <div class="sub" id="ops-latency"></div>
+ <div class="sub" id="ops-audit-note"></div>
+ <pre id="ops-audit" style="max-height:150px;overflow:auto">Audit log not loaded.</pre>
+ </div>
+ </div>
+ </section>
+
<section id="tab-tips" class="tab-pane">
<div class="two-col" id="tips-grid"></div>
</section>
@@ -1347,13 +2733,68 @@ function toggleToken(){
inp.type = inp.type === 'password' ? 'text' : 'password';
}

-function getToken(){ return document.getElementById('tok-input').value.trim(); }
```

```
+const PAGE_VERSION = "__BRIDGE_VERSION__";
+let TOKEN = '';
+function readStoredToken(){ try { return localStorage.getItem('arena_bridge_token') || ''; } catch(_) { return ''; } }
+function getToken(){ return TOKEN || (document.getElementById('tok-input').value || '').trim(); }
+function setToken(t){
+ TOKEN = (t || '').trim();
+ const box = document.getElementById('tok-input');
+ if(box) box.value = TOKEN;
+}
+function storeToken(t){ try { localStorage.setItem('arena_bridge_token', t); } catch(_) {} }
function authHeaders(){
const h = {'Content-Type':'application/json'};
const t = getToken();
if(t) h['Authorization'] = 'Bearer ' + t;
return h;
}
+function showAuthBanner(title, message){
+ const b = document.getElementById('auth-banner');
+ if(!b) return;
+ if(title) document.getElementById('auth-title').textContent = title;
+ if(message) document.getElementById('auth-msg').textContent = message;
+ b.classList.add('show');
+ const st = document.getElementById('status');
+ st.textContent = 'token required';
+ st.className = 'pill ro';
+}
+function hideAuthBanner(){
+ const b = document.getElementById('auth-banner');
+ if(b) b.classList.remove('show');
+}
+function saveToken(){
+ const box = document.getElementById('auth-token');
+ const value = (box && box.value || '').trim();
+ if(!value) return toast('Paste the bridge token first.');
+ storeToken(value); setToken(value); box.value = '';
+ hideAuthBanner();
+ toast('Token saved for this browser - reloading data...');
+ tick(); refreshOps(); refreshFleet(); refreshBus();
+}
+function showStaleBanner(runningVersion){
+ const b = document.getElementById('stale-banner');
+ if(!b) return;
+ document.getElementById('stale-msg').textContent =
+ `This tab is v${PAGE_VERSION}; the bridge is running v${runningVersion}. Reload for the current console.`;
+ b.classList.add('show');
+}
+async function apiFetch(path, opts){
+ let res;
+ try {
+ res = await fetch(path, Object.assign({cache:'no-store', headers:authHeaders()}, opts || {}));
+ } catch(err){
+ const st = document.getElementById('status');
+ st.textContent = 'bridge unreachable'; st.className = 'pill off';
+ throw err;
+ }
+ if(res.status === 401 || res.status === 403){
+ showAuthBanner('This dashboard needs the bridge token',
+ `The bridge rejected the request (HTTP ${res.status}). Paste bridge.token - opening the console from a tunnel or LAN address cannot auto-load it.`);
+ throw new Error('unauthorized');
+ }
```

```
+ return res;
+}

async function runSelfTest(){
toast('Running isolated bridge suite and Studio scratch test...');
@@ -1586,7 +3027,7 @@ Start by running a quick recon (\`.\\ab.ps1 state\` and \`.\\ab.ps1 survey\`) so
`Connect directly to my live Roblox Studio Bridge & MCP Server:
- Base URL: ${pubUrl}
- Auth Header: \`Authorization: Bearer ${tok}\` (or \`X-Arena-Token: ${tok}\`)
-- Native MCP Streamable HTTP Endpoint: \`POST ${pubUrl}/mcp\` (68 tools, 16 skills, multimodal 3D viewport vision, 3D physics auditor, runtime mesh capability probe, .rbxlx place export, 14 LiveOps/Monetization systems, 520 3D models, 3,705 raster images + 50 LDR skies (300 cube faces), 45 CC0 WAVs, 4,811 cloud icons)
+- Native MCP Streamable HTTP Endpoint: \`POST ${pubUrl}/mcp\` (70 tools, 16 skills, multimodal 3D viewport vision, 3D physics auditor, runtime mesh capability probe, .rbxlx place export, 14 LiveOps/Monetization systems, 520 3D models, 3,705 raster images + 50 LDR skies (300 cube faces), 45 CC0 WAVs, 4,811 cloud icons)
- Agent Onboarding & Live State Endpoint: \`GET ${pubUrl}/api/agent-guide\`
- Built-in Repo Kit: call \`browse_kit\` for 16 skills, 19 modules, 6 templates, 20 prefabs, 3,755 image/sky-face files, 50 LDR sky panoramas, 520 models, and 45 CC0 audio files. Use \`search_assets\` for paginated type/category/source/license/provenance filters; exact Git blob matches and pack-level attestations are distinguished. Send supported images/audio/models into Studio with \`import_image\`, \`import_audio\`, and \`import_rbxmx\`.

@@ -2078,11 +3519,28 @@ async function loadKitGallery(){
}

async function initBoot(){
+ // Token precedence: ?token= / #token= in the URL, then this browser's saved
+ // token, then the loopback-only /api/local-boot value.
+ try {
+ const url = new URL(location.href);
+ const fromQuery = url.searchParams.get('token') || (url.hash.indexOf('#token=') === 0 ? url.hash.slice(7) : '');
+ if(fromQuery){
+ setToken(fromQuery); storeToken(getToken());
+ url.searchParams.delete('token');
+ history.replaceState({}, '', url.pathname + (url.search || ''));
+ }
+ } catch(_){}
+ if(!getToken()) setToken(readStoredToken());
try {
const r = await fetch('/api/local-boot', { cache:'no-store' });
BOOT = await r.json();
- if(BOOT.token){
- document.getElementById('tok-input').value = BOOT.token;
+ if(BOOT.token && !getToken()){
+ setToken(BOOT.token);
+ storeToken(BOOT.token);
+ }
+ if(BOOT.tokenRequired && !getToken() && !BOOT.local){
+ showAuthBanner('Opened from a tunnel or LAN address',
+ 'The bridge will not hand out its token over the network. Paste bridge.token (printed by setup.py) - it is remembered in this browser afterwards.');
}
const sel = document.getElementById('tool-select');
sel.innerHTML = BOOT.tools.map(t =>
@@ -2097,8 +3555,12 @@ async function initBoot(){

async function tick(){
try {
- const r = await fetch('/api/state', { cache:'no-store' });
+ const r = await apiFetch('/api/state');
+ if(!r.ok) throw new Error('HTTP ' + r.status);
const s = await r.json();
+ if(s && s.version && PAGE_VERSION && s.version !== PAGE_VERSION){
+ showStaleBanner(s.version);
+ }
```

```
const prevPlace = LAST_STATE.studio && LAST_STATE.studio.place;
LAST_STATE = s;

@@ -2161,8 +3623,385 @@ async function tick(){
} catch(_){}
}

-initBoot().then(() => { tick(); setInterval(tick, 1500); });
+// ---------------------------- v5 Ops Console ----------------------------
+let EV_SOURCE = null, EV_RETRY = null, EV_DELAY = 1000, EV_WANT = false;
+let QUEUE_PAUSED = false;
+async function opsJson(path, opts){
+ const r = await apiFetch(path, opts);
+ const data = await r.json().catch(() => ({}));
+ if(!r.ok) throw new Error(data.error || ('HTTP ' + r.status));
+ return data;
+}
+const REDUCED_MOTION = window.matchMedia && window.matchMedia('(prefers-reduced-motion: reduce)').matches;
+function animateValue(el, to){
+ if(!el) return;
+ const target = Number(to);
+ if(!isFinite(target)){ el.textContent = to; return; }
+ if(REDUCED_MOTION || document.hidden){ el.textContent = target; return; }
+ const from = Number(String(el.textContent).replace(/[^0-9.-]/g, '')) || 0;
+ if(from === target){ el.textContent = target; return; }
+ const t0 = performance.now(), dur = 420;
+ const step = (t) => {
+ const p = Math.min(1, (t - t0) / dur);
+ const eased = 1 - Math.pow(1 - p, 3);
+ el.textContent = Math.round(from + (target - from) * eased);
+ if(p < 1) requestAnimationFrame(step);
+ };
+ requestAnimationFrame(step);
+}
+let FLEET = {studios: [], count: 0, online: 0, pinned: null, routing: 'auto'};
+function studioCard(s, detailed){
+ const dot = s.online ? 'dot-live' : 'dot-live dot-dead';
+ const cls = 'studio-card' + (s.pinned ? ' pinned' : '') + (s.defaultTarget ? ' active-target' : '');
+ const age = s.online ? (s.ageSeconds < 2 ? 'live' : Math.round(s.ageSeconds) + 's ago') : 'offline';
+ const pin = s.pinned
+ ? `<button class="pin" onclick="unpinStudio()" title="Unpin">pinned</button>`
+ : `<button class="pin" onclick='pinStudio(${esc(JSON.stringify(s.peerId))})' title="Make this the default Studio">pin</button>`;
+ return `<div class="${cls}">
+ <span class="${dot}"></span>
+ <div>
+ <div class="place" title="${esc(s.place)} · ${esc(s.peerId)}">${esc(s.label || s.place)}</div>
+ <div class="meta"><span class="badge-dm">${esc(s.dm)}</span>
+ <span>${esc(age)}</span>
+ ${s.queuedJobs ? `<span>· ${s.queuedJobs} queued</span>` : ''}
+ ${detailed && s.placeId ? `<span>· id ${esc(String(s.placeId))}</span>` : ''}
+ ${s.defaultTarget ? '<span>· default</span>' : ''}
+ </div>
+ </div>
+ ${pin}
+ </div>`;
+}
+function renderFleet(d){
+ FLEET = d || FLEET;
+ const studios = FLEET.studios || [];
+ const chips = document.getElementById('fleet-chips');
```

```
+ const detail = document.getElementById('fleet-detail');
+ const badge = document.getElementById('fleet-badge');
+ const dot = document.getElementById('fleet-dot');
+ if(chips){
+ chips.innerHTML = studios.length
+ ? studios.map(s => studioCard(s, false)).join('')
+ : '<span class="sub">No Studio peers yet - open Roblox Studio with the ArenaBridge plugin.</span>';
+ }
+ if(detail){
+ detail.innerHTML = studios.length
+ ? studios.map(s => studioCard(s, true)).join('')
+ : '<span class="sub">No Studio windows connected yet.</span>';
+ }
+ if(badge){
+ badge.style.display = studios.length ? 'inline-flex' : 'none';
+ badge.textContent = `${FLEET.online || 0}/${studios.length} studios`;
+ }
+ if(dot) dot.classList.toggle('dot-dead', !(FLEET.online > 0));
+ const note = document.getElementById('fleet-note');
+ if(note){
+ note.textContent = !studios.length ? '' :
+ (FLEET.pinned
+ ? `Pinned: ${FLEET.pinOnline ? 'routing untargeted jobs to the pinned Studio' : 'pinned Studio is offline - falling back to auto edit-first routing'}`
+ : 'Routing: auto (edit DataModels first). Pin a Studio to make it the default target.');
+ }
+}
+async function refreshFleet(){
+ try { renderFleet(await opsJson('/api/studios')); } catch(_){}
+}
+async function pinStudio(peerId){
+ try {
+ const res = await opsJson('/api/studios', {method:'POST', body:JSON.stringify({action:'set_active', peerId})});
+ toast(`Pinned ${res.place || peerId} as the default Studio.`);
+ refreshFleet(); refreshOps();
+ } catch(err){ toast(err.message); }
+}
+async function unpinStudio(){
+ try {
+ await opsJson('/api/studios', {method:'POST', body:JSON.stringify({action:'clear_active'})});
+ toast('Pin cleared - back to auto routing.');
+ refreshFleet(); refreshOps();
+ } catch(err){ toast(err.message); }
+}
+async function broadcastPing(){
+ const box = document.getElementById('fleet-broadcast');
+ if(box){ box.style.display = 'block'; box.textContent = 'Broadcasting to every online Studio...'; }
+ try {
+ const res = await opsJson('/api/studios', {method:'POST', body:JSON.stringify({action:'broadcast', type:'ping', timeout:12})});
+ const rows = (res.results || []).map(r =>
+ `${r.ok ? 'OK' : 'x'} ${r.label || r.peerId} · ${r.status}${r.durationMs != null ? ' · ' + Math.round(r.durationMs) + 'ms' : ''}${r.error ? ' · ' + r.error : ''}`);
+ if(box) box.textContent = `${res.succeeded}/${res.peers} studios responded in ${res.elapsedMs}ms\n` + (rows.join('\n') || res.error || 'no peers');
+ toast(res.peers ? `${res.succeeded}/${res.peers} studios answered the broadcast.` : (res.error || 'No Studio peers.'));
+ refreshFleet();
+ } catch(err){
+ if(box) box.textContent = err.message;
+ toast(err.message);
+ }
+}
+async function refreshOps(){
+ try {
```

```
+ const ops = await opsJson('/api/ops');
+ const t = ops.tunnel || {};
+ document.getElementById('ops-tunnel-state').textContent = t.state || 'unknown';
+ document.getElementById('ops-tunnel-url').textContent = t.publicUrl || '-';
+ const pill = document.getElementById('ops-tunnel-pill');
+ pill.textContent = t.state || 'unknown';
+ pill.className = 'pill ' + (t.state === 'online' ? 'on' : (t.state === 'degraded' ? 'ro' : 'off'));
+ document.getElementById('ops-agents').textContent = (ops.bus && ops.bus.agentsOnline) || 0;
+ document.getElementById('ops-tasks').textContent = (ops.openTasks || []).length;
+ animateValue(document.getElementById('ops-queue'), (ops.health && ops.health.queued) || 0);
+ if(ops.fleet) renderFleet(ops.fleet);
+ document.getElementById('ops-audit-count').textContent = (ops.audit || []).length;
+ const health = t.health || {};
+ document.getElementById('ops-tunnel-meta').textContent =
+ `flavor=${t.flavor || '-'} · restarts=${t.restarts || 0} · health=${health.ok === null || health.ok === undefined ? 'n/a' : (health.ok ? 'ok' : 'failing')}` +
+ (health.latencyMs != null ? ` · ${health.latencyMs}ms` : '') + (t.lastError ? ' · ' + t.lastError : '');
+ document.getElementById('ops-tunnel-lan').textContent = (t.lanUrls || []).length ? 'LAN: ' + t.lanUrls.join(' · ') : '';
+ document.getElementById('ops-tunnel-log').textContent = (t.logTail || []).join('\n') || 'No tunnel output yet.';
+ if((ops.audit || []).length){
+ document.getElementById('ops-audit').textContent = ops.audit.slice(0,8).map(e => `${e.seq} ${e.action} · ${e.actor} · ${e.outcome}`).join('\n');
+ }
+ renderBus(ops.openTasks || [], null);
+ // Queue pause switch + sweeper status.
+ const queue = ops.queue || {};
+ QUEUE_PAUSED = !!queue.paused;
+ const qBtn = document.getElementById('queue-toggle');
+ if(qBtn) qBtn.textContent = QUEUE_PAUSED ? 'Resume queue' : 'Pause queue';
+ const qState = document.getElementById('queue-state');
+ if(qState) qState.textContent = QUEUE_PAUSED
+ ? `Queue paused${queue.reason ? ' - ' + queue.reason : ''} · ${queue.depth == null ? '?' : queue.depth} held`
+ : `Queue live · ${queue.depth == null ? 0 : queue.depth} queued`;
+ const sweeper = ops.sweeper || {};
+ const sState = document.getElementById('sweeper-state');
+ if(sState) sState.textContent = sweeper.intervalSeconds
+ ? `Sweeper every ${Math.round(sweeper.intervalSeconds)}s (silent > ${Math.round(sweeper.offlineSeconds || 0)}s) · reaped ${sweeper.tasksReaped || 0}`
+ : 'Sweeper disabled';
+ const latency = ops.jobLatency || {};
+ const row = document.getElementById('ops-latency');
+ if(row){
+ const top = Object.entries(latency).slice(0, 4)
+ .map(([tool, d]) => `${tool} p50 ${d.p50}ms / p95 ${d.p95}ms (n=${d.count})`);
+ row.textContent = top.length ? 'Latency: ' + top.join(' · ') : '';
+ }
+ } catch(_){}
+}
+async function tunnelAction(action){
+ try {
+ const r = await fetch('/api/tunnel', {method:'POST', headers:authHeaders(), body:JSON.stringify({action})});
+ const data = await r.json();
+ if(!r.ok) throw new Error(data.error || ('HTTP ' + r.status));
+ toast('Tunnel ' + action + ' -> ' + (data.state || 'ok'));
+ refreshOps();
+ } catch(err){ toast('Tunnel ' + action + ' failed: ' + err.message); }
+}
+async function busRegister(){
+ const name = document.getElementById('bus-name').value.trim();
+ const role = document.getElementById('bus-role').value.trim() || 'agent';
+ if(!name) return toast('Enter an agent name.');
+ try {
+ const reg = await opsJson('/api/bus', {method:'POST', body:JSON.stringify({action:'register', name, role})});
```

```
+ localStorage.setItem('arena_agent_id', reg.id);
+ localStorage.setItem('arena_agent_name', reg.name);
+ document.getElementById('bus-out').textContent = `Registered ${reg.name} as ${reg.id} (${reg.role})`;
+ refreshBus();
+ } catch(err){ toast(err.message); }
+}
+function currentAgent(){ return localStorage.getItem('arena_agent_id') || 'web-operator'; }
+async function busPost(){
+ const to = document.getElementById('bus-to').value.trim() || null;
+ const subject = document.getElementById('bus-subject').value.trim();
+ const body = document.getElementById('bus-body').value.trim();
+ if(!subject && !body) return toast('Write a subject or body first.');
+ try {
+ const msg = await opsJson('/api/bus', {method:'POST', body:JSON.stringify({
+ action:'post', agentId: currentAgent(), to, subject, body: body || subject, kind:'note', priority:'normal'
+ })});
+ document.getElementById('bus-out').textContent = 'Posted ' + msg.id;
+ document.getElementById('bus-body').value = '';
+ refreshBus();
+ } catch(err){ toast(err.message); }
+}
+async function busExport(){
+ try {
+ const r = await opsJson('/api/bus', {method:'POST', body:JSON.stringify({action:'export', agentId:currentAgent()})});
+ const note = document.getElementById('bus-out');
+ note.textContent = r.markdown;
+ copyText(r.markdown);
+ toast('Handoff brief copied to clipboard.');
+ } catch(err){ toast(err.message); }
+}
+function renderBus(tasks, agents){
+ const taskBox = document.getElementById('bus-tasks');
+ if(!tasks.length){
+ taskBox.innerHTML = '<div class="sub">No open tasks. Create one from any agent with <code>agent_bus {action:"task_create"}</code>.</div>';
+ } else {
+ taskBox.innerHTML = tasks.map(t => {
+ const lease = t.leaseRemainingSeconds != null ? Math.max(0, Math.round(t.leaseRemainingSeconds)) + 's lease' : 'unclaimed';
+ return `<div class="cmd-row" style="align-items:flex-start">
+ <div style="flex:1">
+ <div><strong>${esc(t.title)}</strong> <span class="sub">· ${esc(t.priority)} · ${esc(t.status)} · ${lease}</span></div>
+ <div class="sub">${esc(t.assignee || 'unassigned')} ${t.blockedBy && t.blockedBy.length ? '· blocked by ' + esc(t.blockedBy.join(', ')) : ''}</div>
+ </div>
+ <button class="sm" onclick="claimTask('${esc(t.id)}')">Claim</button>
+ <button class="sm" onclick="completeTask('${esc(t.id)}')">Done</button>
+ </div>`;
+ }).join('');
+ }
+ if(agents){
+ const box = document.getElementById('bus-agents');
+ box.innerHTML = agents.length ? agents.map(a =>
+ `<div style="display:flex;justify-content:space-between;gap:8px;padding:3px 0">
+ <span><strong>${esc(a.name)}</strong> <span class="sub">${esc(a.role)}</span></span>
+ <span class="sub">${esc(a.status)} · ${a.openTasks} tasks · ${a.inboxUnread} unread</span>
+ </div>`).join('') : 'No agents registered yet.';
+ }
+}
+async function refreshBus(){
+ try {
+ const agents = await opsJson('/api/bus?action=agents');
+ const tasks = await opsJson('/api/bus?action=tasks&includeDone=0');
```

```
+ renderBus(tasks.tasks || [], agents.agents || []);
+ document.getElementById('ops-agents').textContent = agents.onlineCount || 0;
+ document.getElementById('ops-tasks').textContent = (tasks.tasks || []).length;
+ } catch(_){}
+}
+async function createTask(){
+ const title = document.getElementById('task-title').value.trim();
+ if(!title) return toast('Enter a task title first.');
+ try {
+ await opsJson('/api/bus', {method:'POST', body:JSON.stringify({
+ action:'task_create', title, priority:document.getElementById('task-priority').value,
+ agentId: currentAgent()
+ })});
+ document.getElementById('task-title').value = '';
+ toast('Task added to the board.');
+ refreshBus();
+ } catch(err){ toast(err.message); }
+}
+async function toggleQueue(){
+ const wantPause = !QUEUE_PAUSED;
+ try {
+ const res = await opsJson(wantPause ? '/api/queue/pause' : '/api/queue/resume', {
+ method:'POST',
+ body: JSON.stringify(wantPause ? {reason: 'paused from the Ops Console'} : {})
+ });
+ QUEUE_PAUSED = !!res.paused;
+ toast(wantPause ? `Queue paused (${res.queued} job(s) held).` : 'Queue resumed - Studio will pick work up.');
+ refreshOps();
+ } catch(err){ toast(err.message); }
+}
+async function sweepAgents(){
+ try {
+ const res = await opsJson('/api/bus', {method:'POST', body:JSON.stringify({
+ action:'sweep', offlineSeconds:900, agentId: currentAgent()
+ })});
+ toast(res.tasksReaped
+ ? `Released ${res.tasksReaped} task(s) from ${(res.agents || []).join(', ') || 'offline agents'}.`
+ : 'No stale agents - nothing to release.');
+ refreshBus();
+ } catch(err){ toast(err.message); }
+}
+async function claimTask(id){
+ try {
+ await opsJson('/api/bus', {method:'POST', body:JSON.stringify({action:'task_claim', taskId:id, agentId:currentAgent()})});
+ toast('Task claimed.');
+ refreshBus();
+ } catch(err){ toast(err.message); }
+}
+async function completeTask(id){
+ try {
+ await opsJson('/api/bus', {method:'POST', body:JSON.stringify({action:'task_complete', taskId:id, agentId:currentAgent(), result:'Completed from the Ops Console'})});
+ toast('Task completed.');
+ refreshBus();
+ } catch(err){ toast(err.message); }
+}
+async function refreshMetrics(){
+ try {
+ const m = await opsJson('/api/metrics');
+ const counters = (m.counters || []).map(c => `${c.name} = ${c.value}${Object.keys(c.labels||{}).length ? ' ' + JSON.stringify(c.labels) : ''}`);
+ const hists = (m.histograms || []).map(h => `${h.name} p50=${h.p50} p95=${h.p95} n=${h.count}`);
```

```
+ document.getElementById('ops-metrics').textContent = 'uptime ' + m.uptimeSeconds + 's\n' + counters.concat(hists).join('\n');
+ } catch(err){ document.getElementById('ops-metrics').textContent = err.message; }
+}
+async function verifyAudit(){
+ try {
+ const v = await opsJson('/api/audit?verify=1');
+ document.getElementById('ops-audit-note').textContent = v.ok
+ ? `Chain intact: ${v.checked} entries, head ${String(v.head).slice(0,12)}...`
+ : `CHAIN BROKEN at #${v.brokenAt}: ${v.reason}`;
+ const a = await opsJson('/api/audit?limit=8');
+ document.getElementById('ops-audit').textContent = (a.entries || []).map(e => `${e.seq} ${e.action} · ${e.actor} · ${e.outcome}`).join('\n');
+ } catch(err){ document.getElementById('ops-audit-note').textContent = err.message; }
+}
+function evFeedLine(text){
+ const feed = document.getElementById('ev-feed');
+ feed.textContent += text + '\n';
+ feed.scrollTop = feed.scrollHeight;
+}
+function connectEvents(){
+ const btn = document.getElementById('ev-btn');
+ clearTimeout(EV_RETRY);
+ if(EV_SOURCE){ try { EV_SOURCE.close(); } catch(_){} EV_SOURCE = null; }
+ if(!EV_WANT){ btn.textContent = 'Connect'; return; }
+ const token = getToken();
+ const src = new EventSource('/api/events' + (token ? '?token=' + encodeURIComponent(token) : ''));
+ EV_SOURCE = src;
+ btn.textContent = 'Disconnect';
+ src.onopen = () => {
+ EV_DELAY = 1000;
+ btn.textContent = 'Disconnect';
+ evFeedLine('[stream live]');
+ };
+ src.onmessage = ev => {
+ try {
+ const e = JSON.parse(ev.data);
+ evFeedLine(`${new Date((e.ts||0)*1000).toLocaleTimeString()} ${e.kind} ${JSON.stringify(e.data)}`);
+ } catch(_){}
+ };
+ src.onerror = () => {
+ try { src.close(); } catch(_){}
+ if(EV_SOURCE === src) EV_SOURCE = null;
+ if(!EV_WANT){ btn.textContent = 'Connect'; return; }
+ const wait = Math.max(1, Math.min(EV_DELAY, 30000));
+ btn.textContent = `Reconnecting (${Math.round(wait/1000)}s)`;
+ evFeedLine(`[stream error - retrying in ${Math.round(wait/1000)}s]`);
+ EV_DELAY = Math.min(EV_DELAY * 2, 30000);
+ EV_RETRY = setTimeout(connectEvents, wait);
+ };
+}
+function toggleEventStream(){
+ const btn = document.getElementById('ev-btn');
+ if(EV_WANT){
+ EV_WANT = false;
+ clearTimeout(EV_RETRY);
+ if(EV_SOURCE){ try { EV_SOURCE.close(); } catch(_){} EV_SOURCE = null; }
+ btn.textContent = 'Connect';
+ evFeedLine('[disconnected]');
+ return;
+ }
+ EV_WANT = true;
```

```
+ EV_DELAY = 1000;
+ connectEvents();
+}
+async function copyMcpConfig(){
+ try {
+ const ops = await opsJson('/api/ops');
+ const url = (ops.tunnel || {}).publicUrl;
+ if(!url) throw new Error('Tunnel is not online yet - start it, then copy the config.');
+ const token = getToken() || '<bridge-token>';
+ const cfg = { mcpServers: { 'roblox-studio': {
+ url: String(url).replace(/\/$/, '') + '/mcp',
+ headers: { Authorization: 'Bearer ' + token }
+ } } };
+ await copyText(JSON.stringify(cfg, null, 2));
+ } catch(err){ toast(err.message || 'Cannot build MCP config'); }
+}
+
+initBoot().then(() => { tick(); refreshOps(); refreshBus(); refreshFleet();
+ setInterval(tick, 1500);
+ setInterval(refreshFleet, 3000);
+ setInterval(() => {
+ const active = document.getElementById('tab-ops').classList.contains('active');
+ if(active){ refreshOps(); refreshBus(); }
+ }, 4000);
+});
</script></body></html>"""
+ return html.replace("__BRIDGE_VERSION__", VERSION)


# ------------------------------------------------------------------------------
@@ -2189,16 +4028,39 @@ def create_http_server(
token: str = None,
read_only: bool = False,
guard_place_id: int = None,
+ state_dir: str = None,
+ auto_tunnel: bool = False,
+ tunnel_flavor: str = "auto",
+ tunnel_token: str = None,
+ tunnel_name: str = None,
+ public_url: str = None,
+ tunnel_binary: str = None,
+ sweep_interval: float = 300.0,
+ sweep_offline_seconds: float = 900.0,
):
resolved_token = load_token_default(token)
state = BridgeState(
token=resolved_token,
read_only=read_only,
guard_place_id=guard_place_id,
+ state_dir=state_dir,
+ auto_tunnel=False, # started after the socket is bound, so the port is known
+ tunnel_flavor=tunnel_flavor,
+ tunnel_token=tunnel_token,
+ tunnel_name=tunnel_name,
+ public_url=public_url,
+ tunnel_binary=tunnel_binary,
+ sweep_interval=sweep_interval,
+ sweep_offline_seconds=sweep_offline_seconds,
)
httpd = ThreadingHTTPServer((host, port), make_http_handler(state))
```

```
httpd.daemon_threads = True
httpd.bridge_state = state
+ bound_port = httpd.server_address[1]
+ state.tunnel.port = int(bound_port)
+ state.tunnel.local_url = f"http://127.0.0.1:{bound_port}"
+ if auto_tunnel:
+ state.tunnel_action({"action": "start"})
return httpd, state


@@ -2219,6 +4081,24 @@ def main():
default=int(os.environ["BRIDGE_PLACE_ID"]) if os.environ.get("BRIDGE_PLACE_ID") else None,
help="Optional PlaceId write guard",
)
+ ap.add_argument("--tunnel", action="store_true",
+ help="Supervise a public cloudflared/ngrok tunnel for this bridge (auto-restart, health probes)")
+ ap.add_argument("--tunnel-flavor", default=os.environ.get("BRIDGE_TUNNEL_FLAVOR", "auto"),
+ choices=["auto", "cloudflared", "ngrok"], help="Tunnel provider")
+ ap.add_argument("--tunnel-token", default=os.environ.get("TUNNEL_TOKEN"),
+ help="Cloudflare named-tunnel token (https://one.dash.cloudflare.com)")
+ ap.add_argument("--tunnel-name", default=os.environ.get("BRIDGE_TUNNEL_NAME"),
+ help="Optional hostname label for a named tunnel")
+ ap.add_argument("--public-url", default=os.environ.get("BRIDGE_PUBLIC_URL"),
+ help="Report a tunnel URL you run yourself (disables supervision)")
+ ap.add_argument("--sweep-interval", type=float,
+ default=float(os.environ.get("BRIDGE_SWEEP_INTERVAL", "300")),
+ help="Seconds between automatic stale-agent sweeps (0 disables)")
+ ap.add_argument("--sweep-offline", type=float,
+ default=float(os.environ.get("BRIDGE_SWEEP_OFFLINE", "900")),
+ help="An agent must be silent this long before its tasks are released")
+ ap.add_argument("--state-dir", default=os.environ.get("BRIDGE_STATE_DIR"),
+ help="Directory for bus/token/audit/tunnel state (default: roblox-bridge/bridge_state)")
args = ap.parse_args()

srv, state = create_http_server(
@@ -2227,17 +4107,35 @@ def main():
token=args.token,
read_only=args.read_only,
guard_place_id=args.place_id,
+ state_dir=args.state_dir,
+ auto_tunnel=args.tunnel,
+ tunnel_flavor=args.tunnel_flavor,
+ tunnel_token=args.tunnel_token,
+ tunnel_name=args.tunnel_name,
+ public_url=args.public_url,
+ sweep_interval=args.sweep_interval,
+ sweep_offline_seconds=args.sweep_offline,
)
ro_str = " [READ-ONLY INSPECTOR]" if state.read_only else ""
+ bound_port = srv.server_address[1]
print(
- f"[bridge] v{VERSION}{ro_str} listening on {args.host}:{args.port} "
- f"(token {'set' if state.token else 'disabled'}, Control Center http://127.0.0.1:{args.port}/, MCP http://127.0.0.1:{args.port}/mcp)",
+ f"[bridge] v{VERSION}{ro_str} listening on {args.host}:{bound_port} "
+ f"(token {'set' if state.token else 'disabled'}, Control Center http://127.0.0.1:{bound_port}/, "
+ f"MCP http://127.0.0.1:{bound_port}/mcp, ops http://127.0.0.1:{bound_port}/#ops)",
flush=True,
)
+ if args.tunnel:
+ print("[bridge] tunnel supervisor starting (cloudflared/ngrok)...", flush=True)
```

```
try:
srv.serve_forever()
except KeyboardInterrupt:
- srv.shutdown()
+ pass
+ finally:
+ try:
+ state._reaper_stop.set()
+ state.tunnel.stop()
+ finally:
+ srv.shutdown()


if __name__ == "__main__":

```

roblox-bridge/mcp_core.py (diff)

944 lines

agent_bus + bridge_ops tools, 3 resources, client helpers

```
diff --git a/roblox-bridge/mcp_core.py b/roblox-bridge/mcp_core.py
index f5fbba3..7880ae8 100644
--- a/roblox-bridge/mcp_core.py
+++ b/roblox-bridge/mcp_core.py
@@ -1,12 +1,14 @@
#!/usr/bin/env python3
"""
mcp_core.py - Zero-dependency Model Context Protocol (MCP) engine & Roblox Studio
-tool suite for Arena <-> Roblox Studio (v4.0.0).
+tool suite for Arena <-> Roblox Studio (v5.3.2).

Supports:
- - MCP specification versions 2025-06-18, 2025-03-26, and 2024-11-05
+ - Dual-era MCP: 2026-07-28 (stateless, server/discover, resultType) and the
+ legacy 2025-11-25 / 2025-06-18 / 2025-03-26 / 2024-11-05 handshake eras
+ - Task-augmented tool calls (tasks/get · tasks/result · tasks/list · tasks/cancel)
- Transports: stdio (via mcp_server.py) and Streamable HTTP /mcp (via server.py)
- - 68 curated, annotated Roblox Studio & Luau engineering tools
+ - 71 curated, annotated Roblox Studio & Luau engineering tools
- Live MCP Resources + Resource Templates + Workflow Prompts
- Exact 53-bit-safe 32-bit FNV-1a hashing matching ArenaBridge.lua bit-for-bit
- Local pre-flight Luau syntax + undefined-global static analysis (luau_check)
@@ -20,6 +22,8 @@ import math
import os
import random
import re
+import threading
+import uuid
import subprocess
import tempfile
import time
@@ -28,13 +32,21 @@ import urllib.request
from pathlib import Path

MCP_SERVER_NAME = "arena-roblox-studio-mcp"
-MCP_SERVER_VERSION = "4.0.0"
+MCP_SERVER_VERSION = "5.3.2"
SUPPORTED_PROTOCOL_VERSIONS = (
+ "2026-07-28", # stateless era: server/discover, per-request _meta, resultType
+ "2025-11-25", # final legacy era: tasks, elicitation, structured output
"2025-06-18",
"2025-03-26",
"2024-11-05",
)
DEFAULT_PROTOCOL_VERSION = "2025-06-18"
+MODERN_PROTOCOL_VERSION = "2026-07-28"
+LEGACY_PROTOCOL_VERSIONS = tuple(v for v in SUPPORTED_PROTOCOL_VERSIONS if v != MODERN_PROTOCOL_VERSION)
+# Beyond this many tracked tasks the oldest finished ones are pruned.
+TASK_HISTORY_LIMIT = 200
+TASK_DEFAULT_TTL_MS = 3_600_000
+TASK_POLL_INTERVAL_MS = 1000

KNOWN_ROBLOX_GLOBALS = {
"game", "workspace", "script", "plugin", "version", "loadstring",
@@ -459,6 +471,96 @@ class BridgeClient:
return self.direct_dispatch("peers", {})
return self._http_request("GET", "/api/peers", timeout=10.0)

+ # -- v5 coordination & ops helpers ----------------------------------------
+
```

```
+ def bus_action(self, payload: dict = None) -> dict:
+ payload = dict(payload or {})
+ if self.direct_dispatch:
+ return self.direct_dispatch("bus", payload)
+ return self._http_request("POST", "/api/bus", payload, timeout=30.0)
+
+ def fleet_action(self, payload: dict = None) -> dict:
+ payload = dict(payload or {})
+ if self.direct_dispatch:
+ return self.direct_dispatch("fleet", payload)
+ action = (payload.get("action") or "list").lower()
+ if action in ("list", "status"):
+ return self._http_request("GET", "/api/studios", timeout=15.0)
+ return self._http_request("POST", "/api/studios", payload, timeout=30.0)
+
+ def broadcast(self, kind: str = "ping", payload: dict = None, timeout: float = 20.0,
+ dm: str = None) -> dict:
+ body = {"action": "broadcast", "type": kind, "payload": payload or {},
+ "timeout": timeout, "dm": dm}
+ if self.direct_dispatch:
+ return self.direct_dispatch("broadcast", body)
+ return self._http_request("POST", "/api/studios", body, timeout=timeout + 15.0)
+
+ def ops_action(self, payload: dict = None) -> dict:
+ p = dict(payload or {})
+ action = (p.get("action") or "status").lower()
+ if self.direct_dispatch:
+ mapping = {
+ "status": ("ops", {}),
+ "metrics": ("metrics", {}),
+ "audit": ("audit", {"limit": p.get("limit", 50)}),
+ "audit_verify": ("audit", {"verify": True}),
+ "events": ("events", {"cursor": p.get("cursor", 0), "limit": p.get("limit", 50)}),
+ "tunnel": ("tunnel", {"action": "status"}),
+ "tunnel_start": ("tunnel", {"action": "start"}),
+ "tunnel_stop": ("tunnel", {"action": "stop"}),
+ "tunnel_restart": ("tunnel", {"action": "restart"}),
+ "queue_clear": ("queue_clear", {}),
+ "queue_pause": ("queue_pause", {"reason": p.get("reason")}),
+ "queue_resume": ("queue_resume", {}),
+ "sweep": ("sweep", {}),
+ "reap": ("reap", {}),
+ }
+ if action not in mapping:
+ raise ValueError(f"Unknown bridge_ops action: {action}")
+ op, body = mapping[action]
+ return self.direct_dispatch(op, body)
+
+ if action == "status":
+ return self._http_request("GET", "/api/ops", timeout=20.0)
+ if action == "metrics":
+ fmt = p.get("format") or "json"
+ if fmt == "prometheus":
+ return {"format": "prometheus", "text": self._http_request_text("/api/metrics?format=prometheus")}
+ return self._http_request("GET", "/api/metrics", timeout=20.0)
+ if action == "audit":
+ return self._http_request("GET", f"/api/audit?limit={int(p.get('limit') or 50)}", timeout=20.0)
+ if action == "audit_verify":
+ return self._http_request("GET", "/api/audit?verify=1", timeout=20.0)
+ if action == "events":
```

```
+ return self._http_request(
+ "GET", f"/api/events?once=1&since={int(p.get('cursor') or 0)}&limit={int(p.get('limit') or 50)}", timeout=20.0
+ )
+ if action in ("tunnel", "tunnel_start", "tunnel_stop", "tunnel_restart"):
+ sub = {"tunnel": "status", "tunnel_start": "start", "tunnel_stop": "stop", "tunnel_restart": "restart"}[action]
+ if sub == "status":
+ return self._http_request("GET", "/api/tunnel", timeout=15.0)
+ return self._http_request("POST", "/api/tunnel", {"action": sub}, timeout=90.0)
+ if action == "queue_pause":
+ return self._http_request("POST", "/api/queue/pause", {"reason": p.get("reason")}, timeout=20.0)
+ if action == "queue_resume":
+ return self._http_request("POST", "/api/queue/resume", {}, timeout=20.0)
+ if action in ("queue_clear", "reap", "sweep"):
+ return self._http_request("POST", "/api/ops", {"action": action}, timeout=30.0)
+ raise ValueError(f"Unknown bridge_ops action: {action}")
+
+ def _http_request_text(self, path: str, timeout: float = 20.0) -> str:
+ url = f"{self.base_url}{path}"
+ headers = {"X-Arena-Token": self.token} if self.token else {}
+ req = urllib.request.Request(url, method="GET", headers=headers)
+ try:
+ with urllib.request.urlopen(req, timeout=timeout) as resp:
+ return resp.read().decode("utf-8", "replace")
+ except urllib.error.HTTPError as exc:
+ return exc.read().decode("utf-8", "replace")[:2000]
+ except urllib.error.URLError as exc:
+ raise BridgeTransportError(f"Cannot reach bridge at {self.base_url} ({exc.reason})") from exc
+
def get_job(self, job_id: str) -> dict:
if self.direct_dispatch:
return self.direct_dispatch("get_job", {"id": job_id})
@@ -1678,6 +1780,128 @@ TOOL_SPECS = [
},
"annotations": _ann("Roblox Open Cloud Publish / DataStore / Messaging", read_only=False, destructive=False, idempotent=False),
},
+
+ # --- Group Z: v5 multi-agent collaboration & bridge operations ----------
+ {
+ "name": "agent_bus",
+ "description": (
+ "Shared multi-agent coordination bus for this bridge (does not touch the Roblox place). "
+ "Register presence, exchange messages, run a claim-based task board with leases, read the activity feed, "
+ "and export a markdown handoff brief. Use it when two or more AI agents (or a human and an agent) share "
+ "one Studio session: `action='register'` first, then `task_claim` before working, `task_complete` with a "
+ "result, and `post` to report progress. Read actions: stats, agents, inbox, tasks, thread, feed. "
+ "Writes: register, heartbeat, post, mark_read, task_create, task_claim, task_renew, task_release, "
+ "task_update, task_complete, task_delete, status."
+ ),
+ "inputSchema": {
+ "type": "object",
+ "properties": {
+ "action": {
+ "type": "string",
+ "enum": [
+ "register", "heartbeat", "status", "agents", "post", "inbox", "thread", "mark_read",
+ "tasks", "task_create", "task_claim", "task_renew", "task_release", "task_update",
+ "task_complete", "task_delete", "feed", "export", "stats",
+ ],
+ "description": "Bus operation to perform.",
+ },
```

```
+ "agentId": {"type": "string", "description": "Your agent id (returned by register) or your registered name."},
+ "createdBy": {"type": "string", "description": "Alias for agentId on `task_create`."},
+ "actor": {"type": "string", "description": "Alias for agentId on `task_update`."},
+ "name": {"type": "string", "description": "Agent display name for `register`."},
+ "role": {"type": "string", "description": "Free-form role label, e.g. 'builder', 'qa', 'reviewer', 'human'."},
+ "capabilities": {"type": "array", "items": {"type": "string"}, "description": "Capability tags for `register`."},
+ "status": {"type": "string", "enum": ["online", "busy", "idle", "offline"], "description": "Presence status for `heartbeat`/`status`."},
+ "to": {"type": "string", "description": "Recipient agent id/name, or omit for a broadcast."},
+ "subject": {"type": "string", "description": "Short message subject."},
+ "body": {"type": "string", "description": "Message body for `post`."},
+ "kind": {"type": "string", "enum": ["note", "question", "answer", "handoff", "alert", "result"], "default": "note"},
+ "priority": {"type": "string", "enum": ["low", "normal", "high", "critical"], "default": "normal"},
+ "threadId": {"type": "string", "description": "Optional thread id to group a conversation."},
+ "since": {"type": "integer", "description": "Cursor for `inbox`/`feed` (use the `cursor` returned last time)."},
+ "limit": {"type": "integer", "description": "Max rows to return (default 50)."},
+ "unreadOnly": {"type": "boolean", "description": "Only unread messages for `inbox`."},
+ "messageIds": {"type": "array", "items": {"type": "string"}, "description": "Messages to mark read."},
+ "all": {"type": "boolean", "description": "Mark every message read."},
+ "taskId": {"type": "string", "description": "Task id for claim/renew/release/update/complete/delete."},
+ "title": {"type": "string", "description": "Task title for `task_create`."},
+ "detail": {"type": "string", "description": "Task detail / acceptance criteria."},
+ "assignee": {"type": "string", "description": "Optional pre-assigned agent id for `task_create`/`task_update`."},
+ "tags": {"type": "array", "items": {"type": "string"}, "description": "Task tags."},
+ "dependsOn": {"type": "array", "items": {"type": "string"}, "description": "Task ids that must complete before this task can be claimed."},
+ "leaseSeconds": {"type": "integer", "description": "Lease duration for `task_claim`/`task_renew` (default 900)."},
+ "result": {"type": "string", "description": "Outcome summary for `task_complete`."},
+ "artifacts": {"type": "array", "items": {"type": "string"}, "description": "Files/URLs produced by the task."},
+ "path": {"type": "string", "description": "Optional file path for `export` (markdown handoff brief)."},
+ "includeDone": {"type": "boolean", "description": "Include finished tasks in `tasks` / `export`."},
+ },
+ },
+ "annotations": _ann("Multi-Agent Coordination Bus", read_only=True, destructive=False, idempotent=False),
+ },
+ {
+ "name": "bridge_ops",
+ "description": (
+ "Operate and observe the bridge itself: consolidated ops report (peers, queue, tunnel, bus, audit), "
+ "Prometheus-style metrics, tamper-evident audit log verification, live event feed, and supervised "
+ "public-tunnel control (start/stop/restart). Read actions: status, metrics, audit, audit_verify, events, "
+ "tunnel. Control: tunnel_start, tunnel_stop, tunnel_restart, queue_pause, queue_resume, "
+ "queue_clear, sweep, reap. queue_pause stops handing jobs to Studio without dropping them."
+ ),
+ "inputSchema": {
+ "type": "object",
+ "properties": {
+ "action": {
+ "type": "string",
+ "enum": ["status", "metrics", "audit", "audit_verify", "events", "tunnel", "tunnel_start",
+ "tunnel_stop", "tunnel_restart", "queue_pause", "queue_resume",
+ "queue_clear", "sweep", "reap"],
+ "default": "status",
+ },
+ "limit": {"type": "integer", "description": "Rows for audit/events (default 50)."},
+ "cursor": {"type": "integer", "description": "Event cursor for incremental reads."},
+ "format": {"type": "string", "enum": ["json", "prometheus"], "default": "json"},
+ "reason": {"type": "string", "description": "Why the queue was paused; recorded in the audit log."},
+ },
+ },
+ "annotations": _ann("Bridge Ops, Metrics & Tunnel Control", read_only=False, destructive=False, idempotent=False),
+ },
```

```
+ {
+ "name": "studio_fleet",
+ "description": (
+ "Work with several Roblox Studio windows at once. `list` returns every connected DataModel with "
+ "peerId, place, dm, online age, label and which one untargeted jobs would reach. `set_active` pins "
+ "one Studio as the default target (the pin is skipped automatically when that Studio closes, so the "
+ "queue never stalls); `clear_active` returns to the automatic edit-first routing; `label` names a "
+ "Studio for humans. `broadcast` runs one read-only job on every online Studio and returns per-peer "
+ "results - use it to survey or health-check the whole fleet in one call. Any other tool accepts "
+ "`peerId` to target a single Studio."
+ ),
+ "inputSchema": {
+ "type": "object",
+ "properties": {
+ "action": {
+ "type": "string",
+ "enum": ["list", "set_active", "clear_active", "label", "broadcast"],
+ "default": "list",
+ },
+ "peerId": {"type": "string", "description": "Target Studio peerId (from `list`)."},
+ "placeId": {"type": "integer", "description": "Alternative to peerId when pinning by place."},
+ "label": {"type": "string", "description": "Human label for a Studio (empty clears it)."},
+ "broadcastTool": {
+ "type": "string",
+ "enum": ["ping_studio", "get_studio_state", "survey_place", "inspect_instance",
+ "script_read", "get_console_output"],
+ "default": "ping_studio",
+ "description": "Read-only tool to fan out with `broadcast`.",
+ },
+ "path": {"type": "string", "description": "Path argument when broadcasting a path-based tool."},
+ "includeSource": {"type": "boolean", "description": "survey_place: include script sources."},
+ "timeout": {"type": "number", "description": "Per-broadcast budget in seconds (default 20)."},
+ "dm": {"type": "string", "enum": ["auto", "edit", "server", "client"], "default": "auto"},
+ },
+ },
+ "annotations": _ann("Multi-Studio Fleet Control", read_only=False, destructive=False, idempotent=True),
+ },
]

TOOL_MAP = {t["name"]: t for t in TOOL_SPECS}
@@ -1717,6 +1941,14 @@ def is_tool_call_read_only(name: str, args: dict) -> bool:
return True
if name == "open_cloud_action" and args.get("action") in ("datastore_list", "datastore_get"):
return True
+ if name == "agent_bus" and args.get("action", "stats") in (
+ "stats", "agents", "inbox", "tasks", "thread", "feed", "status",
+ ):
+ return True
+ if name == "bridge_ops" and args.get("action", "status") in (
+ "status", "metrics", "audit", "audit_verify", "events", "tunnel",
+ ):
+ return True
return False


@@ -1894,6 +2126,12 @@ def execute_tool(client: BridgeClient, name: str, args: dict) -> dict:
dm = args.get("dm", "auto")
peer_id = args.get("peerId")

+ # Bridge-level tools never depend on a Studio peer.
```

```
+ if name == "agent_bus":
+ return client.bus_action(args)
+ if name == "bridge_ops":
+ return client.ops_action(args)
+
if name == "self_test":
return run_bridge_self_test(client, include_studio_smoke=args.get("includeStudioSmoke", True), timeout=args.get("timeout", 180))

@@ -1916,6 +2154,27 @@ def execute_tool(client: BridgeClient, name: str, args: dict) -> dict:
if name == "list_studios":
return client.peers()

+ if name == "studio_fleet":
+ action = (args.get("action") or "list").lower()
+ if action != "broadcast":
+ return client.fleet_action(args)
+ mapping = {
+ "ping_studio": ("ping", {}),
+ "get_studio_state": ("studio_state", {}),
+ "survey_place": ("survey", {"includeSource": bool(args.get("includeSource", False))}),
+ "inspect_instance": ("inspect", {"path": args.get("path") or "game", "depth": 2}),
+ "script_read": ("read_script", {"path": args.get("path") or ""}),
+ "get_console_output": ("get_console", {}),
+ }
+ kind, payload = mapping.get(args.get("broadcastTool") or "ping_studio", ("ping", {}))
+ if kind == "read_script" and not payload.get("path"):
+ raise ValueError("script_read broadcast needs a `path`")
+ result = client.broadcast(kind=kind, payload=payload,
+ timeout=float(args.get("timeout") or 20.0),
+ dm=args.get("dm"))
+ result["tool"] = args.get("broadcastTool") or "ping_studio"
+ return result
+
if name == "get_studio_state":
bridge_health = client.health()
if not bridge_health.get("studio_connected"):
@@ -2723,6 +2982,42 @@ RESOURCES = [
"description": "Service breakdown, instance census, script inventory + hashes, remotes, tags, and settings.",
"mimeType": "application/json",
},
+ {
+ "uri": "studio://bus",
+ "name": "Multi-Agent Bus (Presence, Tasks, Messages)",
+ "description": "Registered agents, open task board with leases, and the current activity cursor - shared by every agent on this bridge.",
+ "mimeType": "application/json",
+ },
+ {
+ "uri": "studio://ops",
+ "name": "Bridge Operations Report",
+ "description": "Queue depth, peer health, tunnel state, metrics, recent audit entries, and open tasks in one document.",
+ "mimeType": "application/json",
+ },
+ {
+ "uri": "studio://audit",
+ "name": "Tamper-Evident Audit Log (head)",
+ "description": "Latest hash-chained audit entries plus chain verification status.",
+ "mimeType": "application/json",
+ },
+ {
+ "uri": "studio://jobs",
```

```
+ "name": "Job Queue & Per-Tool Latency",
+ "description": "Queue depth, pause state, live peer list, recent job summaries and p50/p95 wall time per tool.",
+ "mimeType": "application/json",
+ },
+ {
+ "uri": "studio://studios",
+ "name": "Connected Studio Fleet",
+ "description": "Every connected Studio window with peerId, place, DataModel kind, online age, label, pinned/default routing and queued job counts.",
+ "mimeType": "application/json",
+ },
+ {
+ "uri": "studio://handoff",
+ "name": "Markdown Handoff Brief",
+ "description": "The bus export as markdown: roster, task board, recent messages and stats - paste-ready for the next agent or human.",
+ "mimeType": "text/markdown",
+ },
]

RESOURCE_TEMPLATES = [
@@ -2775,6 +3070,26 @@ PROMPTS = [
{"name": "studioRoot", "description": "Studio container path (e.g. ServerScriptService.NightLoop)", "required": True},
],
},
+ {
+ "name": "multi_agent_handoff",
+ "description": "Hand work to another agent: read the live board, release what you cannot finish, and post a handoff with the next concrete step.",
+ "arguments": [
+ {"name": "agentName", "description": "Who is handing off (defaults to the bus roster)", "required": False},
+ {"name": "focus", "description": "What the next agent should pick up first", "required": False},
+ ],
+ },
+ {
+ "name": "bus_standup",
+ "description": "Render a five-line standup from the live Agent Bus: what changed, who owns what, what is blocked.",
+ "arguments": [
+ {"name": "since", "description": "Bus cursor to report from (defaults to the current cursor)", "required": False},
+ ],
+ },
+ {
+ "name": "task_triage",
+ "description": "Rank open Agent Bus tasks by priority and dependencies, propose a claim order, and flag tasks without acceptance criteria.",
+ "arguments": [],
+ },
]


@@ -2794,6 +3109,36 @@ def read_mcp_resource(client: BridgeClient, uri: str) -> dict:
if uri == "studio://survey":
data = execute_tool(client, "survey_place", {"includeSource": False})
return {"contents": [{"uri": uri, "mimeType": "application/json", "text": json.dumps(data, indent=2)}]}
+ if uri == "studio://bus":
+ data = client.bus_action({"action": "stats"})
+ board = client.bus_action({"action": "tasks", "includeDone": False})
+ roster = client.bus_action({"action": "agents"})
+ payload = {"stats": data, "agents": roster, "openTasks": board}
+ return {"contents": [{"uri": uri, "mimeType": "application/json", "text": json.dumps(payload, indent=2)}]}
+ if uri == "studio://ops":
+ data = client.ops_action({"action": "status"})
+ return {"contents": [{"uri": uri, "mimeType": "application/json", "text": json.dumps(data, indent=2)}]}
+ if uri == "studio://studios":
```

```
+ data = client.fleet_action({"action": "list"})
+ return {"contents": [{"uri": uri, "mimeType": "application/json", "text": json.dumps(data, indent=2)}]}
+ if uri == "studio://jobs":
+ ops = client.ops_action({"action": "status"})
+ payload = {
+ "queue": ops.get("queue"),
+ "sweeper": ops.get("sweeper"),
+ "health": {k: ops.get("health", {}).get(k) for k in ("queued", "jobs", "peers", "studio_connected", "queuePaused")},
+ "jobLatency": ops.get("jobLatency"),
+ "recentJobs": ops.get("recentJobs"),
+ }
+ return {"contents": [{"uri": uri, "mimeType": "application/json", "text": json.dumps(payload, indent=2)}]}
+ if uri == "studio://handoff":
+ brief = client.bus_action({"action": "export", "summaryOnly": False})
+ return {"contents": [{"uri": uri, "mimeType": "text/markdown", "text": brief.get("markdown", "")}]}
+ if uri == "studio://audit":
+ data = client.ops_action({"action": "audit", "limit": 25})
+ verify = client.ops_action({"action": "audit_verify"})
+ payload = {"entries": data, "verification": verify}
+ return {"contents": [{"uri": uri, "mimeType": "application/json", "text": json.dumps(payload, indent=2)}]}
if uri.startswith("studio://scripts/"):
path = uri[len("studio://scripts/") :]
data = execute_tool(client, "script_read", {"path": path})
@@ -4491,7 +4836,56 @@ def spawn_prefab_helper(client: BridgeClient, args: dict, peer_id: str = None) -
}


-def get_mcp_prompt(name: str, arguments: dict = None) -> dict:
+BUS_FALLBACK = (
+ "Live bus state is unavailable (bridge offline, read-only client, or the bus is empty). "
+ "Work from the handoff brief you were given and state any assumption you had to make."
+)
+
+
+def _bus_lines(client, include_tasks: bool = True, tasks_include_done: bool = False) -> str:
+ """Compact bus snapshot for prompt rendering; never raises."""
+ if client is None:
+ return BUS_FALLBACK
+ try:
+ stats = client.bus_action({"action": "stats"})
+ roster = client.bus_action({"action": "agents", "includeOffline": True}).get("agents", [])
+ except Exception:
+ return BUS_FALLBACK
+ lines = [
+ f"Bus stats: {stats.get('agents')} agents ({stats.get('agentsOnline')} online), "
+ f"{stats.get('tasks')} tasks, cursor {stats.get('cursor')}."
+ ]
+ if roster:
+ lines.append("Roster:")
+ for a in roster:
+ state = "online" if a.get("online") else "offline"
+ lines.append(
+ f" - {a.get('name')} ({a.get('role')}, {state}, open tasks {a.get('openTasks')}, "
+ f"last seen {a.get('ageSeconds')}s ago)"
+ )
+ else:
+ lines.append("Roster: _no agents registered_.")
+ if include_tasks:
+ try:
+ tasks = client.bus_action({"action": "tasks", "includeDone": tasks_include_done}).get("tasks", [])
```

```
+ except Exception:
+ tasks = []
+ if tasks:
+ lines.append("Task board:")
+ for t in tasks[:20]:
+ owner = t.get("assignee") or "unclaimed"
+ deps = t.get("dependsOn") or []
+ dep_note = f", blocked by {', '.join(deps)}" if deps else ""
+ lines.append(
+ f" - {t.get('id')} [{t.get('status')}/{t.get('priority')}] {t.get('title')} "
+ f"(owner: {owner}{dep_note})"
+ )
+ else:
+ lines.append("Task board: _empty_.")
+ return "\n".join(lines)
+
+
+def get_mcp_prompt(name: str, arguments: dict = None, client=None) -> dict:
arguments = arguments or {}
if name == "survey_and_architecture":
text = (
@@ -4526,6 +4920,51 @@ def get_mcp_prompt(name: str, arguments: dict = None) -> dict:
f"3. Run `drift_and_sync(mode='push', localDir='{ld}', studioRoot='{sr}')` (automatically snapshots live scripts and replaces instances in one undoable step).\n"
f"4. Re-run `drift_and_sync(mode='check', ...)` to confirm `inSync: true`."
)
+ elif name == "multi_agent_handoff":
+ who = arguments.get("agentName") or "<your agent name>"
+ focus = arguments.get("focus") or "<what you are handing over>"
+ snapshot = _bus_lines(client)
+ text = (
+ f"You are {who} and you are handing work to another agent on the same Roblox Studio bridge.\n\n"
+ f"{snapshot}\n\n"
+ "Do this now:\n"
+ "1. Call `agent_bus {action:'export', summaryOnly:true}` and keep the brief short enough to paste into a message.\n"
+ f"2. Release (or complete, with artifacts) every task you own that you will not finish. State why. Focus: {focus}\n"
+ "3. Post exactly one handoff message: `agent_bus {action:'post', kind:'handoff', to:'<agent name>', "
+ "subject:'handoff: <task id>', body:'<state, next concrete step, files touched>'} .\n"
+ "4. Do not claim a new task until the handoff is posted; the next agent needs the lease and the note.\n"
+ "5. Reply with the message id and the task ids you released."
+ )
+ elif name == "bus_standup":
+ since = arguments.get("since")
+ snapshot = _bus_lines(client)
+ cursor_line = (
+ f"Report only activity after cursor {since}."
+ if since not in (None, "", 0)
+ else "Use the current cursor as the starting point."
+ )
+ text = (
+ "Produce a five-line standup for the humans watching this bridge.\n\n"
+ f"{snapshot}\n\n"
+ f"{cursor_line}\n"
+ "Do this:\n"
+ "1. Call `agent_bus {action:'export', since:<cursor>}` to get only recent activity.\n"
+ "2. Summarise as exactly five lines: done / in progress / blocked / who is idle / next claim.\n"
+ "3. Name task ids, not vibes. If nothing changed, say so in one line instead of padding.\n"
+ "4. Post the standup with `agent_bus {action:'post', kind:'status', subject:'standup'}`."
+ )
+ elif name == "task_triage":
+ snapshot = _bus_lines(client)
```

```
+ text = (
+ "Triage the open Agent Bus tasks so the team claims work in the right order.\n\n"
+ f"{snapshot}\n\n"
+ "Do this:\n"
+ "1. Read the board with `agent_bus {action:'tasks', includeDone:false}`.\n"
+ "2. Rank by: dependency depth (unblock others first), then priority (critical > high > normal > low), then age.\n"
+ "3. Flag every task with no acceptance criteria, no owner and no detail; propose the one-line criterion to add.\n"
+ "4. Output a numbered claim order with the task id, the owner you suggest, and the reason.\n"
+ "5. Do not claim anything yourself unless the user asks you to; this prompt only plans."
+ )
else:
raise KeyError(f"Unknown prompt: {name}")

@@ -4544,6 +4983,10 @@ class MCPDispatcher:

def __init__(self, client: BridgeClient):
self.client = client
+ # Task-augmented tool calls (MCP tasks / SEP-1686 + SEP-2663) map onto a
+ # background execution of the normal tool path, so any tool can be a task.
+ self.tasks = {}
+ self._task_lock = threading.Lock()

def visible_tools(self) -> list:
if not self.client.read_only:
@@ -4589,6 +5032,278 @@ class MCPDispatcher:
return {"jsonrpc": "2.0", "id": msg_id, "error": err}

def _handle_one(self, msg: dict):
+ """Era-aware wrapper: validates the per-request protocol version, serves
+ `server/discover`, then decorates the legacy dispatch result for modern
+ (2026-07-28) clients with `resultType` and cache hints."""
+ if not isinstance(msg, dict):
+ return self._dispatch_method(msg)
+ method = msg.get("method") or ""
+ params = msg.get("params") if isinstance(msg.get("params"), dict) else {}
+ meta = msg.get("_meta") if isinstance(msg.get("_meta"), dict) else {}
+ nested = params.get("_meta") if isinstance(params.get("_meta"), dict) else {}
+ requested = (
+ meta.get("io.modelcontextprotocol/protocolVersion")
+ or nested.get("io.modelcontextprotocol/protocolVersion")
+ or params.get("protocolVersion")
+ )
+ if requested and requested not in SUPPORTED_PROTOCOL_VERSIONS and method not in ("initialize", "server/discover"):
+ return self._err(msg.get("id"), -32022, "Unsupported protocol version", {
+ "requestedVersion": requested,
+ "supportedVersions": list(SUPPORTED_PROTOCOL_VERSIONS),
+ })
+ modern = requested == MODERN_PROTOCOL_VERSION
+
+ if method == "server/discover":
+ return self._ok(msg.get("id"), self.discover_result())
+
+ if method == "tasks/get":
+ tid = (params or {}).get("taskId")
+ view = self._task_view(tid)
+ if view is None:
+ return self._err(msg.get("id"), -32602, f"Unknown task: {tid!r}")
+ return self._ok(msg.get("id"), view)
+
+ if method == "tasks/result":
```

```
601 + tid = (params or {}).get("taskId")
602 + timeout_ms = (params or {}).get("timeoutMs") or 120000
603 + payload = self._task_result(tid, float(timeout_ms) / 1000.0)
604 + if payload is None:
605 + return self._err(msg.get("id"), -32602, f"Unknown task: {tid!r}")
606 + return self._ok(msg.get("id"), payload)
607 +
608 + if method == "tasks/list":
609 + return self._ok(msg.get("id"), {"tasks": self._task_list()})
610 +
611 + if method == "tasks/cancel":
612 + tid = (params or {}).get("taskId")
613 + view = self._task_cancel(tid)
614 + if view is None:
615 + return self._err(msg.get("id"), -32602, f"Unknown task: {tid!r}")
616 + return self._ok(msg.get("id"), view)
617 +
618 + resp = self._dispatch_method(msg)
619 + if modern and isinstance(resp, dict) and isinstance(resp.get("result"), dict):
620 + result = resp["result"]
621 + result.setdefault("resultType", "complete")
622 + if method in ("tools/list", "resources/list", "resources/templates/list", "prompts/list"):
623 + result.setdefault("ttlMs", 60000)
624 + result.setdefault("cacheScope", "private")
625 + return resp
626 +
627 + # -- discovery & tasks ----------------------------------------------------
628 +
629 + def capabilities(self) -> dict:
630 + return {
631 + "tools": {"listChanged": False},
632 + "resources": {"subscribe": False, "listChanged": False},
633 + "prompts": {"listChanged": False},
634 + "tasks": {
635 + "list": {},
636 + "cancel": {},
637 + "requests": {"tools": {"call": {}}},
638 + },
639 + }
640 +
641 + def _instructions(self) -> str:
642 + mode_tag = " (Read-Only Inspector)" if self.client.read_only else ""
643 + return (
644 + f"Arena <-> Roblox Studio MCP Server v{MCP_SERVER_VERSION}{mode_tag}. "
645 + "Use `get_studio_state` or `survey_place` first to understand the open place. "
646 + "With several Studio windows connected, `studio_fleet {action:'list'}` shows them, "
647 + "`set_active` pins a default target and `broadcast` fans a read-only job out to all. "
648 + "Long work can be task-augmented (`params.task`), then polled with `tasks/get` and "
649 + "collected with `tasks/result`. "
650 + "Use `multi_edit` / `write_script` (with `replaceInstance: true` when updating already-required ModuleScripts) "
651 + "and `luau_check` to prevent undefined-global runtime bugs."
652 + )
653 +
654 + def discover_result(self) -> dict:
655 + return {
656 + "supportedVersions": list(SUPPORTED_PROTOCOL_VERSIONS),
657 + "protocolVersion": MODERN_PROTOCOL_VERSION,
658 + "capabilities": self.capabilities(),
659 + "serverInfo": {"name": MCP_SERVER_NAME, "version": MCP_SERVER_VERSION},
660 + "instructions": self._instructions(),
```

```
+ "ttlMs": 300000,
+ "cacheScope": "public",
+ }
+
+ @staticmethod
+ def _iso(ts: float) -> str:
+ return time.strftime("%Y-%m-%dT%H:%M:%SZ", time.gmtime(ts))
+
+ def _task_view(self, task_id: str):
+ with self._task_lock:
+ task = self.tasks.get(task_id)
+ if not task:
+ return None
+ return {
+ "taskId": task["taskId"],
+ "status": task["status"],
+ "statusMessage": task.get("statusMessage"),
+ "createdAt": self._iso(task["createdAt"]),
+ "lastUpdatedAt": self._iso(task["updatedAt"]),
+ "ttlMs": task["ttlMs"],
+ "pollIntervalMs": TASK_POLL_INTERVAL_MS,
+ "tool": task["tool"],
+ }
+
+ def _task_list(self) -> list:
+ with self._task_lock:
+ items = sorted(self.tasks.values(), key=lambda t: t["createdAt"], reverse=True)
+ return [
+ {
+ "taskId": t["taskId"],
+ "status": t["status"],
+ "statusMessage": t.get("statusMessage"),
+ "createdAt": self._iso(t["createdAt"]),
+ "lastUpdatedAt": self._iso(t["updatedAt"]),
+ "ttlMs": t["ttlMs"],
+ "pollIntervalMs": TASK_POLL_INTERVAL_MS,
+ }
+ for t in items
+ ]
+
+ def _task_cancel(self, task_id: str):
+ with self._task_lock:
+ task = self.tasks.get(task_id)
+ if not task:
+ return None
+ if task["status"] == "working":
+ task["status"] = "cancelled"
+ task["statusMessage"] = "Cancelled by the client; the in-flight Studio job still finishes, its result is discarded."
+ task["result"] = None
+ task["updatedAt"] = time.time()
+ return self._task_view(task_id)
+
+ def _task_prune(self):
+ with self._task_lock:
+ if len(self.tasks) <= TASK_HISTORY_LIMIT:
+ return
+ finished = sorted(
+ (t for t in self.tasks.values() if t["status"] != "working"),
+ key=lambda t: t["createdAt"],
+ )
```

```
+ for task in finished[: len(self.tasks) - TASK_HISTORY_LIMIT]:
+ self.tasks.pop(task["taskId"], None)
+
+ def _create_task(self, name: str, args: dict, task_params: dict) -> dict:
+ ttl_ms = int(task_params.get("ttl") or TASK_DEFAULT_TTL_MS)
+ task_id = "task-" + uuid.uuid4().hex[:20]
+ now = time.time()
+ initial_message = f"Running {name}..."
+ task = {
+ "taskId": task_id,
+ "tool": name,
+ "status": "working",
+ "statusMessage": initial_message,
+ "createdAt": now,
+ "updatedAt": now,
+ "ttlMs": ttl_ms,
+ "ttlDeadline": now + ttl_ms / 1000.0,
+ "result": None,
+ }
+ with self._task_lock:
+ self.tasks[task_id] = task
+ self._task_prune()
+
+ def worker():
+ try:
+ payload = self._invoke_tool(name, args)
+ except Exception as exc: # noqa: BLE001 - surface into the task
+ payload = {
+ "isError": True,
+ "content": [{"type": "text", "text": f"{name} failed: {exc}"}],
+ "structuredContent": {"ok": False, "error": str(exc)},
+ }
+ with self._task_lock:
+ current = self.tasks.get(task_id)
+ if not current:
+ return
+ if current["status"] == "cancelled":
+ current["updatedAt"] = time.time()
+ return
+ current["result"] = payload
+ current["status"] = "failed" if payload.get("isError") else "completed"
+ current["statusMessage"] = (
+ f"{name} failed" if payload.get("isError") else f"{name} completed"
+ )
+ current["updatedAt"] = time.time()
+
+ threading.Thread(target=worker, name=f"mcp-task-{task_id[-6:]}", daemon=True).start()
+ return {
+ "resultType": "task",
+ "taskId": task_id,
+ "status": "working",
+ "statusMessage": initial_message,
+ "createdAt": self._iso(now),
+ "lastUpdatedAt": self._iso(now),
+ "ttlMs": ttl_ms,
+ "pollIntervalMs": TASK_POLL_INTERVAL_MS,
+ }
+
+ def _task_result(self, task_id: str, timeout: float):
+ deadline = time.monotonic() + max(0.0, timeout)
```

```
+ while True:
+ with self._task_lock:
+ task = self.tasks.get(task_id)
+ if not task:
+ return None
+ if task["status"] in ("completed", "failed", "cancelled"):
+ payload = task["result"] or {
+ "isError": True,
+ "content": [{"type": "text", "text": task.get("statusMessage") or task["status"]}],
+ }
+ payload = dict(payload)
+ payload["_meta"] = {"io.modelcontextprotocol/related-task": {"taskId": task_id}}
+ payload["resultType"] = "complete"
+ return payload
+ if time.monotonic() >= deadline:
+ return {
+ "resultType": "task",
+ "taskId": task_id,
+ "status": "working",
+ "statusMessage": "Still running; call tasks/result again.",
+ "pollIntervalMs": TASK_POLL_INTERVAL_MS,
+ }
+ time.sleep(0.05)
+
+ def _invoke_tool(self, tname: str, targs: dict) -> dict:
+ """Run one tool call and return the MCP CallToolResult payload."""
+ if self.client.read_only and not is_tool_call_read_only(tname, targs):
+ return {
+ "isError": True,
+ "content": [{
+ "type": "text",
+ "text": f"Blocked by Read-Only Inspector mode: tool '{tname}' with arguments {json.dumps(targs)} mutates Studio state.",
+ }],
+ }
+ try:
+ data = execute_tool(self.client, tname, targs)
+ if isinstance(data, dict):
+ data.setdefault("ok", True)
+ data.setdefault("warnings", [])
+ img_b64 = data.pop("_mcp_image_png_b64", None) if isinstance(data, dict) else None
+ content_items = [{"type": "text", "text": json.dumps(data, indent=2)}]
+ if img_b64:
+ content_items.insert(0, {
+ "type": "image",
+ "data": img_b64,
+ "mimeType": "image/png",
+ })
+ return {"isError": False, "content": content_items, "structuredContent": data}
+ except Exception as tool_exc:
+ if isinstance(tool_exc, NoPeerError):
+ data = {"ok": False, "reason": tool_exc.reason, "dm": tool_exc.dm, "warnings": []}
+ return {"isError": True, "content": [{"type": "text", "text": json.dumps(data)}], "structuredContent": data}
+ data = {"ok": False, "reason": "tool_error", "error": str(tool_exc), "warnings": []}
+ return {
+ "isError": True,
+ "content": [{"type": "text", "text": json.dumps(data, indent=2)}],
+ "structuredContent": data,
+ }
+
+ def _dispatch_method(self, msg: dict):
```

```
if not isinstance(msg, dict) or msg.get("jsonrpc") != "2.0":
return self._err(msg.get("id") if isinstance(msg, dict) else None, -32600, "Invalid Request")

@@ -4608,31 +5323,29 @@ class MCPDispatcher:
requested_ver if requested_ver in SUPPORTED_PROTOCOL_VERSIONS
else DEFAULT_PROTOCOL_VERSION
)
- mode_tag = " (Read-Only Inspector)" if self.client.read_only else ""
- return self._ok(msg_id, {
+ payload = {
"protocolVersion": negotiated,
- "capabilities": {
- "tools": {"listChanged": False},
- "resources": {"subscribe": False, "listChanged": False},
- "prompts": {"listChanged": False},
- },
+ "capabilities": self.capabilities(),
"serverInfo": {
"name": MCP_SERVER_NAME,
"version": MCP_SERVER_VERSION,
},
- "instructions": (
- f"Arena <-> Roblox Studio MCP Server v{MCP_SERVER_VERSION}{mode_tag}. "
- "Use `get_studio_state` or `survey_place` first to understand the open place. "
- "Use `multi_edit` / `write_script` (with `replaceInstance: true` when updating already-required ModuleScripts) "
- "and `luau_check` to prevent undefined-global runtime bugs."
- ),
- })
+ "instructions": self._instructions(),
+ }
+ if negotiated == MODERN_PROTOCOL_VERSION:
+ payload["resultType"] = "complete"
+ return self._ok(msg_id, payload)

if method == "ping":
return self._ok(msg_id, {})

if method == "tools/list":
- return self._ok(msg_id, {"tools": self.visible_tools()})
+ tools = []
+ for spec in self.visible_tools():
+ entry = dict(spec)
+ entry.setdefault("execution", {"taskSupport": "optional"})
+ tools.append(entry)
+ return self._ok(msg_id, {"tools": tools})

if method == "tools/call":
tname = params.get("name")
@@ -4644,43 +5357,9 @@ class MCPDispatcher:
if validation_err:
return self._err(msg_id, -32602, validation_err)

- if self.client.read_only and not is_tool_call_read_only(tname, targs):
- return self._ok(msg_id, {
- "isError": True,
- "content": [{
- "type": "text",
- "text": f"Blocked by Read-Only Inspector mode: tool '{tname}' with arguments {json.dumps(targs)} mutates Studio state.",
- }],
- })
```

```
-
- try:
- data = execute_tool(self.client, tname, targs)
- if isinstance(data, dict):
- data.setdefault("ok", True)
- data.setdefault("warnings", [])
- img_b64 = data.pop("_mcp_image_png_b64", None) if isinstance(data, dict) else None
- content_items = [{"type": "text", "text": json.dumps(data, indent=2)}]
- if img_b64:
- content_items.insert(0, {
- "type": "image",
- "data": img_b64,
- "mimeType": "image/png",
- })
- return self._ok(msg_id, {
- "isError": False,
- "content": content_items,
- "structuredContent": data,
- })
- except Exception as tool_exc:
- if isinstance(tool_exc, NoPeerError):
- data = {"ok": False, "reason": tool_exc.reason, "dm": tool_exc.dm, "warnings": []}
- return self._ok(msg_id, {"isError": True, "content": [{"type": "text", "text": json.dumps(data)}], "structuredContent": data})
- data = {"ok": False, "reason": "tool_error", "error": str(tool_exc), "warnings": []}
- return self._ok(msg_id, {
- "isError": True,
- "content": [{"type": "text", "text": json.dumps(data, indent=2)}],
- "structuredContent": data,
- })
+ if isinstance(params.get("task"), dict):
+ return self._ok(msg_id, self._create_task(tname, targs, params["task"]))
+ return self._ok(msg_id, self._invoke_tool(tname, targs))

if method == "resources/list":
return self._ok(msg_id, {"resources": RESOURCES})
@@ -4701,7 +5380,7 @@ class MCPDispatcher:
pname = params.get("name", "")
if not pname:
return self._err(msg_id, -32602, "Missing 'name' parameter.")
- return self._ok(msg_id, get_mcp_prompt(pname, params.get("arguments")))
+ return self._ok(msg_id, get_mcp_prompt(pname, params.get("arguments"), self.client))

if method == "logging/setLevel":
return self._ok(msg_id, {})
```

roblox-bridge/arena_studio.py (diff)

285 lines

ops / metrics / audit / tunnel / tokens / bus CLI

```
diff --git a/roblox-bridge/arena_studio.py b/roblox-bridge/arena_studio.py
index 0d3e7d8..37dd913 100644
--- a/roblox-bridge/arena_studio.py
+++ b/roblox-bridge/arena_studio.py
@@ -1,6 +1,6 @@
#!/usr/bin/env python3
"""
-arena_studio.py - Full-featured CLI for the Arena <-> Roblox Studio MCP Bridge (v4.0.0).
+arena_studio.py - Full-featured CLI for the Arena <-> Roblox Studio MCP Bridge (v5.3.2).

Supports every MCP tool and bridge operation from your terminal or HANDS MODE (`ab.ps1`),
with strict UTF-8 handling on Windows, macOS, and Linux.
@@ -20,6 +20,19 @@ Core commands:
python3 arena_studio.py sync ../nightloop/src ServerScriptService.NightLoop
python3 arena_studio.py run "return {place = game.Name}" [--dm edit|server|client]
python3 arena_studio.py runfile ../jobs/baseline_survey.lua
+
+v5 ops & multi-agent commands:
+ python3 arena_studio.py ops [--json]
+ python3 arena_studio.py metrics [--prometheus]
+ python3 arena_studio.py audit [--verify] [--limit 20]
+ python3 arena_studio.py tunnel status|start|stop|restart
+ python3 arena_studio.py tokens list|create --label ci --role write --ttl 86400|revoke --id tok-123
+ python3 arena_studio.py bus register --name "Gemini 4 Argon" --role partner
+ python3 arena_studio.py bus agents|tasks|feed|export
+ python3 arena_studio.py bus post --agent agent-xxxx --subject "handoff" --body "take the UI pass" --to agent-yyyy
+ python3 arena_studio.py bus task-create --title "Polish shop UI" --priority high --agent agent-xxxx
+ python3 arena_studio.py bus task-claim --task task-xxxx --agent agent-xxxx
+ python3 arena_studio.py bus task-complete --task task-xxxx --agent agent-xxxx --result "shipped"
"""

import argparse
@@ -78,6 +91,26 @@ def call(method: str, path: str, payload=None, timeout: float = 140.0):
return {"error": f"cannot reach bridge at {BASE} ({exc.reason}). Is server.py running?"}


+def call_text(method: str, path: str, payload=None, timeout: float = 60.0) -> str:
+ """Raw-text response helper (Prometheus exposition, SSE snapshots, markdown)."""
+ url = f"{BASE}{path}"
+ headers = {}
+ if TOKEN:
+ headers["X-Arena-Token"] = TOKEN
+ url += ("&" if "?" in url else "?") + f"token={TOKEN}"
+ data = json.dumps(payload).encode("utf-8") if payload is not None else None
+ if data is not None:
+ headers["Content-Type"] = "application/json"
+ req = urllib.request.Request(url, data=data, method=method, headers=headers)
+ try:
+ with urllib.request.urlopen(req, timeout=timeout) as resp:
+ return resp.read().decode("utf-8", "replace")
+ except urllib.error.HTTPError as exc:
+ return f"HTTP {exc.code}: " + exc.read().decode("utf-8", "replace")[:400]
+ except urllib.error.URLError as exc:
+ return f"cannot reach bridge at {BASE} ({exc.reason}). Is server.py running?"
+
+
def submit(kind: str, payload: dict, note: str = None, wait: float = 60.0, dm: str = "auto", peer_id: str = None):
body = {"type": kind, "payload": payload, "note": note, "wait": wait}
if dm and dm != "auto":
@@ -405,6 +438,68 @@ def main() -> int:
```

```
p = sub.add_parser("system", help="install a drop-in server+shared+client system from roblox-kit/systems")
p.add_argument("name", help="e.g. liveops/codes | liveops/playtime-gifts | monetization/offline-earnings | core/data | all")

+ p = sub.add_parser("ops", help="consolidated operations report (peers, queue, tunnel, bus, audit)")
+ p.add_argument("--json", action="store_true")
+
+ p = sub.add_parser("metrics", help="bridge counters, gauges and latency percentiles")
+ p.add_argument("--prometheus", action="store_true")
+
+ p = sub.add_parser("audit", help="read or verify the tamper-evident audit log")
+ p.add_argument("--verify", action="store_true")
+ p.add_argument("--limit", type=int, default=20)
+
+ p = sub.add_parser("studios", help="multi-Studio fleet: list, pin, label, broadcast")
+ p.add_argument("action", nargs="?", default="list", choices=["list", "pin", "unpin", "label", "broadcast"])
+ p.add_argument("--peer", default=None, help="peerId from `studios list`")
+ p.add_argument("--place", default=None, help="Place id, as an alternative to --peer")
+ p.add_argument("--label", default=None, help="Human label (empty string clears it)")
+ p.add_argument("--tool", default="ping_studio",
+ choices=["ping_studio", "get_studio_state", "survey_place", "inspect_instance",
+ "script_read", "get_console_output"],
+ help="Read-only tool to fan out with `broadcast`")
+ p.add_argument("--path", default=None, help="Instance/script path for path-based broadcasts")
+ p.add_argument("--timeout", type=float, default=20.0)
+
+ p = sub.add_parser("queue", help="inspect, hold or clear the job queue")
+ p.add_argument("action", nargs="?", default="status", choices=["status", "pause", "resume", "clear"])
+ p.add_argument("--reason", default=None, help="Why the queue is paused (recorded in the audit log)")
+
+ p = sub.add_parser("tunnel", help="supervised public tunnel (cloudflared/ngrok)")
+ p.add_argument("action", nargs="?", default="status", choices=["status", "start", "stop", "restart"])
+
+ p = sub.add_parser("tokens", help="scoped access tokens (read/write/admin) & rate limits")
+ p.add_argument("action", nargs="?", default="list", choices=["list", "create", "revoke", "roles"])
+ p.add_argument("--label", default="cli-token")
+ p.add_argument("--role", default="write", choices=["read", "write", "admin"])
+ p.add_argument("--ttl", type=int, default=None, help="Token lifetime in seconds (default: never expires)")
+ p.add_argument("--rate", type=float, default=None, help="Requests per second (0 disables throttling)")
+ p.add_argument("--id", default=None, help="Token id to revoke")
+
+ p = sub.add_parser("bus", help="multi-agent coordination bus (presence, messages, tasks)")
+ p.add_argument("action", nargs="?", default="agents",
+ choices=["register", "agents", "inbox", "post", "tasks", "task-create", "task-claim",
+ "task-complete", "task-update", "feed", "export", "sweep", "stats"])
+ p.add_argument("--agent", default=os.environ.get("ARENA_AGENT_ID", "cli-agent"))
+ p.add_argument("--name", default=None)
+ p.add_argument("--role", default="agent")
+ p.add_argument("--to", default=None)
+ p.add_argument("--subject", default="")
+ p.add_argument("--body", default="")
+ p.add_argument("--kind", default="note")
+ p.add_argument("--priority", default="normal")
+ p.add_argument("--task", default=None)
+ p.add_argument("--title", default="")
+ p.add_argument("--detail", default="")
+ p.add_argument("--result", default="")
+ p.add_argument("--status", default=None)
+ p.add_argument("--since", type=int, default=0)
+ p.add_argument("--limit", type=int, default=30)
+ p.add_argument("--out", default=None, help="Write the exported handoff markdown here")
```

```
+ p.add_argument("--summary-only", action="store_true",
+ help="export: one line per task, no message log")
+ p.add_argument("--offline-seconds", type=float, default=900,
+ help="sweep: how long an agent must be silent before its tasks are released")
+
p = sub.add_parser("import-audio", help="import a WAV/OGG/MP3 or built-in CC0 sound into Studio")
p.add_argument("source", help="local audio file path or repo audio filename (e.g. click_001.wav)")
p.add_argument("--target", default="SoundService")
@@ -462,6 +557,57 @@ def main() -> int:
print(json.dumps(call("POST", "/api/queue/clear"), indent=2, ensure_ascii=False))
return 0

+ if args.cmd == "studios":
+ if args.action == "pin":
+ body = {"action": "set_active"}
+ if args.peer:
+ body["peerId"] = args.peer
+ if args.place:
+ body["placeId"] = int(args.place)
+ out = call("POST", "/api/studios", body)
+ elif args.action == "unpin":
+ out = call("POST", "/api/studios", {"action": "clear_active"})
+ elif args.action == "label":
+ out = call("POST", "/api/studios", {"action": "label", "peerId": args.peer,
+ "label": args.label or ""})
+ elif args.action == "broadcast":
+ out = call("POST", "/api/studios", {
+ "action": "broadcast",
+ "tool": args.tool,
+ "path": args.path,
+ "timeout": args.timeout,
+ })
+ else:
+ out = call("GET", "/api/studios")
+ print(json.dumps(out, indent=2, ensure_ascii=False))
+ return 0 if "error" not in out else 1
+
+ if args.cmd == "queue":
+ if args.action == "pause":
+ out = call("POST", "/api/queue/pause", {"reason": args.reason or "paused from the CLI"})
+ elif args.action == "resume":
+ out = call("POST", "/api/queue/resume", {})
+ elif args.action == "clear":
+ out = call("POST", "/api/queue/clear")
+ else:
+ ops = call("GET", "/api/ops")
+ if "error" in ops:
+ out = ops
+ else:
+ queue = ops.get("queue") or {}
+ sweeper = ops.get("sweeper") or {}
+ latency = ops.get("jobLatency") or {}
+ out = {
+ "queue": queue,
+ "sweeper": sweeper,
+ "jobLatency": latency,
+ "recentJobs": (ops.get("recentJobs") or [])[:5],
+ }
+ if not latency:
+ out["note"] = "no completed jobs yet - latency fills in as work runs"
```

```
+ print(json.dumps(out, indent=2, ensure_ascii=False))
+ return 0 if "error" not in out else 1
+
if args.cmd == "watch":
print(f"watching {BASE} - ctrl-c to stop")
seen = set()
@@ -844,6 +990,98 @@ def main() -> int:
"peerId": args.peer,
}, args.full, args.raw_json)

+ # ---------------------------- v5 ops & bus ----------------------------
+ if args.cmd == "ops":
+ data = call("GET", "/api/ops")
+ if args.json:
+ print(json.dumps(data, indent=2, ensure_ascii=False))
+ else:
+ h = data.get("health", {})
+ t = data.get("tunnel", {})
+ b = data.get("bus", {})
+ print(f"bridge v{data.get('version')} uptime {data.get('uptimeSeconds')}s")
+ print(f"studio : {'connected' if h.get('studio_connected') else 'waiting'} peers={len(h.get('peers', []))} queue={h.get('queued')}")
+ print(f"tunnel : {t.get('state')} {t.get('publicUrl') or '-'}")
+ print(f"agents : {b.get('agentsOnline', 0)} online / {b.get('agents', 0)} tasks open={sum(v for k, v in (b.get('taskCounts') or {}).items() if k in ('todo','in_progress','blocked')
)}")
+ rows = data.get("openTasks") or []
+ if rows:
+ print("\nopen tasks:")
+ for row in rows[:10]:
+ print(f" [{row['status']:11}] {row['priority']:8} {row['title']} ({row.get('assignee') or 'unclaimed'})")
+ audit = data.get("audit") or []
+ if audit:
+ print("\nrecent audit:")
+ for e in audit[:5]:
+ print(f" {e['seq']:>4} {e['action']:<22} {e['actor']:<20} {e['outcome']}")
+ return 0
+
+ if args.cmd == "metrics":
+ if args.prometheus:
+ print(call_text("GET", "/api/metrics?format=prometheus"))
+ return 0
+ data = call("GET", "/api/metrics")
+ print(json.dumps(data, indent=2, ensure_ascii=False))
+ return 0
+
+ if args.cmd == "audit":
+ path = "/api/audit?verify=1" if args.verify else f"/api/audit?limit={args.limit}"
+ print(json.dumps(call("GET", path), indent=2, ensure_ascii=False))
+ return 0
+
+ if args.cmd == "tunnel":
+ if args.action == "status":
+ print(json.dumps(call("GET", "/api/tunnel"), indent=2, ensure_ascii=False))
+ else:
+ print(json.dumps(call("POST", "/api/tunnel", {"action": args.action}, timeout=120), indent=2, ensure_ascii=False))
+ return 0
+
+ if args.cmd == "tokens":
+ payload = {"action": args.action}
+ if args.action == "create":
+ payload.update({"label": args.label, "role": args.role})
```

```
+ if args.ttl:
+ payload["ttlSeconds"] = args.ttl
+ if args.rate is not None:
+ payload["rateLimitPerSecond"] = args.rate
+ if args.action == "revoke":
+ if not args.id:
+ print("--id is required for revoke", file=sys.stderr)
+ return 2
+ payload["id"] = args.id
+ print(json.dumps(call("POST", "/api/tokens", payload), indent=2, ensure_ascii=False))
+ return 0
+
+ if args.cmd == "bus":
+ payload = {"action": args.action.replace("-", "_")}
+ payload["agentId"] = args.agent
+ mapping = {
+ "name": "name", "role": "role", "to": "to", "subject": "subject", "body": "body",
+ "kind": "kind", "priority": "priority", "title": "title", "detail": "detail",
+ "result": "result", "since": "since", "limit": "limit",
+ }
+ for attr, key in mapping.items():
+ value = getattr(args, attr, None)
+ if value not in (None, "", 0):
+ payload[key] = value
+ if args.task:
+ payload["taskId"] = args.task
+ if args.status:
+ payload["status"] = args.status
+ if args.out:
+ payload["path"] = args.out
+ if getattr(args, "summary_only", False):
+ payload["summaryOnly"] = True
+ if args.action == "sweep":
+ payload["offlineSeconds"] = getattr(args, "offline_seconds", 900)
+ result = call("POST", "/api/bus", payload)
+ if args.action == "export" and isinstance(result, dict) and result.get("markdown"):
+ print(result["markdown"])
+ if result.get("path"):
+ print(f"\n[written] {result['path']}", file=sys.stderr)
+ return 0
+ print(json.dumps(result, indent=2, ensure_ascii=False))
+ return 0
+
if args.cmd == "import-audio":
targs = {"targetPath": args.target, "peerId": args.peer}
if Path(args.source).is_file():

```

roblox-bridge/setup.py (diff)

205 lines

Supervised tunnel launch + URL watcher

```
diff --git a/roblox-bridge/setup.py b/roblox-bridge/setup.py
index 23c61af..e0880f8 100644
--- a/roblox-bridge/setup.py
+++ b/roblox-bridge/setup.py
@@ -1,7 +1,7 @@
#!/usr/bin/env python3
"""
setup.py - One command to install, configure, and run the Arena <-> Roblox
-Studio Bridge & MCP Server (v4.0.0).
+Studio Bridge & MCP Server (v5.3.2).

What it does:
1. Creates or reuses a shared secret in bridge.token - and if bridge.token is
@@ -10,10 +10,10 @@ What it does:
Plugins directory so you NEVER hit HTTP 401 token mismatches!
2. Writes ArenaBridge.lua v4.0.0 into your OS Roblox Studio Plugins folder with
the port + token baked in (leaving the tracked repo source file clean).
- 3. Starts server.py v4.0.0 on :8077 (serving Studio polling, REST CLI, Web
+ 3. Starts server.py v5.3.2 on :8077 (serving Studio polling, REST CLI, Web
Dashboard, AND Streamable HTTP MCP at http://127.0.0.1:8077/mcp).
4. Optionally writes .mcp.json (`--write-mcp`) for Claude Code / Cursor / VS Code
- and/or opens a public cloudflared tunnel (`--tunnel`).
+ and/or opens a supervised cloudflared/ngrok tunnel (`--tunnel`).

Usage:
python3 setup.py # install plugin + run server & HTTP MCP
@@ -316,13 +316,40 @@ def shutdown(*_):

# ---------------------------------------------------------------------------

+def describe_launch(server_cmd, supervised_tunnel: bool, tunnel_flavor: str,
+ public_url: str, port: int):
+ """The `--dry-run` plan, as (line, colour) pairs - also unit-tested directly."""
+ tunnel_state = (
+ f"supervised {tunnel_flavor}" if supervised_tunnel
+ else (f"external {public_url}" if public_url
+ else "not requested (add --tunnel or --public-url)")
+ )
+ return [
+ (" Dry run - nothing was started.", BOLD),
+ (f" server : {' '.join(server_cmd)}", DIM),
+ (f" tunnel : {tunnel_state}", DIM),
+ (f" dashboard: http://127.0.0.1:{port}", DIM),
+ (" A local dashboard authenticates itself; a tunnel/LAN page needs the token above.", DIM),
+ ]
+
+
def main():
ap = argparse.ArgumentParser(description=__doc__, formatter_class=argparse.RawDescriptionHelpFormatter)
ap.add_argument("--port", type=int, default=8077)
- ap.add_argument("--tunnel", action="store_true", help="Expose bridge + /mcp via cloudflared quick tunnel")
+ ap.add_argument("--tunnel", action="store_true", help="Expose bridge + /mcp via a supervised cloudflared/ngrok tunnel")
+ ap.add_argument("--tunnel-flavor", default="auto", choices=["auto", "cloudflared", "ngrok"],
+ help="Tunnel provider (default: auto-detect)")
+ ap.add_argument("--tunnel-token", default=None,
+ help="Cloudflare named-tunnel token (stable hostname instead of a random quick-tunnel URL)")
+ ap.add_argument("--tunnel-name", default=None,
+ help="Display-only label for a named tunnel; routing still comes from Cloudflare ingress")
+ ap.add_argument("--public-url", default=None,
+ help="Report a tunnel URL you already run yourself (bridge will not manage it)")
```

```
ap.add_argument("--install-only", action="store_true", help="Install plugin (and optional --write-mcp) then exit")
ap.add_argument("--rotate", action="store_true", help="Mint a fresh shared secret token")
ap.add_argument("--read-only", action="store_true", help="Run server & MCP in Read-Only Inspector mode")
+ ap.add_argument("--dry-run", action="store_true",
+ help="Print the resolved launch plan (token, server command, tunnel intent) and exit without starting")
ap.add_argument("--place-id", type=int, default=None, help="Optional PlaceId write guard")
ap.add_argument("--plugins-dir", default=None, help="Explicit Studio Plugins folder override")
ap.add_argument(
@@ -336,7 +363,7 @@ def main():

signal.signal(signal.SIGINT, shutdown)

- say(f"\n{BOLD}Arena <-> Roblox Studio MCP Bridge v4.0.0{OFF}")
+ say(f"\n{BOLD}Arena <-> Roblox Studio MCP Bridge v5.3.2{OFF}")
token = get_token(rotate=args.rotate, explicit_dir=args.plugins_dir, preferred_port=args.port)
say(f" token: {CYAN}{token}{OFF} {DIM}(stored in bridge.token){OFF}")

@@ -363,36 +390,103 @@ def main():
if args.place_id is not None:
server_cmd.extend(["--place-id", str(args.place_id)])

+ supervised_tunnel = bool(args.tunnel) and not args.public_url
+ if supervised_tunnel:
+ import shutil as _shutil
+ have_cloudflared = _shutil.which("cloudflared") is not None
+ have_account_ngrok = _shutil.which("ngrok") is not None
+ flavor = args.tunnel_flavor
+ wanted = ["cloudflared", "ngrok"] if flavor == "auto" else [flavor]
+ found = {"cloudflared": have_cloudflared, "ngrok": have_account_ngrok}
+ if not any(found.get(w) for w in wanted):
+ say("\n Tunnel requested, but no tunnel binary is on PATH.", YELLOW)
+ say(f" looked for: {', '.join(wanted)}", DIM)
+ say(" cloudflared: winget install --id Cloudflare.cloudflared", DIM)
+ say(" ngrok: winget install --id Ngrok.Ngrok", DIM)
+ say(" The bridge still starts and serves 127.0.0.1 - no public URL will appear.", DIM)
+ else:
+ say(f"\n Tunnel: starting supervised {', '.join(w for w in wanted if found.get(w))} tunnel...", GREEN)
+ if args.tunnel:
+ server_cmd.append("--tunnel")
+ server_cmd.extend(["--tunnel-flavor", args.tunnel_flavor])
+ if args.tunnel_token:
+ server_cmd.extend(["--tunnel-token", args.tunnel_token])
+ if args.tunnel_name:
+ server_cmd.extend(["--tunnel-name", args.tunnel_name])
+ if args.public_url:
+ server_cmd.extend(["--public-url", args.public_url])
+
+ if args.dry_run:
+ print()
+ for line, color in describe_launch(server_cmd, supervised_tunnel, args.tunnel_flavor,
+ args.public_url, args.port):
+ say(line, color)
+ return 0
+
spawn(server_cmd, "bridge")
time.sleep(0.8)

- public_url = {"value": None}
-
- if args.tunnel:
```

```
- exe = find_binary("cloudflared")
- if exe:
- def got_url(url):
- if public_url["value"]:
- return
- public_url["value"] = url
- print()
- say("=" * 70, GREEN)
- say(" Paste these lines to Arena (or Streamable HTTP MCP client):", BOLD)
- say(f" URL: {url}", CYAN)
- say(f" MCP URL: {url}/mcp", CYAN)
- say(f" TOKEN: {token}", CYAN)
- say("=" * 70, GREEN)
- print()
-
- spawn([exe, "tunnel", "--url", f"http://localhost:{args.port}"], "tunnel", TUNNEL_RE, got_url)
- else:
- say("\n cloudflared not found. Install via:", YELLOW)
- say(" Windows: winget install --id Cloudflare.cloudflared", DIM)
- say(" macOS: brew install cloudflared", DIM)
- say(f" Or expose manually with: ngrok http {args.port}", DIM)
+ if args.public_url:
+ say("\n" + "=" * 70, GREEN)
+ say(" Public URL (externally managed tunnel):", BOLD)
+ say(f" URL: {args.public_url}", CYAN)
+ say(f" MCP URL: {args.public_url}/mcp", CYAN)
+ say(f" TOKEN: {token}", CYAN)
+ say("=" * 70, GREEN)
+ elif supervised_tunnel:
+ def watch_tunnel():
+ import urllib.request
+ announced = None
+ unavailable_reported = False
+ url = f"http://127.0.0.1:{args.port}/api/tunnel"
+ while True:
+ time.sleep(2.0)
+ try:
+ req = urllib.request.Request(url, headers={"X-Arena-Token": token})
+ with urllib.request.urlopen(req, timeout=5) as resp:
+ info = json.loads(resp.read().decode("utf-8"))
+ except Exception:
+ continue
+ state = info.get("state")
+ public = info.get("publicUrl")
+ if public and public != announced:
+ announced = public
+ print()
+ say("=" * 70, GREEN)
+ say(" Tunnel is live - paste these lines to Arena (or any MCP client):", BOLD)
+ say(f" URL: {public}", CYAN)
+ say(f" MCP URL: {public}/mcp", CYAN)
+ say(f" TOKEN: {token}", CYAN)
+ say(" The supervisor auto-restarts the tunnel and re-prints a new URL if it changes.", DIM)
+ say("=" * 70, GREEN)
+ print()
+ if state in ("error", "blocked") and not unavailable_reported:
+ unavailable_reported = True
+ say(f"\n Tunnel could not start (state={state}):", YELLOW)
+ say(f" {info.get('lastError') or 'no error reported'}", DIM)
+ for line in (info.get("logTail") or [])[-4:]:
```

```
+ say(f" {line}", DIM)
+ say(" The bridge keeps running locally on 127.0.0.1.", DIM)
+ if state == "unavailable" and not unavailable_reported:
+ unavailable_reported = True
+ say("\n No tunnel binary found. Install one of:", YELLOW)
+ for hint in (info.get("installHints") or []):
+ say(f" {hint}", DIM)
+ say(f" Or expose manually with: ngrok http {args.port}", DIM)
+ say(" The bridge keeps running locally on 127.0.0.1.", DIM)
+
+ threading.Thread(target=watch_tunnel, daemon=True).start()
+
+ if not args.tunnel and not args.public_url:
+ print()
+ say(" Tunnel: not requested - this run is local only (no public URL).", YELLOW)
+ say(" Add --tunnel to publish it (needs cloudflared or ngrok),", DIM)
+ say(" or --public-url https://your-host to report a tunnel you run yourself.", DIM)

print()
say(f" Web Dashboard: http://127.0.0.1:{args.port}", GREEN)
+ if args.tunnel or args.public_url:
+ say(f" (opened from a tunnel/LAN address? paste this token when the console asks: {token})", DIM)
say(f" MCP Streamable HTTP: http://127.0.0.1:{args.port}/mcp (Bearer {token})", GREEN)
say(f" MCP stdio server: python \"{HERE / 'mcp_server.py'}\"", GREEN)
say(f" CLI quick check: .\\ab.ps1 ping", DIM)

```

roblox-bridge/test_bridge_mcp.py (diff)

1107 lines

v5 test coverage (scopes, bus, reaping, audit, tunnel)

```
diff --git a/roblox-bridge/test_bridge_mcp.py b/roblox-bridge/test_bridge_mcp.py
index 7d1e453..a85ecd5 100644
--- a/roblox-bridge/test_bridge_mcp.py
+++ b/roblox-bridge/test_bridge_mcp.py
@@ -29,7 +29,9 @@ Tests:

 import json
 import os
+import re
 import socket
+import shutil
 import subprocess
 import sys
 import tempfile
@@ -39,6 +41,9 @@ import unittest
 import urllib.error
 import urllib.request
 from pathlib import Path
+from unittest import mock
+
+from bus_core import AgentBus

 HERE = Path(__file__).resolve().parent
 TOOL_TEST_METRICS = {}
@@ -62,6 +67,1001 @@ import server as bridge_server # noqa: E402
 import setup as bridge_setup # noqa: E402


+class TestV5OpsPlatform(unittest.TestCase):
+    """v5: scoped tokens, rate limits, multi-agent bus, resilient jobs, audit chain, tunnel."""
+
+    def setUp(self):
+        self.tmp = tempfile.mkdtemp(prefix="arena-v5-")
+        self.port = _free_port()
+        self.base = f"http://127.0.0.1:{self.port}"
+        self.admin_token = "admin-secret-v5"
+        self.httpd, self.state = create_http_server(
+            host="127.0.0.1", port=self.port, token=self.admin_token, state_dir=self.tmp,
+        )
+        self.thread = threading.Thread(target=self.httpd.serve_forever, daemon=True)
+        self.thread.start()
+
+    def tearDown(self):
+        self.state._reaper_stop.set()
+        self.state.tunnel.stop()
+        self.httpd.shutdown()
+        self.httpd.server_close()
+
+    def _req(self, path, method="GET", body=None, token=None):
+        headers = {"Content-Type": "application/json"}
+        if token:
+            headers["Authorization"] = f"Bearer {token}"
+        data = json.dumps(body).encode("utf-8") if body is not None else None
+        req = urllib.request.Request(self.base + path, data=data, method=method, headers=headers)
+        try:
+            with urllib.request.urlopen(req, timeout=20) as resp:
+                raw = resp.read().decode("utf-8")
+                return resp.status, (json.loads(raw) if raw and raw.strip().startswith(("{", "[")) else raw)
+        except urllib.error.HTTPError as exc:
+            raw = exc.read().decode("utf-8")
```

```
+ return exc.code, (json.loads(raw) if raw.strip().startswith(("{", "[")) else raw)
+
+ # -- tokens / scopes / rate limiting -----------------------------------
+
+ def test_scoped_tokens_enforce_roles_and_rate_limits(self):
+ created = self.state.tokens.create("reader", role="read", rate_limit=100, burst=100)
+ reader = created["token"]
+ self.assertTrue(created["note"])
+ self.assertEqual(self._req("/api/state", token=reader)[0], 200)
+ self.assertEqual(self._req("/api/jobs", method="POST", body={"type": "ping"}, token=reader)[0], 403)
+ self.assertEqual(self._req("/api/tokens", token=reader)[0], 403)
+
+ # Read scope cannot invoke a mutating MCP tool, even over /mcp.
+ rpc = {"jsonrpc": "2.0", "id": 1, "method": "tools/call",
+ "params": {"name": "write_script", "arguments": {"path": "ServerScriptService.X", "source": "print(1)"}}}
+ status, body = self._req("/mcp", method="POST", body=rpc, token=reader)
+ self.assertEqual(status, 200)
+ self.assertTrue(body["result"]["isError"])
+ self.assertIn("insufficient_scope", json.dumps(body))
+
+ # Admin can list, mint a write token, and revoke it.
+ status, listing = self._req("/api/tokens", token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertGreaterEqual(listing["count"], 2)
+ writer = self.state.tokens.create("writer", role="write", rate_limit=50)
+ status, jobs = self._req("/api/jobs", method="POST",
+ body={"type": "ping", "wait": 0}, token=writer["token"])
+ self.assertEqual(status, 201)
+ status, revoked = self._req("/api/tokens", method="POST",
+ body={"action": "revoke", "id": writer["id"]}, token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertTrue(revoked["revoked"])
+ self.assertEqual(self._req("/api/jobs", method="POST", body={"type": "ping"}, token=writer["token"])[0], 401)
+
+ # Unknown tokens are rejected everywhere except the public health probe.
+ self.assertEqual(self._req("/api/state", token="nope")[0], 401)
+ self.assertEqual(self._req("/api/health")[0], 200)
+
+ # Rate limiting: one-request burst then 429 with Retry-After.
+ slow = self.state.tokens.create("firehose", role="read", rate_limit=0.01, burst=1)
+ self.assertEqual(self._req("/api/state", token=slow["token"])[0], 200)
+ status, body = self._req("/api/state", token=slow["token"])
+ self.assertEqual(status, 429)
+ self.assertIn("rate limit", body["error"])
+ self.assertGreaterEqual(body["retryAfter"], 1)
+
+ # -- multi-agent bus ---------------------------------------------------
+
+ def test_agent_bus_presence_mailbox_leases_and_handoff(self):
+ res = self._req("/api/bus", method="POST", token=self.admin_token, body={
+ "action": "register", "name": "Gemini 4 Argon", "role": "partner",
+ "capabilities": ["roblox", "qa"],
+ })
+ self.assertEqual(res[0], 200)
+ gem = res[1]
+ claude = self.state.bus.handle({"action": "register", "name": "Claude", "role": "builder"})
+ self.assertEqual(self.state.bus.stats()["agents"], 2)
+
+ self.state.bus.handle({"action": "post", "agentId": gem["id"], "to": claude["id"],
+ "subject": "handoff", "body": "take the UI pass", "kind": "handoff"})
```

```
+ self.state.bus.handle({"action": "post", "agentId": gem["id"], "subject": "broadcast",
+ "body": "standup in 5"})
+ inbox = self.state.bus.handle({"action": "inbox", "agentId": claude["id"]})
+ self.assertEqual(inbox["count"], 2)
+ self.assertEqual(inbox["unread"], 2)
+ self.state.bus.handle({"action": "mark_read", "agentId": claude["id"], "all": True})
+ self.assertEqual(self.state.bus.handle({"action": "inbox", "agentId": claude["id"]})["unread"], 0)
+
+ task = self.state.bus.handle({"action": "task_create", "title": "Polish shop UI",
+ "createdBy": gem["id"], "priority": "critical", "tags": ["ui"]})
+ # Claim with a one-second lease; a second agent must be refused while it holds.
+ self.state.bus.handle({"action": "task_claim", "taskId": task["id"], "agentId": gem["id"], "leaseSeconds": 1})
+ with self.assertRaises(ValueError):
+ self.state.bus.handle({"action": "task_claim", "taskId": task["id"], "agentId": claude["id"]})
+ # ...and allowed once the lease expires, without any manual cleanup.
+ time.sleep(1.2)
+ taken = self.state.bus.handle({"action": "task_claim", "taskId": task["id"], "agentId": claude["id"]})
+ self.assertEqual(taken["assignee"], claude["id"])
+ self.assertEqual(taken["leaseExpiries"], 1)
+
+ done = self.state.bus.handle({"action": "task_complete", "taskId": task["id"], "agentId": claude["id"],
+ "result": "UI shipped", "artifacts": ["StarterGui/Shop"]})
+ self.assertEqual(done["status"], "done")
+ handoff = self.state.bus.handle({"action": "export", "path": os.path.join(self.tmp, "HANDOFF.md")})
+ self.assertIn("# Agent handoff brief", handoff["markdown"])
+ self.assertIn("Polish shop UI", handoff["markdown"])
+ self.assertTrue(os.path.isfile(handoff["path"]))
+
+ # -- resilient job queue ------------------------------------------------
+
+ def test_job_idempotency_priority_retry_and_reaping(self):
+ state = self.state
+ job1, _ = state.enqueue_job("ping", note="first", idempotency_key="abc123")
+ job2, _ = state.enqueue_job("ping", note="dedupe", idempotency_key="abc123")
+ self.assertEqual(job1["id"], job2["id"])
+ self.assertEqual(state.jobs[job1["id"]]["deduplicated"], 1)
+ self.assertEqual(len([j for j in state.jobs.values() if j["status"] == "queued"]), 1)
+
+ low, _ = state.enqueue_job("ping", note="low", priority=7)
+ high, _ = state.enqueue_job("ping", note="high", priority=0)
+ peer = state.record_poll({"peer": ["peer-priority"], "dm": ["edit"], "place": ["p"], "placeId": ["1"]})
+ first = state.poll_for_job(peer, wait_seconds=0.1)
+ self.assertEqual(first["id"], high["id"])
+ second = state.poll_for_job(peer, wait_seconds=0.1)
+ self.assertEqual(second["id"], job1["id"]) # priority 5 beats priority 7
+ third = state.poll_for_job(peer, wait_seconds=0.1)
+ self.assertEqual(third["id"], low["id"])
+
+ # Transient failure is retried once, then fails permanently.
+ retry_job, evt = state.enqueue_job("ping", note="retry", max_retries=1)
+ state.poll_for_job(peer, wait_seconds=0.1)
+ state.complete_job({"id": retry_job["id"], "ok": False, "error": "peer disconnected mid-job",
+ "peerId": "peer-priority"})
+ self.assertEqual(state.jobs[retry_job["id"]]["status"], "queued")
+ self.assertFalse(evt.is_set())
+ state.poll_for_job(peer, wait_seconds=0.1)
+ state.complete_job({"id": retry_job["id"], "ok": False, "error": "peer disconnected again",
+ "peerId": "peer-priority"})
+ self.assertEqual(state.jobs[retry_job["id"]]["status"], "error")
+ self.assertTrue(evt.is_set())
```

```
+ self.assertEqual(state.jobs[retry_job["id"]]["retries"], 1)
+
+ # A job claimed by a peer that vanishes is requeued by the reaper.
+ orphan, _ = state.enqueue_job("ping", note="orphan")
+ state.poll_for_job(peer, wait_seconds=0.1)
+ with state.lock:
+ state.jobs[orphan["id"]]["claimed"] = time.time() - 60
+ for pid in list(state.peers):
+ state.peers[pid]["lastPoll"] = 0
+ result = state.reap_jobs()
+ self.assertGreaterEqual(result["recovered"], 1)
+ self.assertEqual(state.jobs[orphan["id"]]["status"], "queued")
+
+ # Timeout reaping finalises a stuck running job.
+ state.clear_queue()
+ stuck, stuck_evt = state.enqueue_job("ping", note="stuck", timeout=1)
+ peer2 = state.record_poll({"peer": ["peer-stuck"], "dm": ["edit"], "place": ["p"], "placeId": ["1"]})
+ state.poll_for_job(peer2, wait_seconds=0.1)
+ with state.lock:
+ state.jobs[stuck["id"]]["claimed"] = time.time() - 30
+ state.reap_jobs()
+ self.assertEqual(state.jobs[stuck["id"]]["status"], "error")
+ self.assertIn("timeout", state.jobs[stuck["id"]]["error"])
+ self.assertTrue(stuck_evt.is_set())
+
+ # -- observability -----------------------------------------------------
+
+ def test_metrics_events_and_tamper_evident_audit(self):
+ self.state.enqueue_job("ping", note="metrics")
+ self.state.telemetry.metrics.observe("unit_latency_ms", 12.5, {"route": "/api/jobs"})
+ self.state.telemetry.metrics.observe("unit_latency_ms", 30.0, {"route": "/api/jobs"})
+ self.state.telemetry.events.emit("unit.event", {"hello": "world"})
+
+ self.state.tokens.create("audited", role="read")
+ status, metrics = self._req("/api/metrics", token=self.admin_token)
+ self.assertEqual(status, 200)
+ names = {c["name"] for c in metrics["counters"]}
+ self.assertIn("bridge_jobs_enqueued_total", names)
+ hist = next(h for h in metrics["histograms"] if h["name"] == "unit_latency_ms")
+ self.assertEqual(hist["count"], 2)
+ self.assertGreaterEqual(hist["p95"], hist["p50"])
+
+ status, text = self._req("/api/metrics?format=prometheus", token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertIn("# TYPE bridge_jobs_enqueued_total counter", text)
+ self.assertIn('unit_latency_ms_count{route="/api/jobs"} 2', text)
+
+ status, events = self._req("/api/events?once=1&since=0&limit=20", token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertTrue(any(e["kind"] == "unit.event" for e in events["events"]))
+
+ status, verify = self._req("/api/audit?verify=1", token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertTrue(verify["ok"])
+ self.assertGreater(verify["entries"], 0)
+
+ # Tamper with an entry in memory: the chain verification must notice.
+ with self.state.telemetry.audit.lock:
+ victim = self.state.telemetry.audit.entries[-1]
+ victim["actor"] = "someone-else"
```

```
241 + broken = self.state.telemetry.audit.verify()
242 + self.assertFalse(broken["ok"])
243 + self.assertIn("hash", broken["reason"])
244 +
245 + def test_tunnel_refuses_to_publish_an_unauthenticated_bridge(self):
246 + open_state = BridgeState(token="", read_only=False, state_dir=tempfile.mkdtemp(prefix="arena-open-"))
247 + blocked = open_state.tunnel_action({"action": "start"})
248 + self.assertEqual(blocked["state"], "blocked")
249 + self.assertIn("without a token", blocked["lastError"])
250 + # Status checks are always allowed.
251 + self.assertIn(open_state.tunnel_action({"action": "status"})["state"], ("stopped", "unavailable"))
252 + # With a token configured the guard steps aside (the sandbox has no binary,
253 + # so the supervisor reports unavailable rather than blocked).
254 + allowed = self.state.tunnel_action({"action": "start"})
255 + self.assertNotEqual(allowed["state"], "blocked")
256 +
257 + def test_ops_report_and_public_health_shape(self):
258 + status, health = self._req("/api/health")
259 + self.assertEqual(status, 200)
260 + self.assertEqual(health["version"], "5.3.2")
261 + self.assertIn("tunnel", health)
262 + self.assertIn("agents", health)
263 + status, ops = self._req("/api/ops", token=self.admin_token)
264 + self.assertEqual(status, 200)
265 + for key in ("health", "tunnel", "bus", "audit", "recentJobs", "openTasks"):
266 + self.assertIn(key, ops)
267 +
268 + # -- v5.1 partner tasks: sweeper, incremental handoff, prompts, tunnel token --
269 +
270 + def test_stale_agent_sweeper_and_incremental_handoff(self):
271 + bus = self.state.bus
272 + builder = bus.handle({"action": "register", "name": "Builder", "role": "builder"})
273 + partner = bus.handle({"action": "register", "name": "Partner", "role": "qa"})
274 + live_task = bus.handle({"action": "task_create", "title": "Held by a live agent",
275 + "createdBy": builder["id"], "priority": "high"})
276 + dead_task = bus.handle({"action": "task_create", "title": "Held by a dead agent",
277 + "createdBy": builder["id"], "detail": "should be released"})
278 + bus.handle({"action": "task_claim", "taskId": live_task["id"], "agentId": builder["id"]})
279 + bus.handle({"action": "task_claim", "taskId": dead_task["id"], "agentId": partner["id"]})
280 +
281 + # Partner stops heart-beating a long time ago; builder is still alive.
282 + bus.agents[partner["id"]]["lastSeen"] = time.time() - 5000
283 + swept = bus.handle({"action": "sweep", "offlineSeconds": 900})
284 + self.assertEqual(swept["tasksReaped"], 1)
285 + self.assertEqual(swept["released"][0]["taskId"], dead_task["id"])
286 + self.assertEqual(bus.tasks[dead_task["id"]]["status"], "todo")
287 + self.assertIsNone(bus.tasks[dead_task["id"]]["assignee"])
288 + self.assertIsNone(bus.tasks[dead_task["id"]]["lease"])
289 + self.assertEqual(bus.tasks[live_task["id"]]["status"], "in_progress")
290 +
291 + # Idempotent: a second sweep releases nothing and posts no second alert.
292 + again = bus.handle({"action": "sweep", "offlineSeconds": 900})
293 + self.assertEqual(again["tasksReaped"], 0)
294 + self.assertFalse(again["alerted"])
295 + alerts = [m for m in bus.messages if m["kind"] == "alert"]
296 + self.assertEqual(len(alerts), 1)
297 + self.assertIn("Stale agent tasks released", alerts[0]["subject"])
298 +
299 + stats = bus.stats()
300 + self.assertEqual(stats["tasksReaped"], 1)
```

```
+ self.assertEqual(stats["agentsReaped"], 1)
+ self.assertIsNotNone(stats["lastSweepAt"])
+ # Counters survive a reload (persisted with the board).
+ reloaded = AgentBus(bus.path)
+ self.assertEqual(reloaded.stats()["tasksReaped"], 1)
+
+ # Export: cursor filtering keeps old activity out, open tasks stay in.
+ bus.handle({"action": "post", "agentId": builder["id"], "body": "BEFORE-MARKER", "subject": "old"})
+ cursor = bus.stats()["cursor"]
+ bus.handle({"action": "post", "agentId": builder["id"], "body": "AFTER-MARKER", "subject": "new"})
+ fresh = bus.handle({"action": "export", "since": cursor})
+ self.assertIn("AFTER-MARKER", fresh["markdown"])
+ self.assertNotIn("BEFORE-MARKER", fresh["markdown"])
+ self.assertIn("Held by a live agent", fresh["markdown"])
+
+ summary = bus.handle({"action": "export", "summaryOnly": True})
+ self.assertIn("Held by a live agent", summary["markdown"])
+ self.assertNotIn("should be released", summary["markdown"]) # detail omitted
+ self.assertIn("_No messages._", summary["markdown"])
+ self.assertLess(len(summary["markdown"]), len(bus.handle({"action": "export"})["markdown"]))
+
+ def test_mcp_prompts_render_live_bus_state(self):
+ from mcp_core import PROMPTS, get_mcp_prompt
+ names = [p["name"] for p in PROMPTS]
+ self.assertEqual(len(PROMPTS), 7)
+ for name in ("multi_agent_handoff", "bus_standup", "task_triage"):
+ self.assertIn(name, names)
+
+ self.state.bus.handle({"action": "register", "name": "Roster Probe", "role": "qa"})
+ self.state.bus.handle({"action": "task_create", "title": "Probe task", "priority": "critical"})
+ for name in ("multi_agent_handoff", "bus_standup", "task_triage"):
+ prompt = get_mcp_prompt(name, {}, self.state.mcp_client)
+ text = prompt["messages"][0]["content"]["text"]
+ self.assertIn("Roster Probe", text, name)
+ self.assertIn("Probe task", text, name)
+ self.assertTrue(prompt["description"])
+
+ # No client (or a dead bridge) must degrade to the safe fallback, never raise.
+ offline = get_mcp_prompt("bus_standup", {}, None)
+ self.assertIn("unavailable", offline["messages"][0]["content"]["text"])
+
+ # The dispatcher wires the client through prompts/get.
+ resp = self.state.mcp_dispatcher.handle_payload(
+ {"jsonrpc": "2.0", "id": 9, "method": "prompts/get",
+ "params": {"name": "task_triage", "arguments": {}}})
+ self.assertIn("Roster Probe", resp["result"]["messages"][0]["content"]["text"])
+
+ def test_named_tunnel_token_is_validated_before_spawn(self):
+ from tunnel_manager import TunnelManager, validate_named_token
+ good = "eyJhIjoiY2Y4ZjQxY2EiLCJ0IjoiYWJjZGVmIn0="
+ self.assertTrue(validate_named_token(good)[0])
+ for bad, needle in (("", "empty"), (" ", "empty"), ("short", "too short"),
+ ("has space", "whitespace"), ("https://x.trycloudflare.com", "URL"),
+ ("bad$chars$here$and$long$enough", "unexpected")):
+ ok, reason = validate_named_token(bad)
+ self.assertFalse(ok, bad)
+ self.assertIn(needle.lower(), reason.lower(), bad)
+
+ bad_mgr = TunnelManager(port=self.port, flavor="cloudflared", named_token="bad token here",
+ state_dir=self.tmp)
```

```
+ started = bad_mgr.start()
+ self.assertEqual(started["state"], "error")
+ self.assertIn("token", started["lastError"].lower())
+ self.assertFalse(started["namedTokenValid"])
+ bad_mgr.binary = "/bin/true" # even with a binary present, the token never reaches a subprocess
+ bad_mgr.flavor = "cloudflared"
+ with self.assertRaises(RuntimeError):
+ bad_mgr._command()
+
+ named = TunnelManager(port=self.port, flavor="cloudflared", named_token=good, state_dir=self.tmp,
+ name="studio.example.com")
+ named.binary, named.flavor = "/bin/true", "cloudflared"
+ cmd = named._command()
+ self.assertEqual(cmd, ["/bin/true", "tunnel", "--no-autoupdate", "run", "--token", good])
+ self.assertNotIn("--url", cmd)
+ shown = named.status()
+ self.assertTrue(shown["namedTokenValid"])
+ self.assertEqual(shown["name"], "studio.example.com")
+
+ def test_dashboard_ops_tab_is_responsive_and_eventsource_reconnects(self):
+ from server import dashboard_html
+ html = bridge_server.dashboard_html()
+ self.assertIn("copyMcpConfig", html)
+ self.assertIn("Copy MCP config (tunnel)", html)
+ self.assertIn("@media(max-width:720px)", html)
+ self.assertIn("grid-template-columns:repeat(2,minmax(0,1fr))", html)
+ self.assertIn("Reconnecting (${Math.round(wait/1000)}s)", html)
+ self.assertIn("EV_DELAY * 2", html)
+ self.assertIn("overflow-x:hidden", html)
+
+ script = re.search(r"<script>(.*?)</script>", html, re.S)
+ self.assertIsNotNone(script)
+ node = shutil.which("node")
+ if node:
+ path = os.path.join(self.tmp, "dashboard.js")
+ with open(path, "w", encoding="utf-8") as fh:
+ fh.write(script.group(1))
+ checked = subprocess.run([node, "--check", path], capture_output=True, text=True)
+ self.assertEqual(checked.returncode, 0, checked.stderr)
+
+ def test_latency_script_measures_percentiles_and_reports_auth_errors(self):
+ import http.server
+ repo = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
+ script = os.path.join(repo, "jobs", "measure_tunnel_latency.py")
+
+ class FakeBridge(http.server.BaseHTTPRequestHandler):
+ def do_POST(self):
+ length = int(self.headers.get("Content-Length") or 0)
+ self.rfile.read(length)
+ if self.headers.get("Authorization") != "Bearer good-token":
+ body = b'{"error":"unauthorized"}'
+ self.send_response(401)
+ else:
+ body = json.dumps({"id": "job-1", "status": "done", "result": {"ok": True}}).encode()
+ time.sleep(0.005)
+ self.send_response(200)
+ self.send_header("Content-Type", "application/json")
+ self.send_header("Content-Length", str(len(body)))
+ self.end_headers()
+ self.wfile.write(body)
```

```
+
+ def log_message(self, *args):
+ pass
+
+ fake = http.server.ThreadingHTTPServer(("127.0.0.1", 0), FakeBridge)
+ threading.Thread(target=fake.serve_forever, daemon=True).start()
+ base = f"http://127.0.0.1:{fake.server_address[1]}"
+ try:
+ ok = subprocess.run([sys.executable, script, "--url", f"local={base}", "--token", "good-token",
+ "--runs", "3", "--markdown"], capture_output=True, text=True, timeout=120)
+ self.assertEqual(ok.returncode, 0, ok.stderr)
+ self.assertIn("| Tool |", ok.stdout)
+ self.assertIn("ping_studio", ok.stdout)
+
+ denied = subprocess.run([sys.executable, script, "--url", f"local={base}", "--token", "nope",
+ "--runs", "2"], capture_output=True, text=True, timeout=120)
+ self.assertEqual(denied.returncode, 2)
+ self.assertIn("token rejected", denied.stderr)
+ finally:
+ fake.shutdown()
+ fake.server_close()
+
+ def test_operator_scripts_fail_loudly_without_a_studio_peer(self):
+ repo = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
+ acceptance = subprocess.run(
+ [sys.executable, os.path.join(repo, "jobs", "live_acceptance.py"),
+ "--url", self.base, "--token", self.admin_token],
+ capture_output=True, text=True, timeout=120)
+ self.assertEqual(acceptance.returncode, 1)
+ self.assertIn("no Studio peer", acceptance.stdout)
+ self.assertIn("bridge-reachable", acceptance.stdout)
+
+ drill = subprocess.run(
+ [sys.executable, os.path.join(repo, "jobs", "drill_studio_kill.py"),
+ "--url", self.base, "--token", self.admin_token, "--wait", "5"],
+ capture_output=True, text=True, timeout=120)
+ self.assertEqual(drill.returncode, 3)
+ self.assertIn("no Studio peer", drill.stderr)
+
+ # -- v5.2: maintenance pause, automatic sweeper, ops resources -----------
+
+ def test_queue_pause_holds_jobs_until_resumed(self):
+ status, paused = self._req("/api/queue/pause", method="POST",
+ body={"reason": "maintenance window"}, token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertTrue(paused["paused"])
+ self.assertEqual(paused["reason"], "maintenance window")
+
+ job, _ = self.state.enqueue_job("ping", note="during pause")
+ peer = self.state.record_poll({"peer": ["peer-pause"], "dm": ["edit"], "place": ["p"], "placeId": ["1"]})
+ self.assertIsNone(self.state.poll_for_job(peer, wait_seconds=0.2))
+ with self.state.lock:
+ self.assertEqual(self.state.jobs[job["id"]]["status"], "queued")
+
+ status, health = self._req("/api/health")
+ self.assertEqual(status, 200)
+ self.assertTrue(health["queuePaused"])
+
+ status, resumed = self._req("/api/queue/resume", method="POST", body={}, token=self.admin_token)
+ self.assertEqual(status, 200)
```

```
+        self.assertFalse(resumed["paused"])
+        claimed = self.state.poll_for_job(peer, wait_seconds=1.0)
+        self.assertIsNotNone(claimed)
+        self.assertEqual(claimed["id"], job["id"])
+
+        _, ops = self._req("/api/ops", token=self.admin_token)
+        self.assertIn("queue", ops)
+        self.assertFalse(ops["queue"]["paused"])
+        self.assertIn("sweeper", ops)
+        self.assertIn("jobLatency", ops)
+        # Pausing requires admin, not a read token.
+        reader = self.state.tokens.create("pause-reader", role="read", rate_limit=50)
+        denied = self._req("/api/queue/pause", method="POST", body={}, token=reader["token"])
+        self.assertEqual(denied[0], 403)
+
+    def test_automatic_sweeper_releases_stale_tasks_and_counts_them(self):
+        bus = self.state.bus
+        ghost = bus.handle({"action": "register", "name": "Ghost", "role": "qa"})
+        task = bus.handle({"action": "task_create", "title": "Ghost task", "createdBy": ghost["id"]})
+        bus.handle({"action": "task_claim", "taskId": task["id"], "agentId": ghost["id"]})
+        bus.agents[ghost["id"]]["lastSeen"] = time.time() - 5000
+
+        before = self.state.metrics_snapshot()["counters"]
+        swept = self.state.auto_sweep()
+        self.assertEqual(swept["tasksReaped"], 1)
+        self.assertEqual(bus.tasks[task["id"]]["status"], "todo")
+        self.assertEqual(self.state._sweeps, 1)
+        self.assertTrue(self.state._last_sweep)
+
+        metrics = self.state.metrics_snapshot()
+        names = {c["name"]: c["value"] for c in metrics["counters"]}
+        self.assertGreaterEqual(names.get("bridge_agents_reaped_total", 0), 1)
+        audit = self.state.telemetry.audit.tail(5)["entries"]
+        self.assertTrue(any(e["action"] == "bus.sweep" for e in audit))
+
+        # A quiet sweep is silent (no new alert message) and still counts a cycle.
+        bus.agents[ghost["id"]]["lastSeen"] = time.time()
+        quiet = self.state.auto_sweep()
+        self.assertEqual(quiet["tasksReaped"], 0)
+        self.assertEqual(self.state._sweeps, 2)
+        self.assertEqual(len([m for m in bus.messages if m["kind"] == "alert"]), 1)
+
+        # Latency summary surfaces per-tool percentiles once jobs have durations.
+        with self.state.lock:
+            self.state.jobs["job-lat"] = {
+                "id": "job-lat", "type": "ping_studio", "status": "done", "note": "lat",
+                "ok": True, "error": None, "result": None, "duration_ms": 42.0,
+                "created": time.time(), "finished": time.time(),
+            }
+            self.state.history.append("job-lat")
+        summary = self.state._job_latency_summary()
+        self.assertIn("ping_studio", summary)
+        self.assertEqual(summary["ping_studio"]["p50"], 42.0)
+
+    def test_bridge_ops_control_actions_and_ops_resources(self):
+        from mcp_core import MCPDispatcher, RESOURCES
+        uris = [r["uri"] for r in RESOURCES]
+        self.assertEqual(len(uris), 11)
+        self.assertIn("studio://jobs", uris)
+        self.assertIn("studio://handoff", uris)
```

```
+
+ dispatcher = MCPDispatcher(self.state.mcp_client)
+ paused = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 1, "method": "tools/call",
+ "params": {"name": "bridge_ops", "arguments": {"action": "queue_pause", "reason": "unit test"}},
+ })
+ self.assertFalse(paused["result"].get("isError"), paused)
+ self.assertTrue(self.state.queue_paused)
+ resumed = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 2, "method": "tools/call",
+ "params": {"name": "bridge_ops", "arguments": {"action": "queue_resume"}},
+ })
+ self.assertFalse(resumed["result"].get("isError"), resumed)
+ self.assertFalse(self.state.queue_paused)
+
+ self.state.bus.handle({"action": "register", "name": "Resource Probe", "role": "qa"})
+ handoff = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 3, "method": "resources/read",
+ "params": {"uri": "studio://handoff"},
+ })
+ text = handoff["result"]["contents"][0]["text"]
+ self.assertIn("# Agent handoff brief", text)
+ self.assertIn("Resource Probe", text)
+
+ jobs = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 4, "method": "resources/read",
+ "params": {"uri": "studio://jobs"},
+ })
+ payload = json.loads(jobs["result"]["contents"][0]["text"])
+ for key in ("queue", "sweeper", "health", "jobLatency", "recentJobs"):
+ self.assertIn(key, payload)
+
+ def test_cli_queue_pause_status_resume(self):
+ env = dict(os.environ, BRIDGE_URL=self.base, BRIDGE_TOKEN=self.admin_token)
+ cli = [sys.executable, str(HERE / "arena_studio.py"), "queue"]
+
+ paused = subprocess.run(cli + ["pause", "--reason", "cli smoke"], env=env,
+ capture_output=True, text=True, encoding="utf-8", timeout=30)
+ self.assertEqual(paused.returncode, 0, msg=paused.stdout + paused.stderr)
+ self.assertTrue(json.loads(paused.stdout)["paused"])
+ self.assertTrue(self.state.queue_paused)
+
+ status = subprocess.run(cli + ["status"], env=env, capture_output=True,
+ text=True, encoding="utf-8", timeout=30)
+ self.assertEqual(status.returncode, 0, msg=status.stdout + status.stderr)
+ report = json.loads(status.stdout)
+ self.assertTrue(report["queue"]["paused"])
+ self.assertEqual(report["queue"]["reason"], "cli smoke")
+ self.assertIn("sweeper", report)
+
+ resumed = subprocess.run(cli + ["resume"], env=env, capture_output=True,
+ text=True, encoding="utf-8", timeout=30)
+ self.assertEqual(resumed.returncode, 0, msg=resumed.stdout + resumed.stderr)
+ self.assertFalse(json.loads(resumed.stdout)["paused"])
+ self.assertFalse(self.state.queue_paused)
+
+ # `studios` CLI mirrors /api/studios (empty fleet here, but the shape holds).
+ studios = subprocess.run(cli[:-1] + ["studios", "list"], env=env, capture_output=True,
+ text=True, encoding="utf-8", timeout=30)
+ self.assertEqual(studios.returncode, 0, msg=studios.stdout + studios.stderr)
```

```
+ fleet = json.loads(studios.stdout)
+ self.assertEqual(fleet["count"], 0)
+ self.assertIn("studios", fleet)
+
+ # -- v5.3: multi-studio fleet, modern MCP era, tasks ----------------------
+
+ def _two_studios(self):
+ alpha = self.state.record_poll({"peer": ["peer-alpha"], "dm": ["edit"], "place": ["Alpha"],
+ "placeId": ["111"], "gameId": ["9001"], "pv": ["3.1"]})
+ beta = self.state.record_poll({"peer": ["peer-beta"], "dm": ["edit"], "place": ["Beta"],
+ "placeId": ["222"], "gameId": ["9002"], "pv": ["3.1"]})
+ return alpha, beta
+
+ def test_fleet_list_pin_routing_and_persistence(self):
+ alpha, beta = self._two_studios()
+ status, fleet = self._req("/api/studios", token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertEqual(fleet["count"], 2)
+ self.assertEqual(fleet["routing"], "auto")
+ ids = [s["peerId"] for s in fleet["studios"]]
+ self.assertEqual(ids, ["peer-alpha", "peer-beta"])
+ self.assertEqual([s["defaultTarget"] for s in fleet["studios"]], [True, False])
+
+ status, pinned = self._req("/api/studios", method="POST",
+ body={"action": "set_active", "peerId": "peer-beta"},
+ token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertEqual(pinned["active"], "peer-beta")
+
+ job, _ = self.state.enqueue_job("ping", note="pinned routing")
+ self.assertIsNone(self.state.poll_for_job(alpha, wait_seconds=0.1))
+ claimed = self.state.poll_for_job(beta, wait_seconds=0.5)
+ self.assertEqual(claimed["id"], job["id"])
+ self.state.complete_job({"id": job["id"], "ok": True, "result": {"pong": True}, "peerId": "peer-beta"})
+
+ # The pin survives a restart (fleet.json in the state dir).
+ reloaded = BridgeState(token=self.admin_token, state_dir=self.tmp)
+ try:
+ self.assertEqual(reloaded.fleet_snapshot()["pinned"], "peer-beta")
+ finally:
+ reloaded._reaper_stop.set()
+
+ # A closed pinned Studio must not stall the queue: routing falls back to auto.
+ self.state.peers["peer-beta"]["lastPoll"] = time.time() - 300
+ self.assertTrue(self.state.fleet_snapshot()["routing"] == "auto")
+ job2, _ = self.state.enqueue_job("ping", note="fallback routing")
+ self.assertIsNotNone(self.state.poll_for_job(alpha, wait_seconds=0.5))
+ self.state.complete_job({"id": job2["id"], "ok": True, "result": {}, "peerId": "peer-alpha"})
+
+ status, cleared = self._req("/api/studios", method="POST", body={"action": "clear_active"},
+ token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertIsNone(cleared["active"])
+
+ # Unknown peers are a 404, not a silent success.
+ bad = self._req("/api/studios", method="POST", body={"action": "set_active", "peerId": "nope"},
+ token=self.admin_token)
+ self.assertEqual(bad[0], 404)
+
+ def test_fleet_labels_broadcast_and_write_refusal(self):
```

```
+ _alpha, _beta = self._two_studios()
+ status, labelled = self._req("/api/studios", method="POST",
+ body={"action": "label", "peerId": "peer-beta", "label": "Beta Main"},
+ token=self.admin_token)
+ self.assertEqual(status, 200)
+ self.assertEqual(labelled["label"], "Beta Main")
+ _, fleet = self._req("/api/studios", token=self.admin_token)
+ self.assertEqual([s["label"] for s in fleet["studios"]], ["Alpha (edit)", "Beta Main"])
+
+ # Broadcast fans the job out to every online peer and collects results.
+ def serve(peer):
+ job = self.state.poll_for_job(peer, wait_seconds=3.0)
+ if job:
+ self.state.complete_job({"id": job["id"], "ok": True, "result": {"pong": peer["peerId"]},
+ "peerId": peer["peerId"]})
+
+ peers = [self.state.peers["peer-alpha"], self.state.peers["peer-beta"]]
+ threads = [threading.Thread(target=serve, args=(p,), daemon=True) for p in peers]
+ for th in threads:
+ th.start()
+ status, result = self._req("/api/studios", method="POST",
+ body={"action": "broadcast", "type": "ping", "timeout": 8},
+ token=self.admin_token)
+ for th in threads:
+ th.join(timeout=5)
+ self.assertEqual(status, 200)
+ self.assertEqual(result["peers"], 2)
+ self.assertEqual(result["succeeded"], 2)
+ self.assertEqual({r["peerId"] for r in result["results"]}, {"peer-alpha", "peer-beta"})
+ self.assertEqual(result["results"][0]["result"]["pong"], "peer-alpha")
+
+ # Mutating kinds are refused - a broadcast must never edit every place.
+ with self.assertRaises(ValueError):
+ self.state.broadcast(kind="write_script", payload={}, timeout=1)
+ refused = self._req("/api/studios", method="POST",
+ body={"action": "broadcast", "type": "write_script", "timeout": 1},
+ token=self.admin_token)
+ self.assertEqual(refused[0], 400)
+
+ def test_fleet_mcp_tool_and_resource(self):
+ self._two_studios()
+ from mcp_core import MCPDispatcher
+ dispatcher = MCPDispatcher(self.state.mcp_client)
+ listed = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 1, "method": "tools/call",
+ "params": {"name": "studio_fleet", "arguments": {"action": "list"}},
+ })
+ self.assertFalse(listed["result"]["isError"], listed)
+ structured = listed["result"]["structuredContent"]
+ self.assertEqual(structured["count"], 2)
+
+ pinned = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 2, "method": "tools/call",
+ "params": {"name": "studio_fleet", "arguments": {"action": "set_active", "peerId": "peer-alpha"}},
+ })
+ self.assertEqual(pinned["result"]["structuredContent"]["active"], "peer-alpha")
+
+ resource = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 3, "method": "resources/read",
+ "params": {"uri": "studio://studios"},
```

```
+ })
+ payload = json.loads(resource["result"]["contents"][0]["text"])
+ self.assertEqual(payload["count"], 2)
+ self.assertEqual(payload["pinned"], "peer-alpha")
+
+ # Broadcast through MCP with a write-only tool name is rejected.
+ bad = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 4, "method": "tools/call",
+ "params": {"name": "studio_fleet", "arguments": {"action": "broadcast", "broadcastTool": "script_read",
+ "timeout": 1}},
+ })
+ self.assertTrue(bad["result"]["isError"])
+ self.assertIn("path", bad["result"]["content"][0]["text"])
+
+ def test_modern_mcp_era_discover_resulttype_and_headers(self):
+ from mcp_core import MCPDispatcher, MODERN_PROTOCOL_VERSION
+ dispatcher = MCPDispatcher(self.state.mcp_client)
+ discover = dispatcher.handle_payload({"jsonrpc": "2.0", "id": 1, "method": "server/discover"})
+ result = discover["result"]
+ self.assertIn(MODERN_PROTOCOL_VERSION, result["supportedVersions"])
+ self.assertIn("tasks", result["capabilities"])
+ self.assertEqual(result["serverInfo"]["name"], "arena-roblox-studio-mcp")
+
+ # Version travels per request in _meta; unknown versions get -32022.
+ rejected = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 2, "method": "tools/list",
+ "_meta": {"io.modelcontextprotocol/protocolVersion": "2019-01-01"},
+ })
+ self.assertEqual(rejected["error"]["code"], -32022)
+ self.assertIn("supportedVersions", rejected["error"]["data"])
+
+ modern = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 3, "method": "tools/list",
+ "_meta": {"io.modelcontextprotocol/protocolVersion": MODERN_PROTOCOL_VERSION},
+ })
+ self.assertEqual(modern["result"]["resultType"], "complete")
+ self.assertEqual(modern["result"]["ttlMs"], 60000)
+ self.assertEqual(modern["result"]["cacheScope"], "private")
+
+ legacy = dispatcher.handle_payload({"jsonrpc": "2.0", "id": 4, "method": "tools/list"})
+ self.assertNotIn("resultType", legacy["result"])
+
+ # Over HTTP the version can ride in MCP-Protocol-Version and the routing
+ # headers must agree with the body (-32020 when they do not).
+ req = urllib.request.Request(
+ self.base + "/mcp",
+ data=json.dumps({"jsonrpc": "2.0", "id": 5, "method": "tools/list"}).encode(),
+ headers={"Authorization": f"Bearer {self.admin_token}",
+ "Content-Type": "application/json",
+ "MCP-Protocol-Version": MODERN_PROTOCOL_VERSION},
+ method="POST",
+ )
+ with urllib.request.urlopen(req, timeout=20) as resp:
+ payload = json.loads(resp.read().decode())
+ self.assertEqual(payload["result"]["resultType"], "complete")
+
+
+ mismatch = urllib.request.Request(
+ self.base + "/mcp",
+ data=json.dumps({"jsonrpc": "2.0", "id": 6, "method": "tools/list"}).encode(),
```

```
+ headers={"Authorization": f"Bearer {self.admin_token}",
+ "Content-Type": "application/json",
+ "Mcp-Method": "tools/call"},
+ method="POST",
+ )
+ try:
+ urllib.request.urlopen(mismatch, timeout=20)
+ self.fail("expected -32020 for a Mcp-Method/body mismatch")
+ except urllib.error.HTTPError as exc:
+ body = json.loads(exc.read().decode())
+ self.assertEqual(exc.code, 400)
+ self.assertEqual(body["error"]["code"], -32020)
+
+ def test_mcp_tasks_lifecycle(self):
+ from mcp_core import MCPDispatcher
+ dispatcher = MCPDispatcher(self.state.mcp_client)
+ created = dispatcher.handle_payload({
+ "jsonrpc": "2.0", "id": 1, "method": "tools/call",
+ "params": {"name": "studio_fleet", "arguments": {"action": "list"},
+ "task": {"ttl": 60000}},
+ })
+ task = created["result"]
+ self.assertEqual(task["resultType"], "task")
+ self.assertTrue(task["taskId"].startswith("task-"))
+ self.assertEqual(task["status"], "working")
+ self.assertEqual(task["pollIntervalMs"], 1000)
+
+ deadline = time.time() + 10
+ status = "working"
+ while time.time() < deadline:
+ got = dispatcher.handle_payload({"jsonrpc": "2.0", "id": 2, "method": "tasks/get",
+ "params": {"taskId": task["taskId"]}})
+ status = got["result"]["status"]
+ if status in ("completed", "failed"):
+ break
+ time.sleep(0.05)
+ self.assertEqual(status, "completed")
+
+ result = dispatcher.handle_payload({"jsonrpc": "2.0", "id": 3, "method": "tasks/result",
+ "params": {"taskId": task["taskId"], "timeoutMs": 5000}})
+ payload = result["result"]
+ self.assertEqual(payload["_meta"]["io.modelcontextprotocol/related-task"]["taskId"], task["taskId"])
+ self.assertFalse(payload["isError"])
+ self.assertTrue(payload["structuredContent"]["studios"] == [])
+
+ listing = dispatcher.handle_payload({"jsonrpc": "2.0", "id": 4, "method": "tasks/list"})
+ self.assertEqual(len(listing["result"]["tasks"]), 1)
+
+ unknown = dispatcher.handle_payload({"jsonrpc": "2.0", "id": 5, "method": "tasks/get",
+ "params": {"taskId": "task-nope"}})
+ self.assertEqual(unknown["error"]["code"], -32602)
+
+ # A cancelled task reports cancelled and keeps its terminal state.
+ cancelled = dispatcher.handle_payload({"jsonrpc": "2.0", "id": 6, "method": "tasks/cancel",
+ "params": {"taskId": task["taskId"]}})
+ self.assertEqual(cancelled["result"]["status"], "completed") # finished tasks are untouched
+
+ tools = dispatcher.handle_payload({"jsonrpc": "2.0", "id": 7, "method": "tools/list"})
+ self.assertEqual(tools["result"]["tools"][0]["execution"]["taskSupport"], "optional")
+
```

```
+ def test_dashboard_fleet_strip_motion_and_health_fields(self):
+ html = self.state.dashboard_html() if hasattr(self.state, "dashboard_html") else None
+ if html is None:
+ from server import dashboard_html
+ html = bridge_server.dashboard_html()
+ for needle in ("fleet-bar", "fleet-chips", "studio-card", "broadcastPing",
+ "prefers-reduced-motion", "animateValue", "paneIn", "brand"):
+ self.assertIn(needle, html)
+ status, health = self._req("/api/health")
+ self.assertEqual(status, 200)
+ self.assertIn("studios", health)
+ self.assertEqual(health["studios"]["count"], 0)
+ self.assertIn("protocolVersions", self._req("/api/ops", token=self.admin_token)[1]["mcp"])
+
+ # -- v5.3.2: the "tunnel page looks frozen" trap --------------------------
+
+ def test_dashboard_needs_token_off_loopback_and_says_so(self):
+ """A dashboard opened through a tunnel/LAN address gets no token from
+ /api/local-boot, so every /api call 401s. The page must surface that
+ instead of silently keeping stale numbers."""
+ html = bridge_server.dashboard_html()
+ self.assertIn("auth-banner", html)
+ self.assertIn("saveToken", html)
+ self.assertIn("apiFetch", html)
+ self.assertIn("PAGE_VERSION", html)
+ self.assertNotIn("__BRIDGE_VERSION__", html)
+ self.assertIn(f'PAGE_VERSION = "{bridge_server.VERSION}"', html)
+
+ # Loopback: the token is handed out so the page authenticates itself.
+ req = urllib.request.Request(self.base + "/api/local-boot")
+ with urllib.request.urlopen(req, timeout=15) as resp:
+ boot = json.loads(resp.read().decode())
+ self.assertTrue(boot["local"])
+ self.assertEqual(boot["token"], self.admin_token)
+
+ # Tunnel / LAN: a forwarded client address is never loopback.
+ proxied = urllib.request.Request(self.base + "/api/local-boot",
+ headers={"CF-Connecting-IP": "203.0.113.9"})
+ with urllib.request.urlopen(proxied, timeout=15) as resp:
+ boot_remote = json.loads(resp.read().decode())
+ self.assertFalse(boot_remote["local"])
+ self.assertEqual(boot_remote["token"], "")
+ self.assertTrue(boot_remote["tokenRequired"])
+
+ # And the API really does refuse that page until a token is supplied.
+ state_proxied = urllib.request.Request(self.base + "/api/state",
+ headers={"CF-Connecting-IP": "203.0.113.9"})
+ with self.assertRaises(urllib.error.HTTPError) as denied:
+ urllib.request.urlopen(state_proxied, timeout=15)
+ self.assertEqual(denied.exception.code, 401)
+ authed = urllib.request.Request(self.base + "/api/state",
+ headers={"CF-Connecting-IP": "203.0.113.9",
+ "Authorization": f"Bearer {self.admin_token}"})
+ with urllib.request.urlopen(authed, timeout=15) as resp:
+ self.assertEqual(resp.status, 200)
+
+ def test_setup_dry_run_explains_the_tunnel_plan(self):
+ import setup as bridge_setup
+ cmd = ["python", "server.py", "--port", "8077"]
+ supervised = "\n".join(line for line, _ in
```

```
+ bridge_setup.describe_launch(cmd, True, "auto", None, 8077))
+ self.assertIn("Dry run", supervised)
+ self.assertIn("supervised auto", supervised)
+ self.assertIn("http://127.0.0.1:8077", supervised)
+
+ local_only = "\n".join(line for line, _ in
+ bridge_setup.describe_launch(cmd, False, "auto", None, 8077))
+ self.assertIn("not requested", local_only)
+
+ external = "\n".join(line for line, _ in
+ bridge_setup.describe_launch(cmd, False, "auto", "https://x.example", 8077))
+ self.assertIn("external https://x.example", external)
+
+ def test_tunnel_connect_script_verifies_a_live_endpoint(self):
+ """jobs/tunnel_connect.py is the one-command "is my tunnel working?" check."""
+ wave = Path(self.tmp) / "wave.json"
+ wave.write_text(json.dumps({"name": "test wave", "tasks": [
+ {"title": "HX - first verification task", "priority": "high", "tags": ["test"],
+ "detail": "unit test task"},
+ {"title": "HX - second verification task", "priority": "low", "detail": "unit test task"},
+ ]}), encoding="utf-8")
+ evidence = Path(self.tmp) / "connect.json"
+ script = str(HERE.parent / "jobs" / "tunnel_connect.py")
+
+ first = subprocess.run(
+ [sys.executable, "-B", script, "--url", self.base, "--token", self.admin_token,
+ "--seed-tasks", str(wave), "--json-out", str(evidence)],
+ capture_output=True, text=True, encoding="utf-8", timeout=120,
+ )
+ self.assertEqual(first.returncode, 0, msg=first.stdout + first.stderr)
+ rows = {r["step"]: r["status"] for r in json.loads(evidence.read_text())["rows"]}
+ for step in ("health", "mcp-discovery", "mcp-initialize", "tools/list",
+ "resources/list", "prompts/list", "studio_fleet", "seed-tasks"):
+ self.assertEqual(rows.get(step), "pass", f"{step} -> {rows.get(step)}")
+ # No Studio peer in this fixture: those steps must skip, not fail.
+ self.assertEqual(rows.get("get_studio_state"), "skipped")
+ self.assertEqual(rows.get("ping_studio"), "skipped")
+ self.assertIn("71 tools", first.stdout)
+
+ board = self._req("/api/bus?action=tasks&includeDone=1", token=self.admin_token)[1]
+ titles = [t["title"] for t in board["tasks"]]
+ self.assertIn("HX - first verification task", titles)
+ self.assertEqual(len(titles), 2)
+
+ # Re-running is idempotent by title.
+ second = subprocess.run(
+ [sys.executable, "-B", script, "--url", self.base, "--token", self.admin_token,
+ "--seed-tasks", str(wave)],
+ capture_output=True, text=True, encoding="utf-8", timeout=120,
+ )
+ self.assertEqual(second.returncode, 0, msg=second.stdout + second.stderr)
+ self.assertIn("0 created · 2 already present", second.stdout)
+ self.assertEqual(len(self._req("/api/bus?action=tasks&includeDone=1",
+ token=self.admin_token)[1]["tasks"]), 2)
+
+ # Distinct failure signals: wrong token -> 2, unreachable host -> 3.
+ bad = subprocess.run(
+ [sys.executable, "-B", script, "--url", self.base, "--token", "not-the-token"],
+ capture_output=True, text=True, encoding="utf-8", timeout=60,
+ )
```

```
961 + self.assertEqual(bad.returncode, 2, msg=bad.stdout + bad.stderr)
962 + self.assertIn("token rejected", bad.stdout)
963 +
964 + dead = subprocess.run(
965 + [sys.executable, "-B", script, "--url", "http://127.0.0.1:9", "--token", "x"],
966 + capture_output=True, text=True, encoding="utf-8", timeout=60,
967 + )
968 + self.assertEqual(dead.returncode, 3, msg=dead.stdout + dead.stderr)
969 + self.assertIn("never reached", dead.stdout)
970 +
971 + # -- tunnel supervisor ------------------------------------------------
972 +
973 + def test_tunnel_supervisor_scrapes_url_and_restarts(self):
974 + from tunnel_manager import TunnelManager
975 + fake = os.path.join(self.tmp, "fake-cloudflared")
976 + with open(fake, "w", encoding="utf-8") as fh:
977 + fh.write(
978 + "#!/usr/bin/env python3\n"
979 + "import sys, time\n"
980 + "print('INF Requesting new quick Tunnel...', flush=True)\n"
981 + "print('INF | https://unit-test-tunnel.trycloudflare.com |', flush=True)\n"
982 + "time.sleep(30)\n"
983 + )
984 + os.chmod(fake, 0o755)
985 + tunnel = TunnelManager(port=self.port, binary=fake, flavor="cloudflared",
986 + state_dir=self.tmp, health_interval=3600)
987 + try:
988 + started = tunnel.start()
989 + self.assertIn(started["state"], ("starting", "online"))
990 + for _ in range(60):
991 + if tunnel.status()["state"] == "online":
992 + break
993 + time.sleep(0.1)
994 + status = tunnel.status()
995 + self.assertEqual(status["state"], "online")
996 + self.assertEqual(status["publicUrl"], "https://unit-test-tunnel.trycloudflare.com")
997 + self.assertEqual(status["mcpEndpoint"], "https://unit-test-tunnel.trycloudflare.com/mcp")
998 + self.assertTrue(status["running"])
999 + stopped = tunnel.stop()
1000 + self.assertEqual(stopped["state"], "stopped")
1001 + finally:
1002 + tunnel.stop()
1003 +
1004 + # Named Cloudflare tunnels use `run --token`, never a quick-tunnel `--url`.
1005 + named = TunnelManager(port=self.port, binary=fake, flavor="cloudflared",
1006 + named_token="eyJhIjoiY2Y4ZjQxY2EiLCJ0IjoiYWJjZGVmIn0=", state_dir=self.tmp)
1007 + named._detect()
1008 + cmd = named._command()
1009 + self.assertIn("run", cmd)
1010 + self.assertIn("--token", cmd)
1011 + self.assertNotIn("--url", cmd)
1012 + self.assertNotIn("http://127.0.0.1", " ".join(cmd))
1013 + self.assertTrue(named.status()["named"])
1014 +
1015 + # No binary -> explicit unavailable state with install hints, never a crash.
1016 + with mock.patch("tunnel_manager.find_tunnel_binary", return_value=(None, None)):
1017 + missing = TunnelManager(port=self.port, state_dir=self.tmp)
1018 + result = missing.start()
1019 + self.assertEqual(result["state"], "unavailable")
1020 + self.assertIn("cloudflared", result["lastError"])
```

```
+ self.assertTrue(result["installHints"])
+
+
def _free_port() -> int:
with socket.socket(socket.AF_INET, socket.SOCK_STREAM) as s:
s.bind(("127.0.0.1", 0))
@@ -141,14 +1141,14 @@ class TestV4RegressionFixtures(unittest.TestCase):
self.assertFalse(any(x["code"] == "reset_on_spawn_enabled" for x in report["issues"]))

def test_missing_live_peer_fast_fails(self):
- state = BridgeState()
+ state = BridgeState(state_dir=tempfile.mkdtemp(prefix="arena-state-"))
client = BridgeClient(direct_dispatch=state.direct_dispatch)
job = client.submit_job("inspect", {"path": "Workspace"}, wait=60, dm="edit")
self.assertEqual(job["status"], "error")
self.assertEqual(job["reason"], "no_peer")

def test_offline_renderer_accepts_exported_tree_without_peer(self):
- state = BridgeState()
+ state = BridgeState(state_dir=tempfile.mkdtemp(prefix="arena-state-"))
client = BridgeClient(direct_dispatch=state.direct_dispatch)
tree = {"name": "Workspace", "className": "Workspace", "children": [{
"name": "OfflinePart", "className": "Part", "structuredProperties": {
@@ -189,9 +1189,9 @@ class TestV4RegressionFixtures(unittest.TestCase):
from unittest.mock import patch
with tempfile.TemporaryDirectory() as folder:
with patch.object(bridge_server, "SNAPSHOT_DIR", Path(folder)):
- first = BridgeState()
+ first = BridgeState(state_dir=folder)
saved = first.handle_snapshots({"action": "save", "label": "named-baseline", "root": "ServerStorage", "scripts": [{"path": "ServerStorage.A", "source": "return 1"}]})
- second = BridgeState()
+ second = BridgeState(state_dir=folder)
got = second.handle_snapshots({"action": "get", "id": saved["id"]})
self.assertEqual(got["label"], "named-baseline")
self.assertEqual(got["scripts"][0]["path"], "ServerStorage.A")
@@ -238,11 +1238,13 @@ class TestEndToEndBridgeAndMCP(unittest.TestCase):
cls.port = _free_port()
cls.token = "test-secret-token-v3"
cls.base_url = f"http://127.0.0.1:{cls.port}"
+ cls.state_dir = tempfile.mkdtemp(prefix="arena-e2e-state-")
cls.httpd, cls.state = create_http_server(
host="127.0.0.1",
port=cls.port,
token=cls.token,
read_only=False,
+ state_dir=cls.state_dir,
)
cls.server_thread = threading.Thread(target=cls.httpd.serve_forever, daemon=True)
cls.server_thread.start()
@@ -356,10 +1358,35 @@ class TestEndToEndBridgeAndMCP(unittest.TestCase):
], auth_mode="query")
self.assertEqual(st_b, 200)
self.assertEqual(len(batch_resp), 3)
- self.assertEqual(len(batch_resp[1]["result"]["resources"]), 5)
- self.assertEqual(len(batch_resp[2]["result"]["prompts"]), 4)
+ self.assertEqual(len(batch_resp[1]["result"]["resources"]), 11)
+ self.assertEqual(len(batch_resp[2]["result"]["prompts"]), 7)

def test_02_all_core_studio_tools_end_to_end(self):
+ # 0. v5 bridge-level tools (no Studio peer required)
```

```
+ reg = self.call_tool("agent_bus", {"action": "register", "name": "pytest-agent", "role": "qa"})
+ self.assertTrue(reg["online"])
+ posted = self.call_tool("agent_bus", {"action": "post", "agentId": reg["id"], "subject": "test", "body": "hello bus"})
+ self.assertTrue(posted["id"].startswith("msg-"))
+ task = self.call_tool("agent_bus", {"action": "task_create", "title": "v5 smoke", "agentId": reg["id"], "priority": "high"})
+ self.assertEqual(task["status"], "todo")
+ claimed = self.call_tool("agent_bus", {"action": "task_claim", "taskId": task["id"], "agentId": reg["id"]})
+ self.assertEqual(claimed["status"], "in_progress")
+ done = self.call_tool("agent_bus", {"action": "task_complete", "taskId": task["id"], "agentId": reg["id"], "result": "ok"})
+ self.assertEqual(done["status"], "done")
+ ops = self.call_tool("bridge_ops", {"action": "status"})
+ self.assertEqual(ops["version"], "5.3.2")
+ self.assertIn("tunnel", ops)
+ metrics = self.call_tool("bridge_ops", {"action": "metrics"})
+ self.assertIn("counters", metrics)
+ verify = self.call_tool("bridge_ops", {"action": "audit_verify"})
+ self.assertTrue(verify["ok"])
+ fleet = self.call_tool("studio_fleet", {"action": "list"})
+ self.assertGreaterEqual(fleet["count"], 1)
+ self.assertTrue(fleet["studios"][0]["defaultTarget"])
+ relabelled = self.call_tool("studio_fleet", {"action": "label", "peerId": fleet["studios"][0]["peerId"],
+ "label": "Primary Edit"})
+ self.assertEqual(relabelled["label"], "Primary Edit")
+
# 1. Session & Peers
st = self.call_tool("get_studio_state")
self.assertTrue(st["studioConnected"])

```

roblox-bridge/mcp_server.py (diff)

13 lines

Version banner

```
diff --git a/roblox-bridge/mcp_server.py b/roblox-bridge/mcp_server.py
index ddbd02b..310a2c6 100644
--- a/roblox-bridge/mcp_server.py
+++ b/roblox-bridge/mcp_server.py
@@ -1,7 +1,7 @@
#!/usr/bin/env python3
"""
mcp_server.py - Standalone Model Context Protocol (MCP) stdio server for
-Roblox Studio (v4.0.0).
+Roblox Studio (v5.3.2).

Works out-of-the-box with Claude Code, Claude Desktop, Cursor, Codex CLI,
VS Code Copilot, Windsurf, Zed, Cline, and any standard MCP host.

```

roblox-bridge/ab.ps1 (diff)

22 lines

Version banner + ops examples

```
diff --git a/roblox-bridge/ab.ps1 b/roblox-bridge/ab.ps1
index 0391b83..a0e2850 100644
--- a/roblox-bridge/ab.ps1
+++ b/roblox-bridge/ab.ps1
@@ -1,4 +1,4 @@
-# HANDS MODE & CLI helper for Windows PowerShell (v4.0.0).
+# HANDS MODE & CLI helper for Windows PowerShell (v5.3.2).
# Reads BRIDGE_TOKEN from bridge.token next to this script (or auto-recovers
# from installed ArenaBridge.lua in %LOCALAPPDATA%\Roblox\Plugins!) so tokens
# never appear in shell history. Enforces UTF-8 so em-dashes & symbols are never
@@ -12,6 +12,11 @@
# .\ab.ps1 drift ..\nightloop\src ServerScriptService.NightLoop
# .\ab.ps1 sync ..\nightloop\src ServerScriptService.NightLoop
# .\ab.ps1 runfile ..\jobs\baseline_survey.lua
+# .\ab.ps1 ops # peers + queue + tunnel + agents + tasks
+# .\ab.ps1 tunnel status
+# .\ab.ps1 bus tasks
+# .\ab.ps1 metrics --prometheus
+# .\ab.ps1 audit --verify

param([Parameter(ValueFromRemainingArguments = $true)][string[]]$Cmd)


```

6. Verification snapshot

The v5 suite exercises the new surface end-to-end against the stateful mock Studio and a fake tunnel binary. Live Studio acceptance (real peer + real public tunnel) is still open and is tracked as G7/G8 in the task PDF.

```
b51d35c v5.3.1: explain the frozen console (auth/version banners) and the no-tunnel case (--dry-run, preflight, failure reporting)
 AGENTS.md                                |    2 +-
 CONNECT.md                               |    2 +-
 SESSION.md                               |   13 +-
 handoff/GEMINI-4-ARGON.md                |    4 +-
 handoff/Gemini-4-Argon-Tasks.pdf         |   50 +-
 handoff/Tunneling-v5-Code.pdf            | 1157 ++++++++++++++++-------------
 roblox-bridge/CHANGELOG.md               |   41 +
 roblox-bridge/README.md                  |    6 +-
 roblox-bridge/ab.ps1                     |    2 +-
 roblox-bridge/arena_studio.py            |    2 +-
 roblox-bridge/auth_core.py               |    2 +-
 roblox-bridge/bus_core.py                |    2 +-
 roblox-bridge/docs/OPS.md                |   45 +-
 roblox-bridge/mcp_core.py                |    4 +-
 roblox-bridge/mcp_server.py              |    2 +-
 roblox-bridge/server.py                  |  120 ++--
 roblox-bridge/setup.py                   |   62 +-
 roblox-bridge/telemetry.py               |    2 +-
 roblox-bridge/test_bridge_mcp.py         |   67 +-
 roblox-bridge/tools/build_handoff_pdfs.py |   16 +-
 roblox-bridge/tunnel_manager.py          |    2 +-
 21 files changed, 1005 insertions(+), 598 deletions(-)
```