COMP 7003
Introduction to Information and Network Security

Assignment-02

User Guide

Anmol Mittal
A01397754
February 2nd, 2025
Course Reference Number (CRN): 91662

Purpose

The purpose of the program is to capture and analyze network traffic at the packet level using Python and Scapy. It will filter packets by protocol (Ethernet, IPv4, ICMP, TCP, UDP, DNS, IPv6, ICMPv6), convert raw packet data into hexadecimal dumps, and parse the packet headers to extract and display key fields such as source/destination MAC and IP addresses, protocol-specific details, and port numbers. The program aims to provide a clear, structured, and human-readable output of packet information.

Installation

Navigate to https://learn.bcit.ca. Download COMP7003-assign02-v1.zip and Extract the contents.

Requirements

```
Need Scapy installed.
```

Building

```
No building required
```

Running

```
sudo python3 main.py -i <interface> -f <filter> -c <count>
```

Command Line Arguments

The following configuration values can be set in <file>:

main.py

Variable	Purpose
<-i> or <--interface>	Specifies the network interface to capture packets on. (Default: any)
<-f> or <--filter>	Specifies the BPF to apply. Common filters include tcp, udp, icmp, arp, ip, ip6, icmp6, and dns.
<-c> or <--count>	Specifies the number of packets to capture. (Default: 1)

Examples

main.py

```
anmol@anmols-x1:~/Documents/BCIT/comp-7003-a2/source$ sudo python3 main.py -i any -c 1 -f udp
Available interfaces: ['lo', 'enp0s31f6', 'wlp2s0']
Starting packet capture on wlp2s0
Starting packet capture on wlp2s0 with filter: udp

Captured Packet 1:
================================================================================================
01005e0000fb0a10c7ff82f808004500016bb5760000ff1119150a0000fbe00000fb14e914e901571ef3000084
0000000004000000040144013101430141013901420133013301430132013301440135013001430130013001300
0130013001300130013001300130013001300130013001300130013801450146036970360461727061000000c8001000011
94000c0469506164056c6f63616c0003323531013001300231300769 6e2d61646472c050000c80010000119400
02c0600132013501380130014501370143013901460131014201340142014201340130013001300146013300138
0138013701350138013001440133013401300136013 2c04c000c8001000011940002c0600146013801340145 01
3001300130013001300130013001300130013001300130c0ab000c8001000011940002c060c00c002f800100001194
0006c00c00020008c06c002f8001000011940006c06c00020008c08d002f8001000011940006c08d00020008c0
db002f8001000011940006c0db00020008
================================================================================================
                                  Parsing Ethernet Header
------------------------------------------------------------------------------------------------
Ethernet Header:
  Destination MAC:            01005e0000fb          | 01:00:5e:00:00:fb
  Source MAC:                 0a10c7ff82f8          | 0a:10:c7:ff:82:f8
  EtherType:                  0800                  | 2048

                                    Parsing IPv4 Header
------------------------------------------------------------------------------------------------
IPv4 Header:
  Version                     4                     | 4
  Header Length               5                     | 5
  Total Length                016b                  | 363
  Identification              b576                  | 46454
  Flags & Frag Offset         0000                  | 0b0000000000000000
    Reserved Bit:             0
    DF (Do not Fragment):     0
    MF (More Fragments):      0
    Fragment Offset:          0x0                   | 0
  Protocol                    11                    | 17
  Source IP                   0a0000fb              | 10.0.0.251
  Destination IP              e00000fb              | 224.0.0.251

                                    Parsing UDP Header
------------------------------------------------------------------------------------------------
UDP Header:
  Source Port                 14e9                  | 5353
  Destination Port            14e9                  | 5353
  Length                      0157                  | 343
  Checksum                    1ef3                  | 7923
----------------------------------------UDP Payload-----------------------------------------
0000840000000004000000040144013101430141013901420133013301430132013301440135013001430130013001
3001300130013001300130013001300130013001300130013001300130013801450146036970360461727061000000c8001
00001194000c0469506164056c6f63616c0003323531013001300231300769 6e2d61646472c050000c80010000
11940002c0600132013501380130014501370143013901460131014201340142014201340130013001300146013
3301380138013701350138013001440133013401300136013 2c04c000c8001000011940002c060014601380134
0145013001300130013001300130013001300130013001300130c0ab000c8001000011940002c060c00c002f800100
0011940006c00c00020008c06c002f8001000011940006c06c00020008c08d002f8001000011940006c08d0002
0008c0db002f8001000011940006c0db00020008
================================================================================================
Packet capture completed on wlp2s0.
anmol@anmols-x1:~/Documents/BCIT/comp-7003-a2/source$
```

```
anmol@anmols-x1:~/Documents/BCIT/comp-7003-a2/source$ sudo python3 main.py -i any -c 1 -f arp
Available interfaces: ['lo', 'enp0s31f6', 'wlp2s0']
Starting packet capture on wlp2s0
Starting packet capture on wlp2s0 with filter: arp

Captured Packet 1:
================================================================================
3c6aa73525aac4509c85928f08060001080006040001c4509c85928f0a0000010000000000000a000047
================================================================================
                              Parsing Ethernet Header
--------------------------------------------------------------------------------
Ethernet Header:
  Destination MAC:          3c6aa73525aa         | 3c:6a:a7:35:25:aa
  Source MAC:               c4509c85928f         | c4:50:9c:85:92:8f
  EtherType:                0806                 | 2054

                                   Parsing ARP Header
--------------------------------------------------------------------------------
ARP Header:
  Hardware Type:            0001                 | 1
  Protocol Type:            0800                 | 2048
  Hardware Size:            06                   | 6
  Protocol Size:            04                   | 4
  Operation:                0001                 | 1
  Sender MAC:               c4509c85928f         | c4:50:9c:85:92:8f
  Sender IP:                0a000001             | 10.0.0.1
  Target MAC:               000000000000         | 00:00:00:00:00:00
  Target IP:                0a000047             | 10.0.0.71
================================================================================
Packet capture completed on wlp2s0.
anmol@anmols-x1:~/Documents/BCIT/comp-7003-a2/source$
```