

C++

compilador

g++

entrada e saída de dados

```
#include <stdio.h>
```

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    printf("Olá\n");
```

```
}
```

```
#include <iostream>
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá" << std::endl;
```

```
}
```



```
#include <iostream>
```

```
int main()  
{  
    std::cout << "Olá" << std::endl;  
}
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá" << std::endl;
```

```
}
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá" << std::endl;
```

```
}
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá" << std::endl;
```

```
}
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá" << "\n";
```

```
}
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá\n";
```

```
}
```

POO

Programação Orientada a Objetos

struct

```
struct Gato
{
    std::string nome;
    int idade;
};
```

class

```
class Gato
{
    std::string nome;
    int idade;

    public:
    void miar()
    {
        std::cout << "miau\n";
    }
};
```

```
class Gato
{
    std::string nome = " ";
    int idade = 0;

    public:
    void miar()
    {
        std::cout << "miau\n";
    }
};
```

operator overload

```
class Gato
{
    public:
    void operator<()
    {
        std::cout << "miau :3\n";
    }

};
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá\n";
```

```
}
```



```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá\n";
```

```
}
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout.operator<<("Olá\n");
```

```
}
```

namespaces

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá\n";
```

```
}
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Olá\n";
```

```
}
```

```
using namespace std;
```

entrada de dados

```
#include <cs50.h>
```



```
#include <stdio.h>
```

```
#include <cs50.h>
```

```
int main()
```

```
{
```

```
    string nome = get_string("Digite seu nome: ");
```

```
    printf("Olá, %s\n", nome);
```

```
}
```

```
#include <iostream>
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Digite seu nome: ";
```

```
    std::string nome;
```

```
    std::cin >> nome;
```

```
    std::cout << "Olá, " << nome << "\n";
```

```
}
```

```
#include <iostream>
```

```
int main()
```

```
{
```

```
    std::cout << "Digite seu nome: ";
```

```
    std::string nome;
```

```
    std::cin >> nome;
```

```
    std::cout << "Olá, " << nome << "\n";
```

```
}
```

arrays

```
int nums[5];  
nums[0] = 7;  
nums[1] = 90;
```

vectors

```
#include <vector>
```

```
int main()
```

```
{
```

```
    std::vector<int> nums;
```

```
    nums.push_back(
```

```
}
```


