

16 December 2021 08:07

18 Jan 2022 uploaded to <https://github.com/CluedIn-io/ImpTools/tree/master/k8/apline>

To enable user creation using an internal resource (rather than Postman etc).

Login to cluedin instance UI as admin and obtain bearer token

[illegible]

Create interactive shell session with a new temporary debug pod

```
kubectrl run -i --tty --rm debug --image=alpine --restart=Never -- sh
```

You are now connected to the pod and can run commands

in powershell

```
PS > kubectl get services | FindStr 9000
cluedin-demo-cluedin          ClusterIP      10.0.68.113   <none>        9000/TCP,9001/TCP,9003/TCP,9006/TCP,9007/TCP,9013/TCP 7d10h
```

In this case `cluedin-demo-cluedin` is the service name that is running on port 9000, yours will vary depending on what names were given during creation of the cluster.

Install curl

in the pod interactive shell session

```
/ # apk --no-cache add curl
```

test access to cluedin server

```
/ # curl http://cluedin-demo-cluedin:9000/health/liveness && echo
OK
```

test cluedin server status - expect all ServiceStatus to be Green... otherwise you need to fix your cluster before continuing

```
/ # apk --no-cache add jq
/ # curl http://cloudein-demo-cloudein:9000/status | jq
```

```
{
  "ServiceStatus": "Green",
  "UpdatedDate": "2021-12-15T22:49:06.9713766+00:00",
  "DataShards": [
    {
      "Type": "Blob",
      "ServiceStatus": "Green"
    },
    {
      "Type": "Configuration",
      "ServiceStatus": "Green"
    }
  ]
}
```

```
{
  "Type": "Data",
  "ServiceStatus": "Green"
},
{
  "Type": "Search",
  "ServiceStatus": "Green"
},
{
  "Type": "Graph",
  "ServiceStatus": "Green"
},
{
  "Type": "Metrics",
  "ServiceStatus": "Green"
}
],
"Components": [
  {
    "Type": "Api",
    "ServiceStatus": "Green"
  },
  {
    "Type": "Authentication",
    "ServiceStatus": "Green"
  },
  {
    "Type": "Crawling",
    "ServiceStatus": "Green"
  },
  {
    "Type": "Scheduling",
    "ServiceStatus": "Green"
  },
  {
    "Type": "ServiceBus",
    "ServiceStatus": "Green"
  },
  {
    "Type": "System",
    "ServiceStatus": "Green"
  }
]
}
#
```

Define TOKEN in the console/shell as the token value from earlier (only the text after the bearer keyword)

e.g.

[illegible]

Run curl command (or script)

```
apk --no-cache add curl jq
```

define these 3 environment variable as required

```
e.g:
export username=cluedinuser@cluedin.com
export password=bLaye3#09RU
export org=cluedin
```

Create this script - or copy and paste into the console (skip the `#!/bin/sh` line if copy and paste)

Update the highlighted parts to match your app endpoint.

```
create_user.sh      #!/bin/sh

code=`echo -n $username | md5sum | cut -d " " -f1 | awk '{print toupper($0)}'`
URL=http://app.k1.cluedin.me/auth/api/account/register?code=\$code
      email=$URL

curl -v --location -g --request POST $URL \
      --header 'Content-Type: application/x-www-form-urlencoded' \
      --header "Authorization: Bearer $TOKEN" \
      --data-urlencode username=$username \
      --data-urlencode password=$password \
      --data-urlencode applicationSubDomain=$org \
      --data-urlencode grant_type=password \
      --data-urlencode confirmpassword=$password \
      --data-urlencode email=$username
```




[illegible]


```
> Content-Length: 166
>
* Mark bundle as not supporting multiuse
< HTTP/1.1 200 OK
< date: Thu, 16 Dec 2021 01:47:54 GMT
< server:
< content-length: 0
< vary: Accept-Encoding
< x-powered-by: CluedIn
< x-cluedin-version: 3.2.0.0
< x-cluedin-data: All your data are belong to you!
< x-robots-tag: noindex,nofollow
< x-correlation-id: 7e21a5b4-9f47-4276-b1fa-0990cb760053
```

if you run it again you get




HTTP/1.1 409 Conflict







Compare with Postman







Rudi Sandbox / Register a new User    Save



POST 

http://app.k1.cluedin.me/auth/api/account/register?code=28A3DB27E2F6A3FED65D83E28E7ED7B4


Params  Authorization Headers (10) Body  Pre-request Script Tests  Settings


 none  form-data  x-www-form-urlencoded  raw  binary  GraphQL



	KEY	VALUE	DESCRIPTION
	username	cluedinuser@cluedin.com	
	password	bLaye3#09RU	
	applicationSubDomain	cluedin	
	grant_type	password	
	confirmpassword	bLaye3#09RU	
	email	cluedinuser@cluedin.com	
	Key	Value	Description

Params  Authorization Headers (9) Body Pre-request Script Tests  Settings

Query Params

	KEY	VALUE
	code	28A3DB27E2F6A3FED65D83E28E7ED7B4
	Key	Value

Headers  7 hidden

	KEY	VALUE
	Content-Type	application/x-www-form-urlencoded
	Authorization	Bearer {{access_token}}
	Key	Value

Raw console log from Postman

```
POST /auth/api/account/register?code=28A3DB27E2F6A3FED65D83E28E7ED7B4 HTTP/1.1
Content-Type: application/x-www-form-urlencoded
Authorization: Bearer
eyJhbGciOiJIUzI1NiIsImtpZCI6IkdGOUZlODAzQzJFNkZGQ0QzRkRBNkY0RkVCNEJmY2IiOiJYXQand0In0.eyJyYmY1OjE2Mjk2OTQ1MDgsImV4cCI6MTY2MTIzMDUwYmlywI
aXNzIjoiaHR9cDovLzE5Ny4wLjAuMS5uaXAuaW86OTAwMS81LCJhdWQ1O1s1U2VydmlVYXBPcmRmYyVUk1LCJqdWJsaWNbcGk1XSsw1Y2xpZW50X2lkIjo1UHVibG1jQXBpQ2xpZW50Iiw1cm9s
ZS5Ieik6SSIsIk9yZ2FuaXphdGlvbk1kIjo1MmM4MTU3ZGZmMC00ZjU0LW1xN2YtZGFkY2YyM2Q5ZDk0Iiw1Q2xpZW50SWQ1O1Jmb291YX11LCJ3PCmdhbm16YXRpb250YW11Ijo1Zm9v
YmFyIiw1T3JnYW5pemF0aW9uQ2xpZW50UmVmZXJlbmN1Ijo1Zm9vYmFyIiw1SWQ1O1JjMTg5NDIxNi0yNzc5LTQ5NDctYjY1Iiw1Q4YjU2YTc0OTFkMTk1LCJhcGkiOiJyOTVmyTc5SM11jYz1j
LTR1M2ItYmIzYy0xNWVhYzJhMDZjYTE1LCJqdGkiOiJFRDU0MTQxOTI2M0FGQjI4QzQ0Rjg5MjEzMU04MDREQSI0Iiw1Q4YjU2YTc0OTFkMTk1LCJhcGkiOiJyOTVmyTc5SM11jYz1j
dmVjQXBpRm9vYmlywIiw1UzI1NiIsImtpZCI6IkdGOUZlODAzQzJFNkZGQ0QzRkRBNkY0RkVCNEJmY2IiOiJYXQand0In0.eyJyYmY1OjE2Mjk2OTQ1MDgsImV4cCI6MTY2MTIzMDUwYmlywI
xPVkZzFh1eoISFg_ABzD1o413nnEBVw741N76MYW0eWvAg1qQZMYUGRrL7EPFV2oxhdWlc3oudRyzoodt19Y0d1I1U4ChZNUrmIgfU7tf1-I-dEUR0OP7d3
_h202H0AkAF0jvS79bUdHfB0ugrVdf1xJtF6sdoqy1Eb1a6nmIs_-tmBPENDMYJJSUZf9YgA9ZLfcBCLcBGQX9HzhYzwhOCdyrLULaBIXGhwzCpXucLau0MifdSx2yYC89-
zRLEI0GcFXh9P-vzSsaXZf1f-boiD33pSQzZqHw
User-Agent: PostmanRuntime/7.28.4
Accept: */*
Cache-Control: no-cache
Postman-Token: bd25ceeb-fb95-43c6-bf7f-9791b0edd1bc
Host: app.k1.cluedin.me
Accept-Encoding: gzip, deflate, br
Connection: keep-alive

username=cluedinuser%40cluedin.com&password=bLaye3%2309RU&applicationSubDomain=cluedin&grant_type=password&confirmpassword=bLaye3%
2309RU&email=cluedinuser%40cluedin.com

HTTP/1.1 200 OK
```

if you run the same request again you get an expected 409 error

```
HTTP/1.1 409 Conflict
date: Thu, 16 Dec 2021 01:42:44 GMT
server:
content-length: 0
vary: Accept-Encoding
x-powered-by: CluedIn
x-cluedin-version: 3.2.0.0
x-cluedin-data: All your data are belong to you!
x-robots-tag: noindex,nofollow
x-correlation-id: 2ca7a836-97c8-4aa2-a5c4-aec2680ca8b5
```

<div> <div>+</div> <div>INVITE A NEW TEAM MEMBER</div> <div>Search</div> </div>			
<input type="checkbox"/>	NAME	ROLES	ACTIVE
<input type="checkbox"/>	<div>C</div> cluedinuser@cluedin.com	OrganizationUser	<input checked="" type="checkbox"/> Active
<input type="checkbox"/>	<div>A</div> admin@cluedin.com <div>This is you</div>	Admin	You cannot deactivate