

# Sql Connector Install - ubuntu - docker

Friday, 4 February 2022 3:34 PM

## Purpose

We often need this connector!

## Journal

Let's add the public nuget feed and specify we want this connector and go from there.

Poking around <https://cluedin-io.github.io/Home/3.2.5/packages/> looks like we can just mainly use the package commands on the cluedin.ps1 script.

note: <https://cluedin-io.github.io/Home/3.5.1/packages/> is the latest as of the time of writing

assume we created our environment with tags

example:

```
./cluedin.ps1 env 331 -tag 3.3.1
./cluedin.ps1 up 331
./cluedin.ps1 stop 331
./cluedin.ps1 start 331
./cluedin.ps1 status 331
./cluedin.ps1 createorg 331 -name cluedin -pass <redacted>
```

configure the feed and add the package

```
PS /home/ubuntu/Home-Dev/src> ./cluedin.ps1 packages -Env 330 -List
+-----+
| CluedIn - Packages [docker] |
+-----+
No packages specified

public feed uri is https://pkgs.dev.azure.com/CluedIn-io/Public/_packaging/Public/nuget/v3/index.json

PS /home/ubuntu/Home-Dev/src> ./cluedin.ps1 packages -Env 330 -AddFeed cluedin-public -Uri
https://pkgs.dev.azure.com/CluedIn-io/Public/_packaging/Public/nuget/v3/index.json


error: Failed to read NuGet.Config due to unauthorized access. Path: '/packages/nuget.config'.
error: Access to the path '/packages/nuget.config' is denied.
error: Permission denied

using find
/home/ubuntu/Home-Dev/src/env/330/packages/nuget.config

try PS /home/ubuntu/Home-Dev/src> chmod a+rxw ./env/330/packages/nuget.config

PS /home/ubuntu/Home-Dev/src> ./cluedin.ps1 packages -Env 330 -AddFeed cluedin-public -Uri
https://pkgs.dev.azure.com/CluedIn-io/Public/_packaging/Public/nuget/v3/index.json
+-----+
| CluedIn - Packages [docker] |
+-----+
Package source with Name: cluedin-public added successfully.

PS /home/ubuntu/Home-Dev/src> cat ./env/330/packages/nuget.config
<?xml version="1.0" encoding="utf-8"?>
<configuration>
  <packageSources>
    <add key="local" value="/packages/local" />
    <add key="cluedin-public" value="https://pkgs.dev.azure.com/CluedIn-io/Public/_packaging/Public/nuget/v3/index.json" />
  </packageSources>
</configuration>
```



```
PS /home/ubuntu/Home-Dev/src> ./cluedin.ps1 packages -Env 330 -Add CluedIn.Connector.SqlServer
+-----+
| CluedIn - Packages [docker] |
+-----+
Added package CluedIn.Connector.SqlServer
```

```
PS /home/ubuntu/Home-Dev/src> cat ./env/330/packages/nuget.config
<?xml version="1.0" encoding="utf-8"?>
<configuration>
  <packageSources>
    <add key="local" value="/packages/local" />
    <add key="cluedin-public" value="https://pkgs.dev.azure.com/CluedIn-io/Public/_packaging/Public/nuget/v3/index.json" />
  </packageSources>
</configuration>

PS /home/ubuntu/Home-Dev/src> cat ./env/330/packages/packages.txt
CluedIn.Connector.SqlServer
```

restore the packages

```
PS /home/ubuntu/Home-Dev/src> ./cluedin.ps1 packages -Env 330 -Restore
```

fail

```
...
ERROR: Could not build package collection.
Write-Error: /Install-Packages.ps1:132
Line
132 Write-Error "Could not compose CluedIn extensions.
~~~~~
Could not compose CluedIn extensions.
```

try

```
PS /home/ubuntu/Home-Dev/src> chmod -R a+rxw ./env/330/components/
PS /home/ubuntu/Home-Dev/src> chmod -R a+rxw ./env/330/packages/
```

retry

```
PS /home/ubuntu/Home-Dev/src> ./cluedin.ps1 packages -Env 330 -Restore
```

success

```
...
Committing restore...
Generating MSBuild file
/tmp/ServerComponent.Extensions/obj/ServerComponent.Extensions.csproj.nuget.g.props.
Generating MSBuild file
/tmp/ServerComponent.Extensions/obj/ServerComponent.Extensions.csproj.nuget.g.targets.
Writing assets file to disk. Path:
/tmp/ServerComponent.Extensions/obj/project.assets.json
Restored /tmp/ServerComponent.Extensions/ServerComponent.Extensions.csproj (in
12.09 sec).

NuGet Config files used:
  /tmp/ServerComponent.Extensions/nuget.config
  /nuget.config
  /tmp/dotnetcli/.nuget/NuGet/NuGet.Config

Feeds used:
  /packages/local
  https://pkgs.dev.azure.com/CluedIn-io/Public/_packaging/Public/nuget/v3/index.json
  https://api.nuget.org/v3/index.json

Installed:
  242 package(s) to
/tmp/ServerComponent.Extensions/ServerComponent.Extensions.csproj
  1>Done Building Project
"/tmp/ServerComponent.Extensions/ServerComponent.Extensions.csproj" (Restore target(s)).

Build succeeded.
  0 Warning(s)
  0 Error(s)

Time Elapsed 00:00:12.96
ServerComponent.Extensions ->
/tmp/ServerComponent.Extensions/ServerComponent.Extensions.dll
[Package Trimming]: Removing 14 libraries from publish output that are available in the
runtime store
- Removing [3.1.5] - Microsoft.Extensions.Caching.Abstractions
- Removing [3.1.5] - Microsoft.Extensions.Caching.Memory
- Removing [3.1.5] - Microsoft.Extensions.Configuration.Abstractions
- Removing [3.1.5] - Microsoft.Extensions.Configuration.Binder
- Removing [3.1.5] - Microsoft.Extensions.Configuration
- Removing [3.1.5] - Microsoft.Extensions.Configuration.EnvironmentVariables
- Removing [3.1.5] - Microsoft.Extensions.DependencyInjection.Abstractions
- Removing [3.1.5] - Microsoft.Extensions.DependencyInjection
- Removing [3.1.5] - Microsoft.Extensions.Logging.Abstractions
- Removing [3.1.5] - Microsoft.Extensions.Logging
- Removing [3.1.5] - Microsoft.Extensions.Options
- Removing [3.1.5] - Microsoft.Extensions.Primitives
- Removing [1.7.1] - System.Collections.Immutable
- Removing [4.7.1] - System.Diagnostics.DiagnosticSource
[Package Trimming]: Removing 9 asset(s) from publish output that are available in the
host
- Removing [4.3.1] - Castle.Core
- Removing [5.0.1] - Castle.Windsor
- Removing [2.0.0] - ComponentHost
- Removing [1.1.2] - Microsoft.DotNet.PlatformAbstractions
- Removing [1.1.2] - Microsoft.Extensions.DependencyModel
- Removing [12.0.2] - Newtonsoft.Json
- Removing [2.6.0] - Serilog
- Removing [4.7.0] - System.Configuration.ConfigurationManager
- Removing [4.7.0] - System.Security.Cryptography.ProtectedData
ServerComponent.Extensions -> /components/ServerComponent/
```

restart the cluster using the manage script

```
--- CluedIn Ghetto Management Script ---

s - status
r - restart all docker containers
x - stop - stop in current state
X - start - opposite of stop
u - up - start and ensuring changed containers are created
w - wipe i.e. tear DOWN cluster and bring it back UP
d - wipe/down i.e. tear DOWN cluster
q - to quit
>r
```

```

+-----+
| CluedIn - Environment => stop [docker] |
+-----+
Stopping cluedin_330_460fc9ca_gql_1 ... done
Stopping cluedin_330_460fc9ca_clean_1 ... done
Stopping cluedin_330_460fc9ca_submitter_1 ... done
Stopping cluedin_330_460fc9ca_annotation_1 ... done
Stopping cluedin_330_460fc9ca_ui_1 ... done
Stopping cluedin_330_460fc9ca_server_1 ... done
Stopping cluedin_330_460fc9ca_datasource_1 ... done
Stopping cluedin_330_460fc9ca_cadvisor_1 ... done
Stopping cluedin_330_460fc9ca_webapi_1 ... done
Stopping cluedin_330_460fc9ca_prometheus_1 ... done
Stopping cluedin_330_460fc9ca_sqlserver_1 ... done
Stopping cluedin_330_460fc9ca_grafana_1 ... done
Stopping cluedin_330_460fc9ca_elasticsearch_1 ... done
Stopping cluedin_330_460fc9ca_smtp4dev_1 ... done
Stopping cluedin_330_460fc9ca_rabbitmq_1 ... done
Stopping cluedin_330_460fc9ca_redis_1 ... done
Stopping cluedin_330_460fc9ca_neo4j_1 ... done
Stopping cluedin_330_460fc9ca_openrefine_1 ... done
Stopping cluedin_330_460fc9ca_seq_1 ... done
+-----+
| CluedIn - Environment => up [docker] |
+-----+
Pulling libpostal (cluedin/libpostal:release-3.3.0)...
release-3.3.0: Pulling from cluedin/libpostal
58690f9b18fc: Already exists
b51569e7c507: Already exists
da8ef40b9eca: Already exists
fb15d46c38dc: Already exists
35afea6de0f9: Pull complete
e147adf7c036: Pull complete
0ea2a8b18eaf: Pull complete
dab5ce78a412: Pull complete
23ae542c0828: Pull complete
1000de8059d2: Pull complete
Digest: sha256:947fe4fd9b538872ae211a822feb504d4a86121c2e7bd015ad1998eb469f0c89
Status: Downloaded newer image for cluedin/libpostal:release-3.3.0
Starting cluedin_330_460fc9ca_sqlserver_1 ... done
Starting cluedin_330_460fc9ca_rabbitmq_1 ... done
Starting cluedin_330_460fc9ca_openrefine_1 ... done
Starting cluedin_330_460fc9ca_smtp4dev_1 ... done
Starting cluedin_330_460fc9ca_neo4j_1 ... done
Starting cluedin_330_460fc9ca_seq_1 ... done
Starting cluedin_330_460fc9ca_grafana_1 ... done
Starting cluedin_330_460fc9ca_redis_1 ... done
Starting cluedin_330_460fc9ca_prometheus_1 ... done
Starting cluedin_330_460fc9ca_elasticsearch_1 ... done
Starting cluedin_330_460fc9ca_cadvisor_1 ... done
Starting cluedin_330_460fc9ca_webapi_1 ... done
Starting cluedin_330_460fc9ca_datasource_1 ... done
Starting cluedin_330_460fc9ca_server_1 ... done
Starting cluedin_330_460fc9ca_annotation_1 ... done
Starting cluedin_330_460fc9ca_ui_1 ... done
Starting cluedin_330_460fc9ca_clean_1 ... done
Starting cluedin_330_460fc9ca_submitter_1 ... done
Starting cluedin_330_460fc9ca_gql_1 ... done

```

check the logs

```

# get the container id for the server
ubuntu@ip-172-31-25-74:~$ sudo docker ps | grep server
a0e9037a1924 cluedin/cluedin-server:release-3.3.0 "sh ./boot.sh" 23
hours ago Up 2 minutes
0.0.0.0:9000-9001->9000-9001/tcp, ::9000-9001->9000-9001/tcp,
0.0.0.0:9003->9003/tcp, ::9003->9003/tcp,
0.0.0.0:9006-9007->9006-9007/tcp, ::9006-9007->9006-9007/tcp,
0.0.0.0:9013->9013/tcp, ::9013->9013/tcp cluedin_330_460fc9ca_server_1
59890c72c032 cluedin/sqlserver:release-3.3.0 "sh -c /init/init.sh" 23
hours ago Up 2 minutes 0.0.0.0:1433->1433/tcp, ::1433->1433/tcp
cluedin_330_460fc9ca_sqlserver_1

# check the server log for the word Sql in the last 10 minutes
ubuntu@ip-172-31-25-74:~$ sudo docker logs --since 10m a0e9037a1924 | grep Sql
'../components/ServerComponent/CluedIn.Connector.SqlServer.dll' ->
'./ServerComponent/CluedIn.Connector.SqlServer.dll'
[06:14:26 INF] SqlClient Registered
[06:14:27 INF] Provider: Sql Server Connector, ID: 838e4ea2-80e0-4b60-b1d1-f052bfcd0caf is
registered

```

check UI

← → ↻ ⚠ Not secure | cluedin.u3.cluedin.me:9080/admin/consume/connector?itemsPerPage=10&pageNo=1

Cluedin

Integrations

Governance

Preparation

Engine Room

Management

Consume

GraphQL

Streams

Export Targets

Administration

All

Search

All

Q

Consume / Export Targets / All Export Targets

Add export target

Search...

Q

Name	Stream Modes	Status
------	--------------	--------

Add Export Target

1 Choose Target

Q

SQL Server

Sql Server Connector

Supports publishing of data to external SQL databases

Total Connector: 1

Cancel

Next

No Export Targets

Please add an export target to see list

Add export target

winner winner 🏆 dinner!