

Modularity Maximization: An Experimental Survey

Adil Chhabra
adil.chhabra@informatik.uni-
heidelberg.de
Heidelberg University
Heidelberg, Germany

Kenneth Langedal*
kenneth.langedal@informatik.uni-
heidelberg.de
Heidelberg University
Heidelberg, Germany

Christian Schulz
christian.schulz@informatik.uni-
heidelberg.de
Heidelberg University
Heidelberg, Germany

Abstract

There has been a wide variety of community detection methods proposed over the last two decades that optimize the modularity objective. Despite this abundance of methods, comparative experimental evaluations remain fragmented: most studies consider only a small subset of available algorithms. As a result, it is often unclear how different modularity-based methods relate to one another in practice, or under which conditions specific design choices are most effective. Most notably, the body of work can largely be divided in two main categories based on whether they use machine learning or not.

In this work, we present an experimental survey of modularity optimization methods, covering more than twenty representative approaches spanning different algorithmic paradigms. We summarize key algorithmic features, and provide a systematic experimental comparison across multiple datasets and evaluation criteria. Our goal is not to identify a single “best” method, but to clarify empirical trade-offs, expose gaps in existing comparisons, and offer practical guidance for researchers and practitioners working with modularity-based graph clustering.

CCS Concepts

• **Theory of computation** → **Graph algorithms analysis**; • **Mathematics of computing** → **Graph theory**; • **Computing methodologies** → **Cluster analysis**.

Keywords

Community detection, Graph clustering, Modularity optimization, Experimental evaluation

ACM Reference Format:

Adil Chhabra, Kenneth Langedal, and Christian Schulz. 2018. Modularity Maximization: An Experimental Survey. In *Proceedings of Make sure to enter the correct conference title from your rights confirmation email (Conference acronym 'XX)*. ACM, New York, NY, USA, 3 pages. <https://doi.org/XXXXXXX.XXXXXXX>

*Corresponding author.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference acronym 'XX, Woodstock, NY

© 2018 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM ISBN 978-1-4503-XXXX-X/2018/06
<https://doi.org/XXXXXXX.XXXXXXX>

1 Introduction

Community detection in graphs.

- Problem definition
- Why modularity?
- State why this survey is needed, missing comparisons in the literature
- At the end, list of contributions (experimental survey stuff)

2 Preliminary

We use the term algorithm to denote a concrete computational procedure. Except where explicitly stated, the algorithms considered here are heuristics for modularity maximization and do not guarantee optimality.

3 Related Work

4 Methods

This section contains a short description outlining the core ideas behind each clustering method. They are grouped the algorithms into categories to make it easier to navigate the survey. With in each category, the algorithms are presented in order of publication date. At the top level of this taxonomy, we have *Learning-based* methods and *Classical modularity optimization* methods. For this distinction, *Learning-based* refers to any method that train model parameters as part of the algorithm.

4.1 Classical Modularity Optimization Methods

CNM. A scalable greedy modularity-optimization algorithm with near-linear running time on large sparse networks and demonstrates its effectiveness on a large real-world network.

Walktrap. Based on the idea that random walks on a graph tend to get “trapped” into densely connected parts corresponding to communities.

Infomap. Infomap frames community detection as an information compression problem: it partitions a graph so that the expected code length of a random walk on the network is minimized, thus uncovering modules where flows concentrate. The alternative *Map Equation* objective function was also introduced here.

Louvain. The famous Louvain method, named after the location the work took place, is a multi-level approach to graph clustering. At each level, the algorithm greedily moves vertices to neighboring clusters based on the modularity delta. Once there are no improving moves, each cluster is contracted into a single vertex, and the process repeats.

CGGCi-RG. Combination of the CGGC (Core Groups Graph Clustering) ensemble scheme with an underlying Randomized Greedy

Table 1: Comparison of the methods included in the experimental survey. The *Code Available* field is defined as follows: × means not available, one ★ means code is available but not prepared for use in any way, ★★ is for methods with open source implementations with well defined input/output formats, and ★★★ means the algorithm is easy to use via portable Python packages such as the CDlib package.

Method	Year	Code Available	Stochastic	Learning-Based	Fixed Cluster Count	Exact	Approx. Running Time
CNM	2004	★★★					$O(n \log^2 n)$
Walktrap	2005	★★★	✓				$O(n^2 \log n)$
Louvain	2008	★★★	✓				?
CGGCI	2012	×	?				?
VNS	2012	×	✓				?
COMBO	2014	★★★	?				?
Hollocou	2017	★★	?				?
VieClus	2018	★★	✓				?
Leiden	2019	★★★	✓				?
DMoN	2020	★	?	✓		✓	?
CommDGI	2020	★	?	✓		✓	?
GNNs	2022	★	?	✓			?
UCoDe	2023	★	?	✓		✓	?
DGCluster	2023	★	?	✓			?
MAGI	2024	★	?	✓		✓	?
Bayan	2024	★★				✓	?
CluStRE	2025	★★	?				?
LIM	2025	?	?	✓		?	?
MaxSAT	2025	?				✓	?

(RG) clustering algorithm. It was the best performing algorithm submitted to the 10th DIMACE Implementation Challenge.

VNS. Variable Neighborhood Search metaheuristic that obtained the second place in the 10th DIMACS Implementation Challenge. It was a close call between VNS and CGGCI-RG.

COMBO. TODO.

Hollocou. Modularity optimization in the streaming setting. For each streamed edge, Hollocou employs a simple decision strategy based on a given parameter and the volumes of the communities of the two nodes.

VieClus. A general memetic algorithm that can be adapted to optimize different objective functions.

Leiden. As a direct improvement to the Louvain method, Leiden addresses a defect in the Louvain method that can lead to disconnected communities.

Bayan. An exact algorithm for modularity optimization that uses Integer Linear Programming solvers.

CluStRE. Improved streaming algorithm with both re-streaming and combined use of VieCLUS in-memory after streaming and contraction.

MaxSAT. An improved exact method for modularity optimization using a MaxSAT formulation.

4.2 Learning-Based Methods

Methods that find model parameters.

DMoN.

CommDGI.

UCoDe.

DGCluster.

MAGI.

5 Experiments

6 Conclusion

Acknowledgments

To Robert, for the bagels and explaining CMYK and color spaces.

References

- [1] Daniel Aloise, Gilles Caporossi, Pierre Hansen, Leo Liberti, Sylvain Perron, and Manuel Ruiz. 2012. Modularity maximization in networks by variable neighborhood search. In *Graph Partitioning and Graph Clustering*. Contemporary Mathematics, Vol. 588. American Mathematical Society, 113–127. doi:10.1090/conm/588/11705
- [2] Samin Aref, Mahdi Mostajabdeh, and Hriday Chheda. 2024. Bayan algorithm: Detecting communities in networks through exact and approximate optimization of modularity. *Physical Review E* 110, 4 (2024), 044315. doi:10.1103/PhysRevE.110.044315
- [3] Aritra Bhowmick, Mert Kusan, Zexi Huang, Ambuj Singh, and Sourav Medya. 2024. DGCLUSTER: A Neural Framework for Attributed Graph Clustering via Modularity Maximization. In *Proceedings of the 38th AAAI Conference on Artificial Intelligence (AAAI 2024)*. AAAI Press, Washington, DC, USA, 11069–11077. doi:10.1609/aaai.v38i10.28983

Algorithm Eng.

Machine Learning




Figure 1: Experimental comparisons visualized.

- [4] Sonja Biedermann, Monika Henzinger, Christian Schulz, and Bernhard Schuster. 2018. Memetic Graph Clustering. In *Proceedings of the 17th International Symposium on Experimental Algorithms (SEA 2018)*. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 3:1–3:15. doi:10.4230/LIPIcs.SEA.2018.3
- [5] Christopher Blöcker, Chester Tan, and Ingo Scholtes. 2024. The map equation goes neural: Mapping network flows with graph neural networks. In *Proceedings of the 38th Conference on Neural Information Processing Systems (NeurIPS 2024)*. Curran Associates, Inc., 17428–17456. doi:10.52202/079017-0554
- [6] Vincent D. Blondel, Jean-Loup Guillaume, Renaud Lambiotte, and Etienne Lefebvre. 2008. Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment* 2008, 10 (2008), P10008. doi:10.1088/1742-5468/2008/10/P10008
- [7] Adil Chhabra, Shai Dorian Peretz, and Christian Schulz. 2025. CluStRE: Streaming Graph Clustering with Multi-Stage Refinement. In *Proceedings of the 23rd International Symposium on Experimental Algorithms (SEA 2025)*. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 11:1–11:20. doi:10.4230/LIPIcs.SEA.2025.11
- [8] Park K. Fung. 2019. InfoFlow: A Distributed Algorithm to Detect Communities According to the Map Equation. *Big Data and Cognitive Computing* 3, 3 (2019), 42. doi:10.3390/bdcc3030042
- [9] Hongchang Gao and Heng Huang. 2018. Deep Attributed Network Embedding. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence (IJCAI 2018)*. International Joint Conferences on Artificial Intelligence Organization, 3364–3370. doi:10.24963/ijcai.2018/467

- [10] Alexandre Hollocou, Julien Maudet, Thomas Bonald, and Marc Lelarge. 2017. A Streaming Algorithm for Graph Clustering. arXiv preprint. doi:10.48550/arXiv.1712.04337
- [11] Yunfei Liu, Jintang Li, Yuehe Chen, Ruofan Wu, Ericbk Wang, Jing Zhou, Sheng Tian, Shuheng Shen, Xing Fu, Changhua Meng, Weiqiang Wang, and Liang Chen. 2024. Revisiting Modularity Maximization for Graph Clustering: A Contrastive Learning Perspective. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD 2024)*. Association for Computing Machinery, New York, NY, United States, 1968–1979. doi:10.1145/3637528.3671967
- [12] Atefeh Moradan, Andrew Draganov, Davide Mottin, and Ira Assent. 2023. UCoDe: Unified community detection with graph convolutional networks. *Machine Learning* 112, 12 (2023), 5057–5080. doi:10.1007/s10994-023-06402-0
- [13] Pascal Pons and Matthieu Latapy. 2005. Computing Communities in Large Networks Using Random Walks. In *Proceedings of the 20th International Symposium on Computer and Information Sciences (ISCIS 2005)*. Springer Berlin Heidelberg, 284–293. doi:10.1007/11569596_31
- [14] Arnaud Prat-Pérez, David Dominguez-Sal, and Josep-Lluís Larriba-Pey. 2014. High quality, scalable and parallel community detection for large real graphs. In *Proceedings of the 23rd International Conference on World Wide Web (WWW 2014)*. Association for Computing Machinery, 225–236. doi:10.1145/2566486.2568010
- [15] Martin Rosvall and Carl T. Bergstrom. 2008. Maps of random walks on complex networks reveal community structure. *Proceedings of the National Academy of Sciences* 105, 4 (2008), 1118–1123. doi:10.1073/pnas.0706851105
- [16] Stanislav Sobolevsky and Alexander Belyi. 2022. Graph neural network inspired algorithm for unsupervised network community detection. *Applied Network Science* 7, 1 (2022), 63. doi:10.1007/s41109-022-00500-z
- [17] Vincent A. Traag, Ludo Waltman, and Nees Jan van Eck. 2019. From Louvain to Leiden: guaranteeing well-connected communities. *Scientific Reports* 9, 1 (2019), 5233. doi:10.1038/s41598-019-41695-z
- [18] Anton Tsitsulin, John Palowitch, Bryan Perozzi, and Emmanuel Müller. 2023. Graph Clustering with Graph Neural Networks. *Journal of Machine Learning Research* 24, 127 (2023), 1–21. <http://jmlr.org/papers/v24/20-998.html>
- [19] Hong Wang, Yinglong Zhang, Zhangqi Zhao, Zhicong Cai, Xuewen Xia, and Xing Xu. 2025. Simple yet effective heuristic community detection with graph convolution network. *Scientific Reports* 15, 1 (2025), 39249. doi:10.1038/s41598-025-22860-z
- [20] Tianqi Zhang, Yun Xiong, Jiawei Zhang, Yao Zhang, Yizhu Jiao, and Yangyong Zhu. 2020. CommDGI: Community Detection Oriented Deep Graph Infomax. In *Proceedings of the 29th ACM International Conference on Information & Knowledge Management (CIKM 2020)*. Association for Computing Machinery, 1843–1852. doi:10.1145/3340531.3412042

A Research Methods

A.1 Part One

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Morbi malesuada, quam in pulvinar varius, metus nunc fermentum urna, id sollicitudin purus odio sit amet enim. Aliquam ullamcorper eu ipsum vel mollis. Curabitur quis dictum nisl. Phasellus vel semper risus, et lacinia dolor. Integer ultricies commodo sem nec semper.

Received 20 February 2007; revised 12 March 2009; accepted 5 June 2009