





# Versioning your code (and more)

An illustration with git

t[n]);return r&&k.extend(!0,e,)

//,json:/\bjson\b/),respondered(),b

pe:function(e){return null n&&(v.min=Ty)

rCase().match(R)||[""],null nv.cros.dimn

e.toUpperCase(),v.hasCantent=Ikt.tes (v.
.url=f+0),v.ifModified&&(k.lastHod.ied{

oreSend&&(!1===v.deforeSenv.Call(y,T,v)|
,i=200<=e&&e<32d||304==c.shift();while(o
"to"+o})}return(v.ate:"success",data:t
),200=e||\*MEAD"==v.type?l="nocontent"

turn k.get(e,void 0,t,"script")}}),k.ead

apAll:function(e)

\*256"withCredentials"in Xt.v


Stéphane DRAY

Lundi 2 novembre 2020

## Introduction



## Science is a long and step-by-step procedure



#### Remember the time



#### Remember the time

#### Track the changes in a project:

- Data gathering: Lab notebook
- Data analysis: Versioning
- Article writing: Versioning



#### Remember the time

#### Track the changes in a project:

- Data gathering: Lab notebook
- Data analysis: Versioning
- Article writing: Versioning





https://miro.medium.com/max/472/1\*B0Ykkbhw5bzhHkY79cYrWg.jpeg

## An example

https://github.com/sdray/ade4/

## Introduction to git

#### git

There are several tools for versioning. This course focuses on git.

git is a program that takes **snapshots** of a directory tree and helps navigating between those snapshots.

- archiving/documentation of development steps
- backtracking to previous versions
- handling of multiple versions
- collaborative development
- backup (using external servers)

Especially useful when developing software, writing papers. . .

#### Some definitions

- repository: a directory including with a .git directory
- **commit**: a snapchot of the repository (a date, an author, a description, a parent)
- working copy: a version of the files of the repository on your computer
- index: a temporary space including the modficiations to be committed

All git commands follow the same pattern:

git SUBCMD ARGS \*

## Starting with git

## Create a repository

git init

#### Demo

- Create a directory
- Move to the directory
- Initialize the repostitory

## Checking the state of the repository

git status

#### Demo

• Check the status of your repository

#### Put a file under version control

#### git add FILE

Files in the directory are ignored by git unless they are explicitly added to the repository

#### Demo

- Create a text file
- Check the status of your repository
- Add the file to your repository
- Check the status of your repository

#### Take a snapshot

git commit -a -m MSG

A snapshot in git is called a commit. The -m option introduces a message describing the changes in the new snapshot.

#### Demo

- Take a snaphsot of your repository
- Check the status of your repository

## Print commit history

git log

#### Demo

• Display the history

#### Print an old version of a file

git show COMMIT ID:PATH

You can retrieve commit id using git log. Only the 6-8 letters of the id are generally enough

#### Demo

• Display the content of your text file at the previous commit

## Summary

Here are the basic commands to archive your work in a git repo:


I want to	I use
Initialize a new (empty) git repo	git init
Put files under version control	git add file1 file2
Take a snapshot	git commit -a -m "commit descr"
See commit history	git log
See previous version of a file	git show aazef345:src/foo.c

The 3 areas of git

## Revisiting git

- Working directory: your files, this is the place where you edit contents
- Commit graph : snapshot storage
- **Index**: a place in-between to prepare commits. It contains a list of modifications selected for the next commit

## Moving between the three areas



#### Moving between the three areas

- git add put updates of the working directory in the index
- **git commit** builds a commit from the contents of the index (option -a selects all modifications and put them in the index before committing)
- git diff shows differences between working directory and the index. With --cached option, shows differences between index and last commit
- git checkout update the working directory with the content of the repo
- git reset HEAD remove the last changes from the index

## Using a distant server

## Why using a distant server

- A backup of your repository
- Work with others
- Increase your visibility
- Increase interactions with users
- Easy distribution of devel versions

There are several source hosting services run by academic or private institutions.

#### Cloning a repo

git clone URL

This command create an (independent) copy of an existing repo, with all its history.

#### Demo

- Try to clone the repository of the course
- Display the history of the repository

## Interact with the distant repository

#### git pull

This command will fetch commits from the cloned repo and update the working directory to latest commit.

#### git push

This command will send commits to the cloned repo. It requires write access.

#### Demo

- Try to obtain the last version of the course (after I update it)
- Modify the course and send your commit

## Summary

Here are the basic commands to work with a distant repo:

I want to	l use
Clone a distant repo	git clone https://github.com/
Update local repo	git pull
Send commits to distant repo	git push

Starting a new project on GitHub

#### Identification

It is possible to use GitHub with https protocol but you will be asked for your GitHub username and password for each action.

ssh provides another way to access to a Git repository. If you generate ssh public and private keys, you can use git without username/password.

```
cd ~/
ssh -keygen - t rsa
```

#### Demo

- Copy the public key on GitHub (Settings)
- Create a new project
- Clone the repo
- Do a few commits
- Push your commits
- Modify and have a look to README.md
- Create an issue

## Dealing with branches

#### Commit graph and branches

Sometimes, you want to do experimental developments that diverge from the main line of development. Branches allow to "play" without messing with that main line.

- The main feature of branches is to allow switching between different versions very easily
- A branch should correspond to a topic, e.g. a bug fix, new feature, etc.
- especially useful when unsure when/if some modifications will be included (that is, very often)
- it permits several concurrent development processes

#### Understanding branches

- commits form a graph
- each commit is linked to its parent(s)
- a branch is a pointer to a commit
- after repo init, there is a single branch called master
- at all time, one branch is selected as the "current branch"

Demo https://learngitbranching.js.org/?NODEMO

#### Branches in practice

- After a commit, a new commit is created in the graph and the current branch is moved to the new commit
- A new branch can be created by

#### git branch BRANCH\_NAME

The new branch is located at the same location than the current branch. Commits act on the current branch

It is possible to switch to a branch by

#### git checkout BRANCH\_NAME

Current branch (and the working directory) is updated to reflect the state of the corresponding commit

#### Branches in practice

A branch can be deleted by

#### git branch -d BRANCH\_NAME

Only the pointer is deleted, not the pointed commits but commit may be hard to find after branch deletion

Two branches can be merged by

#### git merge BRANCH\_NAME


git will try to merge the snapshot pointed by current branch and the one pointed by the branch given in argument.

It creates a new commit and moves the current branch to the newly created commit.

The newly created commit has two parents!

### Work with others

## A distributed system



https://miro.medium.com/max/1698/1\*GgaGcwh5L246YcU5NVDA5A.png

## Dealing with conflicts

What happens if someone push before me? A conflict.

Two commits are in conflict when they contain different updates to the same area of a file. They should be resolved manually after merging

To avoid conflicts, update your branch before you start working on something and make frequent and small commits

#### Demo

- Invite a colleague in your project
- Clone the repo
- Create commit, branches, etc.
- Push
- If they are conflicts, try to solve them

### Git and RStudio

## GUIs for git

There are several GUIs for git. RStudio provides a convenient way to deal with R projects

#### Demo

• Create a project and configure RStudio

## Acknowledgments

This presentation is strongly inspired from the slides of Philippe Veber (LBBE)

A good summary:

https://github.github.com/training-kit/downloads/fr/github-git-cheat-sheet.pdf