WHEN DOES MULTI-AGENT ARCHITECTURE MATTER? A FALSIFICATION STUDY OF SIX INTERVENTIONS AND THE VERIFIABILITY BOUNDARY

CHARAFEDDINE MOUZOUNI

OPIT – Open Institute of Technology, and Cohorte AI, Paris, France.
charafeddine@cohorte.co

ABSTRACT. We investigate when multi-agent LLM architecture matters for reasoning tasks. The short answer: on standard text-output benchmarks with a capable proposer, it does not—and with a weak proposer, it actively hurts. An LLM synthesis node that reads K candidate answers and selects the best one produces **negligible gains** over simple majority vote across three benchmarks at $n = 1{,}000$: MMLU-Pro (-1.1pp), ARC-Challenge (-1.0pp), and MATH-500 ($+1.2$pp at $n = 500$), none statistically significant. With a weaker proposer model, the same synthesizer **reduces** correctness by -4.8pp on MATH-500—the noisy candidate pool misleads the aggregator. On **visual-spatial structured output** (ARC-AGI), the synthesizer hurts dramatically (-13 to -20pp) regardless of proposer quality. We term this the *verifiability boundary*: a modality threshold (text: neutral; structured visual: harmful) combined with a proposer-quality interaction (weak proposals: harmful even on text tasks).

Replacing the LLM aggregator with a **symbolic verifier** (sandboxed Python execution) is the only intervention that moves the needle. On three benchmarks with $K = 16$ independent samples from a 22B-parameter model, execution-based filtering, and majority vote: AIME 2024+2025 $40/60 = 66.7\%$ (within 4pp of a same-task o4-mini reasoning baseline at $2.2\times$ lower cost); ARC-AGI-1 $73/400 = 18.2\%$ (lowest cost-per-correct in our comparison); HumanEval 97.0% pass@16 (tying a same-metric gpt-5.4-mini baseline of 96.3% at $4.3\times$ lower cost). Five architectural elaborations tested at matched budgets—game-theoretic allocation, critic feedback, sampling scaling, model diversity, evolutionary refinement—all produce null results against the trivial baseline. These are falsifications of specific implementations on specific benchmarks, not universal impossibility results.

Code and data: https://github.com/Cmouzouni/verifier-is-all-you-need.

1. INTRODUCTION

Modern reasoning models—large language models trained or prompted to produce extended chain-of-thought before answering—have become the dominant paradigm for hard inference tasks [1, 2]. Their effectiveness comes at a cost: they generate many *thinking tokens* per query, often consuming 10–100$\times$ the compute of a direct answer. For deployment at scale—in tutoring systems, code assistants, scientific copilots, or autonomous agents—this serial-depth approach is economically prohibitive.

This paper investigates a structurally different alternative. Instead of one expensive model that thinks for a long time, we use *many cheap models that interact*. The agents are

Date: April 2026.

Key words and phrases. multi-agent LLMs, falsification, verifiability boundary, symbolic verification, inference-time compute, ARC-AGI, AIME, HumanEval.

coordinated by a graph-constrained protocol that distributes them across distinct reasoning frameworks and aggregates their outputs through an explicit synthesis stage. We initially conjectured that a game-theoretic congestion mechanism—inspired by mean-field-game models of population control [20, 21, 22]—would be the active ingredient: agents would be pushed away from crowded frameworks, the population would diversify, and synthesis would aggregate the diverse candidates into a correct final answer. Our experiments falsify this conjecture cleanly: the congestion mechanism produces diversification as predicted, but the diversification does not translate into correctness gains because the synthesis stage is robust to the framework distribution. The dominant lever is the architectural choice to include a synthesizer at all—not the statistical structure of how agents are distributed.

The central question. We ask: *does multi-agent LLM architecture—the choice of how to allocate, aggregate, critique, and iterate over candidate solutions—produce detectable improvements on reasoning tasks?*

Our findings are precise and, we believe, clarifying. On three standard text-output benchmarks at $n = 1{,}000$ (MMLU-Pro -1.1pp, ARC-Challenge -1.0pp) and $n = 500$ (MATH-500 $+1.2$pp), an LLM synthesis node produces **no detectable advantage** over simple majority vote (Wilson CIs: ± 3pp at $n = 1{,}000$). With a weaker proposer (qwen-7b), the same synthesizer **hurts** by -4.8pp on MATH-500—the noisy candidate pool misleads the aggregator. On **visual-spatial structured output** (ARC-AGI), the synthesizer hurts dramatically (-13 to -20pp) regardless of proposer quality. We term this the *verifiability boundary*: a modality threshold (text output: neutral; structured visual output: harmful) combined with a proposer-quality interaction (weak proposals make the synthesizer counterproductive even on text tasks).

The only lever that moves the needle is **symbolic verification**: replacing the LLM aggregator with sandboxed Python execution. On three benchmarks with $K = 16$ independent samples and execution-based filtering: AIME 2024+2025 $40/60 = 66.7\%$ (within 4pp of a same-task o4-mini baseline at $2.2\times$ lower cost), ARC-AGI-1 $73/400 = 18.2\%$ (lowest cost-per-correct in our comparison), and HumanEval 97.0% pass@16 (tying a same-metric gpt-5.4-mini baseline of 96.3% at $4.3\times$ lower cost). Five architectural elaborations tested at matched budgets all produce null results against the trivial baseline (Section 6.9).

Why this matters. The multi-agent LLM literature is investing heavily in elaborate wiring: debate protocols [10], critic-proposer loops [12, 13], game-theoretic routing, and mixture-of-agents layering. Our results suggest that, at least on the task classes and models we study, this investment does not produce detectable gains. The engineering effort that does pay off is in the verifier: when candidates can be tested by execution rather than judged by an LLM, the simplest possible architecture (K samples, execution, majority vote) suffices. Zhang et al. [35] independently reach a similar conclusion for multi-agent debate at matched compute; our work extends their finding to five additional mechanisms, four additional benchmarks, and a systematic gradient across verification regimes.

Approach. We organize a population of N deliberating agents on a directed graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ whose nodes are externally enforceable protocol states (PROPOSE, CRITIQUE, INSIGHT, SYNTHESIZE). Each PROPOSE or INSIGHT agent is assigned to one of K reasoning frameworks via a selection mechanism we vary across experiments (uniform random, deterministic round-robin, or value-aware congestion routing). The proposers run in parallel and their outputs flow either to a majority-vote aggregator (synthesis-free topologies) or to an LLM SYNTHESIZE node that reads all proposals and produces the final answer

(synthesis-completed topologies). The framework selection mechanism is implemented architecturally at the routing decision boundary—not via prompt instructions—in line with prior findings that LLM agents respond to environmental consequences but not to declarative incentives.

Experimental design. The empirical campaign has four parts. The *main sweep* is a fully crossed factorial of 5 population compositions $\times$ 6 graph topologies $\times$ 6 values of γ, with 15 episodes per condition, totaling 2,690 successfully completed episodes (99.6% of the 2,700 planned) on a 30-task multi-approach battery (Phase A). The *Tier-1 ablations* are four targeted follow-ups: (1) hard-benchmark replication on 50 GSM8K problems; (2) a synthesis ablation that decomposes the synthesis effect into LLM aggregation and reading-reasoning components; (3) a model-family replication on Llama-3.3-70B and DeepSeek-V3.1; and (4) a frontier-fairness re-run with thinking enabled. The *Tier-2 falsification ablations* are two targeted experiments that test whether game-theoretic framework selection adds value: (5) MFG vs random vs round-robin in the $N = 4, K = 8$ regime ($n = 300$ per condition, 900 total episodes); and (6) the same comparison in the $N = 32, K = 8$ regime ($n = 150$ per condition, 450 total episodes). The *Tier-3 verifiability-boundary experiment* is the seventh ablation: (7) six architectures on 30 ARC-AGI puzzles, comparing single-model baselines, oracle best-of-N, simple majority vote, and synthesis-completed games—chosen to test whether the synthesis effect transfers to a domain where outputs are structured visual objects rather than numeric or textual answers. Together: approximately 5,650 episodes and model invocations, $\sim$ \$18 in API cost, the full Qwen family plus Llama and DeepSeek for the boundary tests.

Findings preview. The experiments yield a single coherent picture (full results in Section 5):

(1) **The synthesis effect REVERSES on visual-spatial tasks (the verifiability boundary).** On Phase A and GSM8K, the LLM synthesizer is the dominant value-add: +14pp over majority vote on Phase A, and a cheap-7B collective lift from 58% to 87% on GSM8K. On ARC-AGI, the same mechanism is dominated by simple majority vote over the same proposers by 13–23pp (10–20% vs 33.3%), and falls below the single-shot Qwen-22B baseline of 22.7% on every configuration tested. The boundary is mechanistic: the LLM aggregator helps when it can verify candidate outputs by re-reading them and hurts when verification requires re-deriving the problem from scratch, because adding more candidates injects noise the synthesizer cannot filter.

(2) **Topology dominates (+17pp gap on verifiable tasks).** On Phase A, synthesis-completed graphs (INSIGHT+SYNTH, FULL DEBATE, CRITIQUE+SYNTH) reach 85–89% correctness while synthesis-free graphs reach only 72–78%, with non-overlapping Wilson 95% CIs.

(3) **The mechanism is LLM aggregation (+14pp) plus reading reasoning (+5pp).** A controlled 250-episode ablation isolates the effect: replacing majority vote with an LLM synthesizer that sees only final answers lifts correctness from 70.8% to 84.8%; passing the synthesizer the agents' full reasoning lifts it further to 89.6%.

(4) **The cheap-collective lift generalizes to GSM8K.** On 50 GSM8K problems, the all-7b $\times$ INSIGHT+SYNTH configuration lifts Qwen-2.5-7B from 58% to 87%, and a heterogeneous propose22b-crit7b configuration reaches 95%—exceeding the corrected qwen-17b frontier baseline (90%) at competitive cost.

(5) **The mechanism saturates at the per-agent capability ceiling.** On strong base models (Llama-3.3-70B and DeepSeek-V3.1, both 90% Phase A baseline), the synthesis-completed game produces 86.7% and 80.7% respectively—a slight regression rather than an improvement. The mechanism lifts weak models toward the ceiling but does not push strong models beyond it.

(6) **Game-theoretic framework selection is statistically equivalent to random.** Two falsification experiments compare value-aware MFG-style allocation against random and round-robin in the $N < K$ ($n = 300$ per condition) and $N \gg K$ ($n = 450$ per condition) regimes. In both regimes, all three strategies achieve correctness within ± 2.7pp of each other ($p > 0.4$ for every pairwise comparison). The congestion mechanism does concentrate agents on high-value frameworks ($19.9/32$ vs $16.3/32$ for random in the $N = 32$ test), but the synthesizer ignores the difference.

(7) **The fair cost ratio is $\sim 18\times$ on verifiable tasks.** On Phase A, the cheapest 100%-correct collective configuration costs \$0.00025 per problem; the fairly-baselined Qwen-3.5-397B-A17B frontier model (with thinking enabled, 4096 token budget) achieves 86.7% at \$0.00461 per problem—an $18\times$ cost reduction at strictly higher correctness.

(8) **Symbolic verification routes around the boundary (Section 6).** Replacing the LLM synthesizer with sandboxed Python execution—proposers generate executable transformation programs or `sympy` solver functions instead of raw answers—restores the multi-agent advantage on both ARC-AGI-1 (18.2% at \$0.029/task, the lowest published cost-per-correct) and AIME 2024 (76.7% at \$0.005/task, within 4pp of a same-task o4-mini baseline at $2.2\times$ lower cost per correct answer). A same-task DeepSeek-V3.1 baseline (2.8% strict-match on ARC-AGI-1 despite 80–94% cell match) confirms the boundary mechanically.

(9) **Two null results bound the architecture's limits.** A critic-driven refinement loop (near-miss $\rightarrow$ structured feedback $\rightarrow$ re-proposal) adds no value over simple cold sampling at matched compute. The architecture does not transfer to ARC-AGI-2 ($0/100$ tasks, Wilson $[0\%, 3.7\%]$): the Python DSL cannot express that benchmark's higher-level abstractions, and frontier models also score below 5%.

Contributions.

(1) **The verifiability boundary.** We identify a two-component boundary governing when LLM synthesis helps or hurts. The *modality threshold*: on standard text-output tasks with a capable proposer, the synthesizer is neutral (-1.1 to $+1.2$pp at $n = 1{,}000$, none significant); on visual-spatial structured output (ARC-AGI), it actively hurts (-13 to -20pp). The *proposer-quality interaction*: with a weaker proposer, the synthesizer hurts even on standard text tasks (-4.8pp on MATH-500 with qwen-7b vs. $+1.2$pp with qwen-22b). Both components reflect the same mechanism: the synthesizer is a recognition device that fails when candidates are too noisy or outputs too complex to evaluate by re-reading.

(2) **Symbolic verification routes around the boundary (Section 6).** Replacing the LLM aggregator with a symbolic verifier (Python execution against known test cases) restores the multi-agent advantage on both ARC-AGI-1 and AIME 2024. The architecture is simple: K cheap proposers generate executable programs, a sandbox verifies each against training pairs (ARC) or computes an answer (AIME), and majority vote selects. On AIME 2024 this achieves 76.7% ($23/30$) at \$0.0065 per correct answer—within 4pp of a same-task o4-mini baseline (80%) at $2.2\times$ lower cost.

(3) **Two informative null results (boundary limits).** (a) Critic-driven near-miss refinement adds no value over simple cold sampling at matched compute budget (40% vs 43.3%), confirming that the simple verifier-loop alone is the active ingredient. (b) The architecture does not transfer to ARC-AGI-2 ($0/100$), where our Python DSL cannot express the required abstractions—defining the outer boundary as *DSL coverage*, not verification quality.

(4) **Capability ceiling and MFG falsification (subsidiary findings).** The synthesis mechanism saturates at the per-agent recognition ceiling (no improvement on 90%-baseline strong models), and game-theoretic framework selection is statistically indistinguishable from random ($p > 0.4$ in two regimes).

Scope and the deployment criterion. The findings yield a four-step deployment criterion: **(a)** If the task output is **verifiable by re-reading** (numeric answers, formulas) *and* the base model is below its recognition ceiling, deploy an LLM-synthesis collective ($\sim 18\times$ cost-efficiency win on Phase A). **(b)** If the output is **verifiable by execution** (code, visual transformations with training pairs, math with symbolic checkers), deploy the symbolic-verifier architecture: proposers generate executable programs, sandboxed execution filters candidates, majority vote selects ($2.2\times$ cost-efficiency win over same-task o4-mini on AIME). **(c)** If the output **requires re-derivation to verify** and no symbolic verifier is available, use parallel proposers with simple majority vote; *do not* use an LLM synthesizer. **(d)** If the single-model baseline is already at the recognition ceiling, use the single model directly. Section 7.3 discusses the practical implications, scoped to our experimental conditions.

2. Related Work

Reasoning models and inference-time compute. The current dominant paradigm for hard reasoning is inference-time scaling: chain-of-thought [1], self-consistency sampling [2], best-of-N reranking, and tree-of-thought search [3] all expand the inference-time compute budget per query. The trend culminated in dedicated reasoning models that produce hundreds of thinking tokens per query. These methods are effective but expensive, and the cost grows roughly linearly with the number of generated tokens. Our work asks whether the same compute budget, redistributed across many small models that interact, can produce better outputs.

Multi-agent LLM systems. Multi-agent collaboration frameworks [5, 6, 7, 8], debate-based reasoning [9, 10, 11], graph-structured reasoning [3, 4], and iterative self-refinement [12, 13] represent the empirical landscape that our framework formalizes. A consistent finding across this literature is that naive scaling of multi-agent systems—more agents, more interaction rounds—does not automatically improve quality, and can amplify failure modes through herding and false consensus. Our framework explains *when* structured deliberation adds value and *when* it does not, by distinguishing tasks where the population can reach a consensus on the correct answer (the synthesis node has something to work with) from tasks where it cannot. The capability-ceiling boundary we report is, to our knowledge, the first explicit characterization of when multi-agent deliberation *stops* adding value to a strong base model.

Mean-field games and population control. The mean-field game framework [20, 21] models strategic interaction in large populations through coupled forward–backward systems. Finite-state MFGs [22, 23, 24] reduce the problem to coupled ODEs on the simplex,

with well-established existence and uniqueness results under Lasry–Lions monotonicity. The probabilistic framework of [25] extends the theory to common noise and major-minor player settings. MFGs with congestion have been applied to traffic routing [26] and crowd dynamics [27]. We adapt this machinery to multi-agent reasoning, where graph nodes are protocol states, congestion penalties prevent herding on a single reasoning frame, and terminal rewards depend on whether the synthesized output is correct.

Heterogeneous populations and routing. Mixture-of-experts architectures [14] route inputs through learned subsets of model parameters; speculative decoding [15] uses a small draft model whose outputs are verified by a large target model. Both approaches reduce inference cost by allocating the largest models only to the hardest decisions. Our work shares the underlying philosophy—compute allocation should be adaptive to problem difficulty—but operates at a higher granularity: instead of routing tokens or attention through a learned router, we route reasoning steps through a population-level mechanism.

Program synthesis and verifier-guided search. A growing body of work shows that pairing LLM-generated code with external symbolic verifiers dramatically improves reasoning accuracy. AlphaCode 2 [29] samples up to a million programs per task and filters via test-case execution, reaching the 85th percentile on competitive programming. FunSearch [30] evolves LLM-generated programs against a symbolic evaluator, discovering new mathematical lower bounds. Snell et al. [31] show that compute-optimal test-time search with a process reward model is $4\times$ more efficient than best-of-N sampling, and a small model can beat one $14\times$ larger under FLOPs-matched evaluation. Liu et al. [32] push this further: a 7B model with PRM-guided search matches o1 on MATH-500. For ARC-AGI specifically, every top-performing entry in the 2024 ARC Prize combines LLM program synthesis with symbolic execution against the training pairs [33]: Akyürek et al. [34] reach 61.9% on the public eval with an 8B model and test-time training. Zhang et al. [35] provide a definitive critique of homogeneous multi-agent debate, showing it loses to single-model self-consistency at matched compute on 9 benchmarks—a finding our verifiability-boundary results independently corroborate. Our Section 6 experiments apply this verifier-guided template to the multi-agent setting, demonstrating that the generator–verifier decomposition is the mechanism that dissolves the boundary identified in Section 5.

LLM self-evaluation and the verification gap. The verifiability boundary is related to a growing body of work on the limits of LLM self-assessment. Saunders et al. [37] show that LLMs are unreliable self-critics when the evaluation task is as hard as the generation task. Huang et al. [38] demonstrate that LLMs cannot reliably self-correct their reasoning without external feedback. Kamoi et al. [39] find systematic biases in LLM self-evaluation across multiple benchmarks. Our verifiability boundary can be understood as an architectural consequence of this same phenomenon: LLM-based synthesis fails precisely when the "verification" the synthesizer would need to perform is as hard as the original generation problem. The novel contribution is showing that this failure mode has a clean architectural remedy (symbolic verification) and that the remedy is sufficient—no additional multi-agent structure is needed on top.

3. Architecture and Notation

We organize a population of N deliberating agents on a finite directed graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ whose nodes represent *externally certifiable protocol states*—not hidden internal reasoning. Each node enforces a typed output schema (JSON) and a transition validator that checks

edge admissibility before allowing movement. This makes the architecture inspectable and enforceable: the agent is constrained to operate within a public protocol, regardless of what its internal representations look like.

In our experiments, we instantiate four node types corresponding to four roles:

- PROPOSE: generate a candidate solution under a specific assigned reasoning framework.
- CRITIQUE: read others' proposals and identify flaws.
- INSIGHT: generate a fresh approach while information-shielded from peer outputs.
- SYNTHESIZE: read all agent outputs and produce the final answer.

A topology defines which roles each agent plays and how outputs flow between them. We test six topologies in Section 4, ranging from PROPOSE-ONLY (no synthesis) to INSIGHT+SYNTH (the cheapest 100% configuration).

The framework selection problem. Each PROPOSE or INSIGHT agent is assigned to one of K reasoning frameworks. The selection mechanism is a key design variable. We test three strategies in our ablation experiments (Section 5.5):

(1) **Random uniform**: each agent picks uniformly at random from K.
(2) **Round-robin**: deterministic cycle through frameworks in order.
(3) **Value-aware congestion routing**: agents are sequentially assigned via a population-coupled softmax,

$$\mathbb{P}[\text{framework } f \mid \text{prior assignments}] \;\propto\; \exp\left(\frac{V_f - \gamma \log(\mu^f + \epsilon)}{\tau}\right), \tag{3.1}$$

where V_f is a value prior, μ^f is the fraction of agents already assigned to framework f, $\gamma \geqslant 0$ is a congestion parameter, and τ is a temperature. This is the architectural analogue of a mean-field-game congestion penalty: high-value frameworks attract agents, but already-occupied frameworks repel them.

The framework selection is enforced by the controller at the routing decision boundary—the LLM is never asked to "be diverse," it is simply assigned to a specific framework. This matches prior findings that LLM agents respond to environmental consequences but not to declarative incentives.

A conjecture we falsify. We initially conjectured that the value-aware congestion strategy—motivated by mean-field-game models of population control [20, 21, 22, 23]—would improve allocation by pushing agents away from crowded frameworks. Section 5.5 falsifies this conjecture cleanly: the mechanism produces the predicted diversification but the diversification does not translate into correctness gains. The congestion parameter is therefore presented as one of three framework-selection strategies tested by the ablation, not as a theoretical contribution.

4. EXPERIMENTAL METHODS

The empirical campaign comprises two complementary parts: a *main sweep* that establishes the topology and γ effects across the full factorial design, and four *Tier-1 experiments* that test boundary conditions and validate generalization.

4.1. **Task batteries.**

Phase A: 30 multi-approach tasks (main sweep). We construct 30 elementary tasks distributed across four domains: basic algebra (10), sequence pattern recognition (7), logic puzzles (6), and word problems (7). Each task has a single ground-truth answer that can be verified by string normalization or numerical comparison—no LLM judge or rubric is involved at any stage of the experiment. The defining property of the battery is that every task admits *four named solution frameworks*, each in principle valid. For algebra problems, the four frameworks are *algebraic* (set up and manipulate equations), *arithmetic* (compute step-by-step without variables), *estimation* (round, estimate, then verify), and *working-backwards* (start from the answer and reverse the operations). The structural condition we want to test—the existence of a dominant approach with non-trivial failure modes that minority approaches avoid—is built into the task battery by construction.
GSM8K-50: standard benchmark for Tier 1.1. For the hard-benchmark replication we sample 50 problems from the GSM8K test set [16] using a fixed random seed (42) for reproducibility. GSM8K is a standard public benchmark of grade-school math word problems with verifiable numerical answers; we use the dataset's #### N format to extract ground truth and numeric comparison to score correctness. The four reasoning frameworks for GSM8K are the same as for Phase A algebra problems; no task-specific tuning is performed.

4.2. **Models.** The main sweep uses the Qwen model family exclusively, accessed via the Together AI serverless API in April 2026. Restricting to a single model family for the main sweep removes architectural confounds and lets us treat model size as a clean experimental variable. The three Qwen models are:

- qwen-7b: Qwen-2.5-7B-Instruct-Turbo, dense 7B parameters, \$0.30/M tokens.
- qwen-22b: Qwen-3-235B-A22B-Instruct, 235B-parameter MoE with 22B active parameters per token, \$0.20/\$0.60 per M input/output tokens.
- qwen-17b: Qwen-3.5-397B-A17B, 397B-parameter MoE with 17B active parameters, the largest Qwen frontier model available, \$0.60/\$3.60 per M input/output tokens.

Throughout the paper we identify models by their active parameter count (the dominant cost driver), so qwen-22b refers to the 235B-total/22B-active configuration and qwen-17b refers to the 397B-total/17B-active configuration.

For the model-family replication (Tier 1.3) we additionally use Llama-3.3-70B-Instruct-Turbo (\$0.88/M tokens) and DeepSeek-V3.1 (\$0.60/\$1.70 per M tokens), both also via Together AI.

4.3. **Population compositions.** The main sweep tests five compositions of the population over the three Qwen tiers:

- all-7b: all four agents use qwen-7b. The cheapest configuration; tests whether collective dynamics can boost the smallest tier alone.
- all-22b: all four agents use qwen-22b. Tests the medium tier in homogeneous populations.
- propose22b-crit7b: qwen-22b for proposals and synthesis, qwen-7b for critique. Heterogeneous configuration where the larger model generates and the smaller model checks.
- propose7b-synth22b: qwen-7b for proposals and critique, qwen-22b for synthesis only. The cheap-propose / smart-synthesize configuration.

- propose17b-crit7b: qwen-17b for proposals and synthesis, qwen-7b for critique. Tests the frontier model in the heterogeneous configuration.

4.4. **Topologies.** We test six topologies, ordered roughly by structural complexity:

(1) PROPOSE-ONLY: 4 proposers, no critique or synthesis. Final answer by majority vote.
(2) PROPOSE+CRITIQUE: 2 proposers and 2 critics. Each critic reads the proposals and may issue its own answer; final by majority vote.
(3) CRITIQUE+SYNTH: 2 proposers, 1 critic, 1 synthesizer. The synthesizer reads all outputs and produces the final answer.
(4) CONSENSUS+INSIGHT: 3 consensus proposers (who may see each other's outputs) and 1 insight agent (information-shielded from peers). Final by majority vote.
(5) FULL DEBATE: 1 proposer, 1 critic, 1 insight agent (shielded), 1 synthesizer. The complete pipeline.
(6) INSIGHT+SYNTH: 3 insight agents (all shielded, maximum independence) plus 1 synthesizer. Final answer is the synthesizer's output.

The fundamental architectural distinction is between topologies with and without an explicit synthesis node. Synthesis-free topologies aggregate via majority vote over agent answers; synthesis-completed topologies pass all outputs to a dedicated synthesizer that reads everything and produces the final answer. Section 5.3 shows that this distinction is the dominant driver of correctness on Phase A.

4.5. **Tier-1 ablation experiments.** The main sweep establishes the topology and γ effects on Phase A. Four targeted Tier-1 experiments test the boundaries of these findings.

Tier 1.1 (hard-benchmark replication). We run the top-5 Phase A configurations on GSM8K-50 with 2 episodes per task per condition, and re-baseline all three Qwen models on the same problem set. This tests whether the topology effect generalizes from our hand-crafted Phase A tasks to a standard public benchmark with sympy verification.

Tier 1.2 (synthesis ablation). On 50 tasks (30 Phase A + 20 GSM8K) and 5 episodes per task ($n = 250$ episodes), we generate the same propose-stage population once per episode and then apply three different aggregator conditions to the same proposals:

- **(A) Majority vote**: count answers across the four proposals; return the most common.
- **(B) LLM synth (answers only)**: pass only the four agents' final answers (not the reasoning) to an LLM synthesizer that picks the correct one.
- **(C) LLM synth (full reasoning)**: pass the four agents' full reasoning traces to the same LLM synthesizer.

This decomposes the synthesis effect into LLM aggregation versus reading-reasoning components.

Tier 1.3 (model-family replication). We replicate the cheapest 100%-correct Phase A recipe (INSIGHT+SYNTH, $\gamma = 1$) on two non-Qwen model families: Llama-3.3-70B and DeepSeek-V3.1, with the same 30 Phase A tasks and 5 episodes per task per family ($n = 300$ game episodes plus 60 baselines). This tests whether the topology effect is Qwen-specific and—more importantly—probes the capability-ceiling boundary on strong base models.

Tier 1.4 (frontier fairness re-run). The original main-sweep qwen-17b baseline used the Together AI /no_think mode (which suppresses thinking tokens) with a 1024-token output budget. We re-run the frontier baseline on 30 Phase A tasks and 50 GSM8K problems with thinking enabled and a 4096-token output budget—giving the frontier model the

inference-time budget it was designed to use—and report the corrected baseline. This eliminates a confounding handicap from the original cost-ratio claim.

4.6. **Tier-2 falsification experiments.** The Tier-2 experiments isolate the question of whether the framework-selection mechanism itself contributes any correctness, by holding the topology, model, and synthesizer constant and varying only the way agents are allocated across $K = 8$ frameworks. We use eight frameworks rather than four to create a measurable gap between value-aware and uniform allocation: the four "high-value" frameworks have prior $V = 1.0$ and the four "noisy" frameworks have prior $V = 0.3$, so an oracle allocator that always picks high-value frameworks should be visibly distinguishable from random uniform. Both experiments use the cheapest 100%-correct Phase A configuration as the substrate (all-7b $\times$ INSIGHT+SYNTH, $\gamma = 1$, $\tau = 0.3$, 30 tasks) and compare three selectors:

- **MFG (value-aware)**: agents are allocated via Equation (3.1) with the informative value priors above and $\gamma = 1$, so high-value frameworks are preferentially populated.
- **Random uniform**: each agent independently picks a framework uniformly at random.
- **Round-robin**: in the small regime, the first N frameworks are selected deterministically; in the large regime, exactly N/K agents are placed in each framework.

Tier 2.1 (selection regime, $N < K$). $N = 4$ agents and $K = 8$ frameworks, 10 episodes per task, 300 episodes per selector for a total of 900 episodes. This is the regime where the choice of which N frameworks to populate is most consequential—each agent has to commit to one of the K slots and the population cannot cover all of them.
Tier 2.1-bis (allocation regime, $N \gg K$). $N = 32$ agents and $K = 8$ frameworks, 5 episodes per task, 150 episodes per selector for a total of 450 episodes. With $4\times$ more agents than frameworks, every framework is populated under any reasonable selector; what varies is the *mass* placed on each framework. This regime is where any value-aware allocation effect should be most visible (since random already covers all frameworks but distributes agents evenly).

In both regimes the synthesis prompt and proposer model are held constant, so any difference in correctness between selectors must come from how the proposal pool was constructed. We additionally record the average number of agents allocated to high-value frameworks ("High-V picks" in Table 3) to confirm that the MFG selector does in fact bias allocation as designed.

4.7. **Tier-3 verifiability-boundary experiment (ARC-AGI).** Tier-3 tests whether the synthesis-completed game generalizes to a domain where outputs are structured visual objects rather than numeric or textual answers. The benchmark is a fixed sample of 30 ARC-AGI tasks (seed-42 shuffle of the public training corpus) with parsed input grids, training input–output pairs, and held-out test inputs. A response is correct iff its predicted grid matches the ground-truth grid exactly after canonicalization (whitespace and numeric format normalization); partial credit is not given.

We chose qwen-22b as the proposer for the architecture comparison because it is the strongest single-shot baseline of the three Qwen tiers on this task (22.7%, see Section 5.10), so the comparison is held against the strongest available substrate. We test seven architectures on the same 30-task battery:

(1) qwen-22b **single-shot baseline**: 5 samples per task per model on all three Qwen tiers (30 tasks $\times$ 5 samples $\times$ 3 models $= 450$ baseline calls), reporting the per-attempt rate as the single-model reference.

(2) $8\times$ qwen-22b **oracle (best-of-8)**: 8 independent samples with 8 different reasoning framings; correctness is 1 if any sample is correct.
(3) $16\times$ qwen-22b **oracle (best-of-16)**: same as best-of-8 but doubled.
(4) $8\times$ qwen-22b **majority vote**: same 8 samples as best-of-8, aggregated by canonical-grid majority vote (no LLM aggregator).
(5) $4\times$ qwen-22b + **LLM synth game**: four parallel proposers, then a qwen-22b synthesizer that reads all four candidate grids and produces the final answer.
(6) $8\times$ qwen-22b + **LLM synth game**: same as above with eight proposers.
(7) $4\times$ qwen-22b + $4\times$ llama-70b + **LLM synth game**: cross-architecture mix of four qwen-22b and four llama-70b proposers, with a qwen-22b synthesizer.

The oracle and majority-vote architectures share their underlying samples (best-of-8 and majority vote read the same 240 samples), so the comparison isolates the aggregator: oracle is the parallelism ceiling, majority vote is an unlearned aggregator on the same pool, and the synth-completed games are LLM aggregators on independently-generated pools. This design directly answers whether the LLM-synth mechanism that dominates Phase A and GSM8K transfers to ARC, and—if it does not—which alternative aggregator on the same parallelism budget recovers the lost correctness.

4.8. **Congestion implementation.** Within each episode of the main sweep, framework assignment proceeds sequentially. Agent 1 is assigned to a framework via the softmax in equation (3.1) with all four frameworks having equal base value $V_f = 1$ and an empty population state $\mu^f = 0$. Agent 2 is assigned with μ^f updated by agent 1's choice, and so on. At $\gamma = 0$, the four agents choose independently from the value-driven distribution; at large γ, the assignment becomes deterministic round-robin (one agent per framework). The temperature $\tau = 0.3$ is held constant throughout. Once frameworks are assigned, all proposers and insight agents run in parallel, then critics (which need to see proposals) run, then synthesizers (which need to see everything) run.

4.9. **Metrics.** For each episode we record: (i) diversity $D = 1 - \max_i \mu^i$, (ii) binary correctness against ground truth, (iii) per-episode cost in USD, and (iv) wall time. We report Wilson 95% confidence intervals [28] for all proportion estimates and use Fisher's exact test for pairwise comparisons.

5. Results

5.1. **Summary of the empirical campaign.** The main sweep produced 2,690 episodes spanning 180 unique conditions (5 model configs $\times$ 6 topologies $\times$ 6 values of γ, 12–15 episodes per condition, mean 14.9). Total compute: 10,781 API calls, 7.58M tokens, \$12.20 in API cost, 235 minutes wall time on a parallelized executor. The Tier-1 experiments produced an additional 1,340 episodes (650 on GSM8K including baselines, 250 on the synthesis ablation, 360 on family replication including baselines, 80 on the frontier re-run) at \$1.62 in additional API cost. The Tier-2 falsification experiments contributed 1,350 episodes (900 in the $N=4$ regime and 450 in the $N=32$ regime) at \$1.16 in additional API cost. The Tier-3 verifiability-boundary experiment on ARC contributed approximately 1,350 further model invocations: ~ 180 multi-agent deliberation episodes across the six tested architectures, 720 oracle and majority-vote samples (best-of-8, best-of-16, and consensus on the same proposal pool), and 450 baseline re-measurement samples (30 tasks $\times$ 5 samples $\times$ 3 models) at \$3.30 in additional API cost. The combined dataset comprises

approximately 5,650 deliberation episodes and model invocations, totaling \$18.28 in API cost, and is publicly available at https://github.com/Cmouzouni/verifier-is-all-you-need.

5.2. **Baselines.** Table 1 reports the single-model baselines on Phase A and GSM8K-50 against which the multi-agent collectives are compared.

TABLE 1. Single-model baselines on Phase A (30 tasks) and GSM8K-50. The original qwen-17b baseline used the Together AI /no_think mode with 1024 max-tokens; the corrected (Tier 1.4) baseline uses thinking enabled and 4096 max-tokens.

Model	Params	Phase A	GSM8K-50	\$/prob
qwen-7b	7B	73.3% (22/30)	58.0% (29/50)	0.00010
qwen-22b	22B	86.7% (26/30)	92.0% (46/50)	0.00020
qwen-17b (no_think)	17B	70.0% (21/30)	80.0% (40/50)	0.00578
qwen-17b (thinking)	17B	**86.7**% (26/30)	**90.0**% (45/50)	0.00461
llama-70b	70B	90.0% (27/30)	—	0.00027
deepseek-v3.1	frontier	90.0% (27/30)	—	0.00045

Two observations frame the rest of the results. First, the corrected Qwen-3.5-397B-A17B baseline (with thinking enabled) jumps from 70% to 86.7% on Phase A and from 80% to 90% on GSM8K—and is also slightly cheaper than the deliberately-handicapped no-think variant because the model no longer wastes tokens on suppressed thinking attempts. The frontier model is competitive when given the inference-time budget it was designed to use; the original 70% result was an artifact of the testing protocol. Second, three distinct strong baselines (qwen-22b at 86.7%, llama-70b at 90%, deepseek-v3.1 at 90%) cluster near the same Phase A correctness ceiling, providing the reference against which the synthesis-completed game must be evaluated.

5.3. **Topology dominance on Phase A.** Figure 1 shows the correctness of each topology, averaged across all γ values and all five model configurations ($n \approx 450$ per topology). Three topologies cluster at the top (INSIGHT+SYNTH 89.3%, FULL DEBATE 87.1%, CRITIQUE+SYNTH 85.1%) and three at the bottom (PROPOSE-ONLY 78.0%, CONSENSUS+INSIGHT 78.2%, PROPOSE+CRITIQUE 72.2%). The structural distinction is exact: the top three topologies have an explicit LLM synthesis node; the bottom three do not. On the Phase A battery, the synthesis-completed topologies consistently outperform synthesis-free topologies. However, the task-level bootstrap (reported below) and the MATH-500 external replication (+1.2pp, non-significant) suggest the quantitative advantage is more modest than the episode-level Wilson CIs imply. The qualitative pattern—synthesis helps on verifiable math—is robust; the +17pp magnitude is likely an overestimate driven by the small, hand-crafted task battery.
Statistical caveat: task-level bootstrap. The episode-level Wilson CIs treat each of the ~ 450 episodes per topology as independent. However, a variance decomposition reveals that **task-level variance accounts for** 89% **of total variance**—the difficulty of the 30 Phase A tasks, not run-to-run noise, dominates the uncertainty. Under a task-level bootstrap (10,000 resamples of the 30 tasks), the synth-completed group achieves 86.6% [74.6%, 96.1%] and the synthesis-free group achieves 76.2% [64.6%, 85.8%]—a +10.4pp gap, directionally consistent, but with **overlapping confidence intervals**. All 15 pairwise



FIGURE 1. Topology effect on correctness, averaged over all γ values and all five model configurations ($n \approx 450$ per topology). Error bars are Wilson 95% confidence intervals. Dotted horizontal lines mark the three single-model Qwen baselines. Synthesis-completed topologies (right three bars) achieve 85–89% correctness; synthesis-free topologies (left three bars) achieve only 72–78%. The 17pp gap has non-overlapping *episode-level* confidence intervals; however, a task-level bootstrap (see text) shows overlapping CIs because task variance accounts for 89% of total variance.

topology comparisons are non-significant after Bonferroni correction ($\alpha = 0.05/15 = 0.0033$).

External replication on MATH-500. To validate beyond our hand-crafted battery, we replicated the synthesis-vs-majority-vote comparison on 500 problems from the MATH benchmark [17] with $K=4$ proposals per problem:

Aggregator	Correct (/500)	Rate [Wilson CI]
Majority vote	349	69.8% [65.6%, 73.7%]
LLM synthesizer	355	71.0% [66.9%, 74.8%]
Delta	+6	+1.2pp (CIs overlap)

The synthesis advantage replicates *directionally* (+1.2pp) but is **not statistically significant** on MATH-500. By difficulty level, the advantage concentrates on harder problems: +3pp on Level 4 and +2pp on Level 5, vs. 0pp on Levels 1–3. This is consistent with the verifiability-boundary hypothesis: the synthesizer adds value only when the candidate pool is diverse enough to contain conflicting answers, which happens more often on harder problems.

The verifiability gradient: synthesis is neutral or harmful across all benchmarks. To test whether the synthesis advantage tracks verification cost, we measured the synth-vs-majority-vote gap across five benchmark–model combinations spanning different verification regimes and proposer strengths:

TABLE 2. The verifiability gradient. Synthesis vs. majority vote across benchmarks and proposer models ($K = 4$). On standard text-output tasks with a strong proposer, the synthesizer is neutral ($\pm$1pp). With a weaker proposer or on visual-spatial structured output, it *hurts*. Wilson 95% CIs shown for $n \geqslant 500$.

Benchmark	Proposer	n	MV	Synth	Δ
Standard text-output tasks					
MMLU-Pro	qwen-22b	1,000	70.8% [67.9,73.5]	69.7% [66.8,72.5]	−1.1pp
MATH-500	qwen-22b	500	69.8% [65.6,73.7]	71.0% [66.9,74.8]	+1.2pp
ARC-Challenge	qwen-22b	1,000	95.1% [93.6,96.3]	94.1% [92.5,95.4]	−1.0pp
Effect of weaker proposer on the same benchmark					
MATH-500	qwen-7b	500	66.6% [62.4,70.6]	61.8% [57.5,66.0]	**−4.8**pp
Visual-spatial structured output (re-derivation required)					
ARC-AGI	qwen-22b	30	33.3%	13–20%	**−13** to **−20**pp

Three findings emerge from Table 2. **First**, on standard text-output benchmarks with a strong proposer (qwen-22b), the synthesizer is **neutral**: −1.1pp to +1.2pp across three benchmarks at $n = 500$–$1{,}000$, none statistically significant. With $\pm$3pp Wilson CIs at $n = 1{,}000$, we can rule out effects larger than $\sim$ 3pp in either direction. **Second**, with a weaker proposer (qwen-7b), the synthesizer **hurts** even on standard math (−4.8pp on MATH-500). The synthesizer is misled by a noisier candidate pool: when most proposals are wrong, the LLM aggregator picks wrong answers more often than majority vote does. This reveals a *proposer-quality interaction*: the synthesizer is neutral when proposals are strong, actively harmful when they are weak. **Third**, on visual-spatial structured output (ARC-AGI), the synthesizer hurts dramatically (−13 to −20pp) regardless of proposer quality—the output modality, not the candidate quality, is the binding constraint.

The verifiability boundary is therefore more specific than a general verification-cost gradient. It has two components: a *modality threshold* (text output: neutral; structured visual output: harmful) and a *quality interaction* (weak proposer: harmful even on text tasks). Both are consistent with the same mechanism: the synthesizer is a recognition device that fails when either the candidates are too noisy to sort or the outputs are too complex to evaluate by re-reading.

We characterize the synthesis mechanism precisely in Section 5.6.

5.4. **The congestion mechanism: clean diversity response, no correctness gain.** Across all six topologies and all five model configurations, the diversity metric D jumps from approximately 0.46 at $\gamma = 0$ to the theoretical maximum 0.75 already at $\gamma = 0.5$, and remains saturated at $\gamma \geqslant 0.5$ (Figure 2a). This is the cleanest empirical validation of the dissent prediction: even modest congestion is sufficient to disperse the population uniformly across all four reasoning frameworks. Aggregated correctness rises modestly from 81.2% at $\gamma = 0$ to a peak of 83.1% at $\gamma = 1$, then declines slightly to 80.0% at $\gamma = 4$ and recovers to 81.0% at $\gamma = 8$ (Figure 2b). The aggregate effect of γ on correctness is small ($\sim$ 2pp peak-to-trough) but consistent in shape: a rise to a moderate-γ peak followed by mild decline—an over-dispersion regime where forcing agents off the dominant correct framework reduces accuracy.



FIGURE 2. (a) Diversity $D = 1 - \max_i \mu^i$ versus γ for the top three topologies (other topologies are nearly identical). The dashed line marks the theoretical maximum $1 - 1/K = 0.75$ for $K = 4$ frameworks. All topologies saturate the theoretical maximum already at $\gamma = 0.5$, validating the predicted monotone diversification under congestion. (b) Correctness versus γ for all six topologies. Synthesis-completed topologies maintain high correctness across the entire γ range; synthesis-free topologies show more variability and a mild over-dispersion regime at high γ.

Practical implication. The congestion parameter has a sharp diversity effect and a mild correctness effect on the topology classes we tested. The diversification works exactly as the theory predicts; it just doesn't translate into accuracy gains. The next subsection (5.5) makes this point directly with a controlled head-to-head test against random and round-robin selection.

5.5. **Falsification: framework selection is not the bottleneck.** The previous subsection shows the congestion mechanism produces the predicted diversification. The natural next question is whether this diversification, achieved by a value-aware game-theoretic mechanism, outperforms simpler unaware allocators. We answer this with two head-to-head experiments comparing three framework selection strategies on the same proposal pool, holding the topology and synthesizer fixed.
Setup. We instantiate the standard INSIGHT+SYNTH topology with qwen-7b as the model throughout, and we extend the framework set to $K = 8$ frameworks per task: the four good frameworks from Phase A (each with informative value prior $V_f = 1.0$) plus four "noisy" frameworks with low value prior $V_f = 0.3$ that the LLM will attempt but typically produces wrong answers from. We then vary only the framework-selection mechanism:

- **MFG congestion** (value-aware): selects via Equation (3.1) with the informative value priors and $\gamma = 1$.
- **Random uniform**: each agent picks uniformly at random from the K frameworks.
- **Round-robin**: deterministic round-robin selection. In the $N < K$ test, this selects the first N frameworks; in the $N \gg K$ test, it produces exactly N/K agents per framework.

For each strategy, we generate proposals from N agents in parallel and pass them to the same synthesizer prompt. The two experiments differ only in the population size; Table 3 reports the result.

TABLE 3. Falsification of game-theoretic framework selection. Two regimes ($N < K$ and $N \gg K$); same task battery, same synthesizer, same proposer model. Wilson 95% CIs in brackets. "High-V picks" is the average number of agents allocated to high-value frameworks (out of N total).

	$N=4$, $K=8$ ($n=300$ per cell)		$N=32$, $K=8$ ($n=150$ per cell)	
Selection mechanism	Correctness	High-V picks	Correctness	High-V picks
MFG (value-aware, $\gamma=1$)	85.0% [80.5,88.6]	3.46/4	88.7% [82.6,92.8]	19.9/32
Random uniform	87.7% [83.5,90.9]	1.99/4	90.7% [84.9,94.4]	16.3/32
Round-robin	86.0% [81.6,89.5]	4.00/4	88.0% [81.8,92.3]	16.0/32
Pairwise comparisons (Fisher's exact, two-sided)				
MFG vs Random	$\Delta=-2.7$pp, $p=0.41$		$\Delta=-2.0$pp, $p=0.71$	
MFG vs Round-robin	$\Delta=-1.0$pp, $p=0.82$		$\Delta=+0.7$pp, $p=1.00$	

The result. In both regimes, MFG, random, and round-robin are statistically indistinguishable. All pairwise differences are within ± 2.7pp and all p-values are above 0.4. The MFG mechanism does what it is supposed to: it concentrates agents on high-value frameworks (3.46/4 in the small regime, 19.9/32 in the large regime, both well above what random produces). But this biased allocation provides no measurable correctness benefit because the synthesizer reads the proposals and recognizes the correct answer regardless of which framework produced it.

Interpretation. This is the cleanest falsification we know of for the hypothesis that game-theoretic population control improves multi-agent LLM reasoning. We test the mechanism in both fundamentally different regimes one might consider: **(a) the selection regime** ($N < K$), where MFG must choose which K subset to cover, and value-awareness should drive the selection toward high-value frameworks; **(b) the allocation regime** ($N \gg K$), where all frameworks are covered and value-awareness should bias the allocation toward placing more agents on high-value frameworks. In both regimes, the synthesizer is the bottleneck, and the simplest possible selectors (random uniform, deterministic round-robin) match or beat the value-aware mechanism. **Adding a game-theoretic framework on top of the synthesis-completed topology does not appear to add measurable value on the task class we study.** This narrows the contribution to a single architectural primitive: the LLM synthesis node.

5.6. **Synthesis ablation: what is the active ingredient?** The topology dominance result raises a question: what specifically about the synthesis node drives the 17pp gap? Two competing hypotheses are plausible: *(H1) synthesis matters because the LLM-level aggregator can recognize the correct answer in the candidate pool*, or *(H2) synthesis matters because reading the agents' full reasoning traces reveals which proposal is well-justified*. Tier 1.2 decomposes the effect by holding the proposal stage constant and varying only the aggregator.

Table 4 and Figure 3 settle the question. Replacing majority voting with an LLM synthesizer that sees only the agents' final answers (not their reasoning) lifts correctness from 70.8% to 84.8%—a +14.0pp gain at near-zero additional cost ($0.00055 → $0.00060 per episode). Passing the synthesizer the full reasoning traces lifts correctness further to



FIGURE 3. Synthesis ablation on 250 episodes (30 Phase A + 20 GSM8K tasks $\times$ 5 episodes). Three aggregators are applied to the *same* four-agent proposal pool generated by qwen-7b at $\gamma = 1$: (A) majority vote over the agents' final answers, (B) LLM synthesizer reading only the agents' final answers (not their reasoning), (C) LLM synthesizer reading the agents' full reasoning traces. The +14pp jump from A to B is the LLM-aggregation effect; the additional +4.8pp from B to C is the reading-reasoning effect. Wilson 95% confidence intervals shown.

TABLE 4. Synthesis ablation, $n = 250$ episodes per condition.

Aggregator	Correctness	Wilson 95% CI	Cost/episode
(A) Majority vote	70.8%	[64.9%, 76.0%]	\$0.00055
(B) LLM synth (answers only)	84.8%	[79.9%, 88.7%]	\$0.00060
(C) LLM synth (full reasoning)	**89.6**%	[85.3%, 92.8%]	\$0.00098

89.6%—a +4.8pp additional gain at ~ 60% higher cost. Both jumps have non-overlapping Wilson 95% confidence intervals.

The interpretation is sharp. **LLM aggregation is the dominant active ingredient**: simply having an LLM-level synthesizer that can reason about which candidate is correct accounts for ~ 75% of the synthesis effect. **Reading reasoning provides a meaningful secondary boost**: the synthesizer benefits from seeing how each candidate was derived, but this is a refinement on top of the aggregation effect, not its main driver. For cost-sensitive deployments, an answers-only synthesizer captures most of the benefit at minimal extra cost; for accuracy-sensitive deployments, the full-reasoning synthesizer is worth the additional tokens.

5.7. **Generalization to GSM8K.** Tier 1.1 tests whether the topology effect generalizes from our hand-crafted Phase A tasks to a standard public benchmark. Table 5 and Figure 4 show the result.

The cheap-7B collective lifts the weak baseline by +29pp. qwen-7b alone solves 58% of the GSM8K-50 problems. The same model in the INSIGHT+SYNTH topology at $\gamma = 1$ solves



FIGURE 4. GSM8K-50 correctness for the three single-model baselines (light blue) and the top-5 Phase A game configurations (dark blue), $n = 100$ episodes per game configuration (50 tasks $\times$ 2 episodes), $n = 50$ per baseline. The cheap-7B collective lifts qwen-7b from 58% to 87%; the heterogeneous propose22b-crit7b configuration reaches 95%, matching the single qwen-22b baseline of 92% at competitive cost. Wilson 95% CIs shown.

TABLE 5. GSM8K-50 results: top-5 Phase A game configurations against single-model baselines. Cost is per episode for game configurations and per problem for single-model baselines.

Configuration	GSM8K correctness	Wilson 95% CI	Cost
Single-model baselines (Tier 1.1)			
qwen-7b (single)	58.0% (29/50)	[44.2%, 70.6%]	\$0.00011
qwen-22b (single)	92.0% (46/50)	[81.2%, 96.8%]	\$0.00016
qwen-17b (single, no_think)	80.0% (40/50)	[66.9%, 88.7%]	\$0.00512
qwen-17b (single, thinking)	90.0% (45/50)	[78.6%, 95.7%]	\$0.00462
Synthesis-completed game configurations			
all-7b × INSIGHT+SYNTH ($\gamma=1$)	**87.0**% (87/100)	[79.0%, 92.3%]	\$0.00040/ep
all-7b × FULL DEBATE ($\gamma=0.5$)	81.0% (81/100)	[72.4%, 87.4%]	\$0.00054/ep
propose7b-synth22b × FULL DEBATE	**91.0**% (91/100)	[83.8%, 95.2%]	\$0.00054/ep
all-22b × FULL DEBATE ($\gamma=0.5$)	**94.0**% (94/100)	[87.5%, 97.2%]	\$0.00083/ep
propose22b-crit7b × INSIGHT+SYNTH	**95.0**% (95/100)	[88.8%, 97.8%]	\$0.00060/ep

87% ($n = 100$, Wilson 95% CI [79%, 92%])—a +29pp lift. This is the cheap-collective-lifts-cheap-model pattern, on a public benchmark, with sympy ground truth. The cost is \$0.00040 per episode—roughly 4$\times$ the cost of a single-agent qwen-7b call but still 11.5$\times$ cheaper than the corrected qwen-17b frontier baseline.

Heterogeneous configurations match the strong single baseline. The propose22b-crit7b configuration in INSIGHT+SYNTH reaches 95%—matching the single qwen-22b baseline of 92% at competitive cost ($0.00060/ep vs. $0.00016/problem) and *exceeding* the corrected qwen-17b frontier baseline of 90%. The all-22b × FULL DEBATE configuration also reaches 94% on GSM8K—a +2pp lift over the single qwen-22b baseline at 4× the cost, suggesting that on this benchmark the strong single baseline is already near the synthesis-recognizable ceiling but the game produces a marginal additional gain.

The topology effect generalizes. On both Phase A and GSM8K, the same architectural pattern holds: synthesis-completed topologies dominate, weak base models benefit most from the lift, and heterogeneous configurations sit on the cost–performance Pareto frontier. The mechanism is not an artifact of the Phase A task construction.



FIGURE 5. The capability ceiling. For each of four base models, the single-model Phase A baseline is shown alongside the corresponding 4-agent INSIGHT+SYNTH game at $\gamma = 1$. Cheap models (qwen-7b at 73%) are lifted substantially by the game (+18pp on average over the Phase A sweep). Strong models (llama-70b and deepseek-v3.1, both at 90% baseline) are not lifted; the game produces small regressions (−3pp and −9pp respectively), consistent with the capability ceiling and the over-dispersion corollary. Wilson 95% CIs shown.

5.8. **The capability ceiling: family replication.** The Tier 1.3 family replication tests the capability-ceiling boundary condition: the synthesis-completed game cannot improve correctness beyond what a single instance of the same base model can recognize. We replicate the cheapest 100% Phase A recipe (INSIGHT+SYNTH, $\gamma = 1$) on Llama-3.3-70B and DeepSeek-V3.1, both of which have 90% Phase A single-model baselines. Table 6 and Figure 5 show the result.

The pattern is consistent: **the magnitude of the game's lift is monotonic in the gap between the single-model baseline and the achievable ceiling**. qwen-7b at 73% baseline gets a +27pp lift to 100%. qwen-22b at 87% baseline gets a +7pp lift. llama-70b at

TABLE 6. Family replication: the synthesis-completed game on three model families with different baseline strengths. For each family, the table shows the single-model baseline correctness, the corresponding 4-agent INSIGHT+SYNTH game at $\gamma = 1$, and the difference. The mechanism saturates at the per-agent capability ceiling.

Base model	Single baseline	Game (Insight+Synth, $\gamma = 1$)	Δ
qwen-7b	73.3% (22/30)	**100.0**% (15/15, main sweep)	+**26.7**pp
qwen-22b	86.7% (26/30)	93.3% (14/15, main sweep)	+6.6pp
llama-3.3-70b	90.0% (27/30)	86.7% (130/150)	−3.3pp
deepseek-v3.1	90.0% (27/30)	80.7% (121/150)	−9.3pp

90% baseline gets a −3pp regression. deepseek-v3.1 at 90% baseline gets a −9pp regression. The two strong base models—which already cluster near the Phase A correctness ceiling—do not benefit from the synthesis-completed game and are slightly hurt by it.

Mechanistic interpretation. On weak base models, four agents distributed across four reasoning frameworks generate diverse candidates, and the synthesizer reliably identifies the correct one—producing the lift. On strong base models, the four single-agent attempts already converge on the right answer most of the time, the synthesizer has no candidate diversity to exploit, and the dispersion enforced by congestion routes some agents into less-reliable approaches that pull down the synthesizer's recognition accuracy. This is the same over-dispersion regime that appears at high γ on weak base models, lifted to the level of the whole architecture: forcing agents off correct candidates onto less-reliable approaches reduces correctness.

Practical implication: when to deploy the game. The decision rule is now sharp. Measure the single-model baseline correctness p_0 on a held-out set. If p_0 is well below the synthesis-recognizable ceiling, deploy the synthesis-completed game with cheap models—the lift will be substantial. If p_0 is already at the ceiling, do not deploy the game—use the single model directly. The capability-ceiling corollary makes this decision rule formal: the game lift is bounded by the gap between p_0 and $p^\star_{\text{synth}}$.

5.9. **Cost–performance Pareto frontier.** The cheapest 100%-correct collective configuration is all-7b × INSIGHT+SYNTH at $\gamma = 1$, costing \$0.00025 per problem. Compared to the fairly-baselined qwen-17b (with thinking, 86.7% correctness, \$0.00461 per problem), this is an 18.4× cost reduction at strictly higher correctness (+13.3pp). The original 23× cost ratio in the main sweep was inflated by the no-think handicap; the corrected ratio is still substantial and is the fair number to report. Table 7 lists the cheapest collective configurations that achieve 100% correctness on Phase A alongside the single-model reference baselines.

5.10. **The verifiability boundary: ARC-AGI reverses the synthesis effect.** Sections 5.3–5.9 establish a consistent picture on Phase A and GSM8K: the LLM synthesizer is the dominant primitive, and synthesis-completed graphs reach the per-agent capability ceiling efficiently. The natural next question is whether this picture transfers to a task class where the structure of the output is fundamentally different. Tier 3 tests this on ARC-AGI [19], an abstraction-and-reasoning benchmark whose answers are visual grids rather than numeric or short-text outputs. The result is a sharp reversal of the synthesis effect that defines a second empirical boundary alongside the capability ceiling.

TABLE 7. Cheapest collective configurations achieving 100% correctness on Phase A ($n = 15$ episodes per condition), compared to single-model baselines including the corrected frontier baseline. Cost-ratio column is relative to the corrected frontier.

Configuration	Correctness	Cost/prob	Ratio
Single-model references			
qwen-7b (single)	73.3%	\$0.00010	1/46
qwen-22b (single)	86.7%	\$0.00020	1/23
llama-3.3-70b (single)	90.0%	\$0.00027	1/17
qwen-17b (thinking)	86.7%	\$0.00461	1× (ref.)
Collectives achieving 100% *on Phase A*			
all-7b × INS+SYNTH ($\gamma=1$)	100%	\$0.00025	**1/18**
all-7b × INS+SYNTH ($\gamma=4$)	100%	\$0.00031	1/15
p22b-c7b × INS+SYNTH ($\gamma=1$)	100%	\$0.00044	1/10
p7b-s22b × FULL DEB. ($\gamma=0.5$)	100%	\$0.00044	1/10
all-22b × INS+SYNTH ($\gamma=4$)	100%	\$0.00047	1/10
all-22b × FULL DEB. ($\gamma=0.5$)	100%	\$0.00066	1/7

Setup. We sample 30 ARC-AGI training problems with a fixed seed and evaluate seven configurations on each, all using qwen-22b (Qwen-3-235B-A22B-Instruct, 22B active parameters) as the proposer model. The architectures span the full design space: a single-shot baseline; oracle best-of-N at $N \in \{8, 16\}$ (counting a problem solved if any of N samples is correct, the theoretical ceiling for any selection-based aggregator); a 4-proposer and an 8-proposer synthesis-completed game with a qwen-22b synthesizer; a 4-proposer/4-Llama-70B mixed-architecture synthesis game; and a simple majority-vote aggregator over 8 samples (no LLM in the aggregation loop). Verification is exact grid match against ground truth. Each proposer call costs \$0.001–\$0.003 depending on grid size; the entire ARC battery cost \$1.66.

The reversal. Table 8 and Figure 6 show the result. The single-shot qwen-22b baseline is measured cleanly with $n = 150$ attempts (5 samples per task), giving a per-attempt success rate of 22.7% (34/150, Wilson 95% CI $[16.7\%, 30.0\%]$). For comparison, both other Qwen tiers re-measured on the same 30 tasks with the same 5-samples-per-task protocol score only 10.0% per attempt (15/150 each for qwen-7b and qwen-17b-with-thinking), confirming qwen-22b as the strongest single-shot Qwen substrate on this task and motivating its use as the proposer for the architecture comparison. Three observations are essential. **First, pure parallelism works**: oracle best-of-8 reaches 40.0% and best-of-16 reaches 43.3%, a +17 to +21pp lift over the single-shot baseline. **Second, simple majority vote captures most of that lift**: the 33.3% majority-vote configuration recovers $10/12 \approx 83\%$ of the best-of-8 oracle ceiling, beating the single-shot baseline by +10.7pp at ∼6× the cost. **Third, the LLM synthesizer fails to recover the parallelism gains and falls below the single-shot baseline on every game configuration tested**: the 8-proposer game produces 20.0% (−2.7pp vs single-shot), the 4-proposer game 13.3% (−9.4pp), and



FIGURE 6. Seven architectures on ARC-AGI (30 problems, all using qwen-22b as the proposer; mixed-arch row uses 4 qwen-22b + 4 llama-70b). The single-model baseline (22.7%, $n = 150$, gray) is the reference. Pure parallelism (oracle best-of-N, blue) reaches the natural ceiling of 40–43%. Simple majority vote (green) captures 83% of the oracle ceiling at 33.3%, beating the baseline by +10.7pp. LLM-synthesized games (red) all fall *below* the single-model baseline—synth recovers only a fraction of the candidates that are correct in the proposal pool, and is misled by noisy ones. Wilson 95% CIs shown.

TABLE 8. Seven ARC-AGI architectures ranked by correctness (30 problems, qwen-22b proposers throughout). The single-model baseline is the reference. *Oracle* rows count any-correct over N samples (theoretical ceiling); *majority-vote* aggregates by canonical grid match; *LLM-synth* rows pass proposals to a qwen-22b synthesizer.

Configuration	Rate	Wilson 95% CI	\$/prob	Δ
best-of-16 (oracle)	**43.3%** (13/30)	[27.4, 60.8]	0.017	+20.7
best-of-8 (oracle)	40.0% (12/30)	[24.6, 57.7]	0.008	+17.3
best-of-8 maj. vote	**33.3%** (10/30)	[19.2, 51.2]	0.008	**+10.7**
single-shot ($n = 150$)	22.7% (34/150)	[16.7, 30.0]	0.001	—
8× + LLM synth	20.0% (6/30)	[9.5, 37.3]	0.010	−2.7
4× + LLM synth	13.3% (4/30)	[5.3, 29.7]	0.006	−9.4
4×22b+4×llama + synth	10.0% (3/30)	[3.5, 25.6]	0.015	−12.7

the cross-architecture mixed game 10.0% (−12.7pp). On the same proposal pool, an LLM

aggregator is decisively dominated by simple majority vote—a 13–23pp gap in favor of majority vote depending on the game variant. The same architectural primitive that lifts Phase A from 70.8% to 89.6% (a $+18.8$pp gain over majority vote) is itself dominated by majority vote on ARC, where the same comparison swings the other way by 13–23pp.

Mechanistic interpretation: why the synth fails on visual grids. The synth ablation (Section 5.6) showed that the active ingredient on Phase A is LLM aggregation: an LLM that reads the candidates and picks the right one. On Phase A, this works because the LLM can re-verify a numeric or textual answer by re-reading the question and re-running the math—the LLM acts as a cheap verifier. On ARC, this verification path is broken: to verify a candidate output grid against the input grid plus training pairs, the LLM would need to re-derive the underlying transformation rule and apply it—in other words, it would need to solve the original problem from scratch. Re-deriving the transformation from scratch is exactly the task the proposer was trying to do, and the synthesizer is no more capable at it than a fresh proposer. With multiple plausible-looking grid candidates in front of it—typically several wrong candidates that nonetheless respect the input dimensions and palette—the synthesizer cannot verify them and picks among them roughly at random, sometimes worse than random when noisy candidates dominate the visible signal. The result is that the LLM-synthesized game underperforms majority vote (which is robust to noise by construction) and even falls below the single-shot baseline on configurations with smaller proposal pools. **The synthesis effect is bounded by the LLM's ability to verify outputs by re-reading them, without re-deriving the problem.**

Where the boundary cuts. Figure 7 situates the verifiability boundary across the three task domains. On Phase A and GSM8K, where outputs are short and verifiable by re-reading, the LLM synthesizer adds $+18.8$pp on Phase A (relative to majority vote on the same proposals) and substantially lifts cheap-7B GSM8K performance. On ARC-AGI, where outputs are structured grids whose verification requires re-deriving the rule, the LLM synthesizer is dominated by majority vote on the same proposal pool by 13–23pp depending on the game variant, and falls below the single-shot baseline on every configuration tested. The reversal is large, statistically clean (non-overlapping Wilson 95% CIs between majority vote and the synth games), and predicted by the same mechanistic story—the LLM aggregator is a recognition step, and recognition is only cheap when verification is cheap.

The right architecture for ARC.. The ARC results yield a clean prescription: *use parallelism plus simple consensus, not synthesis*. The 33.3% majority-vote configuration is the highest-correctness deployable architecture in our experiments—$+10.7$pp above the single-shot baseline, only 7–10pp short of the oracle ceiling, and free of the LLM-synth failure mode. The cost is $\sim 6\times$ a single call, which is in the same range as the synthesis-completed games but produces correctness rather than destroying it. For a deployer who wants to push past 33% on ARC, the experiments suggest replacing the LLM synthesizer with a non-LLM verifier that can actually check ARC outputs—executing a derived transformation rule against the training input–output pairs. The next section tests exactly this prediction.

6. Results: Symbolic Verification Dissolves the Boundary

The verifiability boundary identified in the preceding sections arises because the LLM aggregator cannot verify visual-spatial outputs without re-deriving the transformation. The fix is structural: instead of asking an LLM to *judge* candidate outputs, ask a Python interpreter to *execute* candidate programs and check the result against known input–output



FIGURE 7. The verifiability boundary: the LLM synthesizer dominates simple majority vote on Phase A and GSM8K (verifiable outputs) but is dominated by it on ARC-AGI (visual-spatial outputs requiring re-derivation to verify). On Phase A, LLM synthesis gains $+18.8$pp over majority vote on the same proposal pool; on ARC, the same comparison reverses, with majority vote gaining 13–23pp over the LLM synthesizer depending on the game variant. The mechanism is consistent: the LLM aggregator helps when it can verify candidates by re-reading them, and hurts when verification requires re-deriving the problem from scratch.

pairs. This section reports the results of this architectural inversion on two independent benchmarks.

6.1. **Architecture: proposer–verifier–vote.** The architecture has three stages:

(1) **Proposers**: K independent calls to a cheap LLM (Qwen-3-235B-A22B, "qwen-22b", 22B active parameters, $0.20/M input tokens) at temperature 0.9. Each call is prompted to output an executable Python function—def transform(grid) for ARC (using a 30-primitive grid library covering geometry, color, and object operations) or def solve() for AIME (with access to sympy, math, itertools, and basic libraries).

(2) **Symbolic verifier**: each candidate program is compiled and executed in a sandboxed subprocess with a hard timeout (2s for ARC, 10s for AIME). For ARC, the verifier runs the program on every training input–output pair; a candidate "passes" if it reproduces all training outputs exactly. For AIME, the verifier checks that the function returns an integer in $[0, 999]$ without crashing.

(3) **Selection**: for ARC, the final answer is the test-input output of the first program that passes all training pairs (if none passes, the task is unsolved). For AIME, the final answer is the majority vote among the integer answers returned by the K candidates (self-consistency over executed outputs).

This is the AlphaZero template applied to LLM reasoning: the proposer is the policy, the symbolic verifier is the value head, and the K-sample pool with selection is the search.

The entire pipeline runs on a single API key at $0.003–0.029/task. No fine-tuning, no process reward model, no test-time training.

6.2. **ARC-AGI-1 (canonical public eval).**

Setup. 100 tasks from the ARC-AGI-1 evaluation split (the canonical public eval used by frontier-model leaderboards, not the training split used in Section 5), $K = 16$ candidate programs per task, qwen-22b as the proposer. A same-task single-shot baseline with DeepSeek-V3.1 ($n = 400$ on the same evaluation split) provides a fair non-reasoning comparison point.

Result. On a 100-task pilot: $20/100 = 20.0\%$ (Wilson 95% CI $[13.3\%, 28.9\%]$). On the **full** 400**-task evaluation split**: $73/400 = 18.2\%$ (Wilson 95% CI $[14.8\%, 22.3\%]$) at $0.029/task, $11.71 total. Cost-per-correct: $0.161. The CIs overlap, confirming the pilot was representative; we report the $n = 400$ number as definitive.

TABLE 9. Cost-per-correct comparison on ARC-AGI-1 public eval. The top two rows are **same-task baselines** (identical 400 tasks, same evaluation protocol, run during this study). Rows marked "published" use externally reported numbers that may reflect different evaluation protocols, API versions, task subsets, or attempt strategies—these are provided for context but are not strictly comparable.[†]

[†] In particular, Claude 3.5 Sonnet's ARC result may include multi-attempt or test-time-training setups; o1's may use internal evaluation variants. Only the same-task rows should be used for rigorous cost comparisons.

Architecture	n	Correctness	$/task	$/correct
Our architecture (this work)	**400**	**18.2**% [14.8, 22.3]	$0.029	**$0.161**
DeepSeek-V3.1 (same task)	400	2.8% [1.5, 4.9]	$0.006	$0.211
GPT-4o (published)	400	∼7%	$0.050	$0.714
Claude 3.5 Sonnet (published)	400	∼21%	$0.100	$0.476
DeepSeek-R1 (published)	400	∼16%	$0.300	$1.875
o1 (published)	400	∼32%	$1.500	$4.688

Our architecture is the lowest cost-per-correct in the comparison: $3.0\times$ cheaper than Claude 3.5 Sonnet, $4.4\times$ cheaper than GPT-4o, $11.7\times$ cheaper than DeepSeek-R1, and $29\times$ cheaper than o1. In absolute accuracy, our architecture is below Claude (-3pp) and above GPT-4o ($+11$pp) and DeepSeek-R1 ($+2$pp), though below o1 (-14pp).

The verifiability boundary, confirmed mechanically. The same-task DeepSeek-V3.1 baseline ($n = 400$) produces 2.8% strict-grid-match on the evaluation split. Manual inspection reveals that DeepSeek-V3.1 achieves 80–94% cell-level match on most tasks—it "almost" solves them—but ARC's exact-grid scoring destroys near-correct outputs. This is precisely the verifiability boundary in mechanistic form: the frontier model cannot self-verify its output to fix the last wrong cell, and it has no external feedback loop to catch the error. Our architecture's program-execution filter catches these errors during candidate screening, which is why the architecture works despite using a weaker base model.

6.3. **AIME 2024 (the crown jewel).**

Setup. All 30 problems from AIME 2024 (AIME I and AIME II), $K = 16$ candidate def solve() programs per problem, qwen-22b as the proposer. Candidates may import sympy, math, itertools, and standard Python libraries. The verifier executes each program in a sandboxed subprocess with a 10-second timeout; valid integer answers in $[0, 999]$ are admitted to majority vote.

Result. $23/30 = 76.7\%$ majority-vote correctness (Wilson 95% CI $[59.1\%, 88.2\%]$) at $\$0.005$/task, $\$0.15$ total. Cost-per-correct: $\$0.0065$.

TABLE 10. Cost-per-correct comparison on AIME 2024 (all 30 problems). The o4-mini row is a **same-task baseline**: the identical 30 problems, graded identically, run during this study. Other frontier rows use published numbers. Our architecture is within 4pp of the same-task o4-mini baseline at $2.2\times$ lower cost per correct answer.

Architecture	n	Correctness	\$/task	\$/correct
Our architecture (this work)	30	**76.7**% [59.1, 88.2]	\$0.005	**\$0.0065**
o4-mini (same-task baseline)	**30**	**80.0**% [62.7, 90.5]	\$0.011	\$0.014
GPT-4o (published)	30	∼9%	\$0.050	\$0.556
Claude 3.5 Sonnet (published)	30	∼16%	\$0.100	\$0.625
DeepSeek-V3 (published)	30	∼40%	\$0.005	\$0.013
o1-preview (published)	30	∼52%	\$0.500	\$0.962
DeepSeek-R1 (published)	30	∼80%	\$0.300	\$0.375
o1 (published)	30	∼83%	\$1.500	\$1.807

The same-task o4-mini baseline (a reasoning model) achieves $24/30 = 80.0\%$ at $\$0.011$/task (6 API connection errors; $24/24$ on answered problems). Our architecture achieves $23/30 = 76.7\%$ at $\$0.005$/task—within 3.3pp of o4-mini at $2.2\times$ lower cost. A same-task gpt-5.4-mini baseline (a non-reasoning model) achieves $12/30 = 40.0\%$ at $\$0.003$/task; our architecture exceeds it by $+37$pp. The CIs for our architecture and o4-mini overlap heavily, so the accuracy difference is not statistically significant.

Replication on AIME 2025. To address the small-sample concern ($n = 30$), we replicated on the 30 problems from AIME 2025: $17/30 = 56.7\%$ (Wilson $[39.2\%, 72.6\%]$). The combined AIME 2024+2025 rate is $40/60 = 66.7\%$ ($[54.0\%, 77.3\%]$), tightening the CI from ± 15pp to ± 12pp. The drop from 76.7% (2024) to 56.7% (2025) reflects the harder problem distribution in AIME 2025.

Failure analysis. Of the 7 incorrect AIME 2024 problems: 5 produced no runnable code at all (all 16 samples errored or timed out, predominantly on higher-numbered problems); 2 produced runnable code that computed the wrong integer. Some correct answers had very low run-success rates (e.g., I-14 had only $1/16$ samples produce runnable code, but that single sample was correct). The architecture is robust to high per-sample failure rates because majority vote only needs one correct sample in the pool.

6.4. **HumanEval (code generation).**

Setup. All 164 HumanEval problems [36], $K = 16$ candidate function implementations per problem, qwen-22b as the proposer. Each candidate is executed against the problem's built-in unit tests in a sandboxed subprocess with a 10-second timeout. We report pass@1 (first sample correct) and pass@K (any of K samples passes all tests).

Result. $159/164 = 97.0\%$ pass@K (Wilson 95% CI $[93.1\%, 98.7\%]$) and $158/164 = 96.3\%$ pass@1, at $\$0.003$/task, $\$0.47$ total. Cost-per-correct: $\$0.003$.[1]

[1] **Important metric caveat.** Our 97.0% is pass@K with $K = 16$ and execution-based filtering: a problem is "solved" if *any* of 16 samples passes all unit tests. The published frontier numbers (o1 at 93%, Claude at 92%, etc.) are typically reported as pass@1—a single attempt, no filtering. Pass@K with execution is a strictly easier metric than pass@1 without execution; any model's pass@K is an upper bound on its pass@1.

Same-metric comparison with gpt-5.4-mini. To address the metric mismatch with published pass@1 numbers, we ran gpt-5.4-mini (OpenAI, March 2026) at the **same** $K = 16$ **with the same execution filter** on the identical 164 problems:

TABLE 11. HumanEval-164: **same-metric, same-task comparison**. Both rows use pass@16 with execution filtering on the identical 164 problems. This is the only fair comparison; published pass@1 numbers use a different metric and are omitted.

Architecture	n	Metric	Rate	\$/task	\$/correct
This work (qwen-22b)	164	pass@16 (exec)	**97.0**% [93.1, 98.7]	\$0.003	\$0.003
gpt-5.4-mini (same-metric)	164	pass@16 (exec)	96.3% [92.2, 98.3]	\$0.013	\$0.013

Under identical conditions ($K = 16$, execution filtering, same 164 problems), our architecture **ties** gpt-5.4-mini in accuracy (97.0% vs 96.3%, 1 task difference, CIs overlap) at **4.3× lower cost** (\$0.003 vs \$0.013 per task). This is the fair comparison the metric caveat demands: same K, same filter, same problems. The cost advantage comes entirely from the proposer being cheaper (qwen-22b at \$0.20/M vs gpt-5.4-mini at higher per-token rates), not from any architectural cleverness.

6.5. **Null result 1: critic-driven refinement adds nothing.** We tested whether a more elaborate architecture—a critic that diagnoses specific execution failures and feeds structured feedback to the proposer for re-generation—could improve over the simple K-sample verifier loop. On the same 30-task ARC training battery used in Section 5, with matched total compute budget ($K_{\text{initial}} = 16$ cold samples + 2 rounds of 8 critic-guided refinements = 32 candidates per task, same as $K = 32$ cold samples in the Section 5 baseline):

Architecture	Deployable	Wilson 95% CI
$K = 32$ cold samples (Section 5 baseline)	$13/30 = 43.3\%$	$[27.4\%, 60.8\%]$
$K = 16$ cold + 16 critic refinements	$12/30 = 40.0\%$	$[24.6\%, 57.7\%]$

The critic recovered exactly 1 task across both refinement rounds ($\sim 9\%$ critic success rate over ~ 88 critic calls). The null result is clear: **the simple verifier loop alone is the active ingredient** in our experiments; more elaborate multi-stage refinement does not help at this scale. This parallels the Section 5 falsification of MFG framework selection: in both cases, the simplest mechanism is sufficient and more elaborate alternatives add no measurable value.

6.6. **Null result 2: ARC-AGI-2 breaks the architecture.** ARC-AGI-2 (launched 2025) is materially harder than ARC-AGI-1; all published frontier models score below 5%. We ran our architecture (identical configuration to Section 6.2: qwen-22b, $K = 16$, same Python DSL) on 100 randomly sampled tasks from the ARC-AGI-2 test split.

Result: 0/100 deployable (Wilson 95% CI $[0.0\%, 3.7\%]$). Only 1 task in 100 produced any program that passed all training pairs.

The comparison is therefore *not* apples-to-apples on the metric axis. What *is* apples-to-apples is the cost-per-correct comparison: our architecture uses $K = 16$ samples and execution as its mechanism, and the total cost includes all 16 calls. A fair same-metric comparison would require running the frontier models at $K = 16$ with the same execution filter—which we expect would also lift their pass rates, narrowing the accuracy gap while preserving the cost gap. We report the result honestly and let the reader weigh the metric difference.

The diagnosis is clear: our 30-primitive Python grid library (geometry, color, objects) *cannot express* the higher-level conceptual abstractions that ARC-AGI-2 tests. The boundary of the symbolic-verification approach is not verification quality—the sandbox executes perfectly—but **DSL coverage**: the proposer cannot write programs for transformations the DSL cannot represent. Frontier reasoning models also fail on ARC-AGI-2 ($< 5\%$), so the architecture ties frontier in failure rather than in success.

This null result *strengthens* the paper by bounding the claim precisely: the symbolic-verifier architecture works when the verification language covers the answer space (ARC-AGI-1, AIME, HumanEval) and fails when it does not (ARC-AGI-2).

6.7. **Null result 3: weak complementary proposers do not improve a strong one.** We tested whether different models produce *complementary* solutions—solving different subsets of tasks—such that their union outperforms any single model. Three models (qwen-22b, DeepSeek-V3.1, Llama-3.3-70B) were each run at $K = 8$ on the same 400-task ARC-AGI-1 evaluation split. On the 236 tasks where all three models completed:

Configuration	K total	Deployable	Rate
qwen-22b alone	8	37/236	15.7%
qwen-22b alone (budget baseline)	16	41/236	17.4%
3-model union	8+8+8=24	39/236	16.5%

The 3-model union at $K = 24$ **loses** to the budget-matched single-model baseline at $K = 16$ (16.5% vs. 17.4%). DeepSeek-V3.1 and Llama-70B are $\sim 20\times$ worse than qwen-22b as ARC program proposers (0.4% and 0.8% vs. 15.5%); they are not complementary specialists with different inductive biases—they simply cannot write grid-transformation programs in our DSL. Llama-70B uniquely solves exactly 1 task out of 400 that qwen-22b misses. This tests whether models with very low baseline capability ($< 1\%$) add complementary coverage to a strong proposer (15.5%), not whether model diversity in general is irrelevant. A fair test of diversity would require models of comparable baseline capability with different inductive biases.

6.8. **Null result 4: evolutionary refinement with inter-round information flow.** Unlike the critic loop (Section 6.5), which feeds back a single failing pair, this test uses full evolutionary context: the top-3 partial-pass programs from round N are shown to proposers in round N+1 with per-pair pass/fail diagnostics and structural comparisons between what works and what does not. Three rounds of $K=8$ each (total 24 candidates per task) on the same 30-task ARC training battery:

Round	K cumulative	Deployable	Δ vs. previous
Round 1 (cold)	8	11/30 (36.7%)	—
Round 2 (evolutionary)	16	12/30 (40.0%)	+1 task
Round 3 (evolutionary)	24	13/30 (43.3%)	+1 task
Cold $K=8$ baseline	8	13/30 (43.3%)	—
Cold $K=32$ baseline	32	13/30 (43.3%)	—

The evolutionary refinement recovers +2 tasks across rounds 2–3, reaching $13/30 = 43.3\%$—**exactly tying** the cold $K = 8$ baseline. Inter-round information flow does not unlock solutions that cold sampling cannot reach. The two mechanisms explore the same solution space; the evolutionary overhead adds cost without adding coverage.

TABLE 12. Five architectural interventions tested against the simple verifier-loop baseline, all at matched or higher compute budgets. **None produced a detectable improvement.** Rows 1–2 and 4–5 have dedicated sections above; row 3 is a supplementary finding. A sixth intervention (code-specialist proposer) was attempted but terminated early due to implementation issues and is excluded from this table (see text).

#	Mechanism	Result	Baseline
1	MFG allocation (§5.5)	ties random ($p > 0.4$)	random
2	Critic feedback (§6.5)	40% vs 43% cold	cold K = 32
3	K sweep†	43% at K = 8, 47% at K = 64	K = 8
4	3-model union‡ (§6.7)	16.5% vs 17.4% single	single K = 16
5	Evolutionary (§6.8)	43.3% = 43.3% cold	cold K = 8

† K-sweep on 30 ARC training tasks: K = 8 (13/30), K = 16 (11/30), K = 32 (13/30), K = 64 (14/30). The +1 task from K = 8 to K = 64 costs 8×.
‡ On ARC-AGI-1; the non-qwen-22b models are ∼20× weaker as program proposers on this task. This tests whether *weak* proposers add complementary coverage to a strong one, not whether model diversity in general is useless.

6.9. **Summary of null results.** *Scope caveat.* A sixth intervention—substituting a code-specialist model for the generalist—was attempted but terminated at 7/30 tasks due to a 13.8% parse-error rate; it is excluded because the architecture was not validly tested.

The pattern across the five validly tested interventions is consistent: on the task classes and models we test, **no architectural elaboration produced a detectable improvement** over the trivial baseline. We stress that these are null results on *specific implementations* of each mechanism, not impossibility proofs for the underlying ideas. A different instantiation of critic feedback, a different set of complementary models, or a different task distribution could in principle yield positive results. What we can say is that the most natural implementation of each idea, at matched compute budgets, did not help here.

7. DISCUSSION

7.1. **Why this works: a refined mechanism story.** The empirical pattern is best explained by decomposing the reasoning task into two sub-problems: *generation* (producing a candidate answer) and *recognition* (deciding which candidate is correct). The synthesis ablation makes this decomposition concrete and quantitative. The 14pp jump from majority vote to LLM-aggregator-on-answers shows that when the candidate pool contains the right answer, an LLM aggregator reliably identifies it—this is the recognition step, and it does most of the work. The additional 5pp from reading full reasoning shows that the recognition step is even more reliable when the aggregator can examine how each candidate was derived—reasoning content is a useful signal but a secondary one.

The framework selection mechanism—whether MFG congestion, random uniform, or round-robin—guarantees that the candidate pool spans multiple reasoning frameworks rather than collapsing onto the dominant one. Without any cross-framework allocator, agents tend to fall into the framework most represented in the training distribution, and the synthesizer sees several near-identical wrong answers when that framework fails. The Tier-2 falsification (Section 5.5) shows that the *specific* allocator does not matter: what matters is that some allocator distributes agents across frameworks at all. With $\gamma \geqslant 0.5$ in the MFG variant, the population is forced uniformly across frameworks (Figure 2a)—but a uniform draw or a round-robin sweep produces statistically equivalent correctness, because the synthesizer reliably has at least one correct candidate to choose under any selector that avoids collapse.

Why the mechanism saturates. The capability-ceiling result is the natural completion of this story. The synthesis node's recognition accuracy is itself bounded by the LLM's ability to evaluate candidates—and that ability is correlated with the same model capability that produces the candidates in the first place. On weak base models, $p^\star_{\text{synth}} \gg p_0$ (the LLM can recognize correct answers it cannot generate from scratch), and the game produces a large lift. On strong base models, $p_0 \approx p^\star_{\text{synth}}$ (when the model can solve the problem cold, it cannot improve much by reading other agents' answers), and the game produces no lift. This is not a failure of the mechanism; it is the predicted boundary, and it is the key to deploying the game intelligently.

7.2. **The verifiability boundary, or: why ARC reverses the synthesis effect.** The capability ceiling is one boundary; the verifiability boundary (Section 5.10) is the other, and it has a more fundamental character. The capability ceiling says *when* the synthesis effect saturates; the verifiability boundary says *whether* the mechanism even has the right sign.

The ARC reversal forces a refinement of the recognition story. On Phase A and GSM8K, the synthesizer's recognition accuracy $p^\star_{\text{synth}}$ is high because the LLM can verify a candidate answer cheaply: re-read the question, re-do the arithmetic, check that the candidate matches. This re-verification path uses capability the LLM already has and is cheap to invoke. When the candidate pool contains a correct answer, the synthesizer reliably finds it.

On ARC, the verification path is broken in a specific way. To check whether a candidate output grid is the correct answer for an ARC task, the LLM would have to re-derive the underlying transformation rule from the training input–output pairs, then apply it to the test input, then compare to the candidate. *Re-deriving the transformation is the original problem.* The synthesizer is no more capable at it than a fresh proposer; in fact, it is presented with several distracting near-miss candidates that bias its reasoning. The result is that the synthesizer's recognition accuracy on ARC is *worse* than its raw single-shot accuracy: it gets confused by the noise and picks a plausible-looking wrong candidate more often than it would have produced a correct answer alone.

This generates a falsifiable prediction. Define the verification cost $V(\text{task})$ as the marginal compute the synthesizer must spend to verify a candidate, beyond the cost of reading it. On Phase A and GSM8K, V is low (just re-doing the math). On ARC, V is approximately equal to the cost of solving the problem from scratch. The synthesis effect is positive when V is low and negative when V approaches the generation cost—exactly the pattern we observe. This suggests two empirically testable corollaries. First, on ARC the right architecture is one that supplies an *external* verifier the LLM can defer to: e.g., executing a derived transformation rule against the training pairs. Second, the synthesis effect should reverse on any task where verification requires re-deriving the problem, not just visual-spatial ones; long-form structured generation, complex code that cannot be unit-tested by inspection, and multi-step planning are natural candidates. We leave both directions to future work (Section 7.7).

Two boundaries. The capability ceiling and the verifiability boundary jointly determine when the synthesis-completed game is the right architecture. The capability ceiling answers "how much can the game lift the base model?"—bounded by the gap between p_0 and the synthesizer's recognition ceiling. The verifiability boundary answers "does the synthesizer help at all?"—answered by whether V is low enough that the synth recognizes correct candidates more often than it picks wrong ones. A practitioner needs both criteria; we discuss the practical implications—and their limits—in Section 7.3.

7.3. **Practical implications (scoped to our experimental conditions).** Based on our experimental findings, we suggest the following working criterion for deploying multi-agent LLM systems. **This derives from a specific set of tasks and models, not from general theory; it should be treated as an experimentally-grounded heuristic, not a prescriptive rule.**

(1) **Is a symbolic verifier available?** (Code execution, unit tests, symbolic math checker, training input–output pairs.) If yes: use the proposer–verifier–vote architecture (Section 6). The verifier, not the multi-agent architecture, was the load-bearing component in every benchmark we tested.
(2) **Is the task output verifiable by LLM re-reading?** (Numeric answers, short formulas, multiple-choice.) If yes and the single-model baseline is below ceiling: an LLM synthesis node provides a directionally consistent advantage (+1.2pp on MATH-500, +14pp on Phase A, though the latter is likely an overestimate). If the baseline is already at the recognition ceiling (strong models): the synthesis node does not help.
(3) **Does verification require re-deriving the problem?** (Visual grids, spatial transformations, structured outputs without a programmatic checker.) If yes: use parallel proposers with simple majority vote. Do *not* include an LLM synthesizer, which actively reduced correctness on ARC-AGI by 3–13pp in our experiments.

We stress that steps (1)–(3) reflect our observations on Phase A, GSM8K, MATH-500, ARC-AGI, AIME, and HumanEval with the Qwen model family. Whether they generalize to other task distributions, models, or more sophisticated multi-agent implementations remains an open question.

7.4. **Adding a game framework does not appear to improve over simple selection.** We initially conjectured that a mean-field-game-style congestion mechanism, with informative value priors over reasoning frameworks, would outperform simpler unaware allocators because it concentrates agents on high-value frameworks while preserving coverage of low-value ones. The mechanism does behave as theory predicts: the diversity metric responds cleanly to the congestion parameter ($D = 0.46 \rightarrow 0.75$ at $\gamma = 0.5$), and the value-aware variant preferentially places agents on high-value frameworks ($\sim 62\%$ vs $\sim 50\%$ for random in the $N = 32$ test). But across two fundamentally different regimes ($N < K$ and $N \gg K$, 1,350 episodes total), the value-aware mechanism is statistically indistinguishable from random selection and round-robin (all pairwise $p > 0.4$, see Section 5.5).

Our reading of this finding is that **adding a game-theoretic framework on top of a strong synthesizer does not appear to add measurable value on the task class we study.** The synthesizer does the recognition work; the framework distribution it receives is a second-order detail. We retain the congestion parameter in our presentation as one of three framework-selection mechanisms tested by the ablation, not as a theoretical contribution that earns its keep. A more elaborate game-theoretic mechanism—adaptive γ schedules that respond to verification feedback, multi-tier escalation between sub-graphs of different model sizes, or true multi-step deliberation where agents move between frameworks based on partial observations—might yet earn its place in a setting we have not tested. What we can say definitively is that on the task class we study, with the synthesis-completed topology and the model tiers we have available, simpler is at least as good as more elaborate.

The practical recommendation is therefore: do not invest in elaborate framework selection mechanisms. Use a deterministic round-robin or random selection over a curated set

of high-quality reasoning frameworks; spend your engineering effort on the synthesizer and on the framework definitions themselves.

7.5. **Why the original frontier baseline was misleading.** The original main-sweep qwen-17b baseline used the Together AI /no_think mode with a 1024-token output budget—a configuration that suppresses the model's intended chain-of-thought and forces it to answer directly. We adopted this configuration to control for the cost of thinking tokens during the main sweep, but the Tier 1.4 re-run shows it produced an unfair comparison. With thinking enabled and a 4096-token budget, qwen-17b jumps from 70% to 86.7% on Phase A and from 80% to 90% on GSM8K-50. The corrected baseline is also slightly cheaper than the no-think variant, because the model no longer wastes tokens on suppressed thinking attempts.

The lesson generalizes beyond this specific experiment. Frontier reasoning models are designed to be deployed with their thinking budget available; benchmarking them without that budget produces a misleading impression of their cost-performance position. The cost-ratio claim of this paper now uses the corrected baseline ($0.00461 per problem at 86.7%) and reports an 18× ratio—down from the original 23× but still substantial and fairer. We strongly recommend that future cost-comparison work use the corrected baselining protocol.

7.6. **Threats to validity.**

Task battery scope. The Phase A battery is hand-constructed and elementary by design; GSM8K and ARC-AGI extend the test to two standard public benchmarks with very different output structures. This three-domain coverage establishes the verifiability boundary as more than a Phase-A artifact, but the boundary needs replication across more domains to become a robust criterion. MATH [17] (verifiable), HumanEval [36] (verifiable via execution), MuSR [18] (multi-step reasoning, marginal verifiability), and 3D spatial reasoning benchmarks (non-verifiable) are the natural next targets.

Synthesis aggregator confound. The Tier 1.2 ablation establishes that LLM aggregation—not reasoning content—is the dominant active ingredient. This refines but does not eliminate a residual concern: a more sophisticated unlearned aggregator (e.g., trust-weighted vote, or self-consistency-style entropy weighting) might recover much of the synthesis effect without the LLM call. We have not tested this, and it is the most natural follow-up ablation.

Capability-ceiling generalization. Our family-replication result shows that two strong base models (Llama-70B and DeepSeek-V3.1) at 90% Phase A baseline do not benefit from the game. This is consistent with the capability-ceiling story but does not establish it as a universal property; testing more model families and more task batteries would strengthen the claim.

DSL as domain engineering. The symbolic-verification architecture requires a task-specific representation language: a 30-primitive Python grid library for ARC-AGI, a sympy-enabled sandbox for AIME, and a unit-test execution environment for HumanEval. This is non-trivial domain engineering—the "no fine-tuning, no PRM" framing slightly understates the supervision involved. The ARC-AGI-2 null result (0/100) exposes this limit directly: when the DSL cannot express the required abstractions, the architecture fails completely. Practitioners should weigh DSL design effort as part of the deployment cost.

Prompt sensitivity. All experiments use a single prompt template per task type. We have not systematically varied prompts; it is possible that prompt design interacts with the

synthesis-vs-majority-vote comparison, particularly for the synthesizer call (which reads K candidate outputs in a concatenated format). Model version drift is also a concern: all Together AI experiments were conducted over a two-week window (April 2026) against serverless endpoints whose underlying weights could in principle change. We release exact model identifiers and all prompts in the code repository.

Statistical power. The main-sweep per-condition CIs are wide ($\pm$8–15pp at $n = 15$). The aggregate findings (topology effect, γ saturation) are based on $n \approx 450$ per topology and have non-overlapping CIs. The Tier-1 ablations use larger per-condition n (100–250) and the corresponding CIs are tight. Per-cell findings should be interpreted as suggestive rather than as significance tests.

7.7. **Future work.**

Learned verifiers for non-verifiable tasks. Our Section 6 results show that symbolic verification (code execution, unit tests, sympy) dissolves the verifiability boundary. The natural next question is whether *learned* verifiers—process reward models (PRMs) trained on ground-truth trajectories [40]—can play the same role on tasks without natural symbolic verification. If PRM-based selection outperforms majority vote in the proposer–verifier–vote architecture, the approach generalizes beyond the "verifiable tasks" envelope; if not, the boundary is fundamental rather than architectural.

Replication of the verifiability boundary on more domains. We have characterized the boundary on three task domains: Phase A multi-approach math (verifiable, synth helps), GSM8K word problems (verifiable, synth helps), and ARC-AGI visual grids (non-verifiable, synth hurts). Replicating the boundary on additional domains would strengthen the predictive criterion: long-form structured generation, multi-step planning, complex code that requires execution to verify, and 3D spatial layouts are all natural candidates where we expect the synthesis effect to reverse or weaken. A clean dose-response relationship between verification cost and synthesis effect size would convert the boundary from a binary criterion into a continuous one.

Unlearned aggregators. The synthesis ablation establishes that LLM aggregation is the active ingredient on Phase A; an open question is whether more sophisticated unlearned aggregators (trust-weighted vote, self-consistency entropy weighting, learned ranking on top of the proposal pool) can recover most of the LLM-aggregator gain at lower cost. This is the most direct test of whether the synthesis effect requires LLM-level capability or merely requires a better-than-majority-vote aggregator.

Tiered escalation. The current experiments are flat-tier. A tiered system would start at the cheapest model, escalate to larger models when verification fails, and could substantially improve cost efficiency on heterogeneous task distributions. The capability-ceiling result implies that escalation is most useful on tasks where the cheap tier is below ceiling but the larger tier is at it.

The capability ceiling formalized. We have stated the capability ceiling as a qualitative boundary observed across model families. A tighter characterization—ideally, an explicit formula relating $p^{\star}_{\text{synth}}$ to measurable model properties (calibration, instruction-following accuracy, base-task accuracy)—would convert the boundary from a deployment heuristic into a quantitative prediction.

8. Conclusion

We asked when multi-agent LLM architecture matters. Our findings are precise.

On standard text-output tasks with a capable proposer, it does not. At $n = 1{,}000$ on MMLU-Pro (-1.1pp) and ARC-Challenge (-1.0pp), and $n = 500$ on MATH-500 ($+1.2$pp), an LLM synthesis node produces no detectable advantage over simple majority vote. Wilson CIs of ± 3pp at $n = 1{,}000$ are tight enough to rule out effects larger than a few percentage points. Five architectural elaborations all produce null results.

With a weaker proposer, synthesis actively hurts. The same synthesizer reduces correctness by -4.8pp on MATH-500 when proposals come from qwen-7b instead of qwen-22b. The noisier candidate pool misleads the aggregator: majority vote is robust to low-quality proposals (it just picks the most common answer), while the synthesizer tries to reason across them and gets confused.

On visual-spatial structured output, synthesis hurts dramatically. On ARC-AGI (-13 to -20pp), the synthesizer fails regardless of proposer quality because the output modality—grids that require re-derivation to verify—defeats LLM-based recognition entirely.

These three observations define the *verifiability boundary*: a two-component structure comprising a *modality threshold* (text: neutral; structured visual: harmful) and a *proposer-quality interaction* (weak proposer: harmful even on text). Both components reflect one mechanism: the synthesizer is a recognition device that fails when candidates are too noisy to sort or outputs too complex to evaluate by re-reading.

Symbolic verification is the only lever that moves the needle. Replacing the LLM aggregator with sandboxed Python execution achieves frontier-competitive results on three benchmarks: HumanEval 97.0% pass@16 (tying gpt-5.4-mini at $4.3\times$ lower cost under identical conditions), AIME $40/60 = 66.7\%$ (within 4pp of a same-task o4-mini reasoning model at $2.2\times$ lower cost), ARC-AGI-1 $73/400 = 18.2\%$ (lowest cost-per-correct in our comparison). The architecture that achieves these results is the simplest possible one: $K = 16$ independent samples from a single 22B-parameter model, execution-based filtering, majority vote. No elaboration we tested improved on it.

Scope and limitations. These are findings about specific implementations on specific benchmarks, not universal laws. The AIME and ARC-AGI-1 samples ($n = 60$ and $n = 400$ respectively) carry meaningful statistical uncertainty. The HumanEval comparison is same-metric but on a benchmark nearing saturation. A different class of multi-agent mechanisms—adaptive escalation, learned process reward models, or closed-loop architectures with real-time execution feedback—could in principle succeed where our tested interventions did not. What we can say is that the five most natural elaborations, each well-motivated by prior work, each produced a null on the benchmarks we tested.

The broader lesson: on reasoning tasks with a symbolic verifier, the multi-agent architecture question appears to be settled by the trivial solution. The open question is whether this extends to tasks without one.

The complete codebase, all experiment runners, and all cached results are publicly available at https://github.com/Cmouzouni/verifier-is-all-you-need.

References

[1] J. Wei, X. Wang, D. Schuurmans, M. Bosma, B. Ichter, F. Xia, E. Chi, Q. Le, and D. Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *NeurIPS*, 2022.

[2] X. Wang, J. Wei, D. Schuurmans, Q. Le, E. Chi, S. Narang, A. Chowdhery, and D. Zhou. Self-consistency improves chain-of-thought reasoning in language models. In *ICLR*, 2023.

[3] S. Yao, D. Yu, J. Zhao, I. Shafran, T. L. Griffiths, Y. Cao, and K. Narasimhan. Tree of thoughts: Deliberate problem solving with large language models. *arXiv:2305.10601*, 2023.

[4] M. Besta, N. Blach, A. Kubicek, R. Gerstenberger, L. Gianinazzi, et al. Graph of thoughts: Solving elaborate problems with large language models. In *Proc. AAAI*, 2024.
[5] Q. Wu, G. Bansal, J. Zhang, Y. Wu, B. Li, E. Zhu, L. Jiang, X. Zhang, S. Zhang, J. Liu, A. H. Awadallah, R. W. White, D. Burger, and C. Wang. AutoGen: Enabling next-gen LLM applications via multi-agent conversation. *arXiv:2308.08155*, 2023.
[6] S. Hong, M. Zhuge, J. Chen, X. Zheng, Y. Cheng, C. Zhang, et al. MetaGPT: Meta programming for a multi-agent collaborative framework. In *ICLR*, 2024.
[7] G. Li, H. A. A. K. Hammoud, H. Itani, D. Khizbullin, and B. Ghanem. CAMEL: Communicative agents for "mind" exploration of large language model society. In *NeurIPS*, 2023.
[8] C. Qian, W. Liu, H. Liu, N. Chen, Y. Dang, J. Li, et al. ChatDev: Communicative agents for software development. In *Proc. ACL*, 2024.
[9] G. Irving, P. Christiano, and D. Amodei. AI safety via debate. *arXiv:1805.00899*, 2018.
[10] Y. Du, S. Li, A. Torralba, J. B. Tenenbaum, and I. Mordatch. Improving factuality and reasoning in language models through multiagent debate. *arXiv:2305.14325*, 2023.
[11] A. Khan, J. Hughes, D. Valentine, L. Ruis, K. Sachan, A. Raghavan, et al. Debating with more persuasive LLMs leads to more truthful answers. In *ICML*, 2024.
[12] N. Shinn, F. Cassano, A. Gopinath, K. Narasimhan, and S. Yao. Reflexion: Language agents with verbal reinforcement learning. In *NeurIPS*, 2023.
[13] A. Madaan, N. Tandon, P. Gupta, S. Hallinan, L. Gao, S. Wiegreffe, et al. Self-Refine: Iterative refinement with self-feedback. In *NeurIPS*, 2023.
[14] N. Shazeer, A. Mirhoseini, K. Maziarz, A. Davis, Q. Le, G. Hinton, and J. Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In *ICLR*, 2017.
[15] Y. Leviathan, M. Kalman, and Y. Matias. Fast inference from transformers via speculative decoding. In *ICML*, 2023.
[16] K. Cobbe, V. Kosaraju, M. Bavarian, M. Chen, H. Jun, L. Kaiser, et al. Training verifiers to solve math word problems. *arXiv:2110.14168*, 2021.
[17] D. Hendrycks, C. Burns, S. Kadavath, A. Arora, S. Basart, E. Tang, D. Song, and J. Steinhardt. Measuring mathematical problem solving with the MATH dataset. In *NeurIPS Datasets and Benchmarks*, 2021.
[18] Z. Sprague, F. Yin, J. D. Rodriguez, D. Jiang, M. Wadhwa, P. Singhal, X. Zhao, X. Ye, K. Mahowald, and G. Durrett. MuSR: Testing the limits of chain-of-thought with multistep soft reasoning. In *ICLR*, 2024.
[19] F. Chollet. On the measure of intelligence. *arXiv:1911.01547*, 2019.
[20] J.-M. Lasry and P.-L. Lions. Mean field games. *Japanese Journal of Mathematics*, 2(1):229–260, 2007.
[21] M. Huang, R. P. Malhamé, and P. E. Caines. Large population stochastic dynamic games: closed-loop McKean–Vlasov systems and the Nash certainty equivalence principle. *Communications in Information and Systems*, 6(3):221–252, 2006.
[22] D. A. Gomes, J. Mohr, and R. R. Souza. Discrete time, finite state space mean field games. *Journal de Mathématiques Pures et Appliquées*, 93(2):308–328, 2010.
[23] O. Guéant. Existence and uniqueness result for mean field games with congestion effect on graphs. *Applied Mathematics & Optimization*, 72(2):291–303, 2015.
[24] A. Cecchin and G. Pelino. Convergence, fluctuations and large deviations for finite state mean field games. *Stochastic Processes and their Applications*, 129(11):4510–4555, 2019.
[25] R. Carmona and F. Delarue. *Probabilistic Theory of Mean Field Games with Applications*, volume 83–84 of *Probability Theory and Stochastic Modelling*. Springer, 2018.
[26] Y. Achdou, P. Cardaliaguet, F. Delarue, A. Porretta, and F. Santambrogio. *Mean Field Games*, volume 2281 of *Lecture Notes in Mathematics*. Springer, 2020.
[27] A. Lachapelle and M.-T. Wolfram. On a mean field game approach modeling congestion and aversion in pedestrian crowds. *Transportation Research Part B*, 45(10):1572–1589, 2011.
[28] E. B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, 1927.
[29] Y. Li, D. Choi, J. Chung, N. Kushman, J. Schrittwieser, et al. Competition-level code generation with AlphaCode. *Science*, 378(6624):1092–1097, 2022.
[30] B. Romera-Paredes, M. Barekatain, A. Novikov, M. Balog, M. P. Kumar, et al. Mathematical discoveries from program search with large language models. *Nature*, 625:468–475, 2024.
[31] C. Snell, J. Lee, K. Xu, A. Kumar. Scaling LLM test-time compute optimally can be more effective than scaling model parameters. *arXiv preprint arXiv:2408.03314*, 2024.

[32] Z. Liu, Z. Gou, Y. Yang, H. Peng, J. Wang. Can 1B LLM surpass 405B? Rethinking compute-optimal test-time scaling. In *ICLR*, 2025. arXiv:2502.06703.
[33] F. Chollet, M. Knoop, G. Kamradt. ARC Prize 2024: Technical report. *arXiv preprint arXiv:2412.04604*, 2024.
[34] E. Akyürek, B. Damani, L. H. Peng, A. Sharma, S. R. Bowman, et al. The surprising effectiveness of test-time training for abstract reasoning. *arXiv preprint arXiv:2411.07279*, 2024.
[35] Y. Zhang, Y. Du, H. Zhao. Stop overvaluing multi-agent debate: We must rethink evaluation and embrace model heterogeneity. In *NeurIPS*, 2025. arXiv:2502.08788.
[36] M. Chen, J. Tworek, H. Jun, Q. Yuan, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.
[37] W. Saunders, C. Yeh, J. Wu, S. Bills, L. Ouyang, J. Ward, J. Leike. Self-critiquing models for assisting human evaluators. *arXiv preprint arXiv:2206.05802*, 2022.
[38] J. Huang, S. S. Gu, L. Hou, Y. Wu, X. Wang, H. Yu, J. Han. Large language models cannot self-correct reasoning yet. In *ICLR*, 2024. arXiv:2310.01798.
[39] R. Kamoi, Y. Raman, Y. Zhang, J. Liu, R. Balachandran. When can LLMs actually correct their own mistakes? A critical survey of self-correction of LLMs. *Transactions of the ACL*, 2024. arXiv:2406.01297.
[40] H. Lightman, V. Kosaraju, Y. Burda, H. Edwards, B. Baker, T. Lee, J. Leike, J. Schulman, I. Sutskever, K. Cobbe. Let's verify step by step. In *ICLR*, 2024. arXiv:2305.20050.

OPIT – Open Institute of Technology, and Cohorte AI, Paris, France.
Email address: charafeddine@cohorte.co