

Yocto BSP and SDK Build Guide

Version 1.0.0

Display Audio

Solution Team



Release information

The following changes have been made to this document.

Change History

Date	Change
08 Dec. 2017	First release for v1.0.0

Proprietary Notice

Information in this document is provided solely to enable system and software implementers to use Nexell products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Nexell reserves the right to make changes without further notice to any products herein.

Nexell makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Nexell assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Nexell data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Nexell does not convey any license under its patent rights nor the rights of others. Nexell products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Nexell product could create a situation where personal injury or death may occur. Should Buyer purchase or use Nexell products for any such unintended or unauthorized application, Buyer shall indemnify and hold Nexell and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Nexell was negligent regarding the design or manufacture of the part.

Copyright© 2017 Nexell Co.,Ltd. All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electric or mechanical, by photocopying, recording, or otherwise, without the prior written consent of Nexell.

Contact us

[11595] BundangYemiji Bldg. 12F, 31 Hwangsaeul-ro 258 beon gil, Bundang-gu, Sungnam-city, Gyeonggi-do, Korea.

TEL: 82-31-698-7400

FAX: 82-31-698-7455

<http://www.nexell.co.kr>

Table of contents

Chap 1.	Yocto BSP	1
1.1	Introduction	1
1.2	Features and Functionality	1
1.3	Build and Configuration	1
Chap 2.	Solution	4
2.1	Environment	4
2.2	Build	4
2.3	Push	4

Chap 1. Yocto BSP

1.1 Introduction

We release the source compilation and fusing script files of kernel and u-boot developed by Nexell using Yocto Poky system.

The meta-nexell layer is configured to minimize the dependency on the host PC compile environment of the 3rd party or end-user and to reduce the difficulty in configuring the root file system.

1.2 Features and Functionality

- linux kernel, u-boot, 2ndboot build & release
- Binary files packaging & fusing scripts
- systemd, busybox, adb, etc.
- Available Image type
 - **QT5**, Minimal(ready for kernel command line)

1.3 Build and Configuration

1.3.1 Environment

Essentials : Packages needed to build an image on a headless system.

```
$ sudo apt-get install gawk wget git-core diffstat unzip texinfo gcc-multilib build-essential chrpath socat
```

Graphical and Eclipse Plug-In Extras: Packages recommended if the host system has graphics support or if you are going to use the Eclipse IDE.

```
$ sudo apt-get install libsdl1.2-dev xterm
```

Documentation: Packages needed if you are going to build out the Yocto Project documentation manuals.

```
$ sudo apt-get install make xsltproc docbook-utils fop dblatex xmlto
```

SDK Installer Extras: Packages needed if you are going to be using the the standard or extensible SDK.

```
$ sudo apt-get install autoconf automake libtool libglib2.0-dev libarchive-dev
```

OpenEmbedded Self-Test (oe-selftest): Packages needed if you are going to run oe-selftest.

```
$ sudo apt-get install python-git
```

1.3.2 Source download

```
$ mkdir yocto-nexell
$ cd yocto-nexell
$ repo init -u ssh://{USER_ID}@git.nexell.co.kr:29418/nexell/yocto/manifest
$ repo sync
```

If you do not have an ssh account.

```
$ repo init -u git://git.nexell.co.kr/nexell/yocto/manifest
or
$ repo init -u http://git.nexell.co.kr:8081/gerrit/nexell/yocto/manifest
$ repo sync
```

1.3.3 Build

1.3.3.1 Full build

```
$ ./tools/build.sh s5p4418-daudio-ref qt
```

1.3.3.2 Partial build

1.3.3.2.1 Kernel only

```
$ ./tools/build.sh s5p4418-daudio-ref qt -t bl1 -t kernel
```

1.3.3.2.2 Kernel, uboot

```
$ ./tools/build.sh s5p4418-daudio-ref qt -t bl1 -t uboot -t kernel
```

1.3.3.2.3 Rootfs only

```
$ ./tools/build.sh s5p4418-daudio-ref qt -t bl1 -t rootfs
```

1.3.3.3 Clean full build

```
$ ./tools/build.sh s5p4418-daudio-ref qt -c
```

1.3.3.4 Clean partial build

```
$ ./tools/build.sh s5p4418-daudio-ref qt -c -t bl1 -t uboot -t kernel
```

1.3.4 Fusing

If you need usb boot

Set the boot mode switch on the debug board to usb boot mode.

On the host PC side

```
$ ./yocto/result-s5p4418-dauidio-ref-qt/tools/ standalone-uboot-by-usb-download.sh
```

On the target board side (Common)

```
$ fastboot 0
```

1.3.4.1 Full fusing

```
$ ./yocto/result-s5p4418-dauidio-ref-qt/tools/standalone-fastboot-download.sh
```

1.3.4.2 Partial fusing

1.3.4.2.1 Kernel only

```
./yocto/result-s5p4418-dauidio-ref-qt/tools/standalone-fastboot-download.sh -t kernel
```

1.3.4.2.2 Kernel, uboot

```
$ ./yocto/result-s5p4418-dauidio-ref-qt/tools/standalone-fastboot-download.sh -t kernel -t uboot
```

1.3.4.2.3 Rootfs only

```
$ ./yocto/result-s5p4418-dauidio-ref-qt/tools/standalone-fastboot-download.sh -t rootfs
```

1.3.5 DAudio reference SDK installation

```
$ ./tools/build.sh s5p4418-dauidio-ref qt -s -c
```

Installed at : /opt/poky/2.1.x

1.3.6 ADB setting

On the host PC side

```
$ sudo vi etc/udev/rules.d/51-android.rules
```

Modified as follows.

```
SUBSYSTEM=="usb",ATTR{idVendor}=="18d1",MODE="0666"
```

Chap 2. **Solution**

2.1 Environment

```
$ source /opt/poky/2.1.x/environment-setup-cortexa9hf-neon-poky-linux-gnueabi
```

2.2 Build

Display audio solution sdk unzip archive.

Move to uncompressed location.

```
$ make
$ make package
```

2.3 Push

If necessary, with the target board and PC connected to the adb, push the generated package as follows.

```
$ make push
```

On the target board side, enter sync.

```
$ sync
```