

Note: Do not write on the backs; only front pages are digitized and graded.

1. (20 points) Answer with True or False.

• $3n^2 + n^3 \in \Omega(n^3)$ True

• $3n^2 + n^3 \in O(n^4)$ True

2. (10 points) Use the definition of O to show that $5n^2 + 10n \in O(n^2)$.

$5n^2 + 10n \leq 5n^2 + 10n^2, \therefore 5n^2 + 10n \leq 15n^2$ for all $n \geq 1$.
 $c=15$. Thus, $5n^2 + 10n \in O(n^2)$.

3. (20 points) Use the definition of Θ to show that $3n^3 + 5n - 5 \in \Theta(n^3)$.

$3n^3 + 5n - 5 \leq 3n^3 + 5n^3 - 5, \therefore 3n^3 + 5n \leq 8n^3$ for all $n \geq 1$.

$c=8$. Thus, $3n^3 + 5n - 5 \in O(n^3)$

$3n^3 + 5n - 5 \geq 3n^3$ for all $n \geq 0$. Thus, $3n^3 + 5n - 5 \in \Omega(n^3)$

Since $3n^3 + 5n - 5$ exists in $O(n^3)$ and $\Omega(n^3)$, $3n^3 + 5n - 5 \in \Theta(n^3)$

4. (10 points) Use Θ to specify the running time of the following procedure in terms of n .

```
sum = 0 constant
for i in range(n): n steps
    for j in range(5): 5 steps (constant)
        sum = sum + i + j
```

$T(n) = \Theta(n)$

5. (10 points) Use Θ to specify the running time of the following procedure in terms of n .

```
sum = 0 constant
for i in range(n): n
    j = n constant
    while j > 1: log n
        sum = sum + i * j constant
        j = j / 2
```

$T(n) = \Theta(n \log n)$

6. (10 points) Is the running time of the procedure in Question 4 is in $\Omega(n)$? Explain briefly.

Yes, $\Omega(n)$ specifies a lower bound running time of approximately n steps. n steps will take place regardless of input because of the for loop. Thus, the procedure will take at least n steps.

7. (10 points) What is the space complexity of the procedure in Question 4? $S(n) = \Theta(n)$

8. (10 points) Explain what the following function does. The input is a list of numbers.

```
def foo(L):
    if len(L) == 0:
        return 1
    return L[0] * foo(L[1:])
```

If passed an empty list, foo returns 1. Otherwise, it recursively computes the product of numbers in L and returns that product. The recursive call multiplies the first list item by the return value of foo when it is passed the same list, minus the first item.

9. (10 points) Use mathematical induction to explain that the following function correctly adds up all numbers that are divisible by 5 in the input list.

```
def bar(L):
    if len(L) == 0:
        return 0
    if L[0] % 5 == 0:
        return L[0] + bar(L[1:])
    return bar(L[1:])
```

Let k equal the number of items in list L .
 bar works for the smallest case of list length $k=0$ because there are no numbers divisible by 5 in the list. Let $L[1:]$ be a list of length $k-1$. Assuming bar works for all cases $k-1$, bar also returns a value divisible by 5 + the sum of numbers in list of length $k-1$ which are divisible by 5. Thus bar works for all cases of list length k .

10. (10 points) The input of the following function is a binary tree T . Assume that such a tree T has 3 attributes: $T.left$, $T.right$ (both of which are also binary trees), and $T.color$ (which is a string of either "red", "green", or "blue"). If T is empty, the function `is_empty(T)` returns True (if not, it returns False). Complete defining the following Python function so that it correctly counts the number of red nodes in the input binary tree T .

```
def count_red_nodes(T):
    # fill in your codes below to count the number of red nodes in the binary tree T
    if is_empty(T):
        return 0
    count = 0
    if T.color == "red":
        count = 1
    return count + count_red_nodes(T.left) + count_red_nodes(T.right)
```