

Configuration

Basic Structure

The config file, `config.yml`, has all of the configuration settings for widgets, proxmox, docker, and more. This file goes over the structure of `config.yml` file. It is recommended to put your authentication information, like for proxmox and docker, at the top of the document, then widgets.

Authentication

Proxmox

```
proxmox:  
  host: 192.168.1.100  
  user: root@pam  
  pass: yourpassword  
  node: nodename
```

This defines credentials for connecting to the proxmox api.

host: This is the ip address of your proxmox server

user: This is the username for the user you want to use. It will usually be [root@pam](#) if you haven't specifically added any other users that you want to use

pass: This is the password in plain-text for the username you defined above

node: This is the name/hostname for the node (part of the tree under 'Datacenter')

Docker

Setup

In order to use docker, you must setup a ssh key.

1. On the system you plan to use for the dashboard, run `ssh-keygen -t ed25519 -c "Dashboard"`
2. Hit enter on the prompts to use defaults and not add password.
3. On the same machine, run `ssh-copy-id youruser@ipfordocker` Enter the password for the docker system when asked
4. Test by running `ssh youruser@ipfordocker`. If it lets you login without your password, your good to go.

Config

```
docker:
  host: 192.168.1.100
  user: myusername
```

Connects to docker running on an external machine

host: The ip address for the server running docker

user: The username to login as (MUST BE THE SAME AS YOU USED FOR THE SSH KEY)

Custom

```
custom:
  custom1:
    host: 192.168.1.100
    user: root
    password: 1234
    command: systemctl restart myservice.service
  custom2:
    host: 192.168.1.101
    user: myusername
    password: 12345
    command: systemctl restart myservice.service
```

If you aren't using docker or proxmox, you can use this to run any command on any server

[custom name]: You can define multiple custom commands, this is just the name for each one
host: The ip address of the host you want to run the command on
user: The user to run the command as
password: The password for the user you set above
command: The command to run on the host

Widgets

Monitor

Monitor:
myproxmoxservice:
service: proxmox
type: lxc
id: 102
url: http://192.168.1.100:8080
mydockerservice:
service: docker
name: mycontainername
url: http://192.168.1.100:8080
mycustomservice:
service: custom
name: custom1
url: http://192.168.1.100:8080

This widget monitors a web ui and lets you restart a proxmox VM/LXC, docker container, or run a custom command if the service is down

[service name]: The name to display
service: the service used for the software monitored (accepted: proxmox, docker, name of custom service)
url: The exact url for the web ui, including protocol (http/https) and port (:8080) (Required for all services)
type: The thing the service runs on (accepted: vm, lxc) (required

only for proxmox)
id: The id for the lxc/vm (required only for proxmox)
name: Name of the docker container/custom service (required only for docker and custom)