Buffered Serial

1.0

Generated by Doxygen 1.8.18

Chapter 1

Buffered Serial

1.1 Features:

- Developed for the STM32F103.
- Serial communication with DMA in circular mode and IDLE interrupt.
- Configurable quantity of serials and size of rx and tx buffers.
- Simple communication with print string,print character and read line functions.
- STM32CubeIDE project configuration guide.
- Error handling with buffered_serial_error_code.
- UART Error handling

1.2 Considerations:

- BUFFERED_SERIAL_SERIALS_QUANTITY must be configured to correspond the quantity of huart configured, by default is one.
- BUFFERED_SERIAL_BUFFERS_SIZE at most can be maximum value of uint16_t, since buffered_serial_↩ available is this type.
- Buffers can hold at most BUFFERED_SERIAL_BUFFERS_SIZE - 1 data, because when rx_buffer_data_↩ start and rx_buffer_data_finish pointers are equals it can be 0 data or maximum data but the library interpret as 0 data.

1.3 GETTING STARTED

1.3.1 UART Error handling in buffered_serial.c

```
void HAL_UART_ErrorCallback(UART_HandleTypeDef *huart)
{

	HAL_UART_Receive_DMA(huart,buffered_serial_get_huart_serial_descriptor(huart)->rx_buffer,BUFFERED_SERIAL_BUFFERS_SIZE);
}
```

1.3.2 Configure IDLE interrupt in stm32f1xx_it.c

Configure project as described in file project_configuration.pdf in root folder. IDLE interrupt must be configured for all huart interrupt handlers.

```
void USART1_IRQHandler(void)
{
  HAL_UART_IRQHandler(&huart1);
  buffered_serial_update_rx_buffer_data(&huart1);
}
```

1.3.3 Initializing library and getting serial descriptor in main.c file

```
MX_GPIO_Init();
MX_DMA_Init();
MX_USART1_UART_Init();
UART_HandleTypeDef *huarts[] = {&huart1};
buffered_serial_init(huarts);
buffered_serial_serial_descriptor *serial1 = buffered_serial_get_huart_serial_descriptor(&huart1);
```

1.3.4 Writing a string

```
uint8_t test[40] = "2A6V7W5NL5ZZC6AYE84NKZ6MVFMZ5DZSYD9TM3\r\n";
static_strings_string_descriptor *string_descriptor = static_strings_save(test);
buffered_serial_print_string(test,string_descriptor);
static_strings_deallocate(string_descriptor);
```

DON'T FORGET TO DEALLOCATE STRING AFTER USING.

1.3.5 Reading a line

```
if(buffered_serial_available(serial1) > 0){
  uint16_t available = buffered_serial_available(serial1);
  static_strings_string_descriptor *string_descriptor = buffered_serial_read_line(serial1);
  if(string_descriptor != NULL){
    buffered_serial_print_string(serial1,string_descriptor);
    static_strings_deallocate(string_descriptor);
  }
  else{
    handle_error(buffered_serial_error_code);
  }
}
```

DON'T FORGET TO DEALLOCATE STRING AFTER USING.

1.3.6 Writing a character

```
uint8_t character = 'A';
buffered_serial_print_character(serial1,character);
```

1.3.7 Configure serials quantity and size of the buffers

Just edit these constants in buffered_serial.h

```
#define BUFFERED_SERIAL_SERIALS_QUANTITY 1
#define BUFFERED_SERIAL_BUFFERS_SIZE 500
```

Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

Chapter 3

Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

Chapter 4

File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

Chapter 5

Module Documentation

5.1 Serial buffers size and quantity

Constants to configure the quantity of serials and the size of their buffers.

Macros

- #define **BUFFERED_SERIAL_SERIALS_QUANTITY** 1
- #define **BUFFERED_SERIAL_BUFFERS_SIZE** 500

5.1.1 Detailed Description

Constants to configure the quantity of serials and the size of their buffers.

5.2 Error handling

Error codes.

Macros

- #define **BUFFERED_SERIAL_ERROR_CODE_STATIC_STRINGS_ERROR** 0
- #define **BUFFERED_SERIAL_ERROR_CODE_NO_LINE_ENDING_DETECTED** 1

Variables

- uint8_t buffered_serial_error_code

  Global variable to store error code.

5.2.1 Detailed Description

Error codes.

5.2.2 Variable Documentation

5.2.2.1 buffered_serial_error_code

```
uint8_t buffered_serial_error_code
```

Global variable to store error code.

static_strings_error_code

5.3 Serial buffers

rx and tx buffers to receive and transmit data.

Variables

- uint8_t **buffered_serial_rx_buffers** [BUFFERED_SERIAL_SERIALS_QUANTITY][BUFFERED_SERIAL↩ _BUFFERS_SIZE]
- uint8_t **buffered_serial_tx_buffers** [BUFFERED_SERIAL_SERIALS_QUANTITY][BUFFERED_SERIAL↩ _BUFFERS_SIZE]

5.3.1 Detailed Description

rx and tx buffers to receive and transmit data.

Chapter 6

Data Structure Documentation

6.1 buffered_serial_serial_descriptor Struct Reference

Meta data of a buffered serial.

`#include <buffered_serial.h>`

Data Fields

- UART_HandleTypeDef * **huart**
- uint8_t * **rx_buffer**
- uint8_t * rx_buffer_data_start
- uint8_t * rx_buffer_data_finish
- uint8_t * **tx_buffer**

6.1.1 Detailed Description

Meta data of a buffered serial.

6.1.2 Field Documentation

6.1.2.1 rx_buffer_data_finish

`uint8_t* rx_buffer_data_finish`

Pointer to the position ahead the last readable character on buffer.

6.1.2.2 rx_buffer_data_start

`uint8_t* rx_buffer_data_start`

Pointer to the first readable character on the buffer.

The documentation for this struct was generated from the following file:

- buffered_serial.h

Chapter 7

File Documentation

7.1 buffered_serial.c File Reference

Serial communication based on a circular buffer, dma and huart with hal controls and Static Strings.

```
#include "buffered_serial.h"
```

Functions

- void buffered_serial_init (UART_HandleTypeDef **huarts)

  Link huarts and buffers with serial descriptors and init rx data receiving and idle interrupt. Also init the Static Strings library.
- buffered_serial_serial_descriptor * buffered_serial_get_huart_serial_descriptor (UART_HandleTypeDef *huart)

  Returns the serial_descriptor of the provided huart.
- uint16_t buffered_serial_available (buffered_serial_serial_descriptor *serial)

  Calculates and returns the number of characters that can be read from the rx buffer.
- void buffered_serial_print_character (buffered_serial_serial_descriptor *serial, uint8_t character)

  Transmit a character with the specific huart in the serial descriptor.
- void buffered_serial_print_string (buffered_serial_serial_descriptor *serial, static_strings_string_descriptor *string_descriptor)

  Transmit a string with the specific huart in the serial descriptor. Strings larger than BUFFERED_SERIAL_BUFFER↩ S_SIZE will be transmitted in blocks of that size.
- static_strings_string_descriptor * buffered_serial_read_line (buffered_serial_serial_descriptor *serial)

  Read a string in the specific huart buffer in the serial descriptor. String must have \r\n line ending.
- void buffered_serial_update_rx_buffer_data (UART_HandleTypeDef *huart)

  When IDLE line interruption is fired this function updates the rx buffer meta data.
- void **HAL_UART_ErrorCallback** (UART_HandleTypeDef *huart)

7.1.1 Detailed Description

Serial communication based on a circular buffer, dma and huart with hal controls and Static Strings.

7.1.2 Function Documentation

7.1.2.1 buffered_serial_available()

```
uint16_t buffered_serial_available (
            buffered_serial_serial_descriptor * serial )
```

Calculates and returns the number of characters that can be read from the rx buffer.

uint16_t buffered_serial_available(buffered_serial_serial_descriptor *serial)

Parameters

serial	Pointer to the serial descriptor of the target huart.

Returns

Number of characters that can be read from the rx buffer.

7.1.2.2 buffered_serial_get_huart_serial_descriptor()

```
buffered_serial_serial_descriptor* buffered_serial_get_huart_serial_descriptor (
            UART_HandleTypeDef * huart )
```

Returns the serial_descriptor of the provided huart.

buffered_serial_serial_descriptor buffered_serial_get_huart_serial_descriptor(UART_HandleTypeDef *huart)

Parameters

huart	Pointer to a UART_HandleTypeDef.

Returns

A pointer to the serial descriptor of the provided huart. Return NULL if there is no serial descriptor attached to the huart provided.

7.1.2.3 buffered_serial_init()

```
void buffered_serial_init (
            UART_HandleTypeDef ** huarts )
```

Link huarts and buffers with serial descriptors and init rx data receiving and idle interrupt. Also init the Static Strings library.

void buffered_serial_init(UART_HandleTypeDef **huarts)

Parameters

huarts	Array of pointers to huart pointer.

7.1.2.4 buffered_serial_print_character()

```
void buffered_serial_print_character (
            buffered_serial_serial_descriptor * serial,
            uint8_t character )
```

Transmit a character with the specific huart in the serial descriptor.

void buffered_serial_print_character(buffered_serial_serial_descriptor *serial,uint8_t character)

Parameters

character	character to transmit.
serial	Pointer to the serial descriptor of the target huart.

7.1.2.5 buffered_serial_print_string()

```
void buffered_serial_print_string (
            buffered_serial_serial_descriptor * serial,
            static_strings_string_descriptor * string_descriptor )
```

Transmit a string with the specific huart in the serial descriptor. Strings larger than BUFFERED_SERIAL_BUFFE↩ RS_SIZE will be transmitted in blocks of that size.

void buffered_serial_print_string(static_strings_string_descriptor *string,buffered_serial_serial_descriptor *serial)

Parameters

string_descriptor	Pointer to the descriptor of the string to transmit.
serial	Pointer to the serial descriptor of the target huart.

7.1.2.6 buffered_serial_read_line()

```
static_strings_string_descriptor* buffered_serial_read_line (
            buffered_serial_serial_descriptor * serial )
```

Read a string in the specific huart buffer in the serial descriptor. String must have \r\n line ending.

static_strings_string_descriptor *buffered_serial_read_line(buffered_serial_serial_descriptor *serial)

Parameters

serial	Pointer to the serial descriptor of the target huart.

Returns

Pointer to the string descriptor of the line read (See library Static Strings), if NULL check buffered_serial_↩ error_code.

7.1.2.7 buffered_serial_update_rx_buffer_data()

```
void buffered_serial_update_rx_buffer_data (
            UART_HandleTypeDef * huart )
```

When IDLE line interruption is fired this function updates the rx buffer meta data.

void buffered_serial_update_rx_buffer_data(UART_HandleTypeDef *huart)

Parameters

Pointer	to the huart IDLE line interruption source.

7.2 buffered_serial.h File Reference

Serial communication based on a circular buffer, dma and huart with hal controls and Static Strings.

```
#include "stm32f1xx_hal.h"
#include "stm32f1xx_hal_uart.h"
#include "static_strings.h"
```

Data Structures

- struct buffered_serial_serial_descriptor

  Meta data of a buffered serial.

Macros

- #define **BUFFERED_SERIAL_SERIALS_QUANTITY** 1
- #define **BUFFERED_SERIAL_BUFFERS_SIZE** 500
- #define **BUFFERED_SERIAL_ERROR_CODE_STATIC_STRINGS_ERROR** 0
- #define **BUFFERED_SERIAL_ERROR_CODE_NO_LINE_ENDING_DETECTED** 1

Typedefs

- typedef struct buffered_serial_serial_descriptor **buffered_serial_serial_descriptor**

Functions

- void buffered_serial_init (UART_HandleTypeDef **huarts)

  Link huarts and buffers with serial descriptors and init rx data receiving and idle interrupt. Also init the Static Strings library.
- buffered_serial_serial_descriptor * buffered_serial_get_huart_serial_descriptor (UART_HandleTypeDef *huart)

  Returns the serial_descriptor of the provided huart.
- uint16_t buffered_serial_available (buffered_serial_serial_descriptor *serial)

  Calculates and returns the number of characters that can be read from the rx buffer.
- void buffered_serial_print_character (buffered_serial_serial_descriptor *serial, uint8_t character)

  Transmit a character with the specific huart in the serial descriptor.
- void buffered_serial_print_string (buffered_serial_serial_descriptor *serial, static_strings_string_descriptor *string_descriptor)

  Transmit a string with the specific huart in the serial descriptor. Strings larger than BUFFERED_SERIAL_BUFFER↩ S_SIZE will be transmitted in blocks of that size.
- static_strings_string_descriptor * buffered_serial_read_line (buffered_serial_serial_descriptor *serial)

  Read a string in the specific huart buffer in the serial descriptor. String must have \r\n line ending.
- void buffered_serial_update_rx_buffer_data (UART_HandleTypeDef *huart)

  When IDLE line interruption is fired this function updates the rx buffer meta data.

Variables

- uint8_t buffered_serial_error_code

  Global variable to store error code.
- uint8_t **buffered_serial_rx_buffers** [BUFFERED_SERIAL_SERIALS_QUANTITY][BUFFERED_SERIAL_↩ BUFFERS_SIZE]
- uint8_t **buffered_serial_tx_buffers** [BUFFERED_SERIAL_SERIALS_QUANTITY][BUFFERED_SERIAL_↩ BUFFERS_SIZE]
- buffered_serial_serial_descriptor **buffered_serial_serial_descriptors** [BUFFERED_SERIAL_SERIALS_↩ QUANTITY]

7.2.1 Detailed Description

Serial communication based on a circular buffer, dma and huart with hal controls and Static Strings.

7.2.2 Function Documentation

7.2.2.1 buffered_serial_available()

```
uint16_t buffered_serial_available (
            buffered_serial_serial_descriptor * serial )
```

Calculates and returns the number of characters that can be read from the rx buffer.

uint16_t buffered_serial_available(buffered_serial_serial_descriptor *serial)

Parameters

serial	Pointer to the serial descriptor of the target huart.

Returns

Number of characters that can be read from the rx buffer.

7.2.2.2 buffered_serial_get_huart_serial_descriptor()

```
buffered_serial_serial_descriptor* buffered_serial_get_huart_serial_descriptor (
            UART_HandleTypeDef * huart )
```

Returns the serial_descriptor of the provided huart.

buffered_serial_serial_descriptor buffered_serial_get_huart_serial_descriptor(UART_HandleTypeDef ∗huart)

Parameters

huart	Pointer to a UART_HandleTypeDef.

Returns

A pointer to the serial descriptor of the provided huart. Return NULL if there is no serial descriptor attached to the huart provided.

7.2.2.3 buffered_serial_init()

```
void buffered_serial_init (
            UART_HandleTypeDef ** huarts )
```

Link huarts and buffers with serial descriptors and init rx data receiving and idle interrupt. Also init the Static Strings library.

void buffered_serial_init(UART_HandleTypeDef ∗∗huarts)

Parameters

huarts	Array of pointers to huart pointer.

7.2.2.4 buffered_serial_print_character()

```
void buffered_serial_print_character (
            buffered_serial_serial_descriptor * serial,
            uint8_t character )
```

Transmit a character with the specific huart in the serial descriptor.

void buffered_serial_print_character(buffered_serial_serial_descriptor *serial,uint8_t character)

Parameters

character	character to transmit.
serial	Pointer to the serial descriptor of the target huart.

7.2.2.5 buffered_serial_print_string()

```
void buffered_serial_print_string (
            buffered_serial_serial_descriptor * serial,
            static_strings_string_descriptor * string_descriptor )
```

Transmit a string with the specific huart in the serial descriptor. Strings larger than BUFFERED_SERIAL_BUFFE↩ RS_SIZE will be transmitted in blocks of that size.

void buffered_serial_print_string(static_strings_string_descriptor *string,buffered_serial_serial_descriptor *serial)

Parameters

string_descriptor	Pointer to the descriptor of the string to transmit.
serial	Pointer to the serial descriptor of the target huart.

7.2.2.6 buffered_serial_read_line()

```
static_strings_string_descriptor* buffered_serial_read_line (
            buffered_serial_serial_descriptor * serial )
```

Read a string in the specific huart buffer in the serial descriptor. String must have \r\n line ending.

static_strings_string_descriptor *buffered_serial_read_line(buffered_serial_serial_descriptor *serial)

Parameters

serial	Pointer to the serial descriptor of the target huart.

Returns

Pointer to the string descriptor of the line read (See library Static Strings), if NULL check buffered_serial_↩ error_code.

7.2.2.7 buffered_serial_update_rx_buffer_data()

```
void buffered_serial_update_rx_buffer_data (
            UART_HandleTypeDef * huart )
```

When IDLE line interruption is fired this function updates the rx buffer meta data.

void buffered_serial_update_rx_buffer_data(UART_HandleTypeDef ∗huart)

Parameters

Pointer	to the huart IDLE line interruption source.

Index