

## Objectives


- Optimizers
  - Gradient Descent
- 

## Optimizers

Goal: Find "test" = max, or min

Loss function: minimize Two methods

- exact take derivative = 0
- Gradient based method




initial value = seed the generator

### 1 vanilla gradient descent

update function:  $w_{t+1} = w_t - \gamma \nabla L(W)$

$L(W)$  is the loss function

$\gamma$  is the learning rate, a hyperparameter tunable via cross validation



frequent issues:

- gets stuck at local minimum
- vanishing gradient
- if learning rate is increased can get unstuck but risk jumping over desired points if increased too much

## 2 momentum

intuitive:  $w_{t+1} = w_t - \gamma \nabla L(w_t)$  (past gradients)

Actual:  $v_0 = 0$

$$v_{t+1} = \xi v_t + \nabla L(w_t)$$

$$w_{t+1} = w_t - \gamma v_{t+1}$$

issue: can move past desired point because of momentum of past gradients

evaluating performance: Count number of iterations

## 3 Gradient-based Nesterov

$$v_0 = 0$$

$$v_{t+1} = \xi v_t + \nabla L(w_t)$$

$$w_{t+1} = w_t - \gamma(\delta v_{t+1} + \nabla L(w_t))$$

look ahead :  $\delta v_{t+1}$