

## Microprocessor (BCT II / II)

1. Add two numbers located at 3030H and 4040H. Display sum on Port 1. If carry is generated, display it on Port 2. Store sum on 5050H.

```
LDA 3030H
MOV B, A
LDA 4040H
ADD B
STA 5050H
OUT PORT 1
JNC L1
MVI A, 01H
OUT PORT 2
L1: HLT
```

2. Write an Assembly Language Program that retrieves a data located at 2050H and it displays, if it is even and stores FFH on that location if it is odd.

```
LDA 2050H
ANI 01H
JNZ L1
LDA 2050H
OUT PORT 1
HLT
L1: MVI A, FFH
STA 2050H
HLT
```

3. Sixteen bytes of data are stored in memory location at 1050H to 105FH. Replace each data byte by FF.

```
LXI H, 1050H
MVI C, 10H
L1: MVI M, FFH
INX H
DCR C
JNZ L1
HLT
```

4. Sixteen data are stored in memory location at 1050H to 105FH. Transfer the entire block of data to new location starting at 1070H.

```
LXI H, 1050H
MVI C, 10H
LXI D, 1070H
L1:  MOV A, M
      STAX D
      INX H
      INX D
      DCR C
      JNZ L1
      HLT
```

5. Six bytes are stored in memory locations starting at 2050H. Add all the data bytes, save any carry generated while adding the data bytes. Display entire sum at two output ports and store total carry in 2070H and sum in 2071H.

```
LXI H, 2050H
MVI C, 06H
MVI B, 00H
MVI D, 00H
L2:  MOV A, M
      ADD B
      MOV B, A
      JNC L1
      INR D
L1:  INX H
      DCR C
      JNZ L2
      HLT
```

6. If the content of memory location 2050H is greater than or equal to 64H, display 0FH else display FFH.

```
LDA 2050H
CPI 64H
JC L1
MOV A, 0FH
OUT PORT 1
HLT
L1:  MOV A, FFH
      OUT PORT 1
      HLT
```

7. We have a list of data stored at memory location starting at 2050H. The end of the data array is indicated by data byte 00H. Add the set of readings. Display the sum at Port 1 and total carry at Port 2.

```
LXI H, 2050H
MVI B, 00H
MVI C, 00H
L3: MOV A, M
    CPI 00H
    JZ L1
    ADD C
    JNZ L2
    INR B
L2: MOV C, A
    INX H
    JMP L3
L1: MOV A, C
    OUT PORT 1
    MOV A, B
    OUT PORT 2
    HLT
```

8. There are two tables holding twenty data whose starting address is 3000H and 3020H respectively. WAP to add the content of first table with the content of second table having same array index. Store sum and carry into the third and fourth table indexing from 3040H and 3060H respectively.

```
                LXI B, 3000H
                LXI H, 3020H
                LXI D, 3040H
NEXT:           LDAX B
                ADD M
                STAX D
                PUSH H
                PUSH D
                JNC L1
                MVI E, 01H
                JMP CSTORE
L1:             MVI E, 00H
CSTORE:        LXI H, 3060H
                MOV A, L
                ADD C
                MOV L, A
                MOV M, E
                POP H
                POP D
                INX B
                INX D
                INX H
                MOV A, C
                CPI 14H
                JNZ NEXT
                HLT
```

9. For ten bytes data starting from 1120H, write a program to sort the reading in ascending and in descending order. (Note : For descending, do self)

```
START:  LXI H, 1120H
        MVI D, 00H
        MVI C, 0AH
L2:     MOV A, M
        INX H
        CMP M
        JC L1
        MOV B, M
        MOV M, A
        DCX H
        MOV M, B
        INX H
        MVI D, 01H
L1:     DCR C
        JNZ L2
        MOV A, D
        RRC
        JC START
        HLT
```

10. A set of ten readings is stored in memory location starting at 1160H. The readings are expected to be positive (<127). WAP to

- Check each reading to determine whether it is positive or negative.
- Reject all negative readings.
- Add all positive readings & display sum in Port 1 and carry in Port 2.

```
        MVI B, 00H
        MVI C, 00H
        MVI D, 0AH
        LXI H, 1160H
L2:     MOV A, M
        RAL
        JC NEGLECT
        RAR
        ADD B
        JC L1
        MOV B, A
L1:     INR D
NEGLECT: INX H
        DCR D
        JNZ L2
        MOV A, B
        OUT PORT 1
        MOV A, D
        OUT PORT 2
        HLT
```

11. A set of six data bytes is stored starting from memory location 2050H. The set includes some blank spaces (bytes with zero values). WAP to eliminate the blanks from the block.

```
        MVI C, 06H
        LXI H, 2050H
        LXI B, 2050H
L2:     MOV A, M
        CPI 00H
        JZ L1
        STAX B
        INX B
L1:     INX H
        DCR C
        JNZ L2
        HLT
```

12. A set of eight data bytes (4 Pairs) are stored in memory locations starting from 1040H. WAP to add two bytes at a time and store the sum in same memory location, sum replacing the first byte and the carry replacing the second byte. If any pair does not generate a carry, the memory location of the second byte should be cleared i.e. store 00H over there.

```
        MVI C, 04H
        LXI H, 1040H
L2:     MOV A, M
        INX H
        ADD M
        DCX H
        MOV M, A
        INX H
        MVIM, 00H
        JNC L1
        MVIM, 01H
L1:     INX H
        DCR C
        JNZ L2
        HLT
```

13. WAP to read BCD number stored at memory location 2020H and converts it into binary equivalent and finally stores that binary pattern into memory location 2030H.

[Note: BCD number is the combination from 0 to 9]

```

MVI C, 0AH
LXI H, 2020H
MOV A, M
ANI F0H
RRC
RRC
RRC
RRC
MOV B, A
MOV A, 00H
L1: ADD B
    DCR C
    JNZ L1
    MOV D, A
    MOV A, M
    ANI 0FH
    ADD D
    STA 2030H
    HLT
```

14. A binary number (Suppose FF:  $1111\ 1111_2$ ) is stored in memory location 2020H. Convert the number into BCD and store each BCD as two unpacked BCD digits in memory location from 2030H.

```

LXI SP, 2000H
LXI H, 2020H
MOV A, M
CALL PWRTEN
HLT
PWETEN: LXI H, 2030H
        MVI B, 64H
        CALL BINBCD
        MOV M, D
        INX H
        MVI B, 0AH
        CALL BINBCD
        MOV M, D
        INX H
        MOV M, A
        RET
BINBCD: MVI D, 00H
NEXT:  INR D
        SUB B
        JNC NEXT
        DCR D
        ADD B
        RET
```

15. An 8 bit binary number is stored in memory location 1120H. WAP to store ASCII codes of these binary digits (0 to F) in location 1160H and 1161H.

LXI SP, 2000H	CODE:	CPI 0AH
LXI H, 1120H		JC L1
LXI D, 1160H		ADD 07H
MOV A, M	L1:	ADD 30H
ANI F0H		RET
RRC		
RRC		
RRC		
RRC		
CALL CODE		
STAX D		
INX D		
MOV A, M		
ANI 0FH		
CALL CODE		
STAX D		
HLT		

16. WAP to convert ASCII at location 1040H to binary and store at location 1050H.

LXI SP, 2000H	CODE:	CPI 40H
LXI H, 1040H		JC L1
LXI D, 1050H		SUB 07H
MOV A, M	L1:	SUB 30H
ANI F0H		RET
RRC		
RRC		
RRC		
RRC		
CALL CODE		
STAX D		
INX D		
MOV A, M		
ANI 0FH		
CALL CODE		
STAX D		
HLT		

17. A set of three packed BCD numbers are stored in memory locations starting at 1150H. The seven segment codes of digits 0 to 9 for a common cathode LED are stored in memory locations starting at 1170H and the output buffer memory is reserved at 1190H. WAP to unpack the BCD number and select an appropriate seven segment code for each digit. The codes should be stored in output buffer memory.

	LXI SP, 2999H	CODE: PUSH H
	LXI H, 1150H	LXI H, 1170H
	MVI D, 03H	ADD L
	LXI B, 1190H	MOV L, A
NEXT:	MOV A, M	MOV A, M
	ANI F0H	STAX B
	RRC	POP H
	RRC	RET
	RRC	
	RRC	
	CALL CODE	
	INX B	
	MOV A, M	
	ANI 0FH	
	CALL CODE	
	INX B	
	INX H	
	DCR D	
	JNZ NEXT	
	HLT	

18. A multiplicand is stored in memory location 1150H and a multiplier is stored in location 1151H. WAP to multiply these numbers and store result from 1160H.

	MVI B, 08H
	MVI D, 00H
	LXI H, 1150H
	MOV A, M
	MOV E, A
	LXI H, 1151H
	MOV A, M
L2:	RAR
	JNC L1
	LXI H, 0000H
	DAD D
L1:	XCHG
	DAD H
	XCHG
	DCR B
	LNZ L2
	HLT



19. A set of ten packed BCD numbers is stored in the memory location starting at 1150H. WAP to add these numbers in BCD. If carry is generated save it in register B and adjust it for BCD. The final sum is less than 9999<sub>BCD</sub>.

```
LXI SP, 2000H
LXI H, 1150H
MVI C, 0AH
XRA A
MOV B, A
L1:  CALL ADD
      INX H
      DCR C
      JNZ L1
      HLT
```

```
ADD:  ADD M
      DAA
      RNC
      MOV D, A
      MOV A, B
      ADI 01H
      DAA
      MOV B, A
      MOV A, D
      RET
```

20. A dividend is stored in memory location 2020H and a divisor is stored in 2021H. WAP to divide these numbers and store quotient and remainder from 2040H.

```
MVI C, 00H
LXI H, 2021H
MOV A, M
MOV D, A
DCX H
MOV B, M
L2:  MOV A, B
      SUB D
      JC L1
      MOV B, A
      INR C
      JMP L2
L1:  MOV L, C
      MOV H, B
      SHLD 2040H
      HLT
```

21. Write a program for 8085 to convert and copy the ten lower case ASCII codes to upper case from memory location 9050H to 90A0H if any, otherwise copy as they are. Assume there are fifty codes in the source memory. [Note: ASCII code for A=65 ... Z=90, a=97 ... z=122].  
[2063 Kartik]

```
LXI H, 9050H
LXI D, 90A0H
MVI C, 32H
L2:  MOV A, M
      CPI 60H
      JC L1
      SUI 20H
L1:  STAX D
      DCR C
      JNZ L2
      HLT
```


22. Write a program for 8085 to add ten 16-bit BCD numbers from location 4050H and store 24-bit BCD result at the end of the ten given numbers.  
[2062 Chaitra]

```
LXI B, 4050H ; Starting location of the 16-bit BCD Numbers
LXI D, 0000H
LXI H, 0000H
MVI A, 00H

L2:  LDAX B
      ADD L
      INX B
      LDAX B
      ADC H
      JNC L1
      INR E
L1:  INX B
      MOV A, C
      CPI 0AH
      JC L2

      MOV A, L
      STAX B
      INX B
      MOV A, H
      STAX B
      INX B
      MOV A, E
      STAX B
      HLT
```

23. Write an 8085 program to display the BCD digits from 0 to 9 the seven segments as in the following diagram. Use the activating data bits same as the segment number as in figure below. [2059 Shrawan]



```
LXI SP, 2999H
LXI H, 2050H
MOV M, 3FH
INX H
MOV M, 06H
INX H
MOV M, 5BH
INX H
MOV M, 4FH
INX H
MOV M, 66H
INX H
MOV M, 6DH
INX H
MOV M, 7DH
INX H
MOV M, 07H
INX H
MOV M, 7FH
INX H
MOV M, 6FH
LXI B, 2060H
```

```
LDAX B ; Where the BCD digit is located
ANI F0H
RRC
RRC
RRC
RRC
CALL CODE
OUT PORT 1
LDAX B
ANI 0FH
CALL CODE
OUT PORT 2
HLT
```

CODE:

```
LXI H, 2050H
ADD L
MOV L, A
MOV A, M
RET
```

24. Write a program for 8085 to change the bit  $D_5$  of ten numbers stored at address 7600H if the numbers are larger than or equal to 80H. [2061 Ashwin]

```
        LXI H, 7600H
        MVI C, 0AH
L2:     MOV A, M
        CPI 80H
        JC L1
        XRI 20H
        MOV M, A
L1:     INX H
        DCR C
        JNZ L2
```

25. Write a program for 8085 to find the smallest number among ten numbers stored at memory location 4500H. [2060 Bhadra]

```
        LXI H, 4500H
        MVI C, 0AH
        MOV A, M
L2:     INX H
        CMP M
        JC L1
        MOV B, A
        MOV A, M
        MOV M, B
L1:     DCR C
        JNZ L2
        OUT PORT 1
        HLT
```

26. Someone has damaged a program written at 4050H for 8085 microprocessor. The damaging is done by changing the bit D<sub>7</sub> and bit D<sub>5</sub> of each byte. The size of the program is 100 bytes. Now write a program for 8085 to correct this damaged program. [2060 Chaitra]

```
LXI H, 4050H
MVI C, 64H
L1:  MOV A, M
      ANI 80H ; 10000000 B
      RRC
      RRC
      MOV B, A
      MOV A, M
      ANI 20H ; 00100000 B
      RLC
      RLC
      MOV C, A
      MOV A, M
      ANI 5FH ; 01011111 B
      ORA B
      ORA C
      STAX H
      INX H
      DCR C
      JNZ L1
      HLT
```

27. The temperature of two furnaces being monitored by a microprocessor based system. A set of readings of the first furnace recorded by thermal sensor is stored at memory locations starting at 4050H. Corresponding readings from the second furnace is stored at the memory location starting at 4070H. Each reading from the first furnace is expected to be higher than the corresponding reading from the second furnace. Among the eight bit data bit D<sub>7</sub> is used to test the validity of the data. Write an 8085 program to compare valid data from the two tables, if data from first table is larger than the corresponding data from the second table store 01H in the corresponding memory of the third location starting at 4090H and display 01H to indicate the normal operation else store FFH in the corresponding memory location and display FFH in the port to indicate the emergency. When emergency condition is reached stop the operation.

[2060 Jestha]

```

        LXI B, 4050H
        LXI H, 4070H
        LXI D, 4090H
L2:     LDAX B
        CMP M
        JC L1
        JZ L1
        MVI A, 01H
        STAX D
        OUT PORT
        INX B
        IND H
        INX D
        JMP L2
L1:     MVI A, FFH
        STAX D
        OUT PORT
        HLT

```

28. Write a program to transfer eight-bit numbers from 9080H to 9090H if bit D<sub>5</sub> is 1 and D<sub>3</sub> is 0. Otherwise transfer data by changing bit D<sub>2</sub> and D<sub>6</sub> from 1 to 0 or from 0 to 1. Assume there are ten numbers.

[2064 Shrawan]

```

        LXI H, 9080H
        LXI D, 9090H
        MVI C, 0AH
L2:     MOV A, M
        ANI 28H
        CPI 20H
        JZ L1
        MOV A, M
        XRI 44H
        MOV M, A
L1:     MOV A, M
        STAX D
        INX H
        INX D
        DCR C
        JNZ L2
        HLT

```

29. There are two tables T1, T2 in memory having ten eight bit data in each. Write a program for 8085 to find the difference of the corresponding element of these two tables. Store the result of each operation on the corresponding element of the third table. Remember that the result should not be negative ; it should be  $|T1 - T2|$ . [2064 Poush]

```

        LXI SP, 2999H
        LXI H, 5000H      ; TABLE T1
        LXI D, 6000H      ; TABLE T2
        MVI C, 0AH        ; COUNTER FOR 10 DATA
L1:     LDAX D
        MOV B, A
        MOV A, M
        CMP B
        JNC L2
        MOV A, B
        MOV B, M
L2:     SUB B
        PUSH D
        MVI D, 70H        ; TABLE T3
        STAX D
        POP D
        INX H
        INX D
        DCR C
        JNZ L1
        HLT

```

30. Write a program for 8085 to transfer data from a table to another if the number of ones in the data is greater than four else store 00 in the next table. [2065 Kartik]

```

        LXI H, 5000H      ; SOURCE TABLE
        LXI D, 6000H      ; DESTINATION TABLE
ST:     MVI C, 08H        ; NO OF BITS
        MVI B, 00H        ; NO OF 1'S
        MOV A, M
L1:     RLC
        JNC L2
        INR B
L2:     DCR C
        JNZ L1
        MOV A, B
        CPI 04H
        MVI A, 00H
        JC L3
        JZ L3
        MOV A, M
L3:     STAX D
        INX H
        INX D
        MOV A, E
        CPI 0AH          ; SUPPOSE TABLE FOR 10 DATA
        JNZ ST
        HLT

```

31. Write an assembly language program to count no. of –ve element in a data block containing 16 bytes of data; store the count at the end of the block if the count is greater than 8 otherwise stores 0. [2065 Chaitra]

