

### FEATURES

- Qualified for automotive applications
- Complete rate gyroscope on a single chip
- Z-axis (yaw rate) response
- High vibration rejection over wide frequency
- 2000 g powered shock survivability
- Ratiometric to referenced supply
- 5 V single-supply operation
- 105°C operation
- Self-test on digital command
- Ultrasmall and light (<0.15 cc, <0.5 gram)
- Temperature sensor output
- RoHS compliant

### APPLICATIONS

- Vehicle chassis rollover sensing
- Inertial measurement units
- Platform stabilization

### GENERAL DESCRIPTION

The ADXRS620 is a complete angular rate sensor (gyroscope) that uses the Analog Devices, Inc., surface-micromachining process to create a functionally complete and low cost angular rate sensor integrated with all required electronics on one chip. The manufacturing technique for this device is the same high volume BiMOS process that is used for high reliability automotive airbag accelerometers.

The ADXRS620 is an automotive grade gyroscope that is 100% pin, package, temperature, and function compatible to the available industrial grade ADXRS652 gyro. Automotive grade gyroscopes have more extensive guaranteed minimum/maximum specifications due to automotive testing.

The output signal, RATEOUT (1B, 2A), is a voltage that is proportional to angular rate about the axis normal to the top surface of the package. The output is ratiometric with respect to a provided reference supply. An external capacitor sets the bandwidth. Other external capacitors are required for operation.

A temperature output is provided for compensation techniques. Two digital self-test inputs electromechanically excite the sensor to test proper operation of both the sensor and the signal conditioning circuits. The ADXRS620 is available in a 7 mm × 7 mm × 3 mm BGA ceramic package.

### FUNCTIONAL BLOCK DIAGRAM




Figure 1.

#### Rev. B

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

# ADXRS620\* Product Page Quick Links

Last Content Update: 08/30/2016

---

## Comparable Parts

View a parametric search of comparable parts

## Evaluation Kits

- ADXRS620 Evaluation Board

## Documentation

### Data Sheet

- ADXRS620:  $\pm 300^\circ/\text{sec}$  Yaw Rate Gyro Data Sheet

### User Guides

- UG-149: Evaluation Board User Guide for ADXRS620

## Reference Materials

### White Papers

- The Five Motion Senses: MEMS Inertial Sensing to Transform Applications

## Design Resources

- ADXRS620 Material Declaration
- PCN-PDN Information
- Quality And Reliability
- Symbols and Footprints

## Discussions

View all ADXRS620 EngineerZone Discussions

## Sample and Buy

Visit the product page to see pricing options

## Technical Support

Submit a technical question or find your regional support number

---

\* This page was dynamically generated by Analog Devices, Inc. and inserted into this data sheet. Note: Dynamic changes to the content on this page does not constitute a change to the revision number of the product data sheet. This content may be frequently modified.

## TABLE OF CONTENTS

|  |   |  |    |
|--|---|--|----|
| Features .....                                   | 1 | Setting Bandwidth .....                  | 9  |
| Applications.....                                | 1 | Temperature Output and Calibration.....  | 9  |
| General Description .....                        | 1 | Calibrated Performance.....              | 9  |
| Functional Block Diagram .....                   | 1 | ADXRS620 and Supply Ratiometricity ..... | 10 |
| Revision History .....                           | 2 | Null Adjustment .....                    | 10 |
| Specifications.....                              | 3 | Self-Test Function .....                 | 10 |
| Absolute Maximum Ratings.....                    | 4 | Continuous Self-Test.....                | 10 |
| Rate Sensitive Axis .....                        | 4 | Outline Dimensions .....                 | 11 |
| ESD Caution.....                                 | 4 | Ordering Guide .....                     | 11 |
| Pin Configuration and Function Descriptions..... | 5 | Automotive Products.....                 | 11 |
| Typical Performance Characteristics .....        | 6 |  |    |
| Theory of Operation .....                        | 9 |  |    |

## REVISION HISTORY

### 9/10—Rev. A to Rev. B

|                                 |    |
|---------------------------------|----|
| Changes to Ordering Guide ..... | 11 |
|---------------------------------|----|

### 7/10—Rev. 0 to Rev. A

|   |    |
|---|----|
| Changes to Features Section and General Description Section . | 1  |
| Added Note 2 to Ordering Guide.....                           | 11 |
| Added Automotive Products Section.....                        | 11 |

### 3/10—Revision 0: Initial Version

## SPECIFICATIONS

All minimum and maximum specifications are guaranteed. Typical specifications are not guaranteed.  $T_A = -40^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$ ,  $V_S = AV_{CC} = V_{DD} = 5\text{ V}$ ,  $V_{\text{RATIO}} = AV_{CC}$ , angular rate =  $0^{\circ}/\text{sec}$ , bandwidth =  $80\text{ Hz}$  ( $C_{\text{OUT}} = 0.01\text{ }\mu\text{F}$ ),  $I_{\text{OUT}} = 100\text{ }\mu\text{A}$ ,  $\pm 1\text{ g}$ , unless otherwise noted.

Table 1.

| Parameter                                | Conditions   | Min       | Typ     | Max    | Unit                                   |
|--|--|-----------|---------|--------|--|
| SENSITIVITY <sup>1</sup>                 | Clockwise rotation is positive output                    |           |         |        |  |
| Measurement Range <sup>2</sup>           | Full-scale range over specifications range               | $\pm 300$ |         |        | $^{\circ}/\text{sec}$                  |
| Initial and Over Temperature             | $-40^{\circ}\text{C}$ to $+105^{\circ}\text{C}$          | 5.52      | 6       | 6.48   | $\text{mV}/^{\circ}/\text{sec}$        |
| Temperature Drift <sup>3</sup>           |  |           | $\pm 2$ |        | %                                      |
| Nonlinearity                             | Best fit straight line                                   |           | 0.1     |        | % of FS                                |
| NULL <sup>1</sup>                        |  |           |         |        |  |
| Null                                     | $-40^{\circ}\text{C}$ to $+105^{\circ}\text{C}$          | 2.2       | 2.5     | 2.8    | V                                      |
| Linear Acceleration Effect               | Any axis   |           | 0.1     |        | $^{\circ}/\text{sec}/\text{g}$         |
| NOISE PERFORMANCE                        |  |           |         |        |  |
| Rate Noise Density                       | $T_A \leq 25^{\circ}\text{C}$                            |           | 0.05    |        | $^{\circ}/\text{sec}/\sqrt{\text{Hz}}$ |
| FREQUENCY RESPONSE                       |  |           |         |        |  |
| Bandwidth <sup>4</sup>                   |  | 0.01      |         | 2500   | Hz                                     |
| Sensor Resonant Frequency                |  | 12        | 14.5    | 17     | kHz                                    |
| SELF-TEST <sup>1</sup>                   |  |           |         |        |  |
| ST1 RATEOUT Response                     | ST1 pin from Logic 0 to Logic 1                          | $-650$    | $-450$  | $-250$ | mV                                     |
| ST2 RATEOUT Response                     | ST2 pin from Logic 0 to Logic 1                          | 250       | 450     | 650    | mV                                     |
| ST1 to ST2 Mismatch <sup>5</sup>         |  | $-5$      |         | $+5$   | %                                      |
| Logic 1 Input Voltage                    |  | 3.3       |         |        | V                                      |
| Logic 0 Input Voltage                    |  |           |         | 1.7    | V                                      |
| Input Impedance                          | To common  | 40        | 50      | 100    | k $\Omega$                             |
| TEMPERATURE SENSOR <sup>1</sup>          |  |           |         |        |  |
| $V_{\text{OUT}}$ at $25^{\circ}\text{C}$ | Load = $10\text{ M}\Omega$                               | 2.35      | 2.5     | 2.65   | V                                      |
| Scale Factor <sup>6</sup>                | @ $25^{\circ}\text{C}$ , $V_{\text{RATIO}} = 5\text{ V}$ |           | 9       |        | $\text{mV}/^{\circ}\text{C}$           |
| Load to $V_S$                            |  |           | 25      |        | k $\Omega$                             |
| Load to Common                           |  |           | 25      |        | k $\Omega$                             |
| TURN-ON TIME                             | Power on to $\pm 1/2^{\circ}/\text{sec}$ of final        |           |         | 50     | ms                                     |
| OUTPUT DRIVE CAPABILITY                  |  |           |         |        |  |
| Current Drive                            | For rated specifications                                 |           |         | 200    | $\mu\text{A}$                          |
| Capacitive Load Drive                    |  |           |         | 1000   | pF                                     |
| POWER SUPPLY                             |  |           |         |        |  |
| Operating Voltage ( $V_S$ )              |  | 4.75      | 5.00    | 5.25   | V                                      |
| Quiescent Supply Current                 |  |           | 3.5     | 4.5    | mA                                     |
| TEMPERATURE RANGE                        |  |           |         |        |  |
| Specified Performance                    |  | $-40$     |         | $+105$ | $^{\circ}\text{C}$                     |

<sup>1</sup> Parameter is linearly ratiometric with  $V_{\text{RATIO}}$ .

<sup>2</sup> The maximum range possible, including output swing range, initial offset, sensitivity, offset drift, and sensitivity drift at 5 V supplies.

<sup>3</sup> From  $+25^{\circ}\text{C}$  to  $-40^{\circ}\text{C}$  or from  $+25^{\circ}\text{C}$  to  $105^{\circ}\text{C}$ .

<sup>4</sup> Adjusted by external capacitor,  $C_{\text{OUT}}$ . Reducing bandwidth below  $0.01\text{ Hz}$  does not reduce noise further.

<sup>5</sup> Self-test mismatch is described as  $(ST2 + ST1)/((ST2 - ST1)/2)$ .

<sup>6</sup> For a change in temperature from  $25^{\circ}\text{C}$  to  $26^{\circ}\text{C}$ .  $V_{\text{TEMP}}$  is ratiometric to  $V_{\text{RATIO}}$ . See the Temperature Output and Calibration section for more details.

## ABSOLUTE MAXIMUM RATINGS

Table 2.

| Parameter  | Rating           |
|--|------------------|
| Acceleration (Any Axis, 0.5 ms)                      |                  |
| Unpowered  | 2000 g           |
| Powered  | 2000 g           |
| $V_{DD}$ , $V_{CC}$                                  | –0.3 V to +6.0 V |
| $V_{RATIO}$  | $V_{CC}$         |
| ST1, ST2   | $V_{CC}$         |
| Output Short-Circuit Duration<br>(Any Pin to Common) | Indefinite       |
| Operating Temperature Range                          | –55°C to +125°C  |
| Storage Temperature Range                            | –65°C to +150°C  |

Stresses above those listed under the Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Drops onto hard surfaces can cause shocks of greater than 2000 g and can exceed the absolute maximum rating of the device. Exercise care during handling to avoid damage.

## RATE SENSITIVE AXIS

The ADXRS620 is a Z-axis rate-sensing device (also called a yaw rate sensing device). It produces a positive going output voltage for clockwise rotation about the axis normal to the package top, that is, clockwise when looking down at the package lid.




Figure 2. RATEOUT Signal Increases with Clockwise Rotation

## ESD CAUTION



**ESD (electrostatic discharge) sensitive device.** Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

## PIN CONFIGURATION AND FUNCTION DESCRIPTIONS




Figure 3. Pin Configuration

Table 3. Pin Function Descriptions

| Pin No. | Mnemonic           | Description                             |
|---------|--------------------|---|
| 6D, 7D  | CP5                | HV Filter Capacitor (0.1 $\mu$ F)       |
| 6A, 7B  | CP4                | Charge Pump Capacitor (22 nF)           |
| 6C, 7C  | CP3                | Charge Pump Capacitor (22 nF)           |
| 5A, 5B  | CP1                | Charge Pump Capacitor (22 nF)           |
| 4A, 4B  | CP2                | Charge Pump Capacitor (22 nF)           |
| 3A, 3B  | AV <sub>CC</sub>   | Positive Analog Supply                  |
| 1B, 2A  | RATEOUT            | Rate Signal Output                      |
| 1C, 2C  | SUMJ               | Output Amp Summing Junction             |
| 1D, 2D  | NC                 | No Connect                              |
| 1E, 2E  | V <sub>RATIO</sub> | Reference Supply for Ratiometric Output |
| 1F, 2G  | AGND               | Analog Supply Return                    |
| 3F, 3G  | TEMP               | Temperature Voltage Output              |
| 4F, 4G  | ST2                | Self-Test for Sensor 2                  |
| 5F, 5G  | ST1                | Self-Test for Sensor 1                  |
| 6G, 7F  | PGND               | Charge Pump Supply Return               |
| 6E, 7E  | V <sub>DD</sub>    | Positive Charge Pump Supply             |

## TYPICAL PERFORMANCE CHARACTERISTICS

N > 1000 for all typical performance plots, unless otherwise noted.




Figure 4. Null Output at 25°C ( $V_{RATIO} = 5V$ )




Figure 7. Sensitivity Drift over Temperature




Figure 5. Null Drift over Temperature ( $V_{RATIO} = 5V$ )




Figure 8. ST1 Output Change at 25°C ( $V_{RATIO} = 5V$ )




Figure 6. Sensitivity at 25°C ( $V_{RATIO} = 5V$ )




Figure 9. ST2 Output Change at 25°C ( $V_{RATIO} = 5V$ )




Figure 10. Self-Test Mismatch at 25°C ( $V_{RATIO} = 5\text{ V}$ )




Figure 13.  $V_{TEMP}$  Output at 25°C ( $V_{RATIO} = 5\text{ V}$ )




Figure 11. Typical Self-Test Change over Temperature




Figure 14.  $V_{TEMP}$  Output over Temperature ( $V_{RATIO} = 5\text{ V}$ )




Figure 12. Current Consumption at 25°C ( $V_{RATIO} = 5\text{ V}$ )




Figure 15.  $g$  and  $g \times g$  Sensitivity for a 50 g, 10 ms Pulse






Figure 16. Typical Response to 10 g Sinusoidal Vibration (Sensor Bandwidth = 2 kHz)




Figure 19. Typical Shift in 90 sec Null Averages Accumulated over 140 Hours




Figure 17. Typical High g (2500 g) Shock Response (Sensor Bandwidth = 40 Hz)




Figure 20. Typical Shift in Short-Term Null (Bandwidth = 1 Hz)




Figure 18. Typical Root Allan Deviation at 25°C vs. Averaging Time




Figure 21. Typical Noise Spectral Density (Bandwidth = 40 Hz)

## THEORY OF OPERATION

The ADXRS620 operates on the principle of a resonator gyro. Two polysilicon sensing structures each contain a dither frame that is electrostatically driven to resonance, producing the necessary velocity element to produce a Coriolis force during angular rate. At two of the outer extremes of each frame, orthogonal to the dither motion, are movable fingers that are placed between fixed pickoff fingers to form a capacitive pickoff structure that senses Coriolis motion. The resulting signal is fed to a series of gain and demodulation stages that produces the electrical rate signal output. The dual-sensor design rejects external g-forces and vibration. Fabricating the sensor with the signal conditioning electronics preserves signal integrity in noisy environments.

The electrostatic resonator requires 18 V to 20 V for operation. Because only 5 V are typically available in most applications, a charge pump is included on chip. If an external 18 V to 20 V supply is available, the two capacitors on CP1 through CP4 can be omitted and this supply can be connected to CP5 (Pin 6D, Pin 7D). Note that CP5 should not be grounded when power is applied to the ADXRS620. Although no damage occurs, under certain conditions the charge pump may fail to start up after the ground is removed without first removing power from the ADXRS620.

### SETTING BANDWIDTH

External Capacitor  $C_{OUT}$  is used in combination with the on-chip  $R_{OUT}$  resistor to create a low-pass filter to limit the bandwidth of the ADXRS620 rate response. The -3 dB frequency set by  $R_{OUT}$  and  $C_{OUT}$  is

$$f_{OUT} = \frac{1}{(2 \times \pi \times R_{OUT} \times C_{OUT})}$$

This frequency can be well controlled because  $R_{OUT}$  has been trimmed during manufacturing to be  $180 \text{ k}\Omega \pm 1\%$ . Any external resistor applied between the RATEOUT pin (1B, 2A) and SUMJ pin (1C, 2C) results in

$$R_{OUT} = \frac{(180 \text{ k}\Omega \times R_{EXT})}{(180 \text{ k}\Omega + R_{EXT})}$$

In general, an additional hardware or software filter is added to attenuate high frequency noise arising from demodulation spikes at the gyro's 14 kHz resonant frequency. (The noise spikes at 14 kHz can be clearly seen in the power spectral density curve shown in Figure 21). Typically, this additional filter's corner frequency is set to greater than 5× the required bandwidth to preserve good phase response.

Figure 22 shows the effect of adding a 250 Hz filter to the output of an ADXRS620 set to 40 Hz bandwidth (as shown in Figure 21). High frequency demodulation artifacts are attenuated by approximately 18 dB.




Figure 22. Noise Spectral Density with Additional 250 Hz Filter

### TEMPERATURE OUTPUT AND CALIBRATION

It is common practice to temperature-calibrate gyros to improve their overall accuracy. The ADXRS620 has a temperature proportional voltage output that provides input to such a calibration method. The temperature sensor structure is shown in Figure 23. The temperature output is characteristically nonlinear, and any load resistance connected to the TEMP output results in decreasing the TEMP output and temperature coefficient. Therefore, buffering the output is recommended.

The voltage at the TEMP pin (3F, 3G) is nominally 2.5 V at 25°C, and  $V_{RATIO} = 5 \text{ V}$ . The temperature coefficient is  $\sim 9 \text{ mV}/^\circ\text{C}$  at 25°C. Although the TEMP output is highly repeatable, it has only modest absolute accuracy.




Figure 23. Temperature Sensor Structure

### CALIBRATED PERFORMANCE

Using a three-point calibration technique, it is possible to calibrate the null and sensitivity drift of the ADXRS620 to an overall accuracy of nearly 200°/hour. An overall accuracy of 40°/hour or better is possible using more points.

Limiting the bandwidth of the device reduces the flat-band noise during the calibration process, improving the measurement accuracy at each calibration point.

# ADXRS620

## ADXRS620 AND SUPPLY RATIOMETRICITY

The ADXRS620 RATEOUT and TEMP signals are ratiometric to the  $V_{\text{RATIO}}$  voltage, that is, the null voltage, rate sensitivity, and temperature outputs are proportional to  $V_{\text{RATIO}}$ . Thus, the ADXRS620 is most easily used with a supply-ratiometric ADC that results in self-cancellation of errors due to minor supply variations. There is some small error due to nonratiometric behavior. Typical ratiometricity error for null, sensitivity, self-test, and temperature output is outlined in Table 4.

Note that  $V_{\text{RATIO}}$  must never be greater than  $AV_{\text{CC}}$ .

**Table 4. Ratiometricity Error for Various Parameters**

| Parameter         | $V_S = V_{\text{RATIO}} = 4.85 \text{ V}$ | $V_S = V_{\text{RATIO}} = 5.15 \text{ V}$ |
|-------------------|---|---|
| ST1               |   |   |
| Mean              | 0.3%                                      | 0.09%                                     |
| Sigma             | 0.21%                                     | 0.19%                                     |
| ST2               |   |   |
| Mean              | −0.15%                                    | −0.2%                                     |
| Sigma             | 0.22%                                     | 0.2%                                      |
| Null              |   |   |
| Mean              | −0.3%                                     | −0.05%                                    |
| Sigma             | 0.2%                                      | 0.08%                                     |
| Sensitivity       |   |   |
| Mean              | 0.003%                                    | −0.25%                                    |
| Sigma             | 0.06%                                     | 0.06%                                     |
| $V_{\text{TEMP}}$ |   |   |
| Mean              | −0.2%                                     | −0.04%                                    |
| Sigma             | 0.05%                                     | 0.06%                                     |

## NULL ADJUSTMENT

The nominal 2.5 V null is for a symmetrical swing range at RATEOUT (1B, 2A). However, a nonsymmetrical output swing may be suitable in some applications. Null adjustment is possible by injecting a suitable current to SUMJ (1C, 2C). Note that supply disturbances may reflect some null instability. Digital supply noise should be avoided, particularly in this case.

## SELF-TEST FUNCTION

The ADXRS620 includes a self-test feature that actuates each of the sensing structures and associated electronics as if subjected to angular rate. It is activated by standard logic high levels applied to Input ST1 (5F, 5G), Input ST2 (4F, 4G), or both. ST1 causes the voltage at RATEOUT to change about −0.450 V, and ST2 causes an opposite change of +0.450 V. The self-test response follows the viscosity temperature dependence of the package atmosphere, approximately 0.25%/°C.


Activating both ST1 and ST2 simultaneously is not damaging. ST1 and ST2 are fairly closely matched ( $\pm 5\%$ ), but actuating both simultaneously may result in a small apparent null bias shift proportional to the degree of self-test mismatch.

ST1 and ST2 are activated by applying a voltage equal to  $V_{\text{RATIO}}$  to the ST1 and ST2 pins. The voltage applied to ST1 and ST2 must never be greater than  $AV_{\text{CC}}$ .

## CONTINUOUS SELF-TEST

The on-chip integration of the ADXRS620 gives it higher reliability than is obtainable with any other high volume manufacturing method. In addition, it is manufactured under a mature BiMOS process with field-proven reliability. As an additional failure detection measure, a power-on self-test can be performed. However, some applications may warrant continuous self-test while sensing rate. Details outlining continuous self-test techniques are also available in the [AN-768](#) Application Note at [analog.com](#).

## OUTLINE DIMENSIONS



\*BALL A1 IDENTIFIER IS GOLD PLATED AND CONNECTED TO THE D/A PAD INTERNALLY VIA HOLES.

Figure 24. 32-Lead Ceramic Ball Grid Array [CBGA]  
(BG-32-3)

Dimensions shown in millimeters

10-56-2009-B

## ORDERING GUIDE

| Model <sup>1,2</sup> | Temperature Range | Package Description                    | Package Option |
|----------------------|-------------------|--|----------------|
| ADXRS620BBGZ         | -40°C to +105°C   | 32-Lead Ceramic Ball Grid Array (CBGA) | BG-32-3        |
| ADXRS620BBGZ-RL      | -40°C to +105°C   | 32-Lead Ceramic Ball Grid Array (CBGA) | BG-32-3        |
| ADXRS620WBBGZA       | -40°C to +105°C   | 32-Lead Ceramic Ball Grid Array (CBGA) | BG-32-3        |
| ADXRS620WBBGZA-RL    | -40°C to +105°C   | 32-Lead Ceramic Ball Grid Array (CBGA) | BG-32-3        |
| EVAL-ADXRS620Z       |                   | Evaluation Board                       |                |

<sup>1</sup> Z = RoHS Compliant Part.

<sup>2</sup> W = Qualified for Automotive Applications.

## AUTOMOTIVE PRODUCTS

The ADXRS620W models are available with controlled manufacturing to support the quality and reliability requirements of automotive applications. Note that these automotive models may have specifications that differ from the commercial models; therefore, designers should review the Specifications section of this data sheet carefully. Only the automotive grade products shown are available for use in automotive applications. Contact your local Analog Devices account representative for specific product ordering information and to obtain the specific Automotive Reliability reports for these models.

**ADXRS620**

**NOTES**