Match the following

A		B	
1.	ceil()	(a)	Writes HTML expression or JavaScript code to a document.
2.	floor()	(b)	Sets focus to current window.
3.	write()	(c)	Removes white spaces from both sides of string.
4.	focus()	(d)	Returns next integer greater than or equal to given number.
5.	trim()	(e)	Returns the next integer less than or equal to given number.

Ans. : 1. – d, 2. - e, 3. - a, 4. - b, 5. - c

Fill in the Blanks

3.1 Introduction

1. ..... is an interpreted scripting language.

Ans. : **JavaScript**

2. ..... is a set of instructions used to produce various kinds of outputs.

Ans. : **Program**

3. The programs in JavaScript language are called .....

Ans. : **Scripts**

4. ..... is an object oriented scripting language and supports event based programming facility. (March 2022)

Ans. : **JavaScript**

5. ..... is platform independent scripting language.

Ans. : **JavaScript**

6. ..... is knows as Universal client side scripting language.

Ans. : **JavaScript**

7. In ..... scripting the script resides on the client computer. (March 2024)

Ans. : **Client side**

8. In ..... scripting the script resides on web server.

Ans. : **Server side**

9. ..... scripting does not need any server interaction.

Ans. : **Client side**

10. ..... scripting communicates to the server.

Ans. : **Server side**

11. ..... scripts are used for validation purpose. (March 2023)

Ans. : **Client side**

12. ..... scripts requires web browser as an interface.

Ans. : **Client side**

13. ..... scripts requires web server software to execute.

Ans. : Server side

14. ..... is a JavaScript based open source frontend web framework developed for single page application.

Ans. : Angular JS

15. ..... is JavaScript based framework for building interactive user interface.

Ans. : Vue Js

16. In JavaScript function is declared using ..... keyword. (March 2023)

Ans. : function

17. ..... consists of JavaScript libraries for building UI for single page application and mobile application..

Ans. : React

18. At the backend _____ scripting in used. (March 2023)

Ans. : server side

19. _____ is a light weight scripting language. (March 2023)

Ans. : Javascript

3.2 Switch case and Looping Structures

20. JavaScript has a built-in multiway decision statement known as ..... (March 2022, 24)

Ans. : Switch

21. ..... refers to the execution of statement or a group of statements of code for a fixed number of times.

Ans. : Iteration

22. ..... loop combines initialization, condition and loop iteration in single statement. (March 2022, 24)

Ans. : For

23. ..... means increment or decrement value of a running variable.

Ans. : Iteration

24. ..... statement is used to jump out of loop. (March 2022)

Ans. : Break

25. When is necessary to skip statement block and take the control at the beginning for next iteration ..... statement is used. (March 2022, 24)

Ans. : Continue

3.3 Objects in JavaScript

26. The ..... keyword is used to create new object in JavaScript. (March 2022, 24)

Ans. : new

27. An ..... can group data together with functions needed to manipulate it.

Ans. : Object

28. All tangible things are known as ..... **(March 2022)**

Ans. : Objects

29. DOM stands for ..... **(March 2022, 23)**

Ans. : Document Object Model

30. The way in which HTML document content is accessed and modified is called as .....

Ans. : Document Object Model

31. ..... property of DOM object returns the <head> element of the document. **(March 2022, 24)**

Ans. : Head

32. ..... is an object based scripting language.

Ans. : JavaScript

33. ..... property of DOM object sets or returns title of the document.

Ans. : Title

34. ..... property of DOM object returns URL of the HTML document.

Ans. : URL

35. ..... method of DOM object writes HTML expressions or JavaScript code to a document. **(March 2022, 24)**

Ans. : write()

36. ..... method of DOM object adds a newline character after each statement.

Ans. : writeln()

37. Using ..... method id property is used to find an element.

Ans. : getElementById()

38. The ..... property is useful for getting html element and changing its content. **(March 2022)**

Ans. : innerHTML

39. In JavaScript, ... object is parent of all other objects. **(March 2023, 24)**

Ans. : window

40. ..... object represents an open window in a browser.

Ans. : window

41. ..... property of window object sets or returns the name of the window.

Ans. : Name

42. ..... property of window object returns the location object for the window. **(March 2023)**

Ans. : location

43. ..... property of window object returns the document object for the window.

Ans. : document

44. ..... property of window object sets or returns the text in the status bar of a window. (March 2023)

Ans. : status

45. ..... property of window object returns a Boolean value indicating whether a window has been closed or not.

Ans. : closed

46. ..... method of window object display the alert box containing message with OK button.

Ans. : alert ()

47. ..... method of window object displays the confirm dialog box containing message with ok and cancel button.

Ans. : confirm()

48. ..... method of window object displays a dialog box to get input from the user. (March 2022, 24)

Ans. : prompt()

49. ..... method of window object opens the new window.

Ans. : open()

50. ..... method of window object closes the current window. (March 2023)

Ans. : close()

51. ..... method of window object removes focus from the current window. (March 2023, 24)

Ans. : blur()

52. ..... method of window object sets focus to the current window. (March 2023)

Ans. : focus()

53. ..... method of window object prints the content of current window.

Ans. : print()

54. ..... method of window object calls a function or evaluates an expression after a specified number of milliseconds. (March 2024)

Ans. : setTimeout()

55. The _____ method of DOM is used to access form elements. (March 2023)

Ans. : getElementByID()

56. Logical structure of document is defined by _____ object. (March 2023)

Ans. : document

3.4 JavaScript Events

57. ..... are the actions done by users or an application that occurs on the webpage . (March 2022)

Ans. : Events

58. ..... event handler occurs when user leaves field or looses focus of an element. (March 2023)

Ans. : **onblur**

59. ..... event handler occurs when an element gets focus . (March 2023)

Ans. : **onfocus**

60. ..... event handler occurs when user changes content of an element or selects drop down list . (March 2022, 23, 24)

Ans. : **onchange**

61. ..... event handler occurs when user selects some text of an element .

Ans. : **onselect**

62. ..... event handler occurs when user clicks submit button . (March 2023)

Ans. : **onsubmit**

63. ..... event handler occurs when user clicks reset button .

Ans. : **onreset**

64. ..... event handler occurs when page/image has been loaded. (March 2023, 24)

Ans. : **onload**

65. ..... event handler occurs when document page has been unloaded or closes .

Ans. : **onunload**

3.5 JavaScript built-in Objects

66. ..... object helps us to work with number.

Ans. : **Number**

67. ..... property of Number object returns the largest minimum value. (March 2022, 23, 24)

Ans. : **MIN_VALUE**

68. ..... property of number object returns the largest maximum value. (March 2022, 23)

Ans. : **MAX_VALUE**

69. ..... property of Number object represents not a number value.

Ans. : **NaN**

70. ..... method of number object determines whether the given value is an Integer. (March 2022, 24)

Ans. : **isInteger()**

71. ..... method of number object converts the given string into a floating point number.

Ans. : **parseFloat()**

72. ..... method of Number object converts the given string into a integer number.

Ans. : **parseInt()**

73. ..... method of number object returns the string that represents a number with exact digits after a decimal point.

Ans. : isFixed()

74. ..... object is used to store or manipulate text . (March 2022)

Ans. : String

75. ..... property of string object returns number of characters in a string. (March 2022, 23)

Ans. : Length

76. ..... method of string object returns the character at the specified position.

Ans. : charAt()

77. ..... method of string object returns the index of the first occurance of specified character in given string. (March 2022)

Ans. : indexOf()

78. ..... method of string object returns the index of last occurance of specified character in given string. (March 2023, 24)

Ans. : lastIndexOf()

79. ..... method of string object removes whitespace from both sides of a string.

Ans. : trim()

80. ..... method of string object converts a string to lower case.

Ans. : toLowerCase() (March 2022, 23, 24)

81. ..... method of string object convert a string to upper case.

Ans. : toUpperCase()

82. The built in ..... object includes mathematical constants and functions.

Ans. : math

83. ..... method of math object returns the absolute value of a number.

Ans. : abs() (March 2023, 24)

84. ..... method of Math object returns the cube root of a number.

Ans. : cbrt()

85. ..... method of math object returns the next integer greater than or equal to a given number.

Ans. : ceil()

86. ..... method of math object returns the next integer less than or equal to a given number.

Ans. : floor()

87. ..... method of math object returns the highest valued number in a list of numbers.

Ans. : max()

88. ..... method of math object returns the lowest valued number in a list of numbers.

Ans. : min()

89. ..... method of math object returns the base to the exponent power.
Ans. : **pow()**

90. ..... method of math object returns a random number between 0 and 1.
Ans. : **random()**

91. ..... method of math object returns the square root of a number. **(March 2023, 24)**
Ans. : **sqrt()**

92. ..... object is used to create date and time values.
Ans. : **date**

93. ..... method of date object returns the day of the month.
Ans. : **getDate()**

94. ..... method of date object returns the day of the week.
Ans. : **getDay()**

95. ..... method of date object returns the year. **(March 2023, 24)** **(March 2023)**
Ans. : **getFullYear()**

96. ..... method of date object returns the hour. **(March 2023, 24)**
Ans. : **getHours()**

97. ..... method of date object returns the minutes.
Ans. : **getMinutes()**

98. ..... method of date object returns the month.
Ans. : **getMonth()**

99. ..... method of date object returns the seconds. **(March 2023, 24)**
Ans. : **getSeconds()**

100. ..... method of date object sets the day of the month.
Ans. : **setDate()**

101. ..... method of date object sets the full year.
Ans. : **setFullYear()**

102. ..... method sets the hours of a date object.
Ans. : **setHours()**

103. ..... method sets the minutes of a date object.
Ans. : **setMinutes()**

104. ..... method sets the month of a date object.
Ans. : **setMonth()**

105. ..... method sets the seconds of a date object.
Ans. : **setSeconds()**

106. ..... method sets a date to a specified number of milliseconds after/before Jan 1, 1970.
Ans. : **setTime()**

107. An ..... is an object that can store a collection of items. **(March 2023)**
Ans. : **Array**

108. An ..... is a special variable which can hold more than one value at a time. (March 2024)

Ans. : Array

109. The index of the first element of an array is .....

Ans. : Zero

110. ..... is referred to access and set the items in an array.

Ans. : Index Number

111. ..... property of Array object represents the zero based index of the match in the string.

Ans. : Index

112. ..... property of Array object reflect number of elements in array.

Ans. : length

113. ..... method of array object joins two or more arrays and returns a copy of the joined arrays. (March 2023, 24)

Ans. : concat()

114. ..... method of Array object copies array elements within the array, to and from specified position.

Ans. : copyWithin()

115. ..... method of array object returns the value of the first element in an array that satisfies a test in testing. (March 2023)

Ans. : find()

116. ..... method of Array object calls a function for each array element.

Ans. : forEach()

117. ..... method of Array object search the array for an element and returns its position.

Ans. : indexOf()

118. ..... method of array object checks whether an object is an array.

Ans. : isArray()

119. ..... method of array object removes the last element of an array and returns that element. (March 2023, 24)

Ans. : pop()

120. ..... method of array object adds new elements to the end of an array.

Ans. : push()

121. ..... method of array object reverses the order of the elements in an array. (March 2024)

Ans. : reverse()

122. ..... method of array object sorts the elements of an array.

Ans. : sort()

True or False

3.1 Introduction

1. JavaScript is an involved scripting language.

Ans. : False

2. An interpreted language is a type of programming language that executes its instructions directly without compiling machine language.

Ans. : True

3. Program is a set of instructions used to produce various kinds of outputs.

Ans. : True

4. JavaScript was created to destroy web pages.

Ans. : False

5. There is no need of special software to run JavaScript program. **(March 2024)**

Ans. : True

6. Java script is an object oriented scripting language.

Ans. : True

7. JavaScript is not case sensitive language. **(March 2022)**

Ans. : False

8. JavaScript helps the browser to perform input validation. **(March 2023)**

Ans. : True

9. JavaScript cannot handle date and time. **(March 2023, 24)**

Ans. : False

10. JavaScript has the ability to create new functions within scripts.

Ans. : True

11. Functions are declared in JavaScript using var keyword. **(March 2022, 23)**

Ans. : False

12. Software that can run on any hardware platform is called as platform independent software.

Ans. : True

13. JavaScript is platform independent scripting language. **(March 2023)**

Ans. : True

14. There are two types of scripting. **(March 2022, 23, 24)**

Ans. : True

15. In client side scripting, the script resides on client computer and that can run on the client. **(March 2023)**

Ans. : True

16. Client side scripts are placed inside HTML document.

Ans. : True

17. In Server side scripting the scripts resides on web server.

Ans. : True

18. Server side scripting is used at the front end. (March 2022)

Ans. : False

19. Client side scripting is used at the front end. (March 2023, 24)

Ans. : True

20. When a server side script is processed it communicates to the client.

Ans. : False

21. Client side scripting does not need any server interaction.

Ans. : True

22. PHP, ASP.net etc are server side scripting languages. (March 2022, 23)

Ans. : True

23. Client side scripts are generally used for validation purpose.

Ans. : True

24. A Javascript object is an entity having state and behavior. (March 2023, 24)

Ans. : True

25. Server-side scripting is more secure than client-side scripting. (March 2023)

Ans. : True

26. Client-side scripting is more secure than server-side scripting. (March 2023)

Ans. : False

27. Javascript is light weight scripting language. (March 2023, 24)

Ans. : True

28. No need of special software is required to run Javascript programs. (March 2023)

Ans. : True

3.2 Switch case and Looping Structures

29. JavaScript has a built-in multiway decision statement known as switch. (March 2023)

Ans. : True

30. There should not be duplicity between the cases. (March 2022)

Ans. : True

31. The value for the case must be similar data type as the variable in switch.

Ans. : True

32. Iteration refers to the execution of statements of code for a fixed number of times till the condition is satisfied.

Ans. : True

33. For loop combines initializing, condition and loop iteration in single statement.

Ans. : True

34. For loop will execute statement as long as condition becomes false. **(March 2022, 23)**

Ans. : False

35. Iteration means increment or decrement value of a running variable. **(March 2022)**

Ans. : True

36. While loop executes statements as long as the condition is false.

Ans. : False

37. Break statement is used to jump out of loop. **(March 2022, 23, 24)**

Ans. : True

38. Continue statement is used to make early exit from a loop.

Ans. : False

39. Continue statement is used to skip statement block and take the control at the beginning for next iteration.

Ans. : True

40. The default statement is not mandatory in switch case. **(March 2023, 24)**

Ans. : True

3.3 Objects in JavaScript

41. JavaScript is an object based scripting language. **(March 2023, 24)**

Ans. : True

42. A JavaScript object is an entity having properties and objects. **(March 2022, 23)**

Ans. : False

43. Properties and methods of object are accessed with "." Operator. **(March 2023)**

Ans. : True

44. JavaScript supports 4 types of objects. **(March 2023, 24)**

Ans. : False

45. JavaScript gives facility to create user defined objects.

Ans. : True

46. The new keyword is used to create new object in JavaScript. **(March 2023)**

Ans. : True

47. DOM stands for Document Original Model. **(March 2022, 23, 24)**

Ans. : False

48. The way in which HTML document content is accessed and modified is called as DOM.

Ans. : True

49. Head property of DOM object returns the <head> element of the document.

Ans. : True

50. Title property is DOM object returns the name of the document.

Ans. : False

51. URL property of DOM object returns full URL of the HTML document. (March 2022)

Ans. : True

52. Body property of DOM object returns <body> elements respectively.

Ans. : True

53. write() method of DOM object write Java script code to a document. (March 2023)

Ans. : True

54. writeln() method is same as write ( ) method of DOM object. (March 2022, 23, 24)

Ans. : False

55. writeln() method of DOM object adds a new line character after each statement.

Ans. : True

56. The outerHTML property is used to change any HTML element.

Ans. : False

57. window object is parent object of all other objects. (March 2022)

Ans. : True

58. An object of window is created automatically by the browser.

Ans. : True

59. name property of window object sets or returns the name of a window.

Ans. : True

60. location property of window object returns a Boolean value indicating whether a window has been closed or not.

Ans. : False

61. document property of window object returns the document object for the window.

Ans. : True

62. status property of window object sets the name of a window. (March 2022, 24)

Ans. : False

63. alert() method of window object displays the alert box containing message with ok button.

Ans. : True

64. prompt() method of window object displays a dialog box to set output for the user.

Ans. : False

65. confirm() method of window object displays the confirm dialog box containing message with ok and cancel button.

Ans. : True

66. open( ) method of window object removes the focus from the current window. (March 2022, 24)

Ans. : False

67. close() method of window object closes the current window.

Ans. : True

68. blur() method of window object removes focus from the current window.

Ans. : True

69. focus() method of window object removes focus from the current window. **(March 2022)**

Ans. : False

70. print() method of window object prints the content of current window.

Ans. : True

71. setTimeout() method of window object calls a function after a specified number of milliseconds. **(March 2023, 24)**

Ans. : True

72. Set time out() is the correct property of window object. **(March 2023)**

Ans. : False

73. prompt() is the correct method of window object. **(March 2023, 24)**

Ans. : True

74. The inner HTML property is useful for getting html element AND changing its content. **(March 2023)**

Ans. : True

3.4 JavaScript Events

75. Events are the actions done by the user or an application that occurs on the web page. **(March 2022, 24)**

Ans. : True

76. onKeyPress, onKeyDown are keyboard events.

Ans. : True

77. onClick, onMouseUp are mouse events. **(March 2022)**

Ans. : True

78. onblur event handler occurs when an element gets focus.

Ans. : False

79. onfocus event handler occurs which an element gets focus.

Ans. : True

80. onchange event handler occurs when user changes content of an element.

Ans. : True

81. onselect event handler occurs when page image has been loaded. **(March 2022, 24)**

Ans. : False

82. onsubmit event handler occurs when user clicks submit button.

Ans. : True

83. onreset event handler occurs when user clicks reset button.

Ans. : True

84. onload event handler occurs when document/page has been loaded.

Ans. : True

85. onunload event handler occurs when user clicks on submit button. **(March 2022)**

Ans. : False

3.5 JavaScript built-in Objects

86. Number object helps us to work with numbers.

Ans. : True

87. MIN_VALUE property of number object returns the largest minimum value. (March 2022)

Ans. : True

88. MAX_VALUE property of number objects returns the largest minimum value.

Ans. : False

89. NaN property of number of object returns Not a Number value. (March 2022, 24)

Ans. : True

90. isInteger() method of number of object determine whether the given value is a character.

Ans. : False

91. parseFloat() method of number object converts the given string into a floating point number.

Ans. : True

92. parseInt() method of number object converts the given string into an integer number. (March 2024)

Ans. : True

93. isFixed() method of number object returns the string that represents a number with exact digits after a decimal point.

Ans. : True

94. String is used to store zero or more character of text within single or double quotes.

Ans. : True

95. String object is used to store and manipulate numbers. (March 2024)

Ans. : False

96. length property returns the number of characters in a string. (March 2023)

Ans. : True

97. charAt() method of string object returns the character at the specified position.

Ans. : True (March 2023)

98. indexOf() method of string object returns the index of the middle occurrence of the specified character in the given string.

Ans. : False

99. lastIndexOf() method of string object returns the index of the last occurrence of specified character in given string. (March 2024)

Ans. : True

100. substr() method of string object returns the characters you specified.

Ans. : True

101. trim() method of string objects adds the white spaces from both sides of a string.

Ans. : False (March 2023)

102. toLowerCase() method of string object converts a string to capitals. (March 2024)

Ans. : False

103. toUpperCase() method of string object converts the string to upper case.
Ans. : True
104. The Math object includes mathematical constants and functions.
Ans. : True
105. There is no need to create a Math object before using it.
Ans. : True
106. abs() method of math object returns square root of a number.
Ans. : False
107. cbrt() method of math object returns cube root of a number.
Ans. : True
108. ceil() method of math object returns the next integer greater than or equal to a given number. **(March 2023, 24)**
Ans. : True
109. floor() method of math object returns the next integer less than or equal to a given number.
Ans. : True
110. max() method of math object returns the smallest valued number of a list of numbers.
Ans. : False
111. min() method of math object returns the power of the number.
Ans. : False
112. pow() method of math object returns the base to the exponent power. **(March 2024)**
Ans. : True
113. random() method of math object returns a random number between 0 and 1.
Ans. : True
114. sqrt() method of math object returns the square root of a number.
Ans. : True
115. The time object is used to create date and time values.
Ans. : False
116. Date object is created using new keyword. **(March 2024)**
Ans. : True
117. getDate() method of date object returns the day of month.
Ans. : True
118. getDay() method of date object returns the day of the month.
Ans. : False
119. getFullYear() method of date object returns the year.
Ans. : True
120. getHours() method of Date object returns the month. **(March 2023, 24)**
Ans. : False
121. getMinutes() method of Date object returns minutes.
Ans. : True

122. getMonth() method of Date object returns month name.

Ans. : False

123. getSeconds() method of Date object returns seconds.

Ans. : True

124. getTime() method of Date object returns date.

Ans. : False

125. now() method of Date object returns the number of a milliseconds.

Ans. : True

126. setDate() method of Date object set day of the month of a date object.

Ans. : True

127. setFullYear() method of Date object sets year.

Ans. : True

128. setHours() method of Date object set the seconds.

Ans. : False

129. setMinutes() method of Date object sets minutes. **(March 2024)**

Ans. : True

130. setMonth() method of Date object sets month.

Ans. : True

131. setSeconds() method of Date object sets hours.

Ans. : False

132. setTime() method of Date object sets a date to a specified number of milliseconds.

Ans. : True

133. An array is an object that can store a collection of items.

Ans. : True

134. Arrays are used to store single value in single variable.

Ans. : False

135. Items of array can be accessed by referring to its index number.

Ans. : True

136. Index of first element of an array is one. **(March 2023, 24)**

Ans. : False

137. marks[0] is the first element of the array.

Ans. : True

138. Index property of Array object represents two based index of the matching the string.

Ans. : False

139. Length property of Array object reflects number of elements in array. **(March 2024)**

Ans. : True

140. concat() method of Array object joins two or more arrays and returns a copy of joined array.

Ans. : True

141. copyWithin() method of Array object adds array elements within the array to and from a specified positions.

Ans. : False

142. find() method of Array object returns the value of the first element in an array that satisfies a test in testing.

Ans. : True

143. forEach() method of Array object search the array and returns it's position.

Ans. : False

144. indexOf() method of Array object search the array for an element and returns its position. **(March 2024)**

Ans. : True

145. isArray( ) method of Array object removes element from array.

Ans. : False

146. pop() method of Array objects removes the last element of an array and returns that element.

Ans. : True

147. push() method of Array object add new elements to the end of an array and returns the new length.

Ans. : True

148. reverse() method of Array object returns the elements in an array.

Ans. : False

149. sort() method of Array object sorts the elements of an array.

Ans. : True

MCQ (One Correct Answers)

3.1 Introduction

1. ..... is an interpreted scripting language. **(March 2023)**

(a) PHP (b) C++ (c) HTML (d) JavaScript

Ans. : (d)

2. ..... is a set of instructions used to produce various kinds of outputs.

(a) Design (b) Software (c) Program (d) Hardware

Ans. : (c)

3. The programs in JavaScript language are called ..... **(March 2022, 24)**

(a) Website (b) Scripts (c) Web server (d) Software

Ans. : (b)

4. ..... is an object oriented scripting language and supports event based programming facility.
(a) JavaScript (b) C++ (c) Excel (d) Word
Ans. : (a)

5. ..... is platform independent scripting language. (March 2022, 23)
(a) MSWord (b) JavaScript (c) PHP (d) C++
Ans. : (b)

6. ..... is knows as Universal client side scripting language. (March 2023)
(a) Word (b) Powerpoint (c) Tally (d) JavaScript
Ans. : (d)

7. In ..... scripting the script resides on the client computer.
(a) Client Side (b) Server Side (c) My Side (d) Website
Ans. : (a)

8. In .....scripting the script resides on the web server. (March 2024)
(a) Client side (b) My side (c) Server Side (d) Website
Ans. : (c)

9. ..... scripting does not need any server interaction.
(a) Server Side (b) Website (c) My side (d) Client Side
Ans. : (d)

10. ..... scripting communicates to the server.
(a) Client Side (b) Software Side
(c) Server Side (d) Website
Ans. : (c)

11. ..... scripts are used for validation purpose. (March 2022, 24)
(a) Client Side (b) Server Side (c) Website (d) Web Browser
Ans. : (a)

12. ..... scripts requires web browser as an interface. (March 2023)
(a) Server Side (b) Webpage (c) Website (d) Client Side
Ans. : (d)

13. ..... scripts requires web server software to execute.
(a) Client Side (b) Server Side (c) Peer (d) Home
Ans. : (b)

14. ..... is a JavaScript based open source frontend web framework developed for single page application. (March 2024)
(a) Vue JS (b) Response (c) Angular JS (d) React
Ans. : (c)

15. ..... is JavaScript based framework for building interactive user interface.
(a) Vue JS (b) Response (c) React (d) Uue JS
Ans. : (a)

16. ..... consists of JavaScript libraries for building UI for single page application and mobile application..

(a) Angular JS (b) Vue JS (c) Respond (d) React

Ans. : (d)

17. Functions in JavaScript are declared using ..... Keyword.

(a) Function (b) Object (c) Method (d) var

Ans. : (a)

3.2 Switch case and Looping Structures

18. JavaScript has a built-in multiway decision statement known as .....

(a) Condition (b) Switch (c) Break (d) Continue **(March 2022)**

Ans. : (b)

19. ..... refers to the execution of statement or a group of statements of code for a fixed number of times. **(March 2022, 24)**

(a) Statement (b) Function (c) Iteration (d) Method

Ans. : (c)

20. ..... loop combines initialization, condition and loop iteration in single statement.

(a) for (b) Break (c) Switch (d) Continue

Ans. : (a)

21. ..... means increment or decrement value of a running variable.

(a) Switch (b) Method (c) Object (d) Iteration **(March 2022)**

Ans. : (d)

22. ..... statement is used to jump out of loop. **(March 2022, 23)**

(a) Respond (b) Continue (c) Break (d) React

Ans. : (c)

23. To skip statement block and take the control at the beginning for next iteration ..... statement is used. **(March 2022, 24)**

(a) Break (b) Continue (c) React (d) Response

Ans. : (b)

24. Valid decrement operation in javascript. **(March 2023, 24)**

(a) ++ (b) + (c) -- (d) -

Ans. : (c)

25. The default statement is not mandatory in _____. **(March 2023, 24)**

(a) while (b) switch (c) for (d) if

Ans. : (b)

3.3 Objects in JavaScript

26. The ..... keyword is used to create new object in JavaScript.
(a) Next (b) Wend (c) Loop (d) New (March 2022)

Ans. : (d)

27. An ..... can group data together with functions needed to manipulate it.
(a) Method (b) Function (c) Object (d) Response

Ans. : (c)

28. All tangible things are known as .....
(a) Method (b) Objects (c) Function (d) Variable

Ans. : (b)

29. DOM stands for ..... (March 2022)
(a) Document Object Model (b) Document One Model
(c) Design One Model (d) Document Object Manage

Ans. : (a)

30. The way in which HTML document content is accessed and modified is called as ..... (March 2024)
(a) Design Object Model (b) Develop Object Model
(c) Do Object Model (d) Document Object Model

Ans. : (d)

31. ..... property of DOM object returns the <head> element of the document.
(a) head (b) body (c) title (d) link

Ans. : (a)

32. ..... property of DOM object sets or returns title of the document.
(a) head (b) body (c) source (d) Title

Ans. : (d)

33. ..... property of DOM object returns URL of the HTML document.
(a) SRC (b) HREF (c) URL (d) LINK

Ans. : (c)

34. ..... method of DOM object writes HTML expressions or JavaScript code to a document. (March 2022, 24)
(a) write() (b) read() (c) close() (d) ReadOnly()

Ans. : (a)

35. ..... method of DOM object adds a new line character after each statement.
(a) close() (b) writeln() (c) read() (d) readOnly()

Ans. : (b)

36. Using ..... method, id property is used to find an element.
(a) write (b) URL (c) writeln (d) getElementById()

Ans. : (d)

68. ..... method of number object determines whether the given value is floating point number. (March 2022)
(a) parseFloat() (b) parseInt() (c) isFixed() (d) NaN

Ans. : (a)

69. ..... method of number object converts the given string into an integer number.
(a) isInteger() (b) isFixed() (c) parseFloat() (d) parseInt()

Ans. : (d)

70. ..... method of Number object returns the string that represents a number with exact digits after a decimal point.
(a) isInteger() (b) isFixed() (c) parseInt() (d) parseFloat()

Ans. : (b)

71. How to declare string variable ? (March 2022, 24)
(a) var str – new str ( ); (b) var a = I. T.;
(c) a = str. Str; (d) var str = "Information Technology";

Ans. : (d)

72. What will be the output of following program <script type = text/Javascript>.
mystr = "Hello" document · write (mystr·length), </script>
(a) 4 (b) 5 (c) 6 (d) 7

Ans. : (b)

73. ..... object is used to store or manipulate text. (March 2024)
(a) Math (b) Date (c) Number (d) String

Ans. : (d)

74. ..... property of string object returns number of characters in a string.
(a) value (b) length (c) object (d) len

Ans. : (b)

75. ..... method of string object returns the character at the specified position.
(a) indexOf() (b) substr() (c) charAt() (d) trim()

Ans. : (c)

76. ..... method of string object returns the index of the first occurrence of specified character in given string. (March 2022)
(a) indexOf() (b) substr() (c) substring() (d) trim()

Ans. : (a)

77. ..... method of string object returns the index of last occurrence of specified character in given string.
(a) substr() (b) charAt() (c) lastIndexOf() (d) trim()

Ans. : (c)

78. ..... method of string object removes white space from both sides of a string.
(a) trim() (b) substr() (c) indexOf() (d) substring()

Ans. : (a)

79. ..... method of string object converts a string to lower case.
(a) toUpperCase() (b) substr()
(c) trim() (d) toLowerCase() **(March 2022)**

Ans. : (d)

80. ..... method of string object converts a string to upper case.
(a) toLowerCase() (b) toUpperCase()
(c) trim() (d) substring()

Ans. : (b)

81. The built in ..... object includes mathematical constants and functions.
(a) String (b) Date (c) Math (d) Math

Ans. : (c)

82. ..... method of math object returns the absolute value of a number.
(a) abs() (b) cbrt() (c) min() (d) sqrt()

Ans. : (a)

83. ..... method of Math object returns the cube root of a number.
(a) sqrt() (b) max() (c) ceil() (d) cbrt() **(March 2024)**

Ans. : (d)

84. ..... method of math object returns the next integer greater than or equal to a given number.
(a) abs() (b) cbrt() (c) ceil() (d) floor()

Ans. : (c)

85. ..... method of math object returns the next integer less than or equal to a given number.
(a) abs() (b) floor() (c) min() (d) max()

Ans. : (b)

86. ..... method of math object returns the highest valued number in a list of numbers. **(March 2024)**
(a) min() (b) pow() (c) sqrt() (d) max()

Ans. : (d)

87. ..... method of math object returns the lowest valued number in a list of numbers.
(a) pow() (b) max() (c) min() (d) floor()

Ans. : (c)

88. ..... method of math object returns the base to the exponent power.
(a) pow() (b) floor() (c) abs() (d) cbrt()

Ans. : (a)

89. ..... method of math object returns a random number between 0 and 1. **(March 2024)**
(a) abs() (b) random() (c) pow() (d) sqrt()

Ans. : (b)

90. ..... method of math object returns the square root of a number.
(a) cbrt() (b) ceil() (c) sqrt() (d) abs()

Ans. : (c)

115. .....method of Array object returns the value of the first element in an array that satisfies a test in testing.
(a) concat() (b) pop() (c) push() (d) find()

Ans. : (d)

116. .....method of Array object calls a function for each array element.
(a) concat() (b) forEach() (c) pop() (d) push()

Ans. : (b)

117. .....method of Array object search the array for an element and returns its position.
(a) concat() (b) forEach() (c) indexOf() (d) pop()

Ans. : (c)

118. .....method of Array object checks whether an object is an array.
(a) find() (b) pop() (c) forEach() (d) isArray()

Ans. : (d)

119. ..... method of Array object removes the last element of an array and returns that element.
(a) pop() (b) push() (c) find() (d) reverse()

Ans. : (a)

120. .....method of Array object add new elements to the end of an array, and returns the new length.
(a) pop() (b) push() (c) sort() (d) find()

Ans. : (b)

121. .....method of Array object reverses the order of the elements in an array.
(a) find() (b) isArray() (c) pop() (d) reverse() **(March 2024)**

Ans. : (d)

122. .....method of Array object sorts the elements of an array.
(a) concat() (b) sort() (c) pop() (d) find ()

Ans. : (b)

MCQ (Two Correct Answers)

3.1 Introduction

1. Features of JavaScript are ..... **(March 2022, 23)**
(a) It needs special software
(b) JavaScript is light weight scripting language
(c) Cannot create new function
(d) It is object oriented scripting

Ans. : (b), (d)

2. There are two types of Scripting .....
   (a) Server side (b) My side
   (c) Browser side (d) Client side

Ans. : (a), (d)

3. Client Side Scripting .....
   (a) These scripts are placed inside HTML document
   (b) In this type the script resides on Client Computer.
   (c) In this type, the script resides on web server
   (d) To execute script it must be activated by client then it is executed on web server.

Ans. : (a), (b)

3.2 Switch case and Looping Structures

4. Types of loops in JavaScript are ..... **(March 2022, 24)**
   (a) for .....loop (b) while .....loop
   (c) for ....next (d) while .....wend

Ans. : (a), (b)

5. Correct method of for loop are ..... **(March 2024)**

(a)
```
for (i = 1; i< = 5; i++)
    {
    document . write(i);
        }
```

(b)
```
for (i = 1, i! = 4);
    {
    document.write (i);
    }
```

(c)
```
for (i = 1; i < = 5; i + +)
    {
    document.writeln(i);
    }
```

(d)
```
{i – 1, ic = 5, i ++)
    {
     document.write (i),
    }
```

Ans. : (a), (c)

6. Valid keywords in javascript are _____ and _____. **(March 2023, 24)**
   (a) if (b) else (c) SWITCH
   (d) DEFAULT (e) CASE

Ans. : (a), (b)

7. Following are valid keywords in Javascript. **(March 2023)**
   (a) break (b) continue (c) after
   (d) before (e) VAR

Ans. : (a), (b)

3.3 Objects in JavaScript

8. JavaScript supports following types of objects .....
   (a) Variables (b) built-in objects
   (c) User defined objects (d) loops

Ans. : (b), (c)

9. Following are the built in objects in JavaScript .....
   (a) Math (b) Time (c) Array (d) Month

Ans. : (a), (c)

10. Following are the **properties of Document Object Model** ..... (March 2023)
    (a) Src (b) Srcdoc (c) URL (d) title

Ans. : (c), (d)

11. Following are the methods of Document Object Model .....
    (a) body (b) write() (c) URL (d) writeln()

Ans. : (b), (d)

12. Following are the properties of Window object ..... (March 2022, 23, 24)
    (a) name (b) location (c) alert() (d) confirm()

Ans. : (a), (b)

13. Following are the methods of Window object ..... (March 2023)
    (a) open() (b) status (c) closed (d) close()

Ans. : (a), (d)

14. confirm() method of window object displays confirm dialog box containing message with .....and .....button. (March 2022)
    (a) GO (b) OK (c) Cancel (d) Click

Ans. : (b), (c)

15. Following are valid objects in Javascript. (3.3) (March 2023, 24)
    (a) string (b) array (c) for
    (d) while (e) if

Ans. : (a), (b)

3.4 JavaScript Events

16. Following are the event handlers in JavaScript .....
    (a) onsubmit (b) write() (c) onchange (d) writeln()

Ans. : (a), (c)

17. Array with a numeric index and array with named keys are respectively as ____ and _____. (March 2023, 24)
    (a) indexed array (b) bulleted array
    (c) ordered array (d) associative array
    (e) unordered array

Ans. : (a), (d)

3.5 JavaScript built-in Objects

18. In JavaScript following methods of String object returns the characters you specified.
(a) substring() (b) indexOf() (c) substr() (d) lastIndexOf()

Ans. : (a), (c)

19. Following properties of Number Object returns the largest minimum and maximum value .....
(a) MIN_VALUE (b) MAX_VALUE
(c) toLowerCase() (d) toUpperCase()

Ans. : (a), (b)

20. Following are the properties of Number Object in Javascript .....
(a) lowercase (b) Uppercase (c) NaN (d) MAX_VALUE

Ans. : (c), (d)

21. Following are the methods of Number of object in JavaScript ..... **(March 2022, 24) (March 2023)**
(a) NaN (b) parseInt() (c) isFixed() (d) toLowercase()

Ans. : (b), (c)

22. Following are the methods of string objects ..... **(March 2022, 23)**
(a) chartAt() (b) width (c) length (d) trim()

Ans. : (a), (d)

23. To find the highest and lowest valued number in a list of numbers which Math Object methods are used in JavaScript .....
(a) ceil() (b) sqrt() (c) max() (d) min()

Ans. : (c), (d)

24. Following are the methods of Math objects .....
(a) substr() (b) abs() (c) trim() (d) random()

Ans. : (b), (d)

25. Different ways to create new Date object are .....
(a) var d = new Date(); (b) var d = Date()
(c) var d = month() (d) var d = new Date (DateString);

Ans. : (a), (d)

26. Following are the methods of Date object ..... **(March 2023, 24)**
(a) setDateTime() (b) getDateTime()
(c) getTime() (d) getDay()

Ans. : (c), (d)

27. Following methods are used to create Array variable in JavaScript .....
(a) var a = "One, two",
(b) var a = ["One", "Two", "Three"];
(c) array a = ("One", "Two"),
(d) var a = new Array ("One", "Two", "Three");

Ans. : (b), (d)

3.5 JavaScript built-in Objects

(I)

	A		B
(1)	MIN_VALUE (March 2024)	(a)	Represent not a Number value
(2)	MAX_VALUE (March 2024)	(b)	Determines whether the given value is an Integer
(3)	NaN (March 2024)	(c)	Returns the largest minimum value
(4)	isInteger( )	(d)	Returns the largest maximum value

Ans. : (1) – (c), (2) – (d), (3) – (a), (4) – (b)

(II)

	A		B
(1)	parseFloat()	(a)	Used to create date and time values
(2)	parseInt()	(b)	Returns the string that represents a number with exact digits after a decimal point
(3)	isFixed()	(c)	Converts a given string into a floating point number
(4)	Date object	(d)	Converts the given string into integer number

Ans. : (1) – (c), (2) – (d), (3) – (b), (4) – (a)

(III)

	A		B
(1)	Length	(a)	Returns the character at the specified position
(2)	chartAt()	(b)	Returns the index of last occurrence of specified character in given string
(3)	indexOf()	(c)	Returns a number of character in a string
(4)	lastIndexOf()	(d)	Returns the index of the first occurrence of the character

Ans. : (1) – (c), (2) – (a), (3) – (d), (4) – (b)

(IV) (March 2022)

	A		B
(1)	substring()	(a)	Returns the characters you specified
(2)	trim() (March 2023)	(b)	Converts a string into lower case
(3)	toLowerCase()	(c)	Returns length of string
(4)	toUpperCase()	(d)	Converts the string into Upper case
		(e)	Removes white spaces from both sides of a string

Ans. : (1) – (a), (2) – (e), (3) – (b), (4) – (d)