Nu Html Checker

This tool is an ongoing experiment in better HTML checking, and its behavior remains subject to change

Showing results for contents of text-input area

Checker Input

Show ☑ source ☐ outline ☐ image report [Options...]

Check by [text input ⇅] ☐ CSS

```
<!--Brand checkboxes start. CSS classes for checkbox styling is from https://bootswatch.com/lux/-->
<div class="form-group form-group-filters-top">
    <h2 class="heading-4 filter-headings text-capitalize">Brands</h2>
    {% for brand in filters.brands %}
    <div class="custom-control custom-checkbox mb-2">
        {% if selected_brands %}{% if brand in selected_brands %}
        <input type="checkbox" class="custom-control-input" id="brand{{loop.index}}" value="{{brand}}" name="brands"
            checked />
        {% else %}
        <input type="checkbox" class="custom-control-input" id="mobile-brand{{loop.index}}" value="{{brand}}"
            name="brands" />
        {% endif %} {% else %}
        <input type="checkbox" class="custom-control-input" id="mobile-brand{{loop.index}}" value="{{brand}}"
            name="brands" />
        {% endif %}
```

[Check]

Use the Message Filtering button below to hide/show particular messages, and to see total counts of errors and warnings.

[Message Filtering]

1. `Warning` **Consider adding a `lang` attribute to the `html` start tag to declare the language of this document.**

   From line 1, column 100; to line 2, column 47

   `om/lux-->↵<div class="form-group form-group-filters-top">↵     <`

   For further guidance, consult Declaring the overall language of a page and Choosing language tags.

   If the HTML checker has misidentified the language of this document, please file an issue report or send e-mail to report the problem.

2. `Error` **Start tag seen without seeing a doctype first. Expected `<!DOCTYPE html>`.**

   From line 1, column 100; to line 2, column 47

   `om/lux-->↵<div class="form-group form-group-filters-top">↵     <`

3. `Error` **Element `head` is missing a required instance of child element `title`.**

   From line 1, column 100; to line 2, column 47

   `om/lux-->↵<div class="form-group form-group-filters-top">↵     <`

   Content model for element head:

   If the document is an iframe srcdoc document or if title information is available from a higher-level protocol: Zero or more elements of metadata content, of which no more than one is a `title` element and no more than one is a `base` element.

   Otherwise: One or more elements of metadata content, of which exactly one is a `title` element and no more than one is a `base` element.

4. `Error` **Duplicate ID `mobile-brand{{loop.index}}`.**

   From line 13, column 9; to line 14, column 28

   `}↵          <input type="checkbox" class="custom-control-input" id="mobile-brand{{loop.index}}" value="{{brand}}"↵ name="brands" />`

5. `Warning` **The first occurrence of ID `mobile-brand{{loop.index}}` was here.**

   From line 10, column 9; to line 11, column 28

   `}↵          <input type="checkbox" class="custom-control-input" id="mobile-brand{{loop.index}}" value="{{brand}}"↵ name="brands" />`

6. `Error` **Duplicate ID `mobile-price{{loop.index}}`.**

   From line 30, column 9; to line 31, column 27

   `}↵          <input type="radio" class="custom-control-input" id="mobile-price{{loop.index}}" value="{{loop.index}}"↵ name="price" />`

7. `Warning` **The first occurrence of ID `mobile-price{{loop.index}}` was here.**

   From line 27, column 9; to line 28, column 35

   `}↵          <input type="radio" class="custom-control-input" id="mobile-price{{loop.index}}" value="{{loop.index}}"↵ name="price" checked />`

Document checking completed.

Source

```
1.  <!--Brand checkboxes start. CSS classes for checkbox styling is from https://bootswatch.com/lux/-->↵
2.  <div class="form-group form-group-filters-top">↵
3.      <h2 class="heading-4 filter-headings text-capitalize">Brands</h2>↵
4.      {% for brand in filters.brands %}↵
5.      <div class="custom-control custom-checkbox mb-2">↵
6.          {% if selected_brands %}{% if brand in selected_brands %}↵
7.          <input type="checkbox" class="custom-control-input" id="brand{{loop.index}}" value="{{brand}}" name="brands"↵
8.              checked />↵
9.          {% else %}↵
10.         <input type="checkbox" class="custom-control-input" id="mobile-brand{{loop.index}}" value="{{brand}}"↵
11.             name="brands" />↵
12.         {% endif %} {% else %}↵
13.         <input type="checkbox" class="custom-control-input" id="mobile-brand{{loop.index}}" value="{{brand}}"↵
14.             name="brands" />↵
15.         {% endif %}↵
16.         <label class="custom-control-label" for="mobile-brand{{loop.index}}">{{brand}}</label>↵
17.     </div>↵
18.     {% endfor %}↵
19. </div>↵
20. <!--Brand checkboxes end-->↵
21. <!--Price radio buttons start. CSS classes for radio button styling is from https://bootswatch.com/lux/-->↵
22. <div class="form-group mb-0">↵
23.     <h2 class="heading-4 filter-headings text-capitalize">Prices</h2>↵
24.     {% for prices in filters.prices %}↵
25.     <div class="custom-control custom-radio mb-2">↵
26.         {% if selected_price %}{% if selected_price | int == loop.index %}↵
27.         <input type="radio" class="custom-control-input" id="mobile-price{{loop.index}}" value="{{loop.index}}"↵
28.             name="price" checked />↵
29.         {% endif %}{% endif %}↵
30.         <input type="radio" class="custom-control-input" id="mobile-price{{loop.index}}" value="{{loop.index}}"↵
31.             name="price" />↵
32.         <label class="custom-control-label" for="mobile-price{{loop.index}}">{{prices}}</label>↵
33.     </div>↵
34.     {% endfor %}↵
35. </div>↵
36. <!--Price radio buttons end-->↵
```

Used the HTML parser.

Total execution time 5 milliseconds.

About this checker • Report an issue • Version: 21.1.4