Nu Html Checker

This tool is an ongoing experiment in better HTML checking, and its behavior remains subject to change

Showing results for contents of text-input area

Show ☑ source ☐ outline ☐ image report

Options…

Check by text input ⌄ ☐ css

```
{% extends "base.html" %}
{% load static %}

{% block page_header %}
    <div class="container">
        <div class="row">
            <div class="col"></div>
        </div>
    </div>
{% endblock %}

{% block content %}
<div class="container header-container">
    <div class="row">
        <div class="col-12 col-md-6 text-center my-auto">
```

Check

Use the Message Filtering button below to hide/show particular messages, and to see total counts of errors and warnings.

Message Filtering

1. **Error** **Non-space characters found without seeing a doctype first. Expected**

   `<!DOCTYPE html>`**.**

   From line 1, column 1; to line 1, column 25

   `{% extends "base.html" %}↵{% lo`

2. **Error** **Element** `head` **is missing a required instance of child element** `title`**.**

   From line 1, column 1; to line 1, column 25

   `{% extends "base.html" %}↵{% lo`

   Content model for element head:

   If the document is an iframe srcdoc document or if title information is available from a higher-level

   protocol: Zero or more elements of metadata content, of which no more than one is a `title` element and

   no more than one is a base element.

   Otherwise: One or more elements of metadata content, of which exactly one is a `title` element and no

   more than one is a base element.

3. **Error** **Misplaced non-space characters inside a table.**

   From line 32, column 28; to line 34, column 32

```
            <tbody>↵                          {% for item in bag_items %}↵

  <tr>↵
```

4. **Fatal Error** **Cannot recover after last error. Any further errors will be ignored.**

From line 32, column 28; to line 34, column 32

```
            <tbody>↵                          {% for item in bag_items %}↵

  <tr>↵
```

Document checking completed.

Source

```
 1.  {% extends "base.html" %}↵
 2.  {% load static %}↵
 3.  ↵
 4.  {% block page_header %}↵
 5.      <div class="container">↵
 6.          <div class="row">↵
 7.              <div class="col"></div>↵
 8.          </div>↵
 9.      </div>↵
10.  {% endblock %}↵
11.  ↵
12.  {% block content %}↵
13.  <div class="container header-container">↵
14.      <div class="row">↵
15.          <div class="col-12 col-md-6 text-center my-auto">↵
16.              <h2 class="text-orangered my-3">Shopping Bag</h2>↵
17.          </div>↵
18.      </div>↵
19.  ↵
20.      <div class="row">↵
21.          <div class="col-12 col-md-6">↵
22.              {% if bag_items %}↵
23.              <div class="table-responsive">↵
24.                  <table class="table table-borderless text-white">↵
25.                      <thead>↵
26.                          <tr>↵
27.                            <th scope="col">Product Description</th>↵
28.                            <th scope="col">Qty</th>↵
29.                            <th scope="col" class="text-right">Price</th>↵
30.                          </tr>↵
31.                      </thead>↵
32.                      <tbody>↵
33.                          {% for item in bag_items %}↵
34.                              <tr>↵
35.                                  <td>{{ item.product.name }}</td>↵
36.                                  <td>↵
37.                                      <form class="form update-form" action="{% url
     'update_bag' item.item_id %}" method="POST">↵
38.                                          {% csrf_token %}↵
39.                                              <div class="form-row">↵
40.                                                  <div class="col-12">↵
41.                                                      <div class="form-group">↵
42.                                                          <input class="form-control
     qty_input" type="number"↵
43.                                                              name="quantity" value="
     {{ item.quantity }}" min="0" max="9"↵
44.                                                              data-item_id="{{
     item.item_id }}" id="id_qty_{{ item.item_id }}">↵
45.                                                      </div>↵
46.                                                  </div>↵
47.                                              </div>                                  ↵
48.                                      </form>↵
49.                                      <a class="update-link"><small>Update</small>
     </a>↵
```

```
50.                                              <a class="remove-item text-orangered float-
    right" id="remove_{{ item.item_id }}">↵
51.                                                  <small>Remove</small>↵
52.                                              </a>↵
53.                                  </td>↵
54.                                  <td class="text-right">€{{ item.product.price }}</td>↵
55.                              </tr>↵
56.                          {% endfor %}↵
57.                          <tr>↵
58.                              <td colspan="3">↵
59.                                  <h6 class="text-right"><strong>Total: €{{
    total|floatformat:2 }}</strong></h6>↵
60.                              </td>↵
61.                          </tr>↵
62.                          <tr>↵
63.                              <td colspan="3" class="tex
```

Used the HTML parser.

Total execution time 2 milliseconds.