



Quote No: 2512001

Date: 02-12-2025 Tue

TO:

Name : Mr. Jack
Company : KIDO YANGON COMPANY LIMITED.
Contact No. : 09-968 888 248
Subject : Face Scan Device Quotation

FROM

: CODE-X TECHNOLOGY CO., LTD
Address : No.109, 4th Street, Mayangone Township, Yangon.
Phone No. : 09-455 232 057, 09-951 955 790
Email : sales@codextechnologymm.com
Website : www.codextechnologymm.com

Face Scan Device Quotation

NO.	DESCRIPTION	PRICE (MMK)	QUANTITY	UNIT	TOTAL (MMK)
1.	ZKTeco MiniTA – Face Only (In stock) Features <ul style="list-style-type: none">• Visible Light Facial Recognition• Anti-spoofing algorithm against most of color and B/W photos, videos attack and 3D mask attack• 2.8-inch Touch Screen• Supplement lighting with adjustable brightness• Exquisite and compact, easy to install. Support desktop and wall install• Support Multiple Language	500,000	1	Nos	500,000



Specifications

- **Model:** MiniTA
- **Display:** 2.8-inch Touch Screen
- **Face Capacity:** 800
- **User Capacity:** 800
- **Transactions:** 150,000
- **Operating System:** Linux
- **Standard Functions:**
ADMS, T9 Input, DST, Camera, 9 digit user ID, Work Code, Self-service Query, Schedule Bell, Automatic Status Switch
- **Hardware:**
900MHZ Dual Core CPU
Memory 512MB RAM/512 MB ROM
2MP WDR Low Light Camera
Adjustable Light Brightness LED
- **Communication:** WiFi
- **Face Recognition Speed:** $\leq 1s$
- **Biometrics Algorithms:** ZKFace VX5.8
- **Power Supply:** 5V / 2A
- **Working Humidity:** 10%-90%
- **Working Temperature:** 0°C - 45°C
- **Dimensions(W*H*D):** 100*100.2*23.7mm
- **Supported Software:** easyTime Pro



2.	<p>ZKTeco SenseFace – Face Finger (No stock)</p> <p>Features</p> <ul style="list-style-type: none">• Visible Light Facial Authentication Technology and ZK Optical Fingerprint Verification• Multiple Authentication Methods: Facial / Fingerprint / RFID / Password• Available RFID Modules:125 kHz ID Card / 13.56 MHz IC Card• HD Video Door Phone Via SIP Protocol (Version 2.0)• User Data Synchronization: User data can be downloaded/uploaded from one device to another via a USB drive• Compatible with wireless doorbell (optional)• Simple access control functions (Electric Lock; Door Sensor; Exit Button) <p>Specifications</p> <ul style="list-style-type: none">• Model: SenseFace 2A• Display: 2.4"@ TFT Color LCD Screen (320*240)• Camera: WDR Binocular Camera @ 1MP• Operation System: Linux• Hardware<ul style="list-style-type: none">CPU: Dual Core@1GHzRAM: 512MB; ROM: 8GBSpeaker: 8ohm @1WMicrophone: *1 (Sensitivity: -32 dB / Omni-directional / Signal-to-Noise Ratio: -32 dB/Impedance: 2.2kΩ)Supplement Light: YesPhysical Keypad: 17 KeysFingerprint Sensor: ZK Optical Sensor• Authentication method: Fingerprint / Face / Card / Password (Physical Keypad)• Fingerprint Template Capacity: 3,000 (1:N) (Standard)• Face Template Capacity: 1,500 (1:N) (Standard)• Card Capacity: 3,000 (1:N) (Standard)• User Capacity: 3,000 (1:N) (Standard)• Transaction Capacity: 150,000 (1:N)• Max. User Password Length: 8 Digits	750,000	1	Nos	750,000
----	--	---------	---	-----	---------



<ul style="list-style-type: none">• Biometric Authentication Speed: less than 0.5 sec (Fingerprint) less than 0.35 sec (Facial Authentication)• Touchless Biometric Authentication Distance: 30cm to 200cm (Facial Authentication)• False Acceptance Rate (FAR) % : FAR ≤ 0.01% (Visible Light Facial Authentication) FAR ≤ 0.0001% (Fingerprint)• False Rejection Rate (FRR) %: FRR ≤ 0.02% (Visible Light Facial Authentication) FRR ≤ 0.01% (Fingerprint)• Biometric Algorithm: ZKFace V4.0 ZKFingerprint V13.0 (Standard) /V10.0 (Optional)• Card Type: ID Card@125 kHz (Standard) IC Card@13.56 MHz (Optional)• Communication: TCP/IP*1, Wi-Fi (IEEE802.11b/g/n/ax) @ 2.4 GHz (Optional), USB: Type A (USB Drive Only) *1, Electric Lock*1, Door Sensor*1, Exit Button*1• Standard Functions: ADMS, DST, Photo Capture, Event Photo Capture, Up to 14-digit User ID, Access Levels, Groups, Holidays, Record Query, Schedule Bell, Tamper Switch Alarm, Automatic Status Switch, Multiple AuthenticationMethods, SIP Client (Version 2.0), ONVIF (Compatible with Profile S, Profile T, Profile G, Profile C, Profile Q & Profile A), AC Push and TA Push Protocol Switch, HTTPs / SSH Backend Access, T9 Keyboard (Input)• Optional Functions: IC Card, Wi-Fi, Wireless Doorbell• Video Intercom: Video Intercom (ZKTeco Private Protocol via TCP/IP) Support Devices: Standalone Terminal: SenseFace Series Indoor Monitor: VT07-B01, VT07-B01-W Video Intercom (Standard SIP Protocol) Support Devices: Standalone Terminal: SenseFace series Indoor Monitor: VT07-B22L, VT07-B26L-W Software: ZKBio CVAcess, BioTalk Pro Mobile App: ZKBio Zlink, ZKBio Zexus• Power Supply: DC 12V 1.5A• Operating Temperature: -5°C to 45°C				
---	--	--	--	--



	<ul style="list-style-type: none">• Operating Humidity: 20% to 80% RH (Non-condensing)• Dimensions: 205.20 mm*74.19 mm*33.30 mm (L*W*H)• Net Weight: 0.258 Kg• Supported Software: On-Premise Software: ZKBio CVAccess (AC PUSH) & ZKBio Time (TA PUSH) Cloud-based Software: ZKBio Zlink (Supports Web Portal & Mobile App)• Installation: 0.258 Kg Wall-mount (Compatible with Asian Gang Box / Single Gang Box)• Certifications: ISO14001, ISO9001,CE, FCC, RoHS <p>Delivery Time 4 weeks to 8 weeks</p>				
--	---	--	--	--	--

Terms & Condition

Warranty: One Year Warranty upon parts & services within the warranty period. The warranty excludes the damages caused by electronic fluctuation or user misuse or thundering or lightning or natural disaster of service charges.

Validity Date: 1 week.

Delivery: Ex-stock items (Prior to sale).

Payment: 50% on PO Confirmation and 50% on Delivery.