Coverage Priority & Recovery Timeline

Sample passport

Edition 1.0 · November 2026

PART I · WHAT THE SAMPLE IS

A true subset of the full dataset

The sample holds 300 claims copied unchanged from the full dataset. Claims were drawn at random inside each scenario, so every error mechanism appears, and the sample keeps the error-heavy mix of the full product. It exists so you can check the schema, load the files into your own pipeline and judge the structure before you buy. Row for row, anything you see here is in the paid dataset with the same identifiers and values.

The sample is too small to train a detector. At this size a model learns the quirks of 300 rows. Treat it as a fitting room.

File (Parquet)	Rows
d04_claim	300
d04_recovery_finding	300
d04_coverage_state	404
d04_mistaken_payment	104
d04_demand	104
d04_settlement	104
d04_coverage_period	595

Why the coverage table has more patients than claims

The coverage_period table in the sample holds every coverage episode of every patient who has a sampled claim. A patient with two claims in the full dataset may have only one of them here, and the coverage rows stay complete either way.

PART II · USING IT

Five-minute check

1. Open a terminal in the SAMPLE folder and install the two packages.

```
pip install pandas pyarrow
```

2. Load the claim table and the answer key and join them.

```
import pandas as pd
claims = pd.read_parquet('d04_claim.parquet')
key = pd.read_parquet('d04_recovery_finding.parquet')
df = claims.merge(key, on='claim_id')
print(df.scenario_id.value_counts())
```

3. Look at one error end to end. Pick a claim id from the table above, then read its rows in coverage_state, mistaken_payment, demand and settlement. The order of dates is service, first payment, corrected state, demand, settlement.

4. Check the hindsight rule. In d04_coverage_period.parquet, discovered_at tells you the day the claims system learned of a coverage. For a claim paid on day 0, drop every coverage with discovered_at after that date before you compute features.

What to look at in each file

File	Look at
d04_claim	service_date, total_charge and the injury flag. There is no label in this table.
d04_coverage_period	effective_from, effective_to, discovered_at and end_recorded_at. Two of them are hindsight dates.
d04_coverage_state	known_coverages (a JSON list) and the payers determined as primary and secondary, with amounts paid.
d04_mistaken_payment	overpayment, the difference between what was paid and what was owed in the correct order.
d04_demand	recovery_channel and demand_principal.
d04_settlement	settlement_type, interest_assessed, interest_collected and total_received.
d04_recovery_finding	scenario_id and visible_at_adjudication. This is the answer key.

Two habits save time. Join the answer key last and only to score results. Convert the date columns once after loading, because Parquet keeps them as dates and some tools read them as plain objects.

Integrity

manifest.json lists the row count and SHA-256 checksum of each sample file. Claim identifiers match the full dataset, so you can confirm after purchase that the sample rows are present in it unchanged.

Limits of the sample

The sample shows structure and data types. It does not show how the benchmark models behave on the full dataset, and the validation report describes results on all 6,000 claims only.

Sources

Sources for the rules and figures behind the sample are listed in the data passport of the full dataset.