D06 · SAMPLE PASSPORT

The Free Sample, Documented

What the 250-account sample contains, how it was drawn from the baseline cohort, what it is good for, and where it stops.

250	18.8%	6	$0
hospital accounts	carry a planted error	tables, true subset	no registration, direct download

SAMPLE-ID D06-SAMPLE-250	SOURCE baseline cohort, seed 20261110	METHOD stratified subset, not a regeneration
UNIT one row = one hospital account	BENCHMARK none on the sample - see §04	LICENCE synthetic data; no real patients or providers

Every row is a real row of the cohort: the sample is a window into it, not a miniature of it.

Synthetic data. No real patient, provider, or claim is used or reproduced. The sample is for format checks and prototyping, not for estimates.

01 · WHAT THE SAMPLE IS

What the sample is

A true subset. Every row in the sample was drawn from the published baseline cohort - nothing was regenerated. The 250 accounts come with all of their linked rows: applications, payments, cascade steps and the answer-key findings, plus the three policy versions.

What to check first		
Check	Result	Where
Provenance	every row drawn from the published baseline cohort - nothing regenerated; the draw is seeded and reproducible	§02
Prevalence	18.8% in the sample against 18.6% in the cohort - stratified by error type, not a regeneration	§02
Shape	identical columns and manifest structure; CSV copies next to every parquet file	§05
Price	$0 - no registration, direct download	cover
Not for	statistics, benchmarks, policy-volume work: those numbers live in the full 5,000-account cohort	§04

Stratified by error type. Accounts were allocated across the error types by largest remainder, so every type appears at its cohort proportion - including the rarest one. The draw is seeded and reproducible; the full cohort's prevalence (18.6%) is preserved at 18.8% in the sample.

Same shape as the full product. Identical columns, identical manifest structure, CSV copies next to the parquet files. Anything a query or a notebook does against the sample runs unchanged against the full dataset.

02 · HOW IT WAS DRAWN

How it was drawn

Allocation of the 250 accounts across error types (largest-remainder method; pandas sample, random_state=20261110, then shuffled):

Error type	In the cohort	In the sample
correct waterfall (control)	203	203
fpl_miscalculation	17	17
wrong_policy_version	13	13
collection_before_screening	10	10
eligible_service_excluded	6	6
discount_not_applied	1	1

03 · WHAT IT IS GOOD FOR

What it is good for

Format and plumbing. Checking the schema, the joins, the parquet and CSV handling, and the manifest against your own toolchain - before anything is bought.

Query and notebook prototyping. Every join in the product is exercisable on 250 accounts; the sample is small enough to read end-to-end and large enough to catch mistakes.

Teaching. The cascade walk, the answer key and the error signatures are all present at full fidelity.

04 · WHERE IT STOPS

Where it stops

No statistics. Prevalence, medians and distributions estimated on 250 accounts are not the cohort's numbers; the rarest type has a single account here.

No benchmark. The published AUC comes from the full 5,000-account cohort and 5-fold patient-level cross-validation. A metric computed on the sample means nothing.

No policy laboratory. Three policy versions are present, but version-comparison work wants the full cohort's volumes.

05 · FILES

Files

File	Rows	One row is
patient_account	250	one hospital account
assistance_policy_version	3	one policy version
assistance_application	157	one screening decision as processed
payment	1,001	one payment event
waterfall_step	2,158	one cascade step
liability_finding	250	answer key: correct vs actual liability, error type
manifest.json	—	row counts, columns, SHA-256 per table
*.csv	—	exact CSV copies of every table

Provenance	Sample drawn from the baseline cohort: seed 20261110 · specification hash c589d31a9fa94943… · 2026-11-11